

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/04/2014 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Hydrogen Chloride (1.00% - 2.99%) in Nitrogen

Product code : SG-2002-01275

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide America Specialty Gases 6141 Easton Rd Plumsteadville, PA 18949 - USA T 1.800.217.2688

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

www.airliquide.com

Compressed gas H280 Skin Irrit. 2 H315 Eye Irrit. 2A H319

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS04

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation

H319 - Causes serious eye irritation

OSHA-H01 - May displace oxygen and cause rapid suffocation

Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection, face protection, protective clothing, protective gloves

P262 - Do not get in eyes, on skin, or on clothing

P261 - Avoid breathing gas, vapors

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P313 - Get medical advice/attention

CGA-PG20 - Use only with equipment of compatible materials of construction and rated for

cylinder pressure

CGA-PG10 - Use only with equipment rated for cylinder pressure CGA-PG05 - Use a back flow preventive device in the piping

CGA-PG21 - Open valve slowly

CGA-PG06 - Close valve after each use and when empty CGA-PG14 - Approach suspected leak area with caution

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

P403 - Store in a well-ventilated place

2.3. Other hazards

No additional information available

09/09/2014 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Nitrogen	(CAS No)7727-37-9	97.01 - 99	Compressed gas, H280
Hydrogen chloride	(CAS No)7647-01-0	1 - 2.99	Liquefied gas, H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1A, H314

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation

Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. DO NOT apply mouth-to-mouth resuscitation to avoid exposing responder to toxic gas from victim. Apply artificial respiration with bag or mask if breathing stopped. Get immediate medical advice/attention.

First-aid measures after skin contact

: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Get

immediate medical advice/attention.

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion

: Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: Symptoms similar to those listed under inhalation and eye contact.

Symptoms/injuries after inhalation

: May displace oxygen and cause rapid suffocation.

Symptoms/injuries after skin contact

: Causes skin irritation.

Symptoms/injuries after eye contact

Causes serious eye irritation.

Symptoms/injuries after ingestion

: Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

: Not known.

administration
Chronic symptoms

: Gastritis, chronic bronchitis and dermatitis.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen. Get immediate medical attention if breathing difficulty continues or other symptoms such as irritation or inflammation persist!.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media

: Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: The product is not flammable.

Explosion hazard

: Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity

: Reacts with water to form corrosive acids. Corrosive vapors.

5.3. Advice for firefighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting

: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory

protection.

09/09/2014 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.

Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent

premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Equip cleanup crew with proper protection.

Emergency procedures : Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if safe to do so.

Methods for cleaning up : Clean contaminated surfaces with an excess of water. Carefully collect the spill/leftovers. Scoop

absorbed substance into closing containers. Dispose of this material and its container in

accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder

pressure

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or

in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use.

Protect cylinder from physical damage. Store in well ventilated area.

Incompatible products : None known.

Incompatible materials : Reducing agents. Bases or caustic materials.

7.3. Specific end use(s)

Test gas/Calibration gas.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrogen chloride (7647-01-0)			
USA ACGIH Ceiling (ppm)		2 ppm	
USA OSHA OSHA PEL (Ceiling) (mg/m³)		7 mg/m³	
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm	

Nitrogen (7727-37-9)

09/09/2014 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Systems under pressure should be

regularly checked for leakages. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used when asphyxiating gases may be released. Alarm detectors should be used when toxic gases may be released. Consider work permit system e.g. for maintenance

activities.

Hand protection : Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection. Wear

chemically resistant protective gloves when connecting or disconnecting process connections.

Eye protection : Wear safety glasses with side shields. Wear goggles and a face shield when transfilling or

breaking transfer connections. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.

Respiratory protection : None necessary during normal and routine operations. See sections 5 & 6.

Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Clear, colorless gas.

Molecular mass : Not applicable for gas-mixtures.

Color : Colorless

Odor : Irritating/pungent odour
Odor threshold : No data available

pH : Not applicable for gas-mixtures.

Relative evaporation rate (butyl acetate=1) : No data available

Relative evaporation rate (ether=1) : Not applicable for gas-mixtures.

Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available

Flammability (solid, gas) : Not flammable - not combustible

Vapor pressure : Not applicable.

Relative vapor density at 20 °C : No data available

Relative density : No data available

Relative gas density : Lighter or similar to air.

Solubility : Water: Solubility in water of component(s) of the mixture :

•: 720000 mg/l •: 20 mg/l

Log Pow : Not applicable for gas-mixtures.

Log Kow : Not applicable for gas-mixtures.

Viscosity, kinematic : Not applicable.
Viscosity, dynamic : Not applicable.

Explosive properties : Not applicable - not flammable.

Oxidizing properties : None.

Explosive limits : Not applicable - not flammable

9.2. Other information

Additional information : None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water to form corrosive acids. Corrosive vapors.

09/09/2014 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

May react violently with reducing agents.

10.4. Conditions to avoid

Moisture.

10.5. Incompatible materials

Reducing agents. Bases or caustic materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Hydrogen chloride (7647-01-0)	
LD50 oral rat	700 mg/kg
LD50 dermal rabbit	> 5010 mg/kg
LC50 inhalation rat (ppm)	1560 ppm/4h
ATE US (oral)	700.0000000 mg/kg body weight
ATE US (gases)	1405.00000000 ppmV/4h

Nitrogen (7727-37-9)

LC50 inhalation rat (ppm) 410000 ppm/4h

Skin corrosion/irritation : Causes skin irritation.

pH: Not applicable for gas-mixtures.

Serious eye damage/irritation : Causes serious eye irritation.

pH: Not applicable for gas-mixtures.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Hydrogen chloride (7647-01-0)

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

No known effects from this product.

Aspiration hazard : Not classified

Not applicable for gases and gas-mixtures.

: May displace oxygen and cause rapid suffocation.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

Symptoms/injuries after inhalation

administration

: Not known.

Chronic symptoms : Gastritis, chronic bronchitis and dermatitis.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Classification criteria are not met.

09/09/2014 EN (English US) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Persistence and degradability		
Hydrogen Chloride (1.00% - 2.99%) in Nitrogen		
Persistence and degradability	No data available.	
Hydrogen chloride (7647-01-0)		
Persistence and degradability	Not applicable for inorganic gases.	
Nitrogen (7727-37-9)		
Persistence and degradability	No ecological damage caused by this product.	
12.3. Bioaccumulative potential		

2.3. Bioaccumulative potential		
Hydrogen Chloride (1.00% - 2.99%) in Nitrogen		
Log Pow	Not applicable for gas-mixtures.	
Log Kow	Not applicable for gas-mixtures.	
Bioaccumulative potential	No data available.	
Hydrogen chloride (7647-01-0)		
Log Pow	Not applicable for inorganic gases.	
Bioaccumulative potential	No data available.	
Nitrogen (7727-37-9)		
Log Pow	Not applicable for inorganic gases.	

Bioaccumulative potential 12.4. Mobility in soil

Hydrogen Chloride (1.00% - 2.99%) in Nitrogen		
Mobility in soil	No data available.	
Hydrogen chloride (7647-01-0)		
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
Nitrogen (7727-37-9)		
Ecology - soil	No ecological damage caused by this product.	

No ecological damage caused by this product.

12.5. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Must not be discharged to atmosphere. Gas may be scrubbed in alkaline solution under controlled conditions to avoid violent reaction. Ensure that the emission levels

from local regulations or operating permits are not exceeded.

Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more

guidance on suitable disposal methods.

09/09/2014 EN (English US) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1956 Compressed gas, n.o.s.

UN-No.(DOT) : 1956 DOT NA no. : UN1956

DOT Proper Shipping Name : Compressed gas, n.o.s. Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Symbols : G - Identifies PSN requiring a technical name

DOT Packaging Exceptions (49 CFR 173.xxx) : 306;307
DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305
DOT Packaging Bulk (49 CFR 173.xxx) : 314;315
DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Additional information

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. -

Ensure valve protection device (where provided) is correctly fitted.

ADR

Transport document description :

Transport by sea

UN-No. (IMDG) : 1956

Proper Shipping Name (IMDG) : COMPRESSED GAS, N.O.S.

Class (IMDG) : 2.2 - Non-flammable, non-toxic gases

Air transport

UN-No.(IATA) : 1956

Proper Shipping Name (IATA) : COMPRESSED GAS, N.O.S.

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Hydrogen chloride (7647-01-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500 (gas only)
SARA Section 313 - Emission Reporting	1.0 % (acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size)

15.2. International regulations

CANADA

09/09/2014 EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen chloride (7647-01-0)	
Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification Class A - Compressed Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious effects Class E - Corrosive Material	

	Class L - Corrosive iviaterial
Nitrogen (7727-37-9)	
Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification	Class A - Compressed Gas

EU-Regulations

Hydrogen chloride (7647-01-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Hydrogen chloride (7647-01-0)

Listed on AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Hydrogen chloride (7647-01-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Nitrogen (7727-37-9)

Indication of changes

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

-	promulgated March 26, 2012.
Other information	 This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases: see section 16:

t of 11 philaded. See Section 16.		
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3	
Compressed gas	Gases under pressure Compressed gas	
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A	
Liquefied gas	Gases under pressure Liquefied gas	
Skin Corr. 1A	Skin corrosion/irritation Category 1A	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
H280	Contains gas under pressure; may explode if heated	
H314	Causes severe skin burns and eye damage	
H315	Causes skin irritation	
H319	Causes serious eye irritation	

: Revised safety data sheet in accordance with OSHA final rule on GHS implementation

09/09/2014 EN (English US) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H331	Toxic if inhaled

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

09/09/2014 EN (English US) 9/9