SAFETY DATA SHEET



Date of issue/Date of revision 1 May 2016 Version 3

Section 1. Identification		
Product name	: DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK	
Product code	: 00417763	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Industrial applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)	
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)	

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: Not classified.
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 8.4%
GHS label elements	
Signal word	: Warning
Hazard statements	: No known significant effects or critical hazards.
Precautionary statement	<u>s</u>
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.

Version 3

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 2. Hazards identification

Supplemental label elements	: Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.
Hazards not otherwise classified	: Prolonged or repeated contact may dry skin and cause irritation.

Substance/mixture	: Mixture
Product name	: DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Ingredient name	%	CAS number
ropoxypropan-2-ol	≥1.0 - ≤5.0	1569-01-3

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

		United States	Page: 2/11
Inhalation	: No known significant effects or critical hazards.		
Eye contact	: No known significant effects or critical hazards.		

Version 3

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 4. First aid measures

Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>itoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.
Indication of immediate med Notes to physician	 dical attention and special treatment needed, if necessary Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Version 3

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 6. Accidental release measures

Personal p	recautions,	protective e	equipment	and eme	rgency	procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Special precautions	: Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Version 3

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 7. Handling and storage

|--|

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
ropoxypropan-2-ol	None.
Key to abbreviations	

А	=	Acceptable Maximum Peak	S	 Potential skin absorption
ACGIH	=	American Conference of Governmental Industrial Hygienists.	SR	 Respiratory sensitization
С	=	Ceiling Limit	SS	 Skin sensitization
F	=	Fume	STEL	 Short term Exposure limit values
IPEL	=	Internal Permissible Exposure Limit	TD	= Total dust
OSHA	=	Occupational Safety and Health Administration.	TLV	= Threshold Limit Value
R	=	Respirable	TWA	= Time Weighted Average
Z	=	OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances		

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	1	Safety glasses with side shields.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Version 3

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 8. Exposure controls/personal protection

Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Color	: Not available.
Odor	: Characteristic.
Odor threshold	: Not available.
рН	Not available.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 113.33°C (236°F) [Product does not sustain combustion.]
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Upper: 0%
Evaporation rate	: Not available.
Vapor pressure	: Not available.
Vapor density	Not available.
Relative density	: 1.06
Density(lbs / gal)	: 8.85
Solubility	: Soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)
Volatility	: 85% (v/v), 80.57% (w/w)
% Solid. (w/w)	: 19.43

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
1-propoxypropan-2-ol	LD50 Dermal	Rabbit	3550 mg/kg	-
	LD50 Oral	Rat	2504 mg/kg	-
Conclusion/Summary	: There are no data available or	the mixture itself		
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available or	the mixture itself		
Eyes	: There are no data available or	the mixture itself		
Respiratory	: There are no data available or	the mixture itself		
<u>Sensitization</u>				
Conclusion/Summary				
Skin	: There are no data available or	the mixture itself		
Respiratory	: There are no data available or	the mixture itself		
Mutagenicity				
Conclusion/Summary	: There are no data available or	the mixture itself		
Carcinogenicity				
Conclusion/Summary	: There are no data available or	the mixture itself		
Reproductive toxicity				
Conclusion/Summary	: There are no data available on	the mixture itself.		
Teratogenicity				
Conclusion/Summary	: There are no data available on	the mixture itself.		
Specific target organ toxicit	<u>y (single exposure)</u>			

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 11. Toxicological information

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Target organs

Aspiration hazard

: Contains material which causes damage to the following organs: brain. Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, eyes, central nervous system (CNS).

Not available.				
Information on the likely routes of exposure				
Potential acute health effect				
Eye contact	No known significant effects or critical hazards.			
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.			
Ingestion	: No known significant effects or critical hazards.			
Over-exposure signs/symp	i <u>toms</u>			
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	: Adverse symptoms may include the following:			
	irritation			
	dryness cracking			
Ingestion	: No specific data.			
-	cts and also chronic effects from short and long term exposure			
Conclusion/Summary	: There are no data available on the mixture itself. Exposure to component solvent vapor			
Conclusion/Summary	concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.			
<u>Short term exposure</u>				
Potential immediate effects	: There are no data available on the mixture itself.			
Potential delayed effects	: There are no data available on the mixture itself.			
Long term exposure				
Potential immediate effects	: There are no data available on the mixture itself.			
Potential delayed effects	: There are no data available on the mixture itself.			

222169.2 mg/kg

Version 3

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 11. Toxicological information

Potential chronic health ef	<u>ects</u>		
General	 Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. 		
Carcinogenicity	: No known significant effects or critical hazards.		
Mutagenicity	: No known significant effects or critical hazards.		
Teratogenicity	: No known significant effects or critical hazards.		
Developmental effects	ts : No known significant effects or critical hazards.		
Fertility effects	effects : No known significant effects or critical hazards.		
Numerical measures of toxicity			
Acute toxicity estimates			
Route	ATE value		
Oral	156707.5 mg/kg		

Oral Dermal

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
D'	

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Version 3

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 13. Disposal considerations

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	ΙΑΤΑ		
UN number	Not regulated.	Not regulated.	Not regulated.		
UN proper shipping name	-	-	-		
Transport hazard class (es)	-	-	-		
Packing group	-	-	-		
Environmental hazards Marine pollutant substances	No. Not applicable.	No. Not applicable.	No. Not applicable.		

Additional information

DOT	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are listed or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Immediate (acute) health hazard

Composition/information on ingredients

Name	hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
I propoxypropan-2-ol	No.	No.	No.	Yes.	No.

United States	Page: 10/11

Version 3

Product name DFT301 DEFT WOOD STAIN INTERIOR WATER-BASED-GOLDEN OAK

Section 15. Regulatory information

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 1 Physical hazards : 0 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health : 3 Flamma
Date of previous issue
Organization that prepared the MSDS
Key to abbreviations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.