



Material Safety Data Sheet

An **RPM** Company

24 Hour Emergency Phone Numbers:
Medical/Poison Control:
 In U.S.: Call 1-800-222-1222
 Outside U.S.: Call your local poison control center
Transportation/National Response Center:
 1-800-535-5053
 1-352-323-3500

.....
 • NOTE: The National Response Center emergency numbers to
 • be used only in the event of chemical emergencies involving a
 • spill, leak, fire, exposure or accident involving chemicals.
 •

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this MSDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

Section 1 - Chemical Product / Company Information

This Material Safety Data Sheet is available in American Spanish upon request.
 Los Datos de Seguridad del Producto pueden obtenerse en Español si lo requiere.

Product Name:	Plastic Resin Glue	Revision Date:	12/06/2013
Product UPC Number:	070798002036, 070798002043, 070798002081	Supersedes:	12/20/1999
Product Use/Class:	Plastic Resin Glue	MSDS Number:	00030201004
Manufactured for:	DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non-emergency matters)		

Section 2 - Hazards Identification

Emergency Overview: A(n) colored powder product with a slight formaldehyde odor. **WARNING!** Skin sensitizer. May cause sensitization of susceptible persons by skin contact or by inhalation of dust. May be harmful by inhalation, ingestion, skin adsorption. May cause eye, skin, nose, throat and respiratory tract irritation.

Refer to other MSDS sections for other detailed information.

Effects Of Overexposure - Eye Contact: May cause eye irritation. Signs and symptoms may include: pain, tears, swelling, redness and blurred vision.

Effects Of Overexposure - Skin Contact: May cause skin irritation. May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Prolonged exposure to the skin may dry the skin and cause dermatitis or burns.

Effects Of Overexposure - Inhalation: May cause allergic respiratory reaction. May cause sensitization of susceptible persons by inhalation of aerosol or dust. May cause irritation of respiratory tract.

Effects Of Overexposure - Ingestion: May cause severe gastrointestinal disturbance with headache, nausea, vomiting and diarrhea. Acute intoxication by inhalation or ingestion of water soluble barium salts causes vomiting, diarrhea, convulsive tremors and muscular paralysis. Ingestion may cause raising of blood pressure.

Effects Of Overexposure - Chronic Hazards: Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Some reports suggest that formaldehyde may cause respiratory sensitization, such as asthma, and that pre-existing respiratory and skin disorders may be aggravated by exposure.

OSHA has identified 0.5 ppm as the "Action Level", 29 CFR.1048. Please refer to the OSHA Standard for guidance applicable to your specific operation.

Formaldehyde vapor is a known animal carcinogen according to OSHA and NTP and is considered possibly carcinogenic to humans by inhalation. The International Agency for Research on Cancer considers formaldehyde to be a human carcinogen.

Primary Route(s) Of Entry: Skin Contact, Inhalation, Eye Contact

Medical Conditions which May be Aggravated by Exposure: Asthma and asthma-like conditions may worsen from prolonged and repeated exposure. Colds, allergies, asthma, emphysema & other respiratory disorders, and psoriasis, eczema & other skin conditions.

Carcinogenicity:

CAS No.	Chemical Name	ACGIH	OSHA	IARC	NTP
50-00-0	Formaldehyde	Suspected human carcinogen.	Potential cancer hazard.	Carcinogenic to humans.	Known To Be Human Carcinogen.

Section 3 - Composition / Information On Ingredients

Chemical Name	CASRN	Wt%
Urea-formaldehyde polymer	9011-05-6	60-100
Barium sulfate	7727-43-7	1-5
Ammonium sulfate	7783-20-2	1-5
Formaldehyde	50-00-0	1-5

Section 4 - First Aid Measures

First Aid - Eye Contact: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

First Aid - Skin Contact: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist. Remove and wash contaminated clothing.

First Aid - Inhalation: If inhaled, remove to fresh air. If breathing is difficult, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately.

First Aid - Ingestion: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

Note to Physician: None.

COMMENTS: If over-exposure occurs, call your poison control center at 1-800-222-1222.

Section 5 - Fire Fighting Measures

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: Possible dust explosin if dispersed in air in large quantities.

Special Firefighting Procedures: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Wear proper protective equipment as specified in Section 8. Sweep up excess powder. Place remaining powder into containers.

Section 7 - Handling And Storage

Handling: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Keep containers away from excessive heat and freezing. Use in well ventilated area. Provide fresh air such that chemical odors cannot be detected during use and while drying. Do not inhale dusts of this product. Keep away from sources of ignition. Store in a cool, dry, well-ventilated area, away from incompatible substances.

Storage: Avoid excessive heat and freezing. Keep containers closed when not in use. Do not store at temperatures above 120 degrees F. Do not store near acids.

Section 8 - Exposure Controls / Personal Protection

Chemical Name	CASRN	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	Skin
Urea-formaldehyde polymer	9011-05-6	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No
Barium sulfate	7727-43-7	10 MGM3	N.E.	N.E.	5 MGM3	N.E.	N.E.	No
Ammonium sulfate	7783-20-2	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No
Formaldehyde	50-00-0	N.E.	N.E.	0.3 PPM	0.75 PPM	2 PPM	N.E.	No

Important: Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); these limits may vary between states.

Note: An employee's skin exposure to substances having a "YES" in the "SKIN" column in the table above shall be prevented or reduced to the extent necessary under the circumstances through the use of gloves, coveralls, goggles or other appropriate personal protective equipment, engineering controls or work practices.

50-00-0 Formaldehyde is a specially regulated substance for which an OSHA chemical-specific exposure standard exists. Detailed information regarding this substance may be found in 29 CFR 1910.1048. Medical surveillance information regarding this substance may be found in Appendix C to 29 CFR 1910.1048.

Precautionary Measures: Please refer to other sections and subsections of this MSDS.

Engineering Controls: Provide sufficient general and/or local exhaust ventilation to maintain exposure below recommended exposure limit.

Respiratory Protection: A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required.

Skin Protection: Wear rubber gloves.

Eye Protection: Goggles or safety glasses with side shields.

Other protective equipment: Provide eyewash. Provide coveralls if body contact may occur.

Hygienic Practices: Remove and wash contaminated clothing before re-use.

Section 9 - Physical And Chemical Properties

Boiling Range:	Not Established	Vapor Density:	Heavier Than Air
Odor:	Slight Formaldehyde	Odor Threshold:	Not Established
Color:	Amber	Evaporation Rate:	Faster Than n-Butyl Acetate

Solubility in H₂O: Not Established
Freeze Point: Not Established
Vapor Pressure: Not Established
Physical State: Powder
Flash Point, F: Greater than 200
Lower Explosive Limit, %: Not Determined

Specific Gravity: 0.7 - 0.7
pH: Not Established
Viscosity: Not Established
Flammability: Non-Flammable
Method: (Seta Closed Cup)
Upper Explosive Limit, %: Not Determined

When reported, vapor pressure of this product has been calculated theoretically based on its constituent makeup and has not been determined experimentally.

(See section 16 for abbreviation legend)

Section 10 - Stability And Reactivity

Conditions To Avoid: Excessive heat and freezing.

Incompatibility: Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products: Normal decomposition products, i.e., CO_x, NO_x.

Hazardous Polymerization: Hazardous polymerization will not occur under normal conditions.

Stability: Stable under normal conditions.

Section 11 - Toxicological Information

Product LD50: Not Established

Product LC50: Not Established

CASRN	Chemical Name	LD50	LC50
7783-20-2	Ammonium sulfate	Rat:2840 mg/kg	-----
50-00-0	Formaldehyde	-----	Rat:203 mg/m ³

Significant Data with Possible Relevance to Humans: This product contains trace amounts of free formaldehyde. OSHA and NTP identify formaldehyde as a potential carcinogen. IARC identifies formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, the significance of which to humans is unknown. There should be minimal risk when used with ventilation adequate to keep the atmospheric concentration of formaldehyde below the recommended exposure limits. Maintain adequate ventilation to prevent exposure above current OSHA / ACGIH exposure limits. Workplace monitoring of the air to define formaldehyde exposure levels may be necessary. In a two-year inhalation study, rats showed carcinogenic effects in the respiratory system at 15 ppm of formaldehyde.

Section 12 - Ecological Information

Ecological Information: Ecological injuries are not known or expected under normal use.

Section 13 - Disposal Information

Disposal Information: Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA Waste Code if Discarded (40 CFR Section 261): None.

Section 14 - Transportation Information

DOT Proper Shipping Name: Not Regulated.
DOT Technical Name: N.A.

Packing Group: N.A.
Hazard Subclass: N.A.

DOT Hazard Class: N.A.

DOT UN/NA Number: N.A.

Section 15 - Regulatory Information**CERCLA - SARA Hazard Category:**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Immediate Health Hazard, Chronic Health Hazard

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS Number
Barium sulfate	7727-43-7
Ammonium sulfate	7783-20-2
Formaldehyde	50-00-0

Toxic Substances Control Act:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product:

None

Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%:

None

California Proposition 65:

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16 - Other Information**HMIS Ratings:**

Health: 2 Flammability: 1 Reactivity: 0 Personal Protection: X

Volatile Organic Compounds (VOC), less water less exempts: g/L: 0 lb/gal: 0 wt:wt%: 0

Volatile Organic Compounds (VOC), less water less exempts, less LVP-VOCs:

wt:wt%: 0.9

REASON FOR REVISION: Periodic Update**Legend:**

N.A. – Not Applicable

ACGIH – American Conference of Governmental Industrial Hygienists

N.E. – Not Established

SARA – Superfund Amendments and Reauthorization Act of 1986

N.D. – Not Determined

NJRTK – New Jersey Right-to-Know Law

VOC – Volatile Organic Compound

OSHA – Occupational Safety and Health Administration

PEL – Permissible Exposure Limit

HMIS – Hazardous Materials Identification System

TLV – Threshold Limit Value

NTP – National Toxicology Program

CEIL – Ceiling Exposure Limit

STEL – Short Term Exposure Limit

LD50 – Lethal Dose 50

LC50 – Lethal Concentration 50

F – Degree Fahrenheit

MSDS – Material Safety Data Sheet

C – Degree Celsius

CASRN – The Chemical Abstracts Service Registry Number

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. **NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS.** Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.

<End of MSDS>