

Material Safety Data Sheet



Dimethylamine

Section 1. Chemical product and company identification

Product name	: Dimethylamine
Supplier	: AIRGAS INC., on behalf of its subsidiaries 259 North Radnor-Chester Road Suite 100 Radnor, PA 19087-5283 1-610-687-5253
Product use	: Synthetic/Analytical chemistry.
Synonym	: dimethylamine aqueous solution (dot); dma; methanamine, n-methyl- (9ci); dimethylamine, anhydrous; dimethylamine, solution
MSDS #	: 001020
Date of Preparation/Revision	: 4/26/2010.
In case of emergency	: 1-866-734-3438

Section 2. Hazards identification

Physical state	: Gas. [COLORLESS LIQUEFIED COMPRESSED GAS, SOMETIMES SOLID, WITH A DEAD FISH OR AMMONIA ODOR] DANGER! FLAMMABLE GAS. MAY CAUSE FLASH FIRE. CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. CONTENTS UNDER PRESSURE. Keep away from heat, sparks and flame. Do not puncture or incinerate container. Do not breathe gas. Do not ingest. Do not get on skin or clothing. May cause target organ damage, based on animal data. Use only with adequate ventilation. Wash thoroughly after handling. Keep container closed. Do not get in eyes, on skin or on clothing. Avoid breathing gas. Wash thoroughly after handling. Contact with rapidly expanding gases can cause frostbite.
Target organs	: May cause damage to the following organs: lungs, mucous membranes, upper respiratory tract, skin, eyes.
Routes of entry	: Inhalation Dermal Eyes
Potential acute health effects	
Eyes	: Corrosive to eyes. Causes burns. Contact with rapidly expanding gas may cause burns or frostbite.
Skin	: Corrosive to the skin. Causes burns. Contact with rapidly expanding gas may cause burns or frostbite.
Inhalation	: Corrosive to the respiratory system.
Ingestion	: Ingestion is not a normal route of exposure for gases
Potential chronic health effects	: CARCINOGENIC EFFECTS: A4 (Not classifiable for humans or animals.) by ACGIH. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available.
Medical conditions aggravated by over-exposure	: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

Section 3. Composition, Information on Ingredients

<u>Name</u>	<u>CAS number</u>	<u>% Volume</u>	<u>Exposure limits</u>
Dimethylamine	124-40-3	100	ACGIH TLV (United States, 1/2009). STEL: 27.6 mg/m³ 15 minute(s). STEL: 15 ppm 15 minute(s). TWA: 9.2 mg/m³ 8 hour(s). TWA: 5 ppm 8 hour(s). NIOSH REL (United States, 6/2009). TWA: 18 mg/m³ 10 hour(s). TWA: 10 ppm 10 hour(s). OSHA PEL (United States, 11/2006). TWA: 18 mg/m³ 8 hour(s). TWA: 10 ppm 8 hour(s). OSHA PEL 1989 (United States, 3/1989). TWA: 18 mg/m³ 8 hour(s). TWA: 10 ppm 8 hour(s).

Section 4. First aid measures

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

- | | |
|---------------------|---|
| Eye contact | : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. |
| Skin contact | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately. |
| Frostbite | : Try to warm up the frozen tissues and seek medical attention. |
| Inhalation | : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. |
| Ingestion | : As this product is a gas, refer to the inhalation section. |

Section 5. Fire-fighting measures

- | | |
|------------------------------------|---|
| Flammability of the product | : Flammable. |
| Auto-ignition temperature | : 401.85°C (755.3°F) |
| Flash point | : Closed cup: -18°C (-0.4°F). |
| Flammable limits | : Lower: 2.8% Upper: 14.4% |
| Products of combustion | : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides |

- | | |
|---|---|
| Fire-fighting media and instructions | : In case of fire, use water spray (fog), foam or dry chemical. |
|---|---|

In case of fire, allow gas to burn if flow cannot be shut off immediately. Apply water from a safe distance to cool container and protect surrounding area. If involved in fire, shut off flow immediately if it can be done without risk.

Contains gas under pressure. Flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

- | | |
|---|---|
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |
|---|---|

Section 6. Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (section 8). Shut off gas supply if this can be done safely. Isolate area until gas has dispersed.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7. Handling and storage

- Handling** : Use only with adequate ventilation. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Wash thoroughly after handling. High pressure gas. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Do not ingest. Do not get in eyes, on skin or on clothing. Keep container closed. Do not get on skin or clothing. Keep away from heat, sparks and flame. To avoid fire, eliminate ignition sources. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.
- Storage** : Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Segregate from oxidizing materials. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

Section 8. Exposure controls/personal protection

- Engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Personal protection

- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
The applicable standards are (US) 29 CFR 1910.134 and (Canada) Z94.4-93
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Personal protection in case of a large spill** : Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Full chemical-resistant suit and self-contained breathing apparatus should be worn only by trained and authorized persons.

Product name

di-Methylamine

ACGIH TLV (United States, 1/2009).

STEL: 27.6 mg/m³ 15 minute(s).

STEL: 15 ppm 15 minute(s).

TWA: 9.2 mg/m³ 8 hour(s).

TWA: 5 ppm 8 hour(s).

NIOSH REL (United States, 6/2009).

TWA: 18 mg/m³ 10 hour(s).

TWA: 10 ppm 10 hour(s).

OSHA PEL (United States, 11/2006).

TWA: 18 mg/m³ 8 hour(s).

TWA: 10 ppm 8 hour(s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 18 mg/m³ 8 hour(s).

TWA: 10 ppm 8 hour(s).

Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Molecular weight	: 45.1 g/mole
Molecular formula	: C ₂ H ₇ N
Boiling/condensation point	: 6.9°C (44.4°F)
Melting/freezing point	: -92.2°C (-134°F)
Critical temperature	: 164.7°C (328.5°F)
Vapor density	: 1.6 (Air = 1)
Specific Volume (ft³/lb)	: 8.4034
Gas Density (lb/ft³)	: 0.119

Section 10. Stability and reactivity

Stability and reactivity	: The product is stable.
Incompatibility with various substances	: Highly reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Toxicity data

Product/ingredient name	Result	Species	Dose	Exposure
di-Methylamine	LD50 Oral	Rat	698 mg/kg	-
	TDLo Dermal	Rabbit	6 pph	-
	LC50 Inhalation Vapor	Rat	3 g/m ³	2 hours
	LC50 Inhalation Gas.	Mouse	4725 ppm	2 hours
	LC50 Inhalation Gas.	Rat	4540 ppm	6 hours
	LC50 Inhalation Gas.	Rat	11118 ppm	1 hours
	LD50 Inhalation	Rat	11118 ppm	1 hours
	LC50 Inhalation	Rat	11118 ppm	1 hours

IDLH : 500 ppm

Chronic effects on humans : **CARCINOGENIC EFFECTS:** A4 (Not classifiable for humans or animals.) by ACGIH. May cause damage to the following organs: lungs, mucous membranes, upper respiratory tract, skin, eyes.

Other toxic effects on humans : Very hazardous by the following route of exposure: of eye contact (irritant). Hazardous by the following route of exposure: of skin contact (irritant), of inhalation (lung irritant).

Specific effects

Carcinogenic effects	: No known significant effects or critical hazards.
Mutagenic effects	: No known significant effects or critical hazards.
Reproduction toxicity	: No known significant effects or critical hazards.

Section 12. Ecological information

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
di-Methylamine	-	Acute LC50 210000 to 349000 ug/L Fresh water	Fish - Guppy - Poecilia reticulata	96 hours
	-	Acute LC50 120000 ug/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss	96 hours
	-	Acute LC50 118000 to 125000 ug/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss	96 hours
	-	Acute LC50 >100000 ug/L Marine water	Crustaceans - Common shrimp, sand shrimp - Crangon crangon - Adult	48 hours
	-	Acute LC50 50000 to 56500 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours
	-	Acute LC50 20000 ug/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss	96 hours
	-	Acute LC50 17000 ug/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss	96 hours

Products of degradation : Products of degradation: carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO₂ etc.).

Environmental fate : Not available.

Environmental hazards : No known significant effects or critical hazards.

Toxicity to the environment : Not available.

Section 13. Disposal considerations

Product removed from the cylinder must be disposed of in accordance with appropriate Federal, State, local regulation.Return cylinders with residual product to Airgas, Inc.Do not dispose of locally.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	UN1032	DIMETHYLAMINE, ANHYDROUS	2.1	Not applicable (gas).		Reportable quantity 1000 lbs. (454 kg) Limited quantity Yes. Packaging instruction Passenger

Dimethylamine

						aircraft Quantity limitation: Forbidden. Cargo aircraft Quantity limitation: 150 kg Special provisions T50
TDG Classification	UN1032	DIMETHYLAMINE, ANHYDROUS	2.1	Not applicable (gas).		Explosive Limit and Limited Quantity Index 0 ERAP Index 3000 Passenger Carrying Ship Index Forbidden Passenger Carrying Road or Rail Index Forbidden
Mexico Classification	UN1032	DIMETHYLAMINE, ANHYDROUS	2.1	Not applicable (gas).		-

“Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product.”

Section 15. Regulatory information

United States

U.S. Federal regulations : **United States inventory (TSCA 8b)**: This material is listed or exempted.
TSCA precursor chemical list: di-Methylamine
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: di-Methylamine
SARA 311/312 MSDS distribution - chemical inventory - hazard identification: di-Methylamine: Fire hazard, Sudden release of pressure, Immediate (acute) health hazard, Delayed (chronic) health hazard
Clean Water Act (CWA) 307: No products were found.
Clean Water Act (CWA) 311: di-Methylamine
Clean Air Act (CAA) 112 accidental release prevention: di-Methylamine
Clean Air Act (CAA) 112 regulated flammable substances: di-Methylamine
Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

SARA 313

Product name

CAS number

Concentration

Dimethylamine

Form R - Reporting requirements	: Dimethylamine	124-40-3	100
Supplier notification	: Dimethylamine	124-40-3	100

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations	: Connecticut Carcinogen Reporting: This material is not listed. Connecticut Hazardous Material Survey: This material is not listed. Florida substances: This material is not listed. Illinois Chemical Safety Act: This material is not listed. Illinois Toxic Substances Disclosure to Employee Act: This material is not listed. Louisiana Reporting: This material is not listed. Louisiana Spill: This material is not listed. Massachusetts Spill: This material is not listed. Massachusetts Substances: This material is listed. Michigan Critical Material: This material is not listed. Minnesota Hazardous Substances: This material is not listed. New Jersey Hazardous Substances: This material is listed. New Jersey Spill: This material is not listed. New Jersey Toxic Catastrophe Prevention Act: This material is listed. New York Acutely Hazardous Substances: This material is listed. New York Toxic Chemical Release Reporting: This material is not listed. Pennsylvania RTK Hazardous Substances: This material is listed. Rhode Island Hazardous Substances: This material is not listed.
--------------------------	--

Canada

WHMIS (Canada)	: Class A: Compressed gas. Class B-1: Flammable gas. Class E: Corrosive material CEPA Toxic substances: This material is not listed. Canadian ARET: This material is not listed. Canadian NPRI: This material is listed. Alberta Designated Substances: This material is not listed. Ontario Designated Substances: This material is not listed. Quebec Designated Substances: This material is not listed.
-----------------------	--

Section 16. Other information

United States

Label requirements	: FLAMMABLE GAS. MAY CAUSE FLASH FIRE. CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. CONTENTS UNDER PRESSURE.
---------------------------	---

Canada


Label requirements	: Class A: Compressed gas. Class B-1: Flammable gas. Class E: Corrosive material
---------------------------	---

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		4
Physical hazards		0

Dimethylamine

National Fire Protection :
Association (U.S.A.)



Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.