# Material Safety Data Sheet



Bromotrifluoromethane (R-13B1)

# Section 1. Chemical product and company identification

**Product name** Bromotrifluoromethane (R-13B1)

**Supplier** AIRGAS INC., on behalf of its subsidiaries

259 North Radnor-Chester Road

Suite 100

Radnor, PA 19087-5283

1-610-687-5253

**Product use** : Synthetic/Analytical chemistry.

bromofluoroform; halon 1301; monobromotrifluoromethane; **Synonym** 

trifluoromonobromomethane; methane, bromotrifluoro-; bromotrifluoromethane; f-

13b1: freon 13b1

Date of Preparation/

MSDS#

001109 : 10/7/2013.

Revision

In case of emergency

: 1-866-734-3438

### Section 2. Hazards identification

**Physical state** Gas. [COLORLESS, ODORLESS GAS. [NOTE: SHIPPED AS A LIQUEFIED

COMPRESSED GAS.]]

: WARNING! **Emergency overview** 

MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

CONTENTS UNDER PRESSURE.

Do not puncture or incinerate container. May cause target organ damage, based on

animal data.

Contact with rapidly expanding gases can cause frostbite.

**Target organs** May cause damage to the following organs: heart, central nervous system (CNS).

**Routes of entry** : Inhalation

Potential acute health effects

: Contact with rapidly expanding gas may cause burns or frostbite. **Eyes** Skin

: Contact with rapidly expanding gas may cause burns or frostbite.

: Acts as a simple asphyxiant. Inhalation

Ingestion : Ingestion is not a normal route of exposure for gases

Potential chronic health effects

**Target organs** : May cause damage to the following organs: heart, central nervous system (CNS).

**Medical conditions** aggravated by overexposure

: Pre-existing disorders involving any target organs mentioned in this MSDS as being at

risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

### Section 3. Composition, Information on Ingredients

CAS number % Volume **Exposure limits** <u>Name</u>

Build 1.1 Page: 1/6 Bromotrifluoromethane (R-13B1)

Bromotrifluoromethane (R-13B1) 75-63-8 100 ACGIH TLV (United States, 3/2012).

TWA: 6090 mg/m³ 8 hours. TWA: 1000 ppm 8 hours.

NIOSH REL (United States, 1/2013).

TWA: 6100 mg/m³ 10 hours. TWA: 1000 ppm 10 hours.

OSHA PEL 1989 (United States, 3/1989).

TWA: 6100 mg/m³ 8 hours. TWA: 1000 ppm 8 hours.

#### Section 4. First aid measures

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with plenty of water

for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical

attention immediately.

**Skin contact**: In case of contact, immediately flush skin with plenty of water for at least 15 minutes

while removing contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention immediately.

Frostbite : Try to warm up the frozen tissues and seek medical attention.

Inhalation : Move exposed person to fresh air. If not breathing, if breathing is irregular or if

respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention

immediately.

**Ingestion** : As this product is a gas, refer to the inhalation section.

# Section 5. Fire-fighting measures

Flammability of the product : Non-flammable.

**Products of combustion**: Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds

carbonyl halides

**Fire-fighting media and** : Use an extinguishing agent suitable for the surrounding fire. **instructions** 

Apply water from a safe distance to cool container and protect surrounding area. If

involved in fire, shut off flow immediately if it can be done without risk.

Contains gas under pressure. In a fire or if heated, a pressure increase will occur and

the container may burst or explode.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (section 8). Shut off gas supply if this can be done safely. Isolate area until gas has dispersed.

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains

and sewers.

**Methods for cleaning up**: Immediately contact emergency personnel. Stop leak if without risk. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Build 1.1 Page: 2/6

# Section 7. Handling and storage

#### **Handling**

: High pressure gas. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

#### **Storage**

: Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

### Section 8. Exposure controls/personal protection

#### **Engineering controls**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Personal protection**

**Eyes** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

The applicable standards are (US) 29 CFR 1910.134 and (Canada) Z94.4-93

**Hands** 

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Personal protection in case

of a large spill Product name Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product.

bromotrifluoromethane

ACGIH TLV (United States, 3/2012).

TWA: 6090 mg/m<sup>3</sup> 8 hours. TWA: 1000 ppm 8 hours.

NIOSH REL (United States, 1/2013).

TWA: 6100 mg/m³ 10 hours. TWA: 1000 ppm 10 hours.

OSHA PEL 1989 (United States, 3/1989).

TWA: 6100 mg/m<sup>3</sup> 8 hours. TWA: 1000 ppm 8 hours.

Consult local authorities for acceptable exposure limits.

# Section 9. Physical and chemical properties

Molecular weight : 148.92 g/mole
Molecular formula : C-Br-F3

Boiling/condensation point : -57.8°C (-72°F)

Melting/freezing point : -166.1°C (-267°F)

Critical temperature : 66.9°C (152.4°F)

Vapor density : 5.12 (Air=1)

Specific Volume (ft ³/lb) : 2.6042

Gas Density (lb/ft ³) : 0.384

Build 1.1 Page: 3/6

### Section 10. Stability and reactivity

Stability and reactivity

: The product is stable.

Incompatibility with various substances

: Highly reactive or incompatible with the following materials: alkalis.

Hazardous docomposi

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

**Hazardous polymerization**: Under normal conditions of storage and use, hazardous polymerization will not occur.

# Section 11. Toxicological information

**Toxicity data** 

Product/ingredient nameResultSpeciesDoseExposurebromotrifluoromethaneLC50 InhalationRat430 g/m³4 hours

Vapor

LC50 Inhalation

Rat >770000 ppm

1 hours

Gas.

LC50 Inhalation

Rat 84000 ppm

15 minutes

Gas.

**IDLH** : 40000 ppm

Chronic effects on humans : May cause damage to the following organs: heart, central nervous system (CNS).

Other toxic effects on

humans

: No specific information is available in our database regarding the other toxic effects of

this material to humans.

**Specific effects** 

Carcinogenic effects
 Mutagenic effects
 No known significant effects or critical hazards.
 Reproduction toxicity
 No known significant effects or critical hazards.

# Section 12. Ecological information

#### **Aquatic ecotoxicity**

Not available.

**Products of degradation**: Products of degradation: carbon oxides (CO, CO<sub>2</sub>), halogenated compounds.

**Environmental fate** : Not available.

**Environmental hazards**: This product shows a low bioaccumulation potential.

Toxicity to the environment : Not available.

# Section 13. Disposal considerations

Product removed from the cylinder must be disposed of in accordance with appropriate Federal, State, local regulation.Return cylinders with residual product to Airgas, Inc.Do not dispose of locally.

# Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information

Build 1.1 Page: 4/6

Bromotrifluoromethane (R-13B1)										
DOT Classification	UN1009	BROMOTRIFLUOROMETHANE OR REFRIGERANT GAS, R 13B1.	2.2	Not applicable (gas).	The state of the s	Limited quantity Yes.  Packaging instruction Passenger aircraft Quantity limitation: 75 kg  Cargo aircraft Quantity limitation: 150 kg  Special provisions T50				
TDG Classification	UN1009	BROMOTRIFLUOROMETHANE; OR REFRIGERANT GAS R 13B1	2.2	Not applicable (gas).	2	Explosive Limit and Limited Quantity Index 0.125  Passenger Carrying Road or Rail Index 75				
Mexico Classification	UN1009	BROMOTRIFLUOROMETHANE OR REFRIGERANT GAS, R 13B1.	2.2	Not applicable (gas).	NON-PLANMAGIE GAS	-				

"Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

# Section 15. Regulatory information

#### **United States**

**U.S. Federal regulations** 

Bromotrifluoromethane (R-13B1)

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): This material is listed or exempted.

**SARA 302/304**: No products were found.

SARA 311/312 Hazards identification: Sudden release of pressure, Delayed (chronic)

health hazard

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

**SARA 313** 

Product name CAS number Concentration

Form R - Reporting

requirements

Bromotrifluoromethane (R-13B1) 75-63-8 100

**Supplier notification**: Bromotrifluoromethane (R-13B1) 75-63-8 100

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

Build 1.1 Page: 5/6

#### Bromotrifluoromethane (R-13B1)

State regulations

: Connecticut Carcinogen Reporting: This material is not listed.

Connecticut Hazardous Material Survey: This material is not listed.

Florida substances: This material is not listed.

Illinois Chemical Safety Act: This material is not listed.

Illinois Toxic Substances Disclosure to Employee Act: This material is not listed.

Louisiana Reporting: This material is not listed.
Louisiana Spill: This material is not listed.
Massachusetts Spill: This material is not listed.
Massachusetts Substances: This material is listed.
Michigan Critical Material: This material is not listed.

Minnesota Hazardous Substances: This material is not listed.

New Jersey Hazardous Substances: This material is listed.

New Jersey Spill: This material is not listed.

New Jersey Toxic Catastrophe Prevention Act: This material is not listed.

New York Acutely Hazardous Substances: This material is not listed.

New York Toxic Chemical Release Reporting: This material is not listed.

Pennsylvania RTK Hazardous Substances: This material is listed.

Rhode Island Hazardous Substances: This material is not listed.

**Canada** 

WHMIS (Canada) : Class A: Compressed gas.

CEPA Toxic substances: This material is listed.
Canadian ARET: This material is not listed.
Canadian NPRI: This material is listed.

Alberta Designated Substances: This material is not listed.

Ontario Designated Substances: This material is not listed.

Quebec Designated Substances: This material is not listed.

### Section 16. Other information

**United States** 


Label requirements : MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

CONTENTS UNDER PRESSURE.

Canada

Label requirements : Class A: Compressed gas.

Hazardous Material Information System (U.S.A.)



National Fire Protection Association (U.S.A.)



#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Build 1.1 Page: 6/6