Material Safety Data Sheet



Chloropentafluoroethane (Refrigerant Gas R115)

Section 1. Chemical product and company identification

Product name Chloropentafluoroethane (Refrigerant Gas R115)

AIRGAS INC., on behalf of its subsidiaries **Supplier**

259 North Radnor-Chester Road

Suite 100

Radnor, PA 19087-5283

1-610-687-5253

Product use Synthetic/Analytical chemistry.

: ethane, chloropentafluoro-; chloropentafluoroethane; f-115; freon 115; genetron 115; Synonym

pentafluoromonochloroethane; cfc-115

MSDS# 001165 Date of 5/17/2010.

Preparation/Revision

In case of emergency : 1-866-734-3438

Section 2. Hazards identification

Physical state : Gas. [COLORLESS GAS WITH A SLIGHT, ETHEREAL ODOR. [NOTE: SHIPPED AS A

LIQUEFIED COMPRESSED GAS.]]

WARNING!

MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

CONTENTS UNDER PRESSURE.

Do not puncture or incinerate container. May cause target organ damage, based on

animal data.

Contact with rapidly expanding gases can cause frostbite.

May cause damage to the following organs: kidneys, liver, cardiovascular system, skin, **Target organs**

central nervous system (CNS).

Routes of entry : Inhalation

Potential acute health effects

: Contact with rapidly expanding gas may cause burns or frostbite. **Eves**

Skin : Contact with rapidly expanding gas may cause burns or frostbite.

Inhalation : Acts as a simple asphyxiant.

Ingestion : Ingestion is not a normal route of exposure for gases

Potential chronic health

effects **MUTAGENIC EFFECTS**: Not available. TERATOGENIC EFFECTS: Not available.

CARCINOGENIC EFFECTS: Not available.

Medical conditions aggravated by over-

exposure

: Pre-existing disorders involving any target organs mentioned in this MSDS as being at

risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

Section 3. Composition, Information on Ingredients

% Volume **CAS** number **Name Exposure limits**

Chloropentafluoroethane (Refrigerant Gas R115)

76-15-3 100 ACGIH TLV (United States, 1/2009).

TWA: 6320 mg/m³ 8 hour(s). TWA: 1000 ppm 8 hour(s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 1000 ppm 8 hour(s). TWA: 6320 mg/m³ 8 hour(s). NIOSH REL (United States, 6/2009).

TWA: 1000 ppm 10 hour(s). TWA: 6320 mg/m3 10 hour(s).

Build 1.1 Page: 1/6

Section 4. First aid measures

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Frostbite

: Try to warm up the frozen tissues and seek medical attention.

Inhalation

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion

: As this product is a gas, refer to the inhalation section.

Section 5. Fire-fighting measures

Flammability of the product

: Non-flammable.

Products of combustion

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds carbonyl halides

Fire-fighting media and instructions

: Use an extinguishing agent suitable for the surrounding fire.

Apply water from a safe distance to cool container and protect surrounding area. If involved in fire, shut off flow immediately if it can be done without risk.

Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions

: Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (section 8). Shut off gas supply if this can be done safely. Isolate area until gas has dispersed.

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up

Immediately contact emergency personnel. Stop leak if without risk. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7. Handling and storage

Handling

: High pressure gas. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

Storage

: Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

Build 1.1 Page: 2/6

Chloropentafluoroethane (Refrigerant Gas R115)

Section 8. Exposure controls/personal protection

Engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protection

Eves

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

The applicable standards are (US) 29 CFR 1910.134 and (Canada) Z94.4-93

Hands

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Personal protection in case

of a large spill

Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the

product.

Product name

chloropentafluoroethane

ACGIH TLV (United States, 1/2009).

TWA: 6320 mg/m³ 8 hour(s). TWA: 1000 ppm 8 hour(s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 1000 ppm 8 hour(s). TWA: 6320 mg/m3 8 hour(s). NIOSH REL (United States, 6/2009).

TWA: 1000 ppm 10 hour(s). TWA: 6320 mg/m3 10 hour(s).

Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Molecular weight : 154.47 g/mole Molecular formula : C2-CI-F5

Boiling/condensation point : -39.4°C (-38.9°F) **Melting/freezing point** : -141.8°C (-223.2°F) **Critical temperature** : 80°C (176°F)

: 0.006487 g/ml @ 21.1 Vapor density

Specific Volume (ft 3/lb) 17.74 : 0.05635 Gas Density (lb/ft 3)

Section 10. Stability and reactivity

Stability and reactivity

The product is stable.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Hazardous polymerization

: Under normal conditions of storage and use, hazardous polymerization will not occur.

Build 1.1 Page: 3/6

Section 11. Toxicological information

Toxicity data

Product/ingredient nameResultSpeciesDoseExposurechloropentafluoroethaneLC50 InhalationRat4880 g/m34 hours

Vapor

Chronic effects on humans : May cause damage to the following organs: kidneys, liver, cardiovascular system, skin,

central nervous system (CNS).

Other toxic effects on

humans

No specific information is available in our database regarding the other toxic effects of

this material to humans.

Specific effects

Carcinogenic effects : No known significant effects or critical hazards.

Mutagenic effects : No known significant effects or critical hazards.

Reproduction toxicity : No known significant effects or critical hazards.

Section 12. Ecological information

Aquatic ecotoxicity

Not available.

Products of degradation: Products of degradation: carbon oxides (CO, CO₂), halogenated compounds.

Environmental fate : Not available.

Environmental hazards: No known significant effects or critical hazards.

Toxicity to the environment : Not available.

Section 13. Disposal considerations

Product removed from the cylinder must be disposed of in accordance with appropriate Federal, State, local regulation.Return cylinders with residual product to Airgas, Inc.Do not dispose of locally.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	UN1020	CHLOROPENTAFLUOROETHANE OR REFRIGERANT GAS R 115	2.2	Not applicable (gas).		Limited quantity Yes.
						Packaging instruction Passenger aircraft Quantity limitation: 75 kg
						Cargo aircraft Quantity Ilimitation: 150 kg
						Special provisions T50

Build 1.1 Page: 4/6

Chloropentafluoroethane (Refrigerant Gas R115) CHLOROPENTAFLUOROETHANE; **TDG Classification** UN1020 2.2 Not applicable (gas). **Explosive** OR REFRIGERANT Limit and **GAS R 115 Limited** Quantity <u>Index</u> 0.125 Passenger Carrying Road or Rail Index 75 CHLOROPENTAFLUOROETHANE 2.2 UN1020 Mexico Not applicable (gas). OR REFRIGERANT Classification **GAS R 115**

Section 15. Regulatory information

United States

U.S. Federal regulations

: United States inventory (TSCA 8b): This material is listed or exempted.

TSCA 12(b) annual export notification: chloropentafluoroethane

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: chloropentafluoroethane

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: chloropentafluoroethane: Sudden release of pressure, Delayed (chronic) health hazard

Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 accidental release prevention: No products were found.
Clean Air Act (CAA) 112 regulated flammable substances: No products were found.
Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

SARA 313

Form R - Reporting requirements

: Chloropentafluoroethane (Refrigerant Gas R115) 76-15-3 100

Supplier notification

: Chloropentafluoroethane (Refrigerant Gas R115) 76-15-3 100

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

: Connecticut Carcinogen Reporting: This material is not listed.

Connecticut Hazardous Material Survey: This material is not listed.

Florida substances: This material is not listed.

Illinois Chemical Safety Act: This material is not listed.

Illinois Toxic Substances Disclosure to Employee Act: This material is not listed.

Louisiana Reporting: This material is not listed.
Louisiana Spill: This material is not listed.
Massachusetts Spill: This material is not listed.
Massachusetts Substances: This material is listed.
Michigan Critical Material: This material is not listed.

Minnesota Hazardous Substances: This material is not listed. **New Jersey Hazardous Substances:** This material is listed.

New Jersey Spill: This material is not listed.

New Jersey Toxic Catastrophe Prevention Act: This material is not listed.

New York Acutely Hazardous Substances: This material is listed.

New York Toxic Chemical Release Reporting: This material is not listed.

Pennsylvania RTK Hazardous Substances: This material is listed.

Rhode Island Hazardous Substances: This material is not listed.

Build 1.1 Page: 5/6

[&]quot;Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Chloropentafluoroethane (Refrigerant Gas R115)

Canada

WHMIS (Canada) : Class A: Compressed gas.

CEPA Toxic substances: This material is listed.
Canadian ARET: This material is not listed.
Canadian NPRI: This material is listed.

Alberta Designated Substances: This material is not listed.
Ontario Designated Substances: This material is not listed.
Quebec Designated Substances: This material is not listed.

Section 16. Other information

United States


Label requirements : MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

CONTENTS UNDER PRESSURE.

Canada

Label requirements : Class A: Compressed gas.

Hazardous Material Information System (U.S.A.)



National Fire Protection Association (U.S.A.)



Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Build 1.1 Page: 6/6