

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : RADNOR® CLEANER NUCLEAR GRADE
 PRODUCT USE : INSPECTION CLEANER REMOVER
 ITEM CODE(S) : 64000212
 ADDRESS : RADNOR PRODUCTS
 259 N. RADNOR-CHESTER ROAD SUITE 100
 RADNOR, PA 19087-5283
 EMERGENCY TELEPHONE : 866-734-3438
 PREPARATION DATE : DECEMBER 01, 2007
 OSHA REGULATORY STATUS : REGULATED

SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS

ID	HAZARDOUS INGREDIENTS	CAS	OSHA PEL	ACGIH TLV	LD50 SPECIES/ROUTE	LC50 SPECIES/ROUTE	%WT
1	STODDARD SOLVENT	08052-41-3	500 ppm	100 ppm	>3 g/kg rabbit/dermal	>8200 mg/m3 (rat)	10-30 %
2	XYLENE	01330-20-7	100 ppm	100 ppm	>3 ml/kg rabbit/dermal	6700 ppm/4h (rat)	10-30 %
3	LIQUIFIED PETROLEUM GAS	68476-85-7	1000 ppm	1000 ppm	N/Av	57.42% v/v (mice)	10-30 %
4	ISOPROPYL ALCOHOL	00067-63-0	400 ppm	400 ppm	>12 g/kg rabbit/dermal	12000 ppm/8h (rat)	10-30 %
5	ACETONE	00067-64-1	1000 ppm	500 ppm	>20 g/kg rabbit/dermal	16000 ppm/4h (rat)	10-30 %
6	METHYL ETHYL KETONE	00078-93-3	200 ppm	200 ppm	>8000 mg/kg rat/dermal	20 mg/l 4h (rat)	3-7 %
7	PM ACETATE	00108-65-6	N/E	N/E	>7500 mg/kg rabbit/dermal	>5320 ppm/4h (rat)	1-5%

SECTION 3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. STORE BELOW 120°F (49°C), OUT OF SUNLIGHT AND AWAY FROM HEAT SOURCES. DO NOT PUNCTUE OR INCINERATE. AVOID CONTACT WITH SKIN AND EYES. VAPOR HARMFUL. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

EYE: Liquid or vapors may cause redness, burning, tearing, swelling and/or pain.

SKIN: Frequent or prolonged contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Due to being an aerosol, product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat and gastrointestinal tract, resulting in vomiting and/or cramps.

INHALATION: Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, or confusion.

EFFECTS OF ACUTE EXPOSURE: N/Av

EFFECTS OF CHRONIC EXPOSURE: N/ Av

OTHER IMPORTANT HAZARDS: N/Av

**SECTION 4. FIRST AID MEASURES**

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.

INGESTION: Unlikely due to being in aerosol form. Should actual ingestion occur, do not induce vomiting! Drink a glass of water or milk to dilute. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

EYE CONTACT: Immediately flush with plenty of clear water for at least 15 minutes. Make sure to flush under the eyelids. Consult a physician for definitive treatment.

SKIN CONTACT: Remove with soap and water. Continue flushing with water for several minutes. Use skin cream to counter resulting dryness. Consult a physician if irritation continues or if large skin area is affected.

SECTION 5. FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY: Heat, sparks, flame, red hot metal.

MEANS OF EXTINCTION: For warehouse and storage conditions, use NFPA Class B extinguishers (CO₂, dry chemical or universal aqueous film forming foam).

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool fire exposed aerosol containers for containers can rupture violently from heat developed pressure.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents extremely flammable and under pressure. In addition, when liquid or vapor comes into contact with flames or red hot metal, products of combustion will be created. Firemen should wear self-contained breathing apparatus.

FLASH POINT / DETERMINATION: Propellant < 0°F (<-18°C)

UPPER FLAMMABLE LIMIT: 9.5%

LOWER FLAMMABLE LIMIT: 1.8%

AUTO-IGNITION TEMPERATURE: 500°F (260°C)

HAZARDOUS COMBUSTION PRODUCTS: N/Av

EXPLOSION DATA - SENSITIVITY TO MECHANICAL IMPACT: N/Av

EXPLOSION DATA - SENSITIVITY TO STATIC DISCHARGE: N/Av

SECTION 6. ACCIDENTAL RELEASE MEASURES

LEAK / SPILL RESPONSE: Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content should be contained as any other solvent spill. Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove all sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.

SPECIAL INSTRUCTIONS: Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal considerations.

SECTION 7. HANDLING AND STORAGE

HANDLING PROCEDURES / EQUIPMENT: Avoid prolonged or repeated skin contact. Avoid breathing vapors.

STORAGE REQUIREMENTS: Store in area below 120°F (49°C). Do not incinerate (burn) containers. Assure can is in a secure place to prevent knocking over and accidental rupture. Always replace overcap when not in use. For store of pallet quantities, compliance with ANSI/NFPA 30B is recommended.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE PROTECTION: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact could occur, chemical splash proof goggles are recommended.

SKIN PROTECTION: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing such as Sol-Vex® gloves or other clothing impervious to the ingredient listed in Section 2.

ENGINEERING CONTROLS: General ventilation (typically 10 air changes for hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system, may be needed to control air contamination below that of the lowest TLV/PEL rated ingredient from Section 2.

EXPOSURE GUIDELINE LEVELS: Since this product is a mixture, an OSHA or ACGIH exposure value is not available. In determination of any exposure procedures, protection or testing use the lowest rated ingredient in Section 2.



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	> 133 F (56.1 C)	Melting/Freezing Point	> -140 F (-95.3 C)
Flash Point, Liquid Content	> 1 F (-17.0 C)	Flash Point, Propellant	-156 F (-104.4)
Explosive Limits	0.80% to 13.00%	Autoignition Temperature	500 F (260 C)
Flammability	Extremely Flammable Aerosol	Specific Gravity (H₂O = 1)	0.770 g/cc
Molecular Weight	Not Available	Weight	6.427 lbs/gal
Vapor Pressure	100 psig	pH	Not Available
Vapor Density	4.60 g/cc Maximum	Evaporation Rate	Not Available
Physical State	Liquid Under Pressure	Partition Coefficient	Not Available
Viscosity	Not Available	Refractive Index	Not Available
Percent Volatile	100% Wt (100% Vol) Max	VOC Content	5.784 lbs/gal (693.090 g/l)
Percent VOC	90% Wt (91 % Vol) Max	HAP Content	1.285 lbs/gal (154.020 g/l)
Odor Threshold	Not Available	MIR Value	2.472 g O ₃ /g
Odor	Strong solvent	Water Solubility	Not Available
Appearance	Clear liquid	Decomposition Temperature	Not Available

SECTION 10. STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: Heat, sparks, flame, red hot metal.

MATERIALS TO AVOID (INCOMPATIBILITIES): Strong oxidizing materials.

CONDITIONS OF REACTIVITY: N/Av

HAZARDOUS DECOMPOSITION BYPRODUCTS: Oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

ID	ORAL LD50	DERMAL LD50	INHALATION LC50
1	Not Available	500 mg/kg, rabbit	Not Available
2	5045 mg/kg, rat	12800 mg/kg, rabbit	46 mg/l /4 hr, rat
3	Not Available	Not Available	57.42% v/v, mouse
4	2840 mg/kg, rat	4500 mg/kg, rabbit	6300 mg/l /4 hr, rat
5	4800 mg/kg, rat	20000 mg/kg, rabbit	76 mg/kg /4 hr, rat
6	> 2600 mg/kg, mouse	> 8000 mg/kg, rat	20 mg/l /4 hr, rat
7	8532 mg/kg, rat	7500 mg/kg, rabbit	> 5320 ppm /4 hr, rat

ROUTES OF ENTRY: INHALATION[Y] EYE CONTACT[Y] SKIN CONTACT[Y] SKIN ABSORPTION[Y] INGESTION[N]

EXPOSURE LIMITS: Since this product is a mixture, an OSHA or ACGIH exposure value is not available. In determination of any exposure procedures, protection or testing use the lowest rated ingredient in Section 2.

IRRITANCY OF PRODUCT: N/Av

SENSITIZATION TO PRODUCT / MEDICAL CONDITIONS AGGRAVATED: N/Av

CARCINOGENICITY: Ethylbenzene is listed with IARC as Class 2B (possible human carcinogen) and with ACGIH as A3 (confirmed animal carcinogen with unknown relevance to humans). Ethylbenzene is also listed with the State of California as a carcinogen.

TERATOGENICITY / MUTAGENICITY / REPRODUCTIVE TOXICITY: Fetotoxic effects of Xylene have been observed in animals, in the absence of material toxicity. None of the ingredients are known mutagens. Exposure to Xylene and related solvents, such as benzene, toluene and ethanol slows the rate of clearance of from the body, thus enhancing its toxic effects.

TOXICOLOGICAL DATA: None of the ingredients are reproductive toxicants.

SECTION 12. ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS: This product has not been tested for environmental effects.

IMPORTANT ENVIRONMENTAL CHARACTERISTICS: N/Av

AQUATIC TOXICITY: N/Av

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

WASTE DISPOSAL OF PACKAGING: In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

LANDFILL PRECAUTIONS: Not Available

INCINERATION PRECAUTIONS: ** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE **

SECTION 14. TRANSPORTATION INFORMATION

DOT HM-181 SHIPPING INFORMATION

PROPER SHIPPING NAME : Consumer Commodity
HAZARD CLASS OR DIVISION : ORM-D
UN NUMBER : 1950
PACKAGING GROUP : none
LABEL(S) REQUIRED : none



SECTION 15. REGULATORY INFORMATION

ID	TSCA INVENTORY	SARA 302 EHS	RCRA	CERCLA	SARA 313	FIRE	REACTIVITY	SARA 311/312 ACUTE	CHRONIC	PRESSURE	CLEAN AIR ACT	CLEAN WATER ACT
1	✓	—	—	—	—	✓	—	✓	✓	—	—	—
2	✓	—	—	—	—	✓	—	✓	✓	—	—	—
3	✓	—	—	—	—	✓	—	✓	—	✓	—	—
4	✓	—	U239	100 #	20 %	✓	—	✓	✓	—	HAP	100 #
5	✓	—	U002	5000 #	—	✓	—	✓	—	—	—	—
6	✓	—	U159	5000 #	—	✓	—	✓	✓	—	—	—
7	✓	—	—	—	—	✓	—	✓	—	—	—	—

ID	CALIFORNIA	DELAWARE	FLORIDA	MASSACHUSETTS	PENNSYLVANIA	MINNESOTA	NEW JERSEY	NEW YORK	WASHINGTON
1	—	—	✓	2,4	—	ANO	—	—	✓
2	—	—	✓	2,4,5,6 F9	E	ANO	✓	—	✓
3	—	—	—	—	—	—	—	—	—
4	C*	✓	✓	2,4 F8 F9	E	ANO	✓	✓	✓
5	—	✓	✓	2,4,5,6 F8 F9	E	ANO	✓	✓	✓
6	—	✓	✓	2,4,5,6 F8 F9	E	ANO	✓	✓	✓
7	—	—	—	—	—	—	—	—	—

SECTION 16. OTHER INFORMATION

N/E Not Established
N/Av Not Available
N/Ap Not Applicable
IARC International Agency for Research on Cancer
ACGIH American Conference of Governmental Industrial Hygienists
NIOSH National Institute for Occupational Health and Safety
TLV-TWA Threshold Limit Values, Time Weighted Average
NAERG North American Emergency Response Guidebook

The information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond our control. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made.