



Material Safety Data Sheet

MSDS ID NO.: 0106MAR019
Revision date: 01/05/2011

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product name: Marathon Refinery Grade Butane
Synonym: Refinery Grade Butane
Chemical Family: Aliphatic Hydrocarbon
Formula: CH₃CH₂CH₂CH₃

Formula:

Manufacturer:
Marathon Petroleum Company LP
539 South Main Street
Findlay OH 45840

Other information: 419-421-3070
Emergency telephone number: 877-627-5463

2. COMPOSITION/INFORMATION ON INGREDIENTS

Refinery Grade Butane is a mixture of aliphatic petroleum hydrocarbons.

Product information:

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Marathon Refinery Grade Butane	106-97-8	100	1000 ppm TWA	= 1900 mg/m ³ TWA = 800 ppm TWA	

Component Information:

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Normal Butane	106-97-8	55-95	1000 ppm TWA	= 1900 mg/m ³ TWA = 800 ppm TWA	
Iso-Butane	75-28-5	2-20	1000 ppm TWA		
Iso-Pentane	78-78-4	0-15	600 ppm TWA		
Pentane Normal	109-66-0	0-8	600 ppm TWA	= 1800 mg/m ³ TWA = 600 ppm TWA = 2250 mg/m ³ STEL = 750 ppm STEL	

Notes: The manufacturer has voluntarily elected to reflect exposure limits contained in OSHA's 1989 air contaminants standard in its MSDS's, even though certain of those exposure limits were vacated in 1992.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER!

MAY REDUCE OXYGEN AVAILABLE FOR BREATHING
OVEREXPOSURE MAY CAUSE CNS DEPRESSION
BREATHING HIGH CONCENTRATIONS CAN CAUSE IRREGULAR HEARTBEATS WHICH MAY BE FATAL
DIRECT CONTACT WITH LIQUID MAY CAUSE FROSTBITE (FREEZE BURNS)
SEE TOXICOLOGICAL INFORMATION SECTION FOR MORE INFORMATION

EXTREMELY FLAMMABLE COMPRESSED GAS LIQUID
VAPOR MAY CAUSE FLASH FIRE OR EXPLOSION

STABLE

Inhalation:

Product is an anesthetic at high concentrations, producing dizziness, headache, incoordination and narcosis; extremely high concentrations can cause asphyxiation and death by displacement of oxygen from the breathing atmosphere.

Ingestion:

Ingestion not likely.

Skin contact:

Vapor is generally non-irritating to skin. Direct contact with liquified product can cause "cold burn" or frostbite.

Eye contact:

Vapor is generally non-irritating to eyes. Direct contact with liquified product can cause "cold burn" or frostbite.

Carcinogenic Evaluation:

Product information:

Name	IARC Carcinogens:	NTP Carcinogens:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
Marathon Refinery Grade Butane 106-97-8	NE			

Notes:

The International Agency for Research on Cancer (IARC) has not evaluated this product.

Component Information:

4. FIRST AID MEASURES

Eye Contact:

Flush with large amounts of tepid water for at least 15 minutes. Immediately consult a physician if frostbite is suspected (cloudy lens or greyish white tissue around the eye).

Gas: Call a physician if symptoms or irritation occur.

Skin Contact:

If liquified product has caused a "frost burn", remove contaminated clothing. Thaw frostbitten areas slowly with lukewarm water or by wrapping affected areas with blankets. Do not rub affected areas. Let circulation reestablish itself naturally, exercising area if possible. Call a physician.

Ingestion:

Ingestion not likely. If swallowed, immediately call a physician.

Inhalation:

If affected, move person to fresh air. If breathing is difficult, administer oxygen. If not breathing or if no heartbeat, give artificial respiration or cardiopulmonary resuscitation (CPR). Immediately call a physician.

NOTES TO PHYSICIAN:

INHALATION: Hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

Medical Conditions

Aggravated

By Exposure:

No data available.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:

For small fires, Class B fire extinguishing media such as CO₂ or dry chemical can be used. For large fires use water spray or fog. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

Specific hazards:

This product has been determined to be a flammable gas/liquid per the OSHA Hazard Communication Standard, and should be handled accordingly. For additional fire related information see NFPA 30 or North American Emergency Response Guide 115.

5. FIRE FIGHTING MEASURES

Special protective equipment for firefighters:

Bleves (boiling liquid expanding vapor explosions) can occur when a liquid in a pressurized container in close proximity to a fire reaches a temperature well above its boiling point. Its effect could lead to a catastrophic failure of the vessel resulting in flying equipment fragments, a shock wave and a fireball causing serious damage and death. Isolate hazard area. If safe to do so, stop the flow of gas and allow fire to burn out. Extinguishing the flame before shutting off the supply can cause the formation of explosive mixtures. In some cases it may be preferred to allow the flame to continue to burn. Use extreme caution when fighting liquefied petroleum gas fires. Keep surrounding area cool with water spray from a distance and prevent further ignition of combustible material. Avoid use of solid water streams. Contact with water and liquified product can cause increased vaporization.

Flash point:	-76 F
Autoignition temperature:	761 F
Flammable limits in air - lower (%):	1.6
Flammable limits in air - upper (%):	8.4

NFPA rating:

Health: 1
Flammability: 4
Instability: 0
Other: -

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Leaking containers should be moved outdoors or to well-ventilated area and contents transferred to a suitable container. Product vapor is heavier than air and can collect in low areas that are without sufficient ventilation. Advise authorities and National Response Center (800-424-8802) if the product has entered a water course or sewer. Notify local health and pollution control agencies, if appropriate.

7. HANDLING AND STORAGE

Handling:

Product is stored as a liquid but used in the gaseous state. Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Avoid overpressurizing or overfilling cylinders. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues.

Avoid repeated and prolonged skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

- Engineering measures:** Local or general exhaust required in an enclosed area or when there is inadequate ventilation.
- Respiratory protection:** Use atmosphere supplying respirators in the event of oxygen deficiency, when material produces vapors that exceed permissible limits or when excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 1910.134. Self-contained breathing apparatus should be used for fire fighting.
- Skin and body protection:** Wear insulated gloves to prevent skin contact and frostbite.
- Eye protection:** Use goggles or face-shield if there is a potential for splashing.
- Hygiene measures:** Use mechanical ventilation equipment that is explosion-proof.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance:	Colorless Liquefied Gas
Physical state (Solid/Liquid/Gas):	Liquid
Substance type (Pure/Mixture):	Mixture
Color:	Not applicable.
Odor:	Slight Hydrocarbon
Molecular weight:	58
pH:	Neutral
Boiling point/range (5-95%):	31 F
Melting point/range:	Not determined.
Decomposition temperature:	Not applicable.
Specific gravity:	0.6 @ 0 C
Density:	4.86 lb/gal @ 32 F
Bulk density:	No data available.
Vapor density:	2.0 @ 0 C
Vapor pressure:	842 mm Hg @ 70 F
Evaporation rate:	No data available.
Solubility:	Soluble
Solubility in other solvents:	No data available.
Partition coefficient (n-octanol/water):	No data available.
VOC content(%):	No data available.
Viscosity:	No data available.

10. STABILITY AND REACTIVITY

Stability:	The material is stable at 70 F, 760 mm pressure.
Polymerization:	Will not occur.
Hazardous decomposition products:	Carbon monoxide
Materials to avoid:	Strong oxidizers such as nitrates, perchlorates, chlorine, fluorine.
Conditions to avoid:	Sources of heat or ignition.

11. TOXICOLOGICAL INFORMATION

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Product information:

Name	CAS Number	Inhalation:	Dermal:	Oral:
Marathon Refinery Grade Butane	106-97-8	LC50 = 124,000 ppm Hr [Mice]	No data available	No data available

Toxicology Information:

BUTANES: Studies in laboratory animals indicate exposure to extremely high levels of butanes (1-10 or higher vol.% in air) may cause cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

PENTANES: Studies of pentane isomers in laboratory animals indicate exposure to extremely high levels (roughly 10 vol.%) may induce cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

TARGET ORGANS:

central nervous system, heart, eyes, skin,

12. ECOTOXICOLOGICAL INFORMATION

Mobility:

May partition into air, soil and water.

Ecotoxicity:

Harmful to aquatic organisms.

Bioaccumulation:

Not expected to bioaccumulate in aquatic organisms.

Persistence/Biodegradation:

Readily biodegradable in the environment.

13. DISPOSAL CONSIDERATIONS

Cleanup Considerations:

This product as produced is not specifically listed as an EPA RCRA hazardous waste according to federal regulations (40 CFR 261). However, when discarded or disposed of, it may meet the criteria of an "characteristic" hazardous waste. This material could become a hazardous waste if mixed or contaminated with a hazardous waste or other substance(s). It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations. Bleeding off small amounts of this product into the atmosphere or controlled incineration of large amounts are potential disposal methods provided all regulatory requirements are met.

14. TRANSPORT INFORMATION

49 CFR 172.101:

DOT:

Transport Information:

This material when transported via US commerce would be regulated by DOT Regulations.

Proper shipping name:

Butane

14. TRANSPORT INFORMATION

UN/Identification No: UN 1011
Hazard Class: 2.1
Packing group: Not applicable.
DOT reportable quantity (lbs): Not applicable.

Proper shipping name: Butane
UN/Identification No: UN 1011
Hazard Class: 2.1

15. REGULATORY INFORMATION

US Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b): This product and/or its components are listed on the TSCA Chemical Inventory.

OSHA Hazard Communication Standard: This product has been evaluated and determined to be hazardous as defined in OSHA's Hazard Communication Standard.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302: This product contains the following component(s) that have been listed on EPA's Extremely Hazardous Substance (EHS) List:

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Normal Butane	NA
Iso-Butane	NA
Iso-Pentane	NA
Pentane Normal	NA

SARA Section 304: This product contains the following component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	CERCLA/SARA - Hazardous Substances and their Reportable Quantities
Normal Butane	NA
Iso-Butane	NA
Iso-Pentane	NA
Pentane Normal	NA

SARA Section 311/312 The following EPA hazard categories apply to this product:

Acute Health Hazard
Fire Hazard
Sudden Release Of Pressure

SARA Section 313: This product contains the following component(s) that may be subject to reporting on the Toxic Release Inventory (TRI) From R:

Name	CERCLA/SARA 313 Emission reporting:
Normal Butane	None
Iso-Butane	None
Iso-Pentane	None
Pentane Normal	None

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

Normal Butane

- Louisiana Right-To-Know: Not Listed
- California Proposition 65: Not Listed
- New Jersey Right-To-Know: sn 0273
- Pennsylvania Right-To-Know: Present
- Massachusetts Right-To Know: Present
- Florida substance List: Not Listed.
- Rhode Island Right-To-Know: Toxic; Flammable
- Michigan critical materials register list: Not Listed.
- Massachusetts Extraordinarily Hazardous Substances: Not Listed
- California - Regulated Carcinogens: Not Listed
- Pennsylvania RTK - Special Hazardous Substances: Not Listed
- New Jersey - Special Hazardous Substances: flammable - fourth degree
- New Jersey - Environmental Hazardous Substances List: SN 0273 TPQ 500 lb
- Illinois - Toxic Air Contaminants: Not Listed
- New York - Reporting of Releases Part 597 - List of Hazardous Substances: Not Listed

Iso-Butane

- Louisiana Right-To-Know: Not Listed
- California Proposition 65: Not Listed
- New Jersey Right-To-Know: sn 1040
- Pennsylvania Right-To-Know: Present
- Massachusetts Right-To Know: Present
- Florida substance List: Not Listed.
- Rhode Island Right-To-Know: Not Listed
- Michigan critical materials register list: Not Listed.
- Massachusetts Extraordinarily Hazardous Substances: Not Listed
- California - Regulated Carcinogens: Not Listed
- Pennsylvania RTK - Special Hazardous Substances: Not Listed
- New Jersey - Special Hazardous Substances: flammable - fourth degree
- New Jersey - Environmental Hazardous Substances List: SN 1040 TPQ 500 lb
- Illinois - Toxic Air Contaminants: Not Listed
- New York - Reporting of Releases Part 597 - List of Hazardous Substances: Not Listed

Iso-Pentane

- Louisiana Right-To-Know: Not Listed
- California Proposition 65: Not Listed
- New Jersey Right-To-Know: sn 1064
- Pennsylvania Right-To-Know: Present
- Massachusetts Right-To Know: Present
- Florida substance List: Not Listed.

Normal Butane

Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 1064 TPQ 500 lb
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

Pentane Normal

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	sn 1476
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic; Flammable
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 1476 TPQ 500 lb
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

Canadian Regulatory Information:

Canada DSL/NDL Inventory: This product and/or its components are listed either on the Domestic Substances List (DSL) or are exempt.

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Normal Butane	A, B1	1 %
Iso-Butane	A, B1	
Iso-Pentane	B2	
Pentane Normal	B2	1 %

NOTE: Not Applicable.

16. OTHER INFORMATION

Additional Information: No data available.

Prepared by: Mark S. Swanson, Manager, Toxicology and Product Safety

The information and recommendations contained herein are based upon tests believed to be reliable. However, Marathon Petroleum Company LP (MPC) does not guarantee their accuracy or completeness nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of the goods, the merchantability of the goods, or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage maybe required. MPC assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

End of Safety Data Sheet