

**EUCON SRA FLOOR - BULK GALLONS**

Version 5.0

Print Date 12/19/2013

REVISION DATE: 04/23/2013

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : EUCON SRA FLOOR - BULK GALLONS  
 Product code : 10CF 99

COMPANY : Euclid Chemical Company  
 19218 Redwood Road  
 Cleveland, OH 44110

Telephone : 1-800-321-7628  
 Emergency Phone: : U.S. only: 1-800-424-9300  
 International Users Call Collect: 1-703-527-3887

Product use : Admixture

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Black / Brown. Liquid. May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue.

Eyes : Vapor and/or mist may cause eye irritation. Direct contact may cause temporary redness and discomfort.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause moderate irritation.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Repeated overexposure to Ethylene Glycol Butyl Ether may cause hemolysis of the red blood cells leading to possible liver and kidney damage. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung, Liver, Kidney, Nerve, Reproductive

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Poly ethylene glycol mono butyl ether	9004-77-7	30.0 - 60.0
2-(2-(2-Butoxyethoxy)ethoxy)ethanol	143-22-6	15.0 - 40.0
Tetra ethylene glycol mono butyl ether	1559-34-8	15.0 - 40.0

**EUCON SRA FLOOR - BULK GALLONS**

Version 5.0

Print Date 12/19/2013

REVISION DATE: 04/23/2013

Glycol ether solvent	112-34-5	15.0 - 40.0
Sodium hydroxide	1310-73-2	0.1 - 1.0

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

Inhalation	:	Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

Flash point	:	104 °C, 219 °F
Method	:	Cleveland Open Cup
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Smoke, fumes. Carbon monoxide and carbon dioxide can form. Nitrogen oxides can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimize pressure build-up.
Fire and explosion conditions	:	Vapor concentrations in enclosed areas may ignite explosively. Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Personal protective equipment must be

**EUCON SRA FLOOR - BULK GALLONS**

Version 5.0

Print Date 12/19/2013

REVISION DATE: 04/23/2013

worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use. Inspect and replace equipment at regular intervals.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

No known components with exposure limits.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquid
- Color : Black / Brown
- Odor : Mild Etheral
- pH : 10 - 12
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Specific Gravity : 1.002
- % Volatile Weight : 16.0 %

**SECTION 10 - REACTIVITY / STABILITY**

- Substances to avoid : Oxidizing agents. Strong acids. Strong bases.
- Stability : Stable under normal conditions. Avoid welding arcs, flames or other high

**EUCON SRA FLOOR - BULK GALLONS**

Version 5.0

Print Date 12/19/2013

REVISION DATE: 04/23/2013

temperature sources.  
Hazardous polymerization : Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Glycol ether solvent, CAS-No.: 112-34-5  
Acute oral toxicity (LD-50 oral) 6,560 mg/kg ( Rat ) 2,000 mg/kg ( Guinea pig ) 2,200 mg/kg ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : As purchased, this product, when discarded, is not a listed or characteristic hazardous waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product residue. Do not reuse.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA****CFR / DOT:**

Not Regulated

**TDG:**

Not Regulated

**IMDG:**

Not Regulated

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : 2-(2-(2-Butoxyethoxy)ethoxy)ethanol 143-22-6



**EUCON SRA FLOOR - BULK GALLONS**

Version 5.0

Print Date 12/19/2013

REVISION DATE: 04/23/2013

Glycol ether solvent 112-34-5

SARA 311/312 Hazards : Based on an evaluation of the components used, this product does not contain hazardous ingredients identified as per 29 CFR 1910.1200

OSHA Hazardous Components :  
 2-(2-(2-Butoxyethoxy)ethoxy)ethanol 143-22-6  
 Glycol ether solvent 112-34-5

OSHA Flammability : IIIB

Regulatory VOC (less water and exempt solvent) : 165 g/l  
 VOC Method 310 : 16 %

**U.S. State Regulations:**

MASS RTK Components : Sodium hydroxide 1310-73-2

Penn RTK Components : Poly ethylene glycol mono butyl ether 9004-77-7  
 2-(2-(2-Butoxyethoxy)ethoxy)ethanol 143-22-6  
 Tetra ethylene glycol mono butyl ether 1559-34-8  
 Glycol ether solvent 112-34-5  
 Sodium hydroxide 1310-73-2

NJ RTK Components : Poly ethylene glycol mono butyl ether 9004-77-7  
 2-(2-(2-Butoxyethoxy)ethoxy)ethanol 143-22-6  
 Tetra ethylene glycol mono butyl ether 1559-34-8  
 Glycol ether solvent 112-34-5  
 Sodium hydroxide 1310-73-2

Components under California Proposition 65:  
 None known.

**SECTION 16 - OTHER INFORMATION**

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

- |  |   |
|--|---|
| ACGIH - American Conference of Governmental Hygienists                         | PEL - Permissible Exposure Limit                    |
| CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act | RCRA - Resource Conservation and Recovery Act       |
| DOT - Department of Transportation   | RTK - Right To Know                                 |
| DSL - Domestic Substance List  | SARA - Superfund Amendments and Reauthorization Act |
| EPA - Environmental Protection Agency  | STEL - Short Term Exposure Limit                    |
| HMIS - Hazardous Materials Information System                                  | TLV - Threshold Limit Value                         |
| IARC - International Agency for Research on Cancer                             | TSCA - Toxic Substances Control Act                 |
| MSHA - Mine Safety Health Administration                                       | TWA - Time Weighted Average                         |
| NDSL - Non-Domestic Substance List   | V - Volume  |
| NIOSH - National Institute for Occupational Safety and Health                  | VOC - Volatile Organic Compound                     |
| NTP - National Toxicology Program  | WHMIS - Workplace Hazardous Materials Information   |



EUCLID CHEMICAL

**EUCON SRA FLOOR - BULK GALLONS**

Version 5.0  
REVISION DATE: 04/23/2013

Print Date 12/19/2013

System

OSHA - Occupational Safety and Health Administration