



Material Safety Data Sheet

MSDS ID NO.: 0137MAR019
Revision date: 01/24/2012

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product name: Marathon Anionic Emulsified Asphalt
Synonym: Anionic Emulsified Asphalt; AE-P; AE-PL; AE-T; AE-3; AE-60; AE-90; AE-150; AE-200; AE-300; EA-90; EA-150; EA-300; HFE-90; HFE-150; HFE-300; HFMS-2; HFP; HFRS-1; HFRS-2; HFRS-2P; MS-2; MS-3; MWS-90; MWS-150; MWS-300; PEA; PEP; RS-1; RS-2; RS-2L; RS-2P; RS-3; SS-1; SS-1H; SS-1HL; SS-1M; HF Series
Chemical Family: Asphalt
Formula: Mixture
Manufacturer: Marathon Petroleum Company LP
539 South Main Street
Findlay OH 45840

Other information: 419-421-3070
Emergency telephone number: 877-627-5463

2. COMPOSITION / INFORMATION ON INGREDIENTS

This product is an Anionic Emulsified Asphalt mixed with varying proportions of No. 2 fuel oil and an anionic emulsifier. May contain polymer modifiers. Composition varies depending on source of crude and specifications of final product. May contain minor amounts of sulfur, nitrogen and oxygen containing compounds.

Product information:

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Marathon Anionic Emulsified Asphalt	Mixture	100	=0.5 mg/m ³ TWA		

Component Information:

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Asphalt	8052-42-4	30-80	0.5 mg/m ³ TWA		(inhalable fraction, as benzene-soluble aerosol)

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Water	7732-18-5	5-60			
No. 2 Fuel Oil	64741-44-2	0-40			
Polymer Modifier (SBS or SBR)	Mixture	0-5			
Sulfur Compounds	Mixture	0-5			
Anionic Emulsifier	Mixture	0.1-4			
Naphthalene	91-20-3	0.01-0.2	Skin - potential significant contribution to overall exposure by the cutaneous route 10 ppm TWA 15 ppm STEL	= 10 ppm TWA = 50 mg/m ³ TWA = 15 ppm STEL = 75 mg/m ³ STEL	
Hydrogen Sulfide	7783-06-4	0-0.1	1 ppm TWA 5 ppm STEL	= 10 ppm TWA = 14 mg/m ³ TWA = 15 ppm STEL = 21 mg/m ³ STEL	Marathon Exposure Guideline: 10 ppm TWA 15 ppm STEL

Notes:

The manufacturer has voluntarily elected to reflect exposure limits contained in OSHA's 1989 air contaminants standard in its MSDS's, even though certain of those exposure limits were vacated in 1992.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER!

HOT PRODUCT CAN CAUSE BURNS TO SKIN
CONTAINS HYDROGEN SULFIDE GAS. MAY BE FATAL IF INHALED

FUMES FROM HOT PRODUCT CAN CAUSE IRRITATION TO THE EYES, SKIN AND RESPIRATORY SYSTEM

SEE TOXICOLOGICAL INFORMATION SECTION FOR MORE INFORMATION

STABLE

Inhalation:

May release hydrogen sulfide gas which is highly toxic.

Hydrogen sulfide can cause respiratory paralysis and death, depending on the concentration and duration of exposure. Do not rely on ability to smell vapors, since loss of smell rapidly occurs. Effects of overexposure include irritation of the nose and throat, nausea, vomiting, diarrhea, abdominal pain and signs of nervous system depression (e.g. headache, drowsiness, dizziness, loss of coordination and fatigue), irregular heartbeats, pulmonary edema, weakness and convulsions.

Fumes or vapors from the heated material may be irritating to the respiratory tract. Overexposure to this material may cause systemic damage including target organ effects listed under "Toxicological Information."

Ingestion:

Contact with hot material may cause thermal burns. If swallowed at ambient temperature no significant adverse effects are expected. May cause irritation of the mouth, throat and gastrointestinal tract. Ingestion of large amounts may cause gastrointestinal blockage.

Skin contact:

Contact with hot material may cause thermal burns. Contact may cause reddening, itching and inflammation. Skin contact may cause harmful effects in other parts of the body.

Eye contact:

Exposure to hot material can cause thermal burns. Vapors may cause eye irritation and sensitivity to light. Effects may become more serious with repeated or prolonged contact.

Carcinogenic Evaluation:

Product information:

Name	IARC Carcinogens:	NTP Carcinogens:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
Marathon Anionic Emulsified Asphalt Mixture	NE			

Notes:

The International Agency for Research on Cancer (IARC) has not evaluated this product.

Component Information:

Name	IARC Carcinogens:	NTP Carcinogens:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
------	----------------------	---------------------	-------------------------	-------------------------------

Name	IARC Carcinogens:	NTP Carcinogens:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
Asphalt 8052-42-4	Emissions of oxidized asphalt from roofing operations - Probable Human carcinogen (2A); Emissions of straight-run asphalt from paving operations - Possible Human carcinogen (2B)	Reasonably Anticipated To Be A Human Carcinogen	A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free)	Present
Naphthalene 91-20-3	Monograph 82 [2002]	Reasonably Anticipated To Be A Human Carcinogen male rat-clear evidence; female rat-clear evidence; male mice-no evidence; female mice-some evidence	A4 - Not Classifiable as a Human Carcinogen	Present

Notes:

The International Agency for Research on Cancer (IARC) has determined that there is inadequate evidence for the carcinogenicity of diesel fuel/fuel oil in humans. IARC determined that there was limited evidence for the carcinogenicity of marine diesel fuel in animals. Distillate (light) diesel fuels were not classifiable as to their carcinogenicity to humans (Group 3A)

The International Agency for Research on Cancer (IARC) has determined that there is no evidence that severely solvent-refined oils are carcinogenic to experimental animals.

The International Agency for Research on Cancer (IARC) and the Environmental Protection Agency (EPA) have determined that naphthalene is a possible human carcinogen.

The International Agency for Research on Cancer (IARC) concluded that occupational exposures to oxidized asphalt and their emissions during roofing operations are "probably carcinogenic to Humans" (Group 2A). IARC concluded that occupational exposures to hard asphalts and their emissions during mastic asphalt work are "possibly carcinogenic to humans" (Group 2B). IARC concluded that occupational exposures to straight-run asphalts and their emissions during paving operations are "possibly carcinogenic to humans" (Group 2B).

4. FIRST AID MEASURES

Eye Contact:

If hot material comes in contact with eyes hold the eyelids apart and flush the eye with a large amount of cool water for at least 15 minutes. GET IMMEDIATE MEDICAL ATTENTION.

Skin Contact:

If hot material gets on skin, immediately flush affected area with large amounts of cool water. Do not attempt to remove the material from the skin, or to remove contaminated clothing. Get immediate medical attention. For cold material, immediately wash skin with plenty of soap and water while removing contaminated clothing and shoes. Get medical attention if irritation persists. Place contaminated clothing in closed container until cleaned or discarded. If clothing is to be laundered, inform the person performing the operation of contaminant's hazardous properties. Discard contaminated leather goods.

Ingestion:

Do not induce vomiting. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Never give anything by mouth to an unconscious person. Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.

Inhalation:

Remove to fresh air. If not breathing, institute rescue breathing. If breathing is difficult, ensure airway is clear and give oxygen. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.

NOTES TO PHYSICIAN:

INHALATION: Inhalation exposure can produce toxic effects. Treat intoxications as hydrogen sulfide exposures. Monitor for respiratory distress. If cough or difficulty in breathing develops, evaluate for upper respiratory tract inflammation, bronchitis, and pneumonitis.

SKIN: Hot material may cause skin burns. Immerse skin covered with hot material in cool water to limit tissue damage and prevent spread of liquid material. Consider leaving cooled material on skin unless contraindicated by contamination or potential for tattooing. If removal is necessary, mineral oil may be of assistance in minimizing skin loss when removing cool, hardened asphalt.

EYES: Hot material may cause burns to the eyes. Early ophthalmologic evaluation is recommended.

Medical Conditions Aggravated By Exposure:

respiratory system, lungs, skin,

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:

For small fires, Class B fire extinguishing media such as CO₂, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

5. FIRE FIGHTING MEASURES

Specific hazards:

This product is neither a flammable nor combustible material, but will burn when heated to extremely high temperatures. For additional fire related information, see NFPA 30 or the North American Emergency Response Guide 128.

Special protective equipment for firefighters:

Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Keep run-off water out of sewers and water sources.

Flash point:

>200 F

Autoignition temperature:

No data available.

Flammable limits in air - lower (%):

1.0

Flammable limits in air - upper (%):

6.0

NFPA rating:

Health: 2

Flammability: 1

Instability: 0

Other: -

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Advise authorities and National Response Center (800-424-8802) if the product has entered a water course or sewer. Notify local health and pollution control agencies, if appropriate. Contain liquid with sand or soil. Recover and return product to source.

7. HANDLING AND STORAGE

Handling:

Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues.

Significant concentrations of hydrogen sulfide (H₂S) gas can be generated and accumulate in storage tanks and bulk transport compartments which may require additional precautions and procedures during loading/unloading. When opening covers and outlet caps on storage tanks, use face shield and gloves to avoid possible injury from pressurized product. Stay upwind and vent open hatches before unloading. Keep heating coils and flues in storage tanks, trucks and kettles covered with product (8"). Do not overheat.

Avoid skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

Engineering measures:	Local or general exhaust required in an enclosed area or when there is inadequate ventilation.
Respiratory protection:	Where there is potential for airborne exposure to hydrogen sulfide (H ₂ S) above exposure limits, a NIOSH approved, self-contained breathing apparatus (SCBA) or equivalent operated in a pressure demand or other positive pressure mode should be used. When H ₂ S vapors exceed permissible limits, i.e., in confined spaces or bulk transport loading/unloading, a positive-pressure atmosphere supplying respirator is recommended. Self-contained breathing apparatus should be used for fire fighting.
Skin and body protection:	Insulated gloves when handling hot material.
Eye protection:	Goggles and faceshield when handling hot material.
Hygiene measures:	Rubberized suits or coats may be needed for some maintenance operations with hot material.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance:	Black-brown Liquid Emulsion
Physical state (Solid/Liquid/Gas):	Liquid
Substance type (Pure/Mixture):	Mixture
Color:	Black-Brown
Odor:	Tar
Molecular weight:	Not determined.
pH:	Neutral
Boiling point/range (5-95%):	>212 F
Melting point/range:	60 F
Decomposition temperature:	Not applicable.
Specific gravity:	0.9-1.05
Density:	7.5-8.7 lbs/gal
Bulk density:	No data available.
Vapor density:	No data available.
Vapor pressure:	Negligible @ 77 F
Evaporation rate:	No data available.
Solubility:	Negligible
Solubility in other solvents:	No data available.
Partition coefficient (n-octanol/water):	No data available.
VOC content(%):	No data available.
Viscosity:	No data available.

10. STABILITY AND REACTIVITY

Stability:	The material is stable at 70 F, 760 mm pressure.
Polymerization:	Will not occur.
Hazardous decomposition products:	Combustion produces toxic oxides of sulfur, carbon monoxide, sulfur dioxide, hydrogen sulfide and hydrocarbons.
Materials to avoid:	Strong oxidizers such as nitrates, chlorates, peroxides.
Conditions to avoid:	Excessive heat, sources of ignition, open flame.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Product information:

Name	CAS Number	Inhalation:	Dermal:	Oral:
Marathon Anionic Emulsified Asphalt	Mixture	No data available	No data available	No data available

Toxicology Information:

PETROLEUM ASPHALT: Eye and upper respiratory tract irritation has been reported in some asphalt workers (paving and roofing operations) but they are typically mild and transient. Some studies indicate that asphalt paving workers may experience lower respiratory tract symptoms (e.g., coughing, wheezing, and shortness of breath) and pulmonary function changes. Other studies of asphalt workers found no consistent relationship between exposure to asphalt fumes and pulmonary function. Increased levels of 1-hydroxypyrene (a marker for exposure to polycyclic aromatic hydrocarbons) have been observed in the urine of asphalt workers. Genotoxicity studies (e.g., DNA adducts in the urine) of asphalt workers have been largely inconclusive.

A slight increase in lung cancer mortality was reported in a study of European workers exposed to paving and mastic asphalt, but conclusions were equivocal. A follow-up case-control epidemiology study of asphalt paving workers sponsored by the International Association for Research in Cancer (IARC) concluded that there was no evidence that asphalt exposure was linked to lung cancer.

An increase in skin tumors was observed in lifetime studies of laboratory rodents exposed to extracts of asphalt (bitumen). The relevance of these studies to humans is not clear. No increase in skin tumors was observed in a lifetime bioassay where laboratory mice were treated with paving fume condensates. No increase in lung or other tumors were observed in a lifetime inhalation study in laboratory rats exposed to fumes from paving asphalt.

ASPHALTS USED IN ROOFING OPERATIONS: Some asphalts including roofing flux are further processed (oxidized) by the user or customer before use. An increased incidence of skin tumors was observed in a mouse skin carcinogenicity study where animals were exposed to condensed fumes collected from an oxidized roofing asphalt (BURA Type III) at above 450°F. Additional studies where mice were exposed to oxidized roofing asphalt fume condensates both as a tumor initiator and as a tumor promoter indicate that roofing fume condensate caused tumors as a result of initiation.

MIDDLE DISTILLATES, PETROLEUM: Long-term repeated (lifetime) skin exposure to similar materials has been reported to result in an increase in skin tumors in laboratory rodents. The relevance of these findings to humans is not clear at this time.

HYDROGEN SULFIDE: Hydrogen sulfide gas has an unpleasant odor that diminishes with increased exposure. Eye irritation may occur at levels above 4 ppm. Olfactory fatigue occurs rapidly at levels of 50 ppm or higher. Odor is not a reliable warning property. Respiratory effects include irritation with possible pulmonary edema at levels above 50 ppm. At 500 ppm immediate loss of consciousness and death can occur. NIOSH has determined that 100 ppm hydrogen sulfide is immediately dangerous to life and health (IDLH).

NAPHTHALENE: Severe jaundice, neurotoxicity (kernicterus) and fatalities have been reported in young children and infants as a result of hemolytic anemia from overexposure to naphthalene. Persons with Glucose 6-phosphate dehydrogenase (G6PD) deficiency are more prone to the hemolytic effects of naphthalene. Adverse effects on the kidney have been reported in persons overexposed to naphthalene but these effects are believed to be a consequence of hemolytic anemia, and not a direct effect. Hemolytic anemia has been observed in laboratory animals exposed to naphthalene. Laboratory rodents exposed to naphthalene vapor for 2 years (lifetime studies) developed non-neoplastic and neoplastic tumors and inflammatory lesions of the nasal and respiratory tract. Cataracts and other adverse effects on the eye have been observed in laboratory animals exposed to high levels of naphthalene. Findings from a large number of bacterial and mammalian cell mutation assays have been negative. A few studies have shown chromosomal effects (elevated levels of Sister Chromatid Exchange or chromosomal aberrations) in vitro. Naphthalene has been classified as Possibly Carcinogenic to Humans (2B) by IARC, based on

findings from studies in laboratory animals.

TARGET ORGANS: central nervous system, respiratory system, lungs, skin, eyes, blood,

12. ECOTOXICOLOGICAL INFORMATION

Mobility:

Not classified in terms of mobility in air, soil and water.

Ecotoxicity:

Harmful to aquatic organisms.

Bioaccumulation:

May bioaccumulate in aquatic organisms.

Persistence/Biodegradation:

Not readily biodegradable.

13. DISPOSAL CONSIDERATIONS

Cleanup Considerations:

This material as supplied and by itself, when discarded or disposed of, is not an EPA RCRA hazardous waste according to federal regulations. This material could become a hazardous waste if mixed or contaminated with a hazardous waste or other substance(s). It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations.

14. TRANSPORT INFORMATION

49 CFR 172.101:

DOT:

Transport Information: This material when transported via US commerce is NOT REGULATED by DOT regulations.

Packing group: Not applicable.

DOT reportable quantity (lbs): Not applicable.

15. REGULATORY INFORMATION

US Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b): This product and/or its components are listed on the TSCA Chemical Inventory.

OSHA Hazard Communication Standard:

This product has been evaluated and determined to be hazardous as defined in OSHA's Hazard Communication Standard.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302: This product contains the following component(s) that have been listed on EPA's Extremely Hazardous Substance (EHS) List:

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Asphalt	NA
Water	NA
No. 2 Fuel Oil	NA
Polymer Modifier (SBS or SBR)	NA
Sulfur Compounds	NA
Anionic Emulsifier	NA
Naphthalene	NA
Hydrogen Sulfide	= 500 lb TPQ

SARA Section 304: This product contains the following component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	CERCLA/SARA - Hazardous Substances and their Reportable Quantities
Asphalt	NA
Water	NA
No. 2 Fuel Oil	NA
Polymer Modifier (SBS or SBR)	NA
Sulfur Compounds	NA
Anionic Emulsifier	NA
Naphthalene	= 100 lb final RQ = 45.4 kg final RQ
Hydrogen Sulfide	= 100 lb final RQ = 45.4 kg final RQ

SARA Section 311/312 The following EPA hazard categories apply to this product:

Acute Health Hazard
Chronic Health Hazard

SARA Section 313: This product contains the following components, which if in exceedance of the de minimus threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic Release Reporting (Form R).

Name	CERCLA/SARA 313 Emission reporting:
Asphalt	None
Water	None
No. 2 Fuel Oil	None
Polymer Modifier (SBS or SBR)	None
Sulfur Compounds	None
Anionic Emulsifier	None
Naphthalene	= 0.1 % de minimis concentration
Hydrogen Sulfide	None

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

Asphalt

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	sn 0170

Asphalt

Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic; Flammable
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - third degree
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Present
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

Water

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

No. 2 Fuel Oil

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed

Asphalt

Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

Polymer Modifier (SBS or SBR)

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

Sulfur Compounds

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

Anionic Emulsifier

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.

Asphalt

Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

Naphthalene

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	carcinogen, initial date 4/19/02
New Jersey Right-To-Know:	sn 1322
Pennsylvania Right-To-Know:	Environmental hazard
Massachusetts Right-To Know:	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic; Flammable
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	carcinogen
New Jersey - Environmental Hazardous Substances List:	SN 1322 TPQ 500 lb
Illinois - Toxic Air Contaminants	Present
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	= 1 lb RQ land/water = 100 lb RQ air

Hydrogen Sulfide

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	sn 1017
Pennsylvania Right-To-Know:	Environmental hazard
Massachusetts Right-To Know:	Extraordinarily hazardous
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic; Flammable
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	extraordinarily hazardous
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 1017 TPQ 500 lb
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	= 100 lb RQ air = 100 lb RQ land/water

Asphalt

Canadian Regulatory Information:

Canada DSL/NDSL Inventory: This product and/or its components are listed either on the Domestic Substances List (DSL) or are exempt.

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Water	Uncontrolled product according to WHMIS classification criteria	
Naphthalene	B4, D2A	1 %
Hydrogen Sulfide	A, B1, D1A, D2B	1 %

NOTE: Not Applicable.

16. OTHER INFORMATION

Additional Information: The pronounced and easily-recognized rotten egg odor of hydrogen sulfide gas (H₂S) can be detected at concentrations as low as 0.003-0.13 ppm. Since higher H₂S concentrations (100-200 ppm) cause olfactory fatigue and other hydrocarbon odors can "mask" H₂S, the sense of smell cannot be used as a reliable indicator of H₂S exposure.

Prepared by: Diana Samples-Caudill, Toxicology and Product Safety

The information and recommendations contained herein are based upon tests believed to be reliable. However, Marathon Petroleum Company LP (MPC) does not guarantee their accuracy or completeness nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of the goods, the merchantability of the goods, or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage maybe required. MPC assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

End of Safety Data Sheet