

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009**SECTION 1. IDENTIFICATION**

Product name : Industrial Enamel Paint, Gloss, Safety Red, 425 g

Product code : 892.191

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : CANUTEC (24/7): +1 (613) 996-6666 or/ou *666 (cellular/cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on useRecommended use : Paint
Coatings**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Eye irritation : Category 2A

Skin sensitization : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ systemic toxicity - single exposure : Category 3

Simple Asphyxiant : Category 1

GHS label elements

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**

Version 9.0	Revision Date: 11/29/2017	SDS Number: 408196-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------



Signal Word :

Hazard Statements :

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
May displace oxygen and cause rapid suffocation.

Precautionary Statements :

Prevention:
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Industrial Enamel Paint, Gloss, Safety Red, 425 g

Version 9.0	Revision Date: 11/29/2017	SDS Number: 408196-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	>= 20 - < 30
Propane	74-98-6	>= 10 - < 20
Butane	106-97-8	>= 5 - < 10
n-Butyl acetate	123-86-4	>= 5 - < 10
Isobutyl methyl ketone	108-10-1	>= 1 - < 5
2-(Propyloxy)ethanol	2807-30-9	>= 1 - < 5
2-Methoxy-1-methylethyl acetate	108-65-6	>= 1 - < 5
Pentan-2-one	107-87-9	>= 1 - < 5
Isobutyl acetate	110-19-0	>= 1 - < 5
Ethylbenzene	100-41-4	>= 0.1 - < 1
Cobalt bis(ethylhexanoate)	Not Assigned	>= 0.1 - < 1
Zirconium octoate	22464-99-9	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. Get medical attention.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.

Industrial Enamel Paint, Gloss, Safety Red, 425 g

Version 9.0 Revision Date: 11/29/2017 SDS Number: 408196-00008 Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

II

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
Prolonged or repeated contact may dry skin and cause irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009**II****Environmental precautions**

- : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

- : Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE**Technical measures**

- : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

- : Use with local exhaust ventilation. Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential

Advice on safe handling

- : Do not spray on an open flame or other ignition source.

Do not get on skin or clothing.
Do not breathe vapors or spray mist.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage

- : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**
Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Keep cool. Protect from sunlight.

Materials to avoid

: Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable solids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which in contact with water emit flammable gases
 Explosives

Recommended storage temperature : 49 °C

Further information on storage stability : Protect from frost, heat and sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	500 ppm 1,190 mg/m ³	CA QC OEL
		STEV	1,000 ppm 2,380 mg/m ³	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
		TWA	800 ppm	CA ON OEL
		STEL	1,000 ppm	ACGIH
n-Butyl acetate	123-86-4	STEL	200 ppm	CA AB OEL

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**
Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

			950 mg/m ³	
		TWA	150 ppm 713 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	150 ppm 713 mg/m ³	CA QC OEL
		STEV	200 ppm 950 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Isobutyl methyl ketone	108-10-1	TWA	50 ppm 205 mg/m ³	CA AB OEL
		STEL	75 ppm 307 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWAEV	50 ppm 205 mg/m ³	CA QC OEL
		STEV	75 ppm 307 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
2-(Propyloxy)ethanol	2807-30-9	TWA	25 ppm 110 mg/m ³	CA ON OEL
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWA	50 ppm 270 mg/m ³	CA ON OEL
Pentan-2-one	107-87-9	STEL	250 ppm 881 mg/m ³	CA AB OEL
		TWA	200 ppm 705 mg/m ³	CA AB OEL
		TWA	150 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		TWAEV	150 ppm 530 mg/m ³	CA QC OEL
		STEL	150 ppm	ACGIH
Isobutyl acetate	110-19-0	TWA	150 ppm 713 mg/m ³	CA AB OEL
		TWA	150 ppm	CA BC OEL
		TWAEV	150 ppm 713 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m ³	CA AB OEL
		STEL	125 ppm 543 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**
Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

		STEV	125 ppm 543 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
Zirconium octoate	22464-99-9	TWA	5 mg/m ³ (Zirconium)	CA AB OEL
		STEL	10 mg/m ³ (Zirconium)	CA AB OEL
		TWAEV	5 mg/m ³ (Zirconium)	CA QC OEL
		STEV	10 mg/m ³ (Zirconium)	CA QC OEL
		TWA	5 mg/m ³ (Zirconium)	CA BC OEL
		STEL	10 mg/m ³ (Zirconium)	CA BC OEL
		TWA	5 mg/m ³ (Zirconium)	ACGIH
		STEL	10 mg/m ³ (Zirconium)	ACGIH

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI
Isobutyl methyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

Engineering measures

: Minimize workplace exposure concentrations.
 Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential
 Use with local exhaust ventilation.
 Dust formation may be relevant in the processing of this pro-

Industrial Enamel Paint, Gloss, Safety Red, 425 g

Version 9.0	Revision Date: 11/29/2017	SDS Number: 408196-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

duct. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection Material	: Protective gloves
Remarks	: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
Eye protection	: Wear the following personal protective equipment: Safety goggles
Skin and body protection	: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Hygiene measures	: Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Color	: red
Odor	: solvent

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**

Version 9.0	Revision Date: 11/29/2017	SDS Number: 408196-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-42 °C
Flash point	:	-35 °C Active ingredient
Evaporation rate	:	5.6
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	16 % (V)
Lower explosion limit / Lower flammability limit	:	1 % (V)
Vapor pressure	:	Not applicable
Relative vapor density	:	4.6
Relative density	:	No data available
Density	:	0.78 g/cm ³
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
------------	---	----------------------------------------

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**

Version 9.0 Revision Date: 11/29/2017 SDS Number: 408196-00008 Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: > 40 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

Ingredients:**Acetone:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 40 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg

Propane:

Acute inhalation toxicity	: LC50 (Rat): > 800000 ppm
---------------------------	----------------------------

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Exposure time: 15 min
Test atmosphere: gas

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: vapor

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Isobutyl methyl ketone:

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg
Acute inhalation toxicity : LC50 (Rat): 11.6 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

2-(Propyloxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 3,089 mg/kg
Acute dermal toxicity : LD50 (Rabbit): 1,337 mg/kg

2-Methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC0 (Rat): 9.48 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Pentan-2-one:

Acute oral toxicity : LD50 (Rat): 1,600 - 3,200 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l
Exposure time: 4 h

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Test atmosphere: vapor
Method: OECD Test Guideline 436
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Isobutyl acetate:

Acute oral toxicity : LD50 (Rat): 13,413 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 30 mg/l
Exposure time: 6 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 17,400 mg/kg

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17.2 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Cobalt bis(ethylhexanoate):

Acute oral toxicity : LD50 (Rat): 3,129 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

Zirconium octoate:

Acute oral toxicity : LD50 (Rat): 2,043 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009**Ingredients:****Acetone:**

Assessment: Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:Species: Rabbit
Result: No skin irritation

Assessment: Repeated exposure may cause skin dryness or cracking.

Isobutyl methyl ketone:Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Assessment: Repeated exposure may cause skin dryness or cracking.

2-(Propyloxy)ethanol:Species: Rabbit
Result: No skin irritation**2-Methoxy-1-methylethyl acetate:**Species: Rabbit
Result: No skin irritation**Pentan-2-one:**Species: Guinea pig
Method: OECD Test Guideline 404
Result: No skin irritation**Isobutyl acetate:**

Assessment: Repeated exposure may cause skin dryness or cracking.

Cobalt bis(ethylhexanoate):

Result: No skin irritation

Zirconium octoate:Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009**Ingredients:****Acetone:**

Species: Rabbit
Result: Irritation to eyes, reversing within 21 days
Method: OECD Test Guideline 405

n-Butyl acetate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Isobutyl methyl ketone:

Result: Irritation to eyes, reversing within 21 days
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

2-(Propyloxy)ethanol:

Species: Rabbit
Result: Irritation to eyes, reversing within 21 days

2-Methoxy-1-methylethyl acetate:

Species: Rabbit
Result: No eye irritation

Pentan-2-one:

Species: Rabbit
Result: Irritation to eyes, reversing within 7 days

Isobutyl acetate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
Remarks: Based on data from similar materials

Ethylbenzene:

Species: Rabbit
Result: No eye irritation

Zirconium octoate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**

Version 9.0	Revision Date: 11/29/2017	SDS Number: 408196-00008	Date of last issue: 06/27/2017
			Date of first issue: 12/30/2009

Respiratory sensitization

Not classified based on available information.

Ingredients:**Acetone:**

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

n-Butyl acetate:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Isobutyl methyl ketone:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

2-(Propyloxy)ethanol:

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

2-Methoxy-1-methylethyl acetate:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Isobutyl acetate:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Ethylbenzene:

Test Type: Human repeat insult patch test (HRIPT)
Routes of exposure: Skin contact
Result: negative

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

||

Cobalt bis(ethylhexanoate):

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse

Method: OECD Test Guideline 429

Result: positive

Assessment: Probability or evidence of skin sensitization in humans

Zirconium octoate:

Test Type: Maximization Test

Routes of exposure: Skin contact

Species: Guinea pig

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Acetone:**Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negativeGenotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Hamster
Application Route: Intraperitoneal injection
Result: negative**Propane:**Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negativeGenotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative**Butane:**Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negativeGenotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Isobutyl methyl ketone:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

2-(Propyloxy)ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Pentan-2-one:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Result: negative

Isobutyl acetate:

Genotoxicity in vitro

: Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negativeTest Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo

: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials**Ethylbenzene:**

Genotoxicity in vitro

: Test Type: Chromosome aberration test in vitro
Result: negativeTest Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo

: Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo
Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative**Zirconium octoate:**

Genotoxicity in vitro

: Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo

: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials**Carcinogenicity**

Suspected of causing cancer.

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**

Version 9.0 Revision Date: 11/29/2017 SDS Number: 408196-00008 Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Ingredients:**Acetone:**

Species: Mouse
Application Route: Skin contact
Exposure time: 1 Years
Result: negative

Isobutyl methyl ketone:

Species: Rat
Application Route: inhalation (vapor)
Exposure time: 2 Years
Method: OECD Test Guideline 451
Result: positive
Remarks: The mechanism or mode of action may not be relevant in humans.

Species: Mouse
Application Route: inhalation (vapor)
Exposure time: 2 Years
Method: OECD Test Guideline 451
Result: positive
Remarks: The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

2-Methoxy-1-methylethyl acetate:

Species: Rat
Application Route: inhalation (vapor)
Exposure time: 2 Years
Result: negative
Remarks: Based on data from similar materials

Ethylbenzene:

Species: Rat
Application Route: Inhalation
Exposure time: 104 weeks
Result: positive
Remarks: The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Cobalt bis(ethylhexanoate):

Species: Rat
Application Route: Inhalation
Exposure time: 105 weeks
Result: positive
Remarks: Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009**Content****Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

Ingredients:**Acetone:**

Effects on fertility	:	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Mouse Result: negative

Propane:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
Effects on fetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative

Butane:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
Effects on fetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative

n-Butyl acetate:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Method: OECD Test Guideline 416
----------------------	---	---------------------------------------------------------------------------------------------------------------------------------------------------

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Isobutyl methyl ketone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: inhalation (vapor)
Result: negative

2-(Propyloxy)ethanol:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: inhalation (vapor)
Result: negative

2-Methoxy-1-methylethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Pentan-2-one:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 421
Result: negative

Isobutyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Method: OPPTS 870.3800
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 415
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Cobalt bis(ethylhexanoate):

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: positive

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

Zirconium octoate:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**

Version 9.0	Revision Date: 11/29/2017	SDS Number: 408196-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT-single exposure

May cause drowsiness or dizziness.

Ingredients:**Acetone:**

Assessment: May cause drowsiness or dizziness.

Propane:

Assessment: May cause drowsiness or dizziness.

Butane:

Assessment: May cause drowsiness or dizziness.

n-Butyl acetate:

Assessment: May cause drowsiness or dizziness.

Isobutyl methyl ketone:

Assessment: May cause respiratory irritation.

2-Methoxy-1-methylethyl acetate:

Assessment: May cause drowsiness or dizziness.

Isobutyl acetate:

Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Ingredients:**Ethylbenzene:**

Routes of exposure: inhalation (vapor)

Target Organs: Auditory system

Assessment: Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity**Ingredients:****Acetone:**

Species: Rat

LOAEL: 1,700 mg/kg

Application Route: Ingestion

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**

Version 9.0	Revision Date: 11/29/2017	SDS Number: 408196-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Exposure time: 90 Days

Propane:

Species: Rat
NOAEL: 7.214 mg/l
Application Route: inhalation (gas)
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

Butane:

Species: Rat
NOAEL: 9000 ppm
Application Route: inhalation (gas)
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

n-Butyl acetate:

Species: Rat
NOAEL: 2.4 mg/l
Application Route: inhalation (vapor)
Exposure time: 90 Days

Isobutyl methyl ketone:

Species: Rat
NOAEL: 1,840 mg/m³
Application Route: inhalation (vapor)
Exposure time: 13 Weeks

2-(Propyloxy)ethanol:

Species: Rat
LOAEL: 195 mg/kg
Application Route: Ingestion
Exposure time: 6 Weeks

2-Methoxy-1-methylethyl acetate:

Species: Rat
NOAEL: > 1,000 mg/kg
Application Route: Ingestion
Exposure time: 41 - 45 Days
Method: OECD Test Guideline 422

Species: Mouse
NOAEL: 1.62 mg/l
Application Route: inhalation (vapor)
Exposure time: 2 y
Remarks: Based on data from similar materials

Species: Rabbit
NOAEL: > 1,838 mg/kg

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Application Route: Skin contact
Exposure time: 90 Days
Remarks: Based on data from similar materials

Isobutyl acetate:

Species: Rat
NOAEL: 316 mg/kg
Application Route: Ingestion
Exposure time: 92 Days
Remarks: Based on data from similar materials

Ethylbenzene:

Species: Rat, female
LOAEL: 75 ppm
Application Route: inhalation (vapor)
Exposure time: 104 Weeks

Zirconium octoate:

Species: Rat
NOAEL: 300 mg/kg
Application Route: Ingestion
Exposure time: 91 - 93 Days
Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Ingredients:**Ethylbenzene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Acetone:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 6,210 - 8,120 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates (Chron- : NOEC (Daphnia magna (Water flea)): 1,106 - 2,212 mg/l
Exposure time: 28 d

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Chronic toxicity)

n-Butyl acetate:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 18 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia sp. (Water flea)): 44 mg/l Exposure time: 48 h
Toxicity to algae	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
	NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 23.2 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	: IC50 (Tetrahymena pyriformis): 356 mg/l Exposure time: 40 h

Isobutyl methyl ketone:

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 179 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 200 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 30 mg/l Exposure time: 21 d
Toxicity to microorganisms	: EC10 (Pseudomonas putida): 275 mg/l Exposure time: 16 h

2-(Propyloxy)ethanol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 5,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 5,000 mg/l Exposure time: 48 h

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Toxicity to algae	: NOEC (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to microorganisms	: IC50: > 1,000 mg/l Exposure time: 16 h

2-Methoxy-1-methylethyl acetate:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 500 mg/l Exposure time: 48 h
Toxicity to algae	: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
	NOEC (Pseudokirchneriella subcapitata (algae)): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): >= 100 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	: EC10: > 1,000 mg/l Exposure time: 0.5 h

Pentan-2-one:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 1,240 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 110 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): > 150 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

NOEC (Pseudokirchneriella subcapitata (green algae)): 73.77 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Isobutyl acetate:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 17 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 25 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 370 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 95 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (Pseudomonas putida): 200 mg/l
Exposure time: 16 h

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l
Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 5.4 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.96 mg/l
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 209

Zirconium octoate:

Industrial Enamel Paint, Gloss, Safety Red, 425 g

Version 9.0 Revision Date: 11/29/2017 SDS Number: 408196-00008 Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 0.17 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: No toxicity at the limit of solubility.
Toxicity to algae	:	EC50 (Desmodesmus subspicatus (green algae)): 49.3 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
		EC10 (Desmodesmus subspicatus (green algae)): 32 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 25 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): 112.1 mg/l Exposure time: 17 h Method: DIN 38 412 Part 8 Remarks: Based on data from similar materials

Persistence and degradability

Ingredients:

Acetone:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 91 % Exposure time: 28 d
------------------	---	-------------------------------------------------------------------------------

Propane:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 100 % Exposure time: 385.5 h Remarks: Based on data from similar materials
------------------	---	------------------------------------------------------------------------------------------------------------------------------------

Butane:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 100 % Exposure time: 385.5 h Remarks: Based on data from similar materials
------------------	---	------------------------------------------------------------------------------------------------------------------------------------

n-Butyl acetate:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 83 %
------------------	---	--------------------------------------------------------

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Exposure time: 28 d
Method: OECD Test Guideline 301D

Isobutyl methyl ketone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

2-(Propyloxy)ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 20 d

2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Pentan-2-one:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Isobutyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 20 d

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

Cobalt bis(ethylhexanoate):

Biodegradability : Result: Readily biodegradable.
Biodegradation: 60 %
Exposure time: 10 d

Zirconium octoate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 99 %
Exposure time: 28 d
Method: OECD Test Guideline 301E
Remarks: Based on data from similar materials

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009**Bioaccumulative potential****Ingredients:****Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.24

Butane:

Partition coefficient: n-octanol/water : log Pow: 2.31

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

Isobutyl methyl ketone:

Partition coefficient: n-octanol/water : log Pow: 1.9

2-(Propyloxy)ethanol:

Partition coefficient: n-octanol/water : log Pow: 0.673

2-Methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.2

Pentan-2-one:

Partition coefficient: n-octanol/water : log Pow: 0.857

Isobutyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

Ethylbenzene:Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): < 100
Remarks: Based on data from similar materials

Partition coefficient: n-octanol/water : log Pow: 3.6

Mobility in soil

No data available

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**

Version 9.0 Revision Date: 11/29/2017 SDS Number: 408196-00008 Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Domestic regulation**TDG**

UN number : UN 1950
Proper shipping name : AEROSOLS

Class

Packing group : Not assigned by regulation

Labels

ERG Code : 2.1

Marine pollutant : 126

no

SECTION 15. REGULATORY INFORMATION**Volatile organic compounds
(VOC) content**

VOC content: 72.52 % / 568.72 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA ON OEL	: Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA BC OEL / STEL	: short-term exposure limit
CA ON OEL / TWA	: Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	: Time-weighted average exposure value
CA QC OEL / STEV	: Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan);

**Industrial Enamel Paint, Gloss, Safety Red,
425 g**Version
9.0Revision Date:
11/29/2017SDS Number:
408196-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/29/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8