



THE INTERNATIONAL GROUP, INC.

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** 0200 Series Products (Petrofibe®)  
**Other means of identification** See page 8  
**SDS number** 0200 Series (928960)\_USA\_English  
**Recommended use** Further processing , Misc. multiple uses  
**Recommended restrictions** None known.

### Manufacturer/Importer/Supplier/Distributor information

**Company Name** The International Group Inc.  
**Address** 50 Salome Dr.  
Toronto  
ON, M1S2A8, CA  
**Telephone** 001-(416)-293-4151  
**E-mail** -  
**Contact person** -  
**Emergency phone number** 001-(416)-293-4151  
001-(800)-561-3509  
**CHEMTREC (North America)** 001-(800)-424-9300

## 2. Hazard(s) identification

**Physical hazards** Not classified.  
**Health hazards** Not classified.  
**OSHA defined hazards** Not classified.

This product does not meet the criteria for classification according to OSHA Hazard Communication Standard (OSHA GHS).

### Label elements

**Hazard symbol** None.  
**Signal word** None.  
**Hazard statement** The product does not meet the criteria for classification.  
**Precautionary statement**  
**Prevention** Observe good industrial hygiene practices.  
**Response** Wash hands after handling.  
**Storage** Store away from incompatible materials.  
**Disposal** Dispose of waste and residues in accordance with local authority requirements.

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** None.

## 3. Composition/information on ingredients

### Substances

Chemical name	Common name and synonyms	CAS number	%
Foots oil		64742-67-2	100

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

<b>Inhalation</b>	Solid: No specific first aid measures noted. If fumes from heated product are inhaled: Move to fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Solid: No specific first aid measures noted. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn.
<b>Eye contact</b>	Solid: No specific first aid measures noted. Exposure to fumes, vapors or smoke of over heated product can result in irritation of eyes. Direct contact of molten material will cause injury and burns. When handling of molten product eye shield must be worn at all times. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Administer prompt first aid measures. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Solid: No specific first aid measures noted. Not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Contact with hot product may cause severe burns. Get medical attention immediately.
<b>Most important symptoms/effects, acute and delayed</b>	Eye and skin contact: When heated, contact with molten product can cause injury and burns.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically.
<b>General information</b>	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water on molten material: Explosion hazard could result.
<b>Specific hazards arising from the chemical</b>	By heating and fire, irritating vapors/gases may be formed. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Do not direct water at source of leak or safety devices as icing may occur. Use water spray to cool unopened containers. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Handle as a thermoplastic. With molten spills, allow the material to solidify and cool. Keep material out of sewers and watercourses by diking or impounding. Recover and place into appropriate containers for recycling or disposal, according to prevailing local, state and federal laws.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Allow material to solidify, and scrape up. Following product recovery, flush area with water.  Small Spills: Where possible allow molten material to solidify naturally.  Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water.

## 7. Handling and storage

### Precautions for safe handling

When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers. Do not handle until all safety precautions have been read and understood. Heat only in areas with appropriate exhaust ventilation. Do not breathe fume/mist/vapors. Avoid contact with molten material. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment. Wash contaminated clothing before reuse. The material is a solid at room temperature exhibiting elevated temperature softening characteristics. Above its softening point, the material liquefies and flows more readily as the temperature increases. The material may be used as a hot liquid for application purposes and requires caution in handling.

### Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

## 8. Exposure controls/personal protection

### Occupational exposure limits

No exposure limits noted for ingredient(s).

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear approved safety goggles. Wear a face shield when working with molten material.

#### Skin protection

##### Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

#### Skin protection

##### Other

The material may be utilized in molten form. Proper protective splash resistant clothing, thermal gloves, splash resistant shoes, and eye shields must be worn to prevent injury. Use molten material in well ventilated areas. When working in confined areas, use of appropriate respiratory gear is recommended.

#### Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

#### Physical state

Solid.

#### Form

Soft solid.

#### Color

Off-white to brown.

### Odor

Petroleum.

### Odor threshold

No data available.

### pH

Not applicable.

### Melting point/freezing point

86 - 194 °F (30 - 90 °C)

### Initial boiling point and boiling range

> 572 °F (> 300 °C)

### Flash point

> 302.0 °F (> 150.0 °C) ASTM D-93

### Evaporation rate

< 0.01 (Butyl acetate = 1)

### Flammability (solid, gas)

Will support a flame above flash point.

## Upper/lower flammability or explosive limits

<b>Flammability limit - lower (%)</b>	No data available.
<b>Flammability limit - upper (%)</b>	No data available.
<b>Explosive limit - lower (%)</b>	0.9 % v/v
<b>Explosive limit - upper (%)</b>	7 % v/v
<b>Vapor pressure</b>	< 0.01 mm Hg (77 °F/25 °C)
<b>Vapor density</b>	> 5 (Air = 1)
<b>Relative density</b>	0.85 - 0.92 (77 °F/25 °C)
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	< 0.1 % (68 °F/20 °C)
<b>Partition coefficient (n-octanol/water)</b>	No data available.
<b>Auto-ignition temperature</b>	No data available.
<b>Decomposition temperature</b>	No data available.
<b>Viscosity</b>	No data available.
<b>Other information</b>	
<b>Partition coefficient (oil/water)</b>	< 0.01
<b>Percent volatile</b>	< 1 % v/v

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Decomposition of this product can generate carbon dioxide, carbon monoxide and other products such as aldehydes and ketones depending on conditions of oxidation.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Not relevant at normal room temperatures. When heated, irritating vapors may be formed. Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.
<b>Skin contact</b>	Health injuries are not known or expected under normal use. Molten material will produce thermal burns.
<b>Eye contact</b>	Health injuries are not known or expected under normal use. Molten material will produce thermal burns.
<b>Ingestion</b>	Health injuries are not known or expected under normal use. Contact with hot material can cause thermal burns which may result in permanent damage.

**Symptoms related to the physical, chemical and toxicological characteristics** Eye and skin contact: Contact with molten material may cause thermal burns.

### Information on toxicological effects

<b>Acute toxicity</b>	Not expected to be acutely toxic.
<b>Skin corrosion/irritation</b>	Thermal burn hazard - contact with hot material may cause thermal burns.
<b>Serious eye damage/eye irritation</b>	Not classified. Direct contact of molten product to the eyes will cause thermal burns and eye injury.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not classified.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	Not classified.

**Carcinogenicity** Not expected to be hazardous by OSHA criteria.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Not listed.

**NTP Report on Carcinogens**

Not listed.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Reproductive toxicity** Not classified.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Solid product: Not likely, due to the form of the product.

**Chronic effects** Not expected to be hazardous by OSHA criteria. Exposure to vapors, fumes, or smoke from molten material handled in confined areas can produce irritation of respiratory tracts, and possible physical discomfort to sensitive individuals.

**Further information** None.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Mobility in soil** The product is insoluble in water.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

### DOT

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**General information** This product is not regulated as dangerous goods for solid. Shipped hot molten product requires a class 9 "HOT" with statement: Elevated temperature material, liquid, N.O.S. 9, UN3257, III (WAX)



Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	18-August-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 1 Flammability: 1 Physical hazard: 0

### NFPA ratings



### Disclaimer

This material safety data sheet is offered for your information only. We believe the statements, technical information and recommendations contained here in are reliable, but are given without warranty or guarantee of any kind, expressed or implied. THE INTERNATIONAL GROUP, INC. assumes no responsibility for any loss, damage or expense, direct or consequential, arising from the use of our material. It is the responsibility of the user to determine the suitability and completeness of such information for the required use or application. We do not assume any legal responsibility for nor do we give permission, inducement or recommendation to practice any patented invention without a license. Further, it is the user's obligation to utilize this material in full compliance with all health, safety and environmental regulations.

**PRODUCT  
NUMBER**

---

0201A  
0202C  
0205A  
0205D  
0208A  
0208B  
0211A  
0212A  
0217A  
0218A  
0225A  
0260A  
0260U  
0293A  
R-6429A