



THE INTERNATIONAL GROUP, INC.

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

<b>Name of the substance</b>	<b>0300 Series Products (Petax®)</b>
<b>Identification number</b>	649-254-00-X (Index number)
<b>Registration number</b>	01-2119490412-42-0014
<b>Synonyms</b>	See page 10
<b>SDS number</b>	0300 Series (921275)_Europe_English
<b>Issue date</b>	11-March-2015
<b>Version number</b>	02
<b>Revision date</b>	20-April-2015
<b>Supersedes date</b>	11-March-2015

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Identified uses</b>	Various end uses e.g. pharmaceutical excipient, personal care/cosmetics, food contact coatings, additive for wax blends, use in adhesives etc.
<b>Uses advised against</b>	None known.

### 1.3. Details of the supplier of the safety data sheet

<b>Company name</b>	The International Group Inc.
<b>Address</b>	50 Salome Dr. Toronto ON, M1S2A8, CA
<b>Telephone</b>	001-(416)-293-4151
<b>E-mail</b>	-
<b>Contact person</b>	-

<b>1.4. Emergency telephone number</b>	001-(416)-293-4151
	001-(800)-561-3509
<b>CHEMTREC (North America)</b>	001-(800)-424-9300

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This substance is classified according to Regulation (EC) 1272/2008 (CLP Regulation) and Directive 67/548/EEC and their amendments respectively.

#### Classification according to Regulation (EC) No 1272/2008 as amended

#### Hazard summary

<b>Physical hazards</b>	Not classified for physical hazards.
<b>Health hazards</b>	Not classified for health hazards. However, occupational exposure to the mixture or substance(s) may cause adverse health effects.
<b>Environmental hazards</b>	Not classified for hazards to the environment.
<b>Specific hazards</b>	None known.
<b>Main symptoms</b>	Eye and skin contact: Contact with molten material may cause thermal burns.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

<b>Contains:</b>	Petrolatum
<b>Hazard pictograms</b>	None.
<b>Signal word</b>	None.
<b>Hazard statements</b>	The product does not meet the criteria for classification.

#### Precautionary statements

<b>Prevention</b>	Observe good industrial hygiene practices.
<b>Response</b>	Wash hands after handling.

<b>Storage</b>	Store away from incompatible materials.
<b>Disposal</b>	Dispose of waste and residues in accordance with local authority requirements.
<b>Supplemental label information</b>	None.
<b>2.3. Other hazards</b>	None known.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

##### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Petrolatum	100	8009-03-8 232-373-2	01-2119490412-42-0014	649-254-00-X	
<b>Classification:</b>	<b>DSD:</b> -				N
	<b>CLP:</b> Repr. 2;H361, STOT RE 1;H372				N

##### List of abbreviations and symbols that may be used above

Notes: For further information please refer to Section 16.

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### SECTION 4: First aid measures

**General information** If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Solid: No specific first aid measures noted. If fumes from heated heated product are inhaled: Move to fresh air. Call a POISON CENTRE or doctor/physician if you feel unwell.
<b>Skin contact</b>	Solid: No specific first aid measures noted. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn.
<b>Eye contact</b>	Solid: No specific first aid measures noted. Exposure to fumes, vapors or smoke of over heated product can result in irritation of eyes. Direct contact of molten material will cause injury and burns. When handling of molten product eye shield must be worn at all times. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Administer prompt first aid measures. Get medical attention immediately.
<b>Ingestion</b>	Solid: No specific first aid measures noted. Not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Contact with hot product may cause severe burns. Get medical attention immediately.

**4.2. Most important symptoms and effects, both acute and delayed** Eye and skin contact: When heated, contact with molten product can cause injury and burns.

**4.3. Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically.

### SECTION 5: Firefighting measures

**General fire hazards** No unusual fire or explosion hazards noted.

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water on molten material: Explosion hazard could result.

**5.2. Special hazards arising from the substance or mixture** By heating and fire, irritating vapours/gases may be formed. During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

<b>Special protective equipment for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Special fire fighting procedures</b>	In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Do not direct water at source of leak or safety devices as icing may occur. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Keep unnecessary personnel away. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8.

**For emergency responders** Wear appropriate protective equipment and clothing during clean-up.

**6.2. Environmental precautions** Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water.

**6.3. Methods and material for containment and cleaning up** Handle as a thermoplastic. With molten spills, allow the material to solidify and cool. Keep material out of sewers and watercourses by diking or impounding. Recover and place into appropriate containers for recycling or disposal, according to prevailing local, regional and national laws.

Large Spills: Stop leak if you can do so without risk. Use water spray to reduce vapours or divert vapour cloud drift. Isolate area until gas has dispersed. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Allow material to solidify, and scrape up. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Where possible allow molten material to solidify naturally.

Never return spills to original containers for re-use.

**6.4. Reference to other sections** For personal protection, see section 8. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling** When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers. Do not handle until all safety precautions have been read and understood. Heat only in areas with appropriate exhaust ventilation. Do not breathe fume/mist/vapors. Avoid contact with molten material. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment. Wash contaminated clothing before reuse. The material is a solid at room temperature exhibiting elevated temperature softening characteristics. Above its softening point, the material liquefies and flows more readily as the temperature increases. The material may be used as a hot liquid for application purposes and requires caution in handling.

**7.2. Conditions for safe storage, including any incompatibilities** Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS). When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

**7.3. Specific end use(s)** When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Belgium. Exposure Limit Values.

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.

##### Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m <sup>3</sup>

##### Czech Republic. OELs. Government Decree 361

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	Ceiling	10 mg/m <sup>3</sup>	Aerosol
	TWA	5 mg/m <sup>3</sup>	Aerosol

**Denmark. Exposure Limit Values**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	TLV	1 mg/m <sup>3</sup>	Mist.

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m <sup>3</sup>	Mist.

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	Ceiling	5 mg/m <sup>3</sup>	Mist.

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	TWA	1 mg/m <sup>3</sup>	Mist.

**Ireland. Occupational Exposure Limits**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.

**Italy. OELs**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m <sup>3</sup>

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements (Hygiene Norm HN 23:2007)**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	STEL	3 mg/m <sup>3</sup>	Fume and mist.
	TWA	1 mg/m <sup>3</sup>	Fume and mist.

**Netherlands. OELs (binding)**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m <sup>3</sup>	Mist.

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	TLV	1 mg/m <sup>3</sup>	Mist.

**Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m <sup>3</sup>	Aerosol
	TWA	5 mg/m <sup>3</sup>	Aerosol

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m <sup>3</sup>	Aerosol
	TWA	5 mg/m <sup>3</sup>	Aerosol

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m <sup>3</sup>
	TWA	5 mg/m <sup>3</sup>

**Slovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemical agents**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	TWA	1 mg/m <sup>3</sup>	Fume and mist.
		5 ppm	Fume and mist.

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	STEL	3 mg/m <sup>3</sup>	Fume and mist.
		15 ppm	Fume and mist.

**Spain. Occupational Exposure Limits**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.

**Sweden. Occupational Exposure Limit Values**

Components	Type	Value	Form
Petrolatum (CAS 8009-03-8)	STEL	3 mg/m <sup>3</sup>	Mist.
	TWA	1 mg/m <sup>3</sup>	Mist.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no-effect level (DNEL)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**8.2. Exposure controls**

**Appropriate engineering controls** Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**General information** Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The material may be utilized in molten form. Proper protective splash resistant clothing, thermal gloves, splash resistant shoes, and eye shields must be worn to prevent injury. Use molten material in well ventilated areas. When working in confined areas, use of appropriate respiratory gear is recommended.

**Eye/face protection** Wear approved safety goggles. Wear a face shield when working with molten material.

**Skin protection**

**- Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**- Other** Wear appropriate chemical resistant clothing to prevent any possibility of skin contact.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Environmental exposure controls** Contain spills and prevent releases and observe national regulations on emissions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

**Physical state** Solid, Liquid.  
**Form** Soft solid.  
**Colour** White to yellow.  
**Odour** None to slight petroleum odor.  
**Odour threshold** No data available.  
**pH** Not applicable.  
**Melting point/freezing point** 30 - 90 °C (86 - 194 °F)  
**Initial boiling point and boiling range** > 300 °C (> 572 °F)  
**Flash point** > 165,0 °C (> 329,0 °F) ASTM D-92  
**Evaporation rate** < 0,01 (Butyl acetate = 1)  
**Flammability (solid, gas)** Will support a flame above flash point.

#### Upper/lower flammability or explosive limits

**Flammability limit - lower (%)** No data available.  
**Flammability limit - upper (%)** No data available.  
**Explosive limit - lower (%)** 0,9 %  
**Explosive limit - upper (%)** 7 %  
**Vapour pressure** < 0,01 mm Hg (77 °F/25 °C)  
**Vapour density** > 5 (Air = 1)  
**Relative density** 0,85 - 0,92 (77 °F/25 °C)  
**Solubility(ies)** < 0,1 % (68 °F/20 °C)  
**Partition coefficient (n-octanol/water)** No data available.  
**Auto-ignition temperature** No data available.  
**Decomposition temperature** No data available.  
**Viscosity** No data available.  
**Explosive properties** Not explosive.  
**Oxidizing properties** Not oxidizing.

### 9.2. Other information

**Partition coefficient (oil/water)** < 0,01  
**Percent volatile** < 1 %

## SECTION 10: Stability and reactivity

**10.1. Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.  
**10.2. Chemical stability** Material is stable under normal conditions.  
**10.3. Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.  
**10.4. Conditions to avoid** Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.  
**10.5. Incompatible materials** Strong oxidising agents.  
**10.6. Hazardous decomposition products** Decomposition of this product can generate carbon dioxide, carbon monoxide and other products such as aldehydes and ketones depending on conditions of oxidation.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

#### Information on likely routes of exposure

**Inhalation** Not relevant at normal room temperatures. When heated, irritating vapours may be formed. Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.

<b>Skin contact</b>	Health injuries are not known or expected under normal use. Molten material will produce thermal burns.
<b>Eye contact</b>	Health injuries are not known or expected under normal use. Molten material will produce thermal burns.
<b>Ingestion</b>	Health injuries are not known or expected under normal use. Contact with hot material can cause thermal burns which may result in permanent damage.
<b>Symptoms</b>	Eye and skin contact: Contact with molten material may cause thermal burns.

#### 11.1. Information on toxicological effects

<b>Acute toxicity</b>	Not expected to be acutely toxic.
<b>Skin corrosion/irritation</b>	Thermal burn hazard - contact with hot material may cause thermal burns.
<b>Serious eye damage/eye irritation</b>	Not classified. Direct contact of molten product to the eyes will cause thermal burns and eye injury.
<b>Respiratory sensitisation</b>	Not classified.
<b>Skin sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Germ cell mutagenicity</b>	Not classified.
<b>Carcinogenicity</b>	Not expected to cause cancer.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Petrolatum (CAS 8009-03-8) 3 Not classifiable as to carcinogenicity to humans.

<b>Reproductive toxicity</b>	Not classified.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Solid product: Not likely, due to the form of the product.
<b>Mixture versus substance information</b>	No information available.
<b>Other information</b>	None.

### SECTION 12: Ecological information

<b>12.1. Toxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
<b>12.2. Persistence and degradability</b>	No data is available on the degradability of this product.
<b>12.3. Bioaccumulative potential</b>	No data available.
<b>Partition coefficient n-octanol/water (log Kow)</b>	No data available.
<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	No data available.
<b>12.5. Results of PBT and vPvB assessment</b>	Not a PBT or vPvB substance or mixture.
<b>12.6. Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. 16 03 06
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

Not regulated as dangerous goods.

### RID

Not regulated as dangerous goods.

### ADN

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

**14.7. Transport in bulk** Not applicable.

### according to Annex II of MARPOL 73/78 and the IBC

#### Code

#### General information

This product is not regulated as dangerous goods for solid and molten product shipped under 212 °F/100 °C. Hot molten product shipped over 212 °F/100 °C requires a class 9 "HOT" with statement: Elevated temperature material, liquid, N.O.S. 9, UN3257, III (WAX).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**

Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended**

Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended**

Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended**

Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

#### Restrictions on use

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Petrolatum (CAS 8009-03-8)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended**

Petrolatum (CAS 8009-03-8)

**Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended**

Petrolatum (CAS 8009-03-8)

#### Other EU regulations

**Directive 2012/18/EU on major accident hazards involving dangerous substances**

Not listed.

**Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work**

Petrolatum (CAS 8009-03-8)

**Directive 94/33/EC on the protection of young people at work**

Petrolatum (CAS 8009-03-8)

#### Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

#### National regulations

Follow national regulation for work with chemical agents.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

**List of abbreviations**

DNEL: Derived No-Effect Level.  
PNEC: Predicted No-Effect Concentration.  
LD50: Lethal Dose, 50%.  
LC50: Lethal Concentration, 50%.  
TWA: Time weighted average.  
STEL: Short term exposure limit.  
DOT: Department of Transportation.  
IATA: International Air Transport Association.  
IMDG: International Maritime Dangerous Goods.  
OSHA: Occupational Safety and Health Administration.  
CAS: Chemical Abstracts Service.  
WHMIS: Workplace Hazardous Materials Information System.  
HMIS: Hazardous Materials Identification System.  
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.  
CLP: Regulation No. 1272/2008.  
DSD: Directive 67/548/EEC.  
Notes relating to the identification, classification and labelling of substances (Annex VI to Regulation (EC) No 1272/2008 as amended):  
Note N: The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen.

**References**

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices  
IARC Monographs. Overall Evaluation of Carcinogenicity  
HSDB® - Hazardous Substances Data Bank  
Registry of Toxic Effects of Chemical Substances (RTECS)

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any statements or R-phrases and H-statements under Sections 2 to 15**

H361 Suspected of damaging fertility or the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

This material safety data sheet is offered for your information only. We believe the statements, technical information and recommendations contained here in are reliable, but are given without warranty or guarantee of any kind, expressed or implied. THE INTERNATIONAL GROUP, INC. assumes no responsibility for any loss, damage or expense, direct or consequential, arising from the use of our material. It is the responsibility of the user to determine the suitability and completeness of such information for the required use or application. We do not assume any legal responsibility for nor do we give permission, inducement or recommendation to practice any patented invention without a license. Further, it is the user's obligation to utilize this material in full compliance with all health, safety and environmental regulations.

**PRODUCT  
NUMBER**

---

0305A  
0305C  
0307A  
0310A  
0313A  
0316A  
0320A  
0321A  
0322A  
0323A  
0324A  
0328A  
0329A  
0330A  
0386A  
R-2915B  
R-3571A  
R-3606C  
R-3869A  
R-4322A  
R-5728C  
R-5965A  
R-6145A  
R-6181A  
R-6261A  
R-6269A  
R-6441A  
R-6452A