



Product Name: HS ink Cyan
MSDS No. 031-37S06CC
First issue: 2011/09/30
Revised:
Page 1 of 10

Material Safety Data Sheets

1. Product and Company Identification

Product Name : HS ink Cyan
Product Code : SPC-0473C-5, SPC-0589C-5
General Use : Ink for ink jet printer
Product Description : Solvent pigment ink
MSDS Number : 031-37S06CC
Manufacture
Company Name : Mimaki Engineering Co., Ltd
Address : 2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan
Telephone No. : +81-268-64-2413
Importer/Distributor Established in USA
Company Name : MIMAKI USA. INC.
Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A
Telephone No. : 1-678-730-0100
Emergency Telephone No. : +81-268-64-2413

2. Hazards Identification

[GHS Classification]

Physical Hazards

Explosives	: Not applicable
Flammable Gases	: Not applicable
Flammable Aerosols	: Not applicable
Oxidizing gases	: Not applicable
Gases under Pressure	: Not applicable
Flammable Liquids	: Category 4
Flammable Solids	: Not applicable
Self-reactive Substances and mixtures	: Not applicable
Pyrophoric Liquids	: Not applicable
Pyrophoric Solids	: Not applicable
Self-heating Substances and Mixtures	: Classification not possible
Substances and Mixtures, which in	: Not applicable
Contact with Water, Emit Flammable	
Gases	

Material Safety Data Sheets

Oxidizing Liquids	: Not applicable
Oxidizing Solids	: Not applicable
Organic Peroxides	: Not applicable
Corrosive to Metals	: Classification not possible

Health Hazards

Acute Toxicity – Oral	: Category 5
Acute Toxicity – Dermal	: Category 5
Acute Toxicity –Inhalation (Steam)	: Category 4
Skin Corrosion / Irritation	: Category 2
Eye Damage / Irritation	: Category 2A
Sensitization – Respiratory	: Classification not possible
Sensitization – Skin	: Category 1
Germ Cell Mutagenicity	: Category 2
Carcinogenicity	: Classification not possible
Toxic to Reproduction	: Category 2
Specific Target Organ Toxicity (Single Exposure)	: Category 1 (respiratory system) : Category 2 (central nervous system)
Specific Target Organ Toxicity (Repeated Exposure)	: Category 1 (systemic toxicity)
Aspiration Hazard	: Classification not possible

Environmental Hazards

Hazardous to the Aquatic Environment - Acute Hazard	: Category 3
Hazardous to the Aquatic Environment - Long Term Hazard	: Classification not possible
Hazardous to the Ozone Layer	: Classification not possible

[GHS Label Elements]

Symbol



Signal Word

Danger

Material Safety Data Sheets

Hazard Statements

- H227 Combustible liquid
- H303 May be harmful if swallowed
- H313 May be harmful in contact with skin
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H341 Suspected of causing genetic defects
- H361 Suspected of damaging fertility or the unborn child
- H370 Cause damage to respiratory system
- H371 May cause damage to central nervous system
- H372 Causes damage to systemic toxicity through prolonged or repeated exposure
- H402 Harmful to aquatic life

Precautionary Statements

[Prevention]

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from flames and hot surfaces. - No smoking.
- P260 Do not breathe gas, mist and vapours.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves, protective clothing, eye protection and face protection.

[Response]

- P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 IF exposed or concerned: Get medical attention or advice.
- P314 Get medical advice or attention if you feel unwell.
- P332 + P313 If skin irritation occurs: Get medical advice or attention.

Material Safety Data Sheets

P337 + P313 If eye irritation persists: Get medical advice or attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire, use foam, carbon dioxide, dry chemical and water spray.

[Storage]

P403 + P235 Store in a well –ventilated place. Keep cool.

[Disposal]

P501 Dispose of contents and container in accordance with local, regional, national and international regulation.

HMIS Rating (scale 0 – 4)

Health = 2

Flammability= 2

Reactivity = 1

Protective Equipment = G

②	Health
②	Flammability
①	Reactivity
G	Protective Equipment


NFPA Rating (scale 0 – 4)

Health = 2

Flammability = 2

Instability = 1

Special = None



3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.	Chemical Formula
1	Phthalocyanine blue	0.1-5	Registered	Trade secret
2	Vinyl chloride / Vinyl acetate copolymer resin	0.1-5	Registered	Trade secret
3	Polyester resin	0.1-5	Registered	Trade secret
4	Dipropylene glycol methyl ether acetate	10-30	88917-22-0	C ₉ H ₁₈ O ₄
5	Dipropylene glycol dimethyl ether	10-30	111109-77-4	C ₈ H ₁₈ O ₃
6	3-Methoxybutyl acetate	10-30	4435-53-4	C ₄ H ₆ O ₂
7	N-Methyl-2-pyrrolidone	10-30	212-828-1	C ₅ H ₉ NO
8	Cyclohexanone	1-5	108-94-1	C ₆ H ₁₀ O
9	Additives	0.1-5	Registered	Trade secret

Material Safety Data Sheets

4. First Aid Measures

Inhalation	: If inhaled, immediately remove to fresh air and keep warm and calm. If breathing irregularly or not breathing, give artificial respiration and consult a doctor immediately.
Eye Contact	: Flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Consult an ophthalmologist immediately.
Skin Contact	: Wash skin thoroughly with plenty of water. If on clothing, remove immediately contaminated clothing.
Ingestion	: Do not induce vomiting. If swallowed, keep calm and consult a doctor immediately. Keep from swallowing vomit.
Protection to First-Aiders	: Wear tools for appropriate protection. Ventilate. See section 7 and 8.
Note to Physician	: See section 7 and 8.

5. Fire Fighting Measures

Flammable Properties	: Avoid breathing combustion products. Flash point : 68 degree C Ignition point : Not available Explosion point : 15.00~0.85 vol%
Extinguishing Media	: Foam, carbon dioxide, dry chemical, water spray. Never splash water.
Fire Fighting	: Wear tools for appropriate protection.
Instructions	Eliminate ignition sources. Stay upwind. Keep people away. Keep wetted with water surrounding equipment. Avoid discharge chemical substances to rivers and sewers.

Material Safety Data Sheets

6. Accidental Release Measures

Personal Precautions	: Wear tools for appropriate protection. Keep unnecessary and unprotected personnel from entering in vicinity of spill. Ventilate. See section 8.
Environmental Precautions	: Avoid discharge to rivers and environmental effects.
Steps to be Taken if Material is Spilled	: Small spills: Absorb with nonflammable absorbent such as dry sand and dirt. Large spills: Pump spills into a sealing container and remove to safe place. Use non-sparking equipment during recovery operation and ground equipment. See section 13, Disposal Considerations, for disposing of waste.
Second-Accident Precautions	: Prepare proper fire extinguishers and eliminate all sources of ignition in vicinity of spill. Avoid walking on the spills. Use safety tools to prevent sparks.

7. Handling and Storage

Handling	: Handle in well-ventilated area. Prohibit use of fire, sparks and heat source. Use antistatic clothing and shoes. Ground equipment against electrostatics and use spark-proof tools. Keep from increasing of temperature for flammable substance. Use local exhaust system and proper protection if working in closed area. Use proper protection (gloves, masks, aprons, goggles, etc.)
Storage	: Keep from sunlight and store in well-ventilated area. Keep from flame or heat source. Keep from freezing. Store in oxidizer and organic peroxides separately.

Material Safety Data Sheets

8. Exposure Controls / Personal Protection

Exposure Limit Values

No	Chemical Name		TWA	STEL	Ceiling	Skin	SEN
1	Cyclohexanone	OSHA PEL	50ppm	N.E.	N.E.	N.E.	N.E.
		ACGIH TLV	20ppm	50ppm	N.E.	N.E.	N.E.

Exposure Controls

Occupational Exposure Controls

Engineering Controls : Use explosion-proof equipment if handle in volume.

Use exhaust system to prevent vapor build-up.

Keep heat or fire sources from handling area.

If working indoors, use proper equipment to protect workers from direct exposure or use local exhaust system to protect workers from exposure.

Personal Protection

Respiratory : Wear protective masks for hazardous materials.

Protection

Hand Protection : Wear gloves resistant to organic solvents and chemicals.

Eye Protection : Wear chemical goggles.

Skin Protection : Wear clothing to protect skin from direct exposure.

Wear protective clothing resistant to chemicals.

Environmental Exposure Controls

: Not available

9. Physical and Chemical Properties

Appearance - Physical State : Liquid (25 degree C)

- Color : Cyan

Odor : Solvent odor

pH : Not available

Boiling Point / Boiling Range : 156 degree C~209 degree C

Melting Point / Melting Range : <- 30 degree C

Flash Point : 68 degree C

Flammability (Solid, Gas) : Not Applicable

Material Safety Data Sheets

Upper / Lower Flammability or Explosive Limits	: 15.00~0.85 vol%
Vapor Pressure	: 450 Pa (20 degree C)
Vapour Density	: 6.6
Relative Density	: 0.97 (25 degree C)
Solubility (Ies)	: Very small amount
Partition Coefficient (n-octanol / Water)	: Not available
Viscosity	: 3.5 mPa·s (25 degree C)

10. Stability and Reactivity

Conditions to Avoid	: Excessive heat and cold, sparks, ignition sources, direct sunlight and high humidity.
Stability	: Stable
Materials to Avoid	: Oxidant, explosive substance
Hazardous Reactions/ Decomposition Products	: To burn this product may be produce toxic gases such as CO and low-molecular-weight monomers.
Other	: Plastic and rubbers might be melted.

11. Toxicological Information

Acute Toxicity	: Rats LD50 >2,000mg/kg: Category 5 : Rabbit LD50 >2,000mg/kg: Category 5 : Rats LC50 >10mg/L (4h) : Category 4
Carcinogenicity	: Cyclohexanone IARC Group 3 (Not Classifiable as to its Carcinogenic)
Others	: Not available

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ecotoxicity	: Hazardous to the aquatic environment
-------------	--

Material Safety Data Sheets

Acute hazard L(E)C50 >10.0mg/L: Category 3

Persistence and : Not available

Degradability

Bioaccumulative : Not available

Potential

13. Disposal Considerations

: Have waste inks, containers and other materials disposed by licensed industrial waste disposer.

Adsorb to diatom earth and others to dispose waste inks, and use open incinerator.

Dispose of wastes by licensed industrial waste disposer to comply with the local laws and regulations.

Empty inks and other materials out of containers if disposed.

Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

Us Department of Transportation (DOT)

Hazardous Materials : Not applicable

15. Regulatory Information

TSCA Status : All components on TSCA INVENTORY.

SARA TitleIII

Section 311/312 : Fire Hazard: Yes

(40 CFR 370) Pressure Hazard: No

Reactivity Hazard: No

Immediate Hazard: Yes

Delayed Hazard: Yes



Product Name: HS ink Cyan

MSDS No. 031-37S06CC

First issue: 2011/09/30

Revised:

Page 10 of 10

Material Safety Data Sheets

California Proposition 65 : This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and / or reproductive toxicity.

16. Other Information

References : International Chemical Safety Cards (ICSC)

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.

Revision history

Version	Date	Content
1.0	2011/09/30	First issue