

Safety Data Sheets

Product Name: Dye Sublimation Ink Sb53

Deep Black

SDS No. 037-W220566 First issue: 2012/12/20

Revised: 2015/9/8

1. Identification

Product Name : Dye Sublimation Ink Sb53 Deep Black

Order No. : SB53-DK-44 / SB53-DK-2L

General Use : Ink jet printing ink
Product Description : Sublimation ink
SDS Number : 037-W220566

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413

Importer / Distributor Established in USA

Company Name : MIMAKI USA, INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.

Telephone No. : +1-678-730-0700 Emergency Telephone No. : +81-268-64-2281

2. Hazards Identification

[GHS Classification]

Physical Hazards

Flammable Liquids : Not classified

Health Hazards

Acute Toxicity – Oral : Category 4
Sensitization – Skin : Category 1

The above list does not include category being non-classifiable or not-applicable.

[GHS Label Elements]

Symbol



Signal Word Warning



Deep Black

SDS No. 037-W220566 First issue: 2012/12/20

Revised: 2015/9/8

Hazard Statements

H302 Harmful if swallowed

H317 May cause an allergic skin reaction

Precautionary Statements

[Prevention]

P261 Avoid breathing gas/mist.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

[Response]

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P330 Rinse mouth.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash before reuse.

[Disposal]

P501 Dispose of contents and container in accordance with local, regional, national and international regulation.

3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	Glycerol	10-25	56-81-5
2	Lignosulfonic acid, sodium salt	5-10	68512-35-6
3	Disperse Dye	2.5 - 5	Trade Secret
4	Water	balance	7732-18-5

4. First Aid Measures

Inhalation : Remove person to fresh air and keep comfortable for breathing. Call

a POISON CENTER or doctor/physician.

Eye Contact : Flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Get

immediate medical attention.



Deep Black

SDS No. 037-W220566 First issue: 2012/12/20

Revised: 2015/9/8

Skin Contact : Wash with plenty of soap and water. If skin irritation or rash occurs:

Get medical advice/attention. Take off contaminated clothing and

wash before re-use.

Ingestion : If swallowed, get medical attention.

Note To Physician : Treat symptomatically and supportively.

5. Fire Fighting Measures

Flammable Properties : Flash Point: >100 °C

Suitable Extinguishing : CO2, powder or water spray. Fight largerfires with water spray or

Media alcohol resistant foam.

Unsuitable Extinguishing : Do not scatter spilled material with high-pressure water streams.

Media

Fire Fighting : Move container from fire area if it can be done without risk. Do not

Instructions scatter spilled material with high-pressure water streams. Cool

containers with water spray until well after the fire is out. Stay away from the ends of tanks. Avoid inhalation of material or

combustion by-products.

Special Protective : Wear full protective fire fighting gear including self contained

Equipment and breathing apparatus (SCBA) for protection against possible

Precautions for exposure.

Firefighters

6. Accidental Release Measures

Personal Precautions : Wear personal protective clothing and equipment, see Section 8.

Avoid release to the environment.

Measures for : Do not allow to enter sewers/surface or ground water. Inform

environmental protection respective authorities in case of seepage into water course or sewage

system.

Measures for : Absorb with liquid-binding material (sand, diatomite, sawdust).

cleaning/collecting Send for recovery or disposal in suitable containers. Dispose

contaminated material as waste according to item 13. Avoid use of

solvents.



Deep Black

SDS No. 037-W220566 First issue: 2012/12/20

Revised: 2015/9/8

7. Handling and Storage

Handling : Avoid breathing gas/mist. Wash hands thoroughly after handling. Do

not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective

gloves/protective clothing/eye protection/face protection.

Requirements to be met : Ideal storage temperature: 10-30 degree C. Store in a cool location.

by storerooms and Use only containers specifically designed for this substance/product.

receptacles

Further information : Store in cool, dry conditions in well sealed containers. Protect from

about storage conditions heat and direct sunlight.

8. Exposure Controls / Personal Protection

Exposure Limit Values

No	Chemical Name		TWA
1	Claragnal	OSHA	15 mg/m3 TWA (mist, total particulate);
	Glycerol	ОБПА	5 mg/m3 TWA (mist, respirable fraction)

Exposure Controls

Occupational Exposure Controls

Engineering Controls : Provide local exhaust or process enclosure ventilation system. Ensure

compliance with applicable exposure limits.

Personal Protection

Respiratory : Consult with a health and safety professional for specific respirators

Protection appropriate for your use.

Vapor Respirator

Hand Protection

ion : Wear appropriate chemical resistant gloves.





Deep Black SDS No. 037-W220566

First issue: 2012/12/20 Revised: 2015/9/8

Eye Protection : Wear splash resistant safety goggles with a faceshield. Provide an

Safety Glasses emergency eye wash fountain and quick drench shower in the

immediate work area.

Skin Protection : Wear appropriate chemical resistant clothing.



Environmental Exposure Controls

: Not available

9. Physical and Chemical Properties

Appearance - Physical State : liquid

- Color : Black

Odor : Weak

pH : 8.0 at 20 ℃

Boiling Point / Boiling Range : 100 ℃

Melting Point / Melting Range : Not available

Decomposition Temperature : Not available

Flash Point :>100 °C

Vapor Pressure ∶ 23hPa at 20 °C

Relative Density 又は Specific Gravity : Not available

Water Solubility : Miscible Viscosity : 5.0 at 20 °C

10. Stability and Reactivity

Conditions to Avoid : Stable under recommended storage and handling conditions.

Stability : Stable under recommended storage and handling conditions.

Materials to Avoid : Strong oxidizers.

Hazardous Reactions / : In case of fire, carbon and nitrogen oxides are the main combustion

Decomposition Products gases.



Deep Black

SDS No. 037-W220566 First issue: 2012/12/20

Revised: 2015/9/8

11. Toxicological Information

Acute Toxicity : Category 4 (Oral) as a product.

Component Analysis - LD50/LC50

Glycerin (56-81-5)

Oral LD50 Rat 12600 mg/kg; Dermal LD50 Rabbit >10 g/kg;

Inhalation LC50 Rat >570 mg/m3 1 h

Eye Irritation : Not available
Skin Irritation : Not available

Sensitization : May cause sensitization by skin contact.

Repeated Dose Toxicity : Not available
Mutagenicity : Not available
Carcinogenicity : Not available
Reproductive and Developmental Toxicity

: Not available

12. Ecological Information

Handling is noted because it might influence the environment when

leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the

river, and the drain ditch.

Ecotoxicity : At present there are no ecotoxicological assessments.

Persistence and : Not available

Degradability

Bioaccumulative : Not available

Potential

Other Adverse Effects : Not available

13. Disposal Considerations

: Comply with all USA, national and local regulations. Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

Do not dump this product into sewers, on the ground or into any body



Deep Black

SDS No. 037-W220566 First issue: 2012/12/20

Revised: 2015/9/8

of water.

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

Land Transport : Not regulated

(ADR/RID)(cross-border)

Air Transport : Not regulated

(ICAO/IATA)

Sea Transport : Not regulated

(IMDG)

Marine Pollutant : No

15. Regulatory Information

International Inventories

TSCA : All components are listed on the TSCA Inventory.

DSL : Additives Does not comply

Legend

TSCA- United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.