



THE INTERNATIONAL GROUP, INC.

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** 0400 - 0500 Series Products

**Other means of identification** See page 8

**SDS number** 0400 - 0500 Series (928962)\_Canada\_English

**Recommended use** Further processing , Misc. multiple uses

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Company name** The International Group Inc.

**Address** 50 Salome Dr.  
Toronto  
ON  
M1S2A8  
CA

**Telephone** 416-293-4151

**E-mail** Not available.

**Emergency phone number** 416-293-4151

## 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Not classified.

**Environmental hazards** Not classified.

Not classified as hazardous according to applicable GHS hazard classification criteria.

### Label elements

**Hazard symbol** None.

**Signal word** None.

**Hazard statement** Not available.

**Precautionary statement**

**Prevention** Observe good industrial hygiene practices.

**Response** Wash thoroughly after handling.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

**Other hazards** None known.

**Supplemental information** None.

## 3. Composition/information on ingredients

### Substances

Chemical name	Common name and synonyms	CAS number	%
Slack wax, petroleum		64742-61-6	100

## 4. First-aid measures

**Inhalation** Solid: No specific first aid measures noted. If fumes from heated product are inhaled: Move to fresh air. Call a POISON CENTER or doctor/physician if you feel unwell. Call a physician if symptoms develop or persist.

**Skin contact** Solid: No specific first aid measures noted. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn.

**Eye contact** Solid: No specific first aid measures noted. Exposure to fumes, vapors or smoke of over heated product can result in irritation of eyes. Direct contact of molten material will cause injury and burns. When handling of molten product eye shield must be worn at all times. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Administer prompt first aid measures. Get medical attention if irritation develops and persists.

**Ingestion** Solid: No specific first aid measures noted. Not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Contact with hot product may cause severe burns. Get medical attention immediately.

**Most important symptoms/effects, acute and delayed** Eye and skin contact: When heated, contact with molten product can cause injury and burns.

**Indication of immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically.

**General information** If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

## 5. Fire-fighting measures

**Suitable extinguishing media** Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water on molten material: Explosion hazard could result.

**Specific hazards arising from the chemical** By heating and fire, irritating vapors/gases may be formed. During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire fighting equipment/instructions** In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Do not direct water at source of leak or safety devices as icing may occur. Use water spray to cool unopened containers. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

**General fire hazards** No unusual fire or explosion hazards noted.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Avoid inhalation of vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Handle as a thermoplastic. With molten spills, allow the material to solidify and cool. Keep material out of sewers and watercourses by diking or impounding. Recover and place into appropriate containers for recycling or disposal, according to prevailing local, regional and national laws.

Large Spills: Stop the flow of material, if this is without risk. Stop leak if you can do so without risk. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Allow material to solidify, and scrape up. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Where possible allow molten material to solidify naturally.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers. Do not handle until all safety precautions have been read and understood. Heat only in areas with appropriate exhaust ventilation. Do not breathe fume/mist/vapors. Avoid contact with molten material. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment. Wash contaminated clothing before reuse. The material is a solid at room temperature exhibiting elevated temperature softening characteristics. Above its softening point, the material liquefies and flows more readily as the temperature increases. The material may be used as a hot liquid for application purposes and requires caution in handling.

### Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

## 8. Exposure controls/personal protection

### Occupational exposure limits

No exposure limits noted for ingredient(s).

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear approved safety goggles. Wear a face shield when working with molten material.

#### Skin protection

##### Hand protection

Avoid exposure - obtain special instructions before use. For prolonged or repeated skin contact use suitable protective gloves. Wear appropriate chemical resistant gloves. Wear protective gloves. Suitable gloves can be recommended by the glove supplier.

##### Other

The material may be utilized in molten form. Proper protective splash resistant clothing, thermal gloves, splash resistant shoes, and eye shields must be worn to prevent injury. Use molten material in well ventilated areas. When working in confined areas, use of appropriate respiratory gear is recommended. Wear appropriate chemical resistant clothing to prevent any possibility of skin contact.

#### Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. Avoid exposure - obtain special instructions before use. Use personal protective equipment as required. Wear positive pressure self-contained breathing apparatus (SCBA). When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

Do not breathe dust. When using, do not eat, drink or smoke. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Wash hands after handling. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

#### Physical state

Solid.

#### Form

Soft solid.

#### Color

Off-white to brown.

#### Odor

Petroleum.

#### Odor threshold

No data available.

#### pH

Not applicable.

#### Melting point/freezing point

89.6 - 194 °F (32 - 90 °C)

#### Initial boiling point and boiling range

> 572 °F (> 300 °C)

<b>Flash point</b>	> 347.0 °F (> 175.0 °C) ASTM D-93
<b>Evaporation rate</b>	< 0.01 (Butyl acetate = 1)
<b>Flammability (solid, gas)</b>	Will support a flame above flash point.

#### Upper/lower flammability or explosive limits

**Flammability limit - lower (%)** No data available.

**Flammability limit - upper (%)** No data available.

**Explosive limit - lower (%)** 0.9 % v/v

**Explosive limit - upper (%)** 7 % v/v

**Vapor pressure** < 0.01 mm Hg (77 °F/25 °C)

**Vapor density** > 5 (Air = 1)

**Relative density** 0.85 - 0.92 (77 °F/25 °C)

#### Solubility(ies)

**Solubility (water)** < 0.1 % (68 °F/20 °C)

**Partition coefficient (n-octanol/water)** No data available.

**Auto-ignition temperature** No data available.

**Decomposition temperature** No data available.

**Viscosity** No data available.

#### Other information

**Explosive properties** Not explosive.

**Oxidizing properties** Not oxidizing.

**Partition coefficient (oil/water)** < 0.01

**Percent volatile** < 1 % v/v

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.

**Conditions to avoid** Avoid heat, sparks, open flames and other ignition sources. Vapors may form explosive mixture with air. Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition products** Decomposition of this product can generate carbon dioxide, carbon monoxide and other products such as aldehydes and ketones depending on conditions of oxidation.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** Not relevant at normal room temperatures. When heated, irritating vapors may be formed. Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.

**Skin contact** Health injuries are not known or expected under normal use. Molten material will produce thermal burns.

**Eye contact** Health injuries are not known or expected under normal use. Molten material will produce thermal burns.

**Ingestion** Health injuries are not known or expected under normal use. Contact with hot material can cause thermal burns which may result in permanent damage.

**Symptoms related to the physical, chemical and toxicological characteristics** Eye and skin contact: Contact with molten material may cause thermal burns.

### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

<b>Skin corrosion/irritation</b>	Thermal burn hazard - contact with hot material may cause thermal burns.
<b>Serious eye damage/eye irritation</b>	Not classified. Direct contact of molten product to the eyes will cause thermal burns and eye injury.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not classified.
<b>Skin sensitization</b>	Irritating to skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. None known. This product is not expected to cause skin sensitization. Due to partial or complete lack of data the classification is not possible.
<b>Germ cell mutagenicity</b>	Not classified.
<b>Carcinogenicity</b>	Not expected to be hazardous by WHMIS criteria. Not expected to be hazardous by OSHA criteria. Not expected to cause cancer.
<b>Reproductive toxicity</b>	Not classified.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Solid product: Not likely, due to the form of the product.
<b>Chronic effects</b>	Not expected to be hazardous by WHMIS criteria. Not expected to be hazardous by OSHA criteria. Not expected to be hazardous. Exposure to vapors, fumes, or smoke from molten material handled in confined areas can produce irritation of respiratory tracts, and possible physical discomfort to sensitive individuals.
<b>Further information</b>	None.

## 12. Ecological information

<b>Ecotoxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	The product is insoluble in water.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

<b>Disposal instructions</b>	Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations. Dispose of contents/container (in accordance with related regulations). When your own wastewater treatment plant is not available, collect entire waste and then charge to a licensed industrial waste management professional with manifests for industrial waste.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company. 01-04-00
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

<b>TDG</b>	Not regulated as dangerous goods.
<b>IATA</b>	Not regulated as dangerous goods.
<b>IMDG</b>	Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**General information** This product is not regulated as dangerous goods for solid. Shipped hot molten product requires a class 9 "HOT" with statement: Elevated temperature material, liquid, N.O.S. 9, UN3257, III (WAX)

## 15. Regulatory information

### Canadian regulations

#### Controlled Drugs and Substances Act

Not regulated.

#### Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### Greenhouse Gases

Not listed.

#### Precursor Control Regulations

Not regulated.

### International regulations

#### Stockholm Convention

Not applicable.

#### Rotterdam Convention

Not applicable.

#### Kyoto protocol

Not applicable.

#### Montreal Protocol

Not applicable.

#### Basel Convention

Not applicable.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other Information

**Issue date** 18-August-2015  
**Revision date** -  
**Version #** 01

**Disclaimer**

This material safety data sheet is offered for your information only. We believe the statements, technical information and recommendations contained here in are reliable, but are given without warranty or guarantee of any kind, expressed or implied. THE INTERNATIONAL GROUP, INC. assumes no responsibility for any loss, damage or expense, direct or consequential, arising from the use of our material. It is the responsibility of the user to determine the suitability and completeness of such information for the required use or application. We do not assume any legal responsibility for nor do we give permission, inducement or recommendation to practice any patented invention without a license. Further, it is the user's obligation to utilize this material in full compliance with all health, safety and environmental regulations.

**PRODUCT  
NUMBER**

---

0405A  
0406A  
0426A  
0431A  
0431B  
0431G  
0431H  
0439A  
0451A  
0456A  
0487A  
0487B  
0491A  
0493A  
0501A  
0541A  
0542A  
0543A  
0544A  
0547A  
0568A  
R-5479A