

**MATERIAL SAFETY DATA SHEET**

CODE: M/L 044

This Material Safety Data Sheet complies with the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200

**PRODUCT: LENOX ROSIN CORE LEAD FREE SOLDER**

NFPA/HMIS HAZARD CODES: HEALTH: 1/1 FIRE: 0/0 REACTIVITY: 0/0 SPECIAL: N/A

0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**SECTION I**

**MANUFACTURER NAME:** LENOX **ISSUE DATE:** October, 2007  
 1690 Lowery Street  
 Winston-Salem, NC 27101  
**INFORMATION PHONE:** 336-777-8600

**SECTION II HAZARDOUS INGREDIENTS**

INGREDIENT	CAS NO.	US-NIOSH RTECS NO.	US OSHA AL	US OSHA PEL	ACGIH TLV	APPROX. VOL. % <sup>(1)</sup>	WT. PERCENT <sup>(2)</sup>
<b>SOLDER</b>	<b>COMPONENTS</b>	>>>>>>>>	>>>>>>>>	>>>>>>>>	>>>>>>>>	97.0	
Tin	7440-31-5	XP7320000	NE	2.0mg/m3	2.0mg/m3		Balance
Copper (dust)	7440-50-8	GL5325000	NE	1.0mg/m3	1.0mg/m3		3.0-4.0
(fume)				0.1mg/m3	0.2mg/m3		
<b>CORE</b>	<b>COMPONENTS</b>	>>>>>>>>	>>>>>>>>	>>>>>>>>	>>>>>>>>	3.0 <sup>(3)</sup>	
Rosin	65997-06-0	NK	NE	0.1mg/m3 <sup>(4)</sup>	0.2 mg/m3 <sup>(4)</sup>	2.5	

**NOTES:** \*1 = Product formulation is to customer specification and appears on product packaging or packing slip.  
 \*2 = Product weight formulation is to customer specification and appears on product packaging or packing slip.  
 \*3 = Remaining constituents, by volume, are inert or constitute less than the declaratory reporting threshold.  
 \*4 = Aliphatic Aldehydes, measured as formaldehyde (CAS #50-00-0; RTECS #LP89250000), best indicator of Rosin pyrolysis products.

NE = NONE ESTABLISHED AL = ACTION LEVEL PEL = PERMISSIBLE EXPOSURE LIMIT TLV = THRESHOLD LIMIT VALUE

**SECTION III PHYSICAL DATA**

**APPEARANCE & ODOR (AT NORMAL CONDITIONS):** Solid - silver to silver gray metallic metal - no odor: Contains core of light yellow color with rosin odor.  
**SPECIFIC GRAVITY (H2O=1):** Information not available  
**MELTING POINT RANGE (DEGREES F):** 227-250 (441-482 Degrees F)  
**BOILING POINT (DEGREES C):** Information not available  
**SOLUBILITY IN WATER:** Insoluble

**SECTION IV FIRE AND EXPLOSION HAZARD DATA**

**FLASH POINT:** Non-flammable  
**FLAMMABLE LIMITS:** Not applicable  
**EXTINGUISHING MEDIA:** No specific agents available  
**SPECIAL FIRE FIGHTING PROCEDURES:** If involved in fire, use full protective clothing and NIOSH/MSHA approved self-contained breathing apparatus operated in a positive-pressure mode.  
**UNUSUAL FIRE & EXPLOSION HAZARDS:** The solid metal form is not a fire hazard. However, dust generated from processing operations may present a moderate fire or explosion hazard.

**SECTION V REACTIVITY DATA**

**STABILITY:** Stable  
**CONDITIONS TO AVOID:** Not applicable  
**INCOMPATIBILITY:** Chlorine, Turpentine, and Magnesium, and Acetylene Gas.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** At temperatures above the melting point metal oxide fumes may be evolved.  
**HAZARDOUS POLYMERIZATION:** Will not occur.

## SECTION VI HEALTH HAZARD DATA

**NOTE:** Exposure to the solid form of this product presents few health hazards in itself. However, normal handling or processing of this material may result in exposure to product components and/or decomposition products, which may present a health hazard.

**ROUTES OF ENTRY:** Dust/fume inhalation; dust ingestion.

### **SYMPTOMS & EFFECTS OF OVEREXPOSURE:**

**Chronic (prolonged)** overexposure to **Tin** can result in benign pneumoconiosis (stannous). This form of pneumoconiosis produces progressive x-ray changes of the lungs as long as exposure exists, but there is no distinctive fibrosis, no evidence of disability and no special complicating factors.

**Acute (severe short-term)** overexposure to **Tin** can cause irritation of the eyes, skin, mucous membranes and respiratory system. Acute overexposure to **Copper** can cause irritation of the eyes, nose throat, and skin, and under severe fume overexposure may cause metal fume fever with flu-like symptoms such as sweet metal taste, dry throat, coughing, fever and chills, tight chest, dyspnea, headache, blurred vision, back pain, nausea, vomiting, fatigue. Symptoms usually disappear within 24 hours. **Copper** may cause skin and hair discoloration. Inhalation of **Copper** dusts may cause changes in the gums and mucous linings of the mouth, which is generally attributable to localized tissue effect rather than general toxicity. Acute overexposure to **Rosin** pyrolysis products is characterized by irritation of the eyes, nose, throat, and cough.

### **MEDICAL CONDITIONS POSSIBLY**

**AGGRAVATED BY EXPOSURE:** Pre-existing conditions of the lungs; Wilson's Disease (genetic trait)

**CARCINOGENICITY:** Not listed as a carcinogen by NTP, IARC, OSHA, and ACGIH.

### **EMERGENCY & FIRST AID PROCEDURES:**

- SKIN:** Normal hygiene and first aid procedures - wash with soap and water. If irritation develops obtain medical attention.
- EYES:** Flush well with running water to remove particulate. If irritation persists obtain medical attention.
- ACUTE INHALATION:** Remove from exposure. Obtain immediate medical attention. If breathing has stopped, initiate artificial resuscitation.
- INGESTION:** Give water; induce vomiting only in a conscious non-convulsing individual; obtain immediate medical attention.

## SECTION VII PROTECTION MEASURES

- RESPIRATORY PROTECTION:** Respiratory protection is required where airborne exposures exceed U.S. OSHA/ACGIH permissible air concentrations. Respirator selection shall be made in accordance with the U.S. OSHA Respiratory Protection Standard, 29 CFR 1910.134.
- VENTILATION:** Good general ventilation, or ventilation, as described in "Industrial Ventilation, A Manual of Recommended Practice," by the American Conference of Governmental Industrial Hygienists, is recommended to maintain exposure levels below the Permissible Exposure Limits (PEL's) or Threshold Limit Values (TLV's) specified by U.S. OSHA or other local or state regulations.
- PROTECTIVE GLOVES:** Recommended for prolonged contact/heat.
- EYE PROTECTION:** Safety glasses or goggles are recommended where the possibility exists of getting dust particles in the eyes. Safety glasses or goggles with face shield are recommended around molten metal.
- OTHER PROTECTIVE EQUIPMENT:** Safety equipment should be worn as appropriate for the work environment.
- WORK/HYGIENIC PRACTICES:** Do not permit eating, drinking, or the use of cosmetics or tobacco products while handling or processing material or in solder work areas. Practice good personal hygiene procedures. Wash hands and face thoroughly before eating, drinking, applying cosmetics or using tobacco products. Keep melting/soldering temperatures as low as possible to minimize the generation of fumes.

## SECTION VIII PRECAUTIONS FOR SAFE HANDLING & USE

### **PRECAUTIONS TO BE TAKEN**

**IN HANDLING & STORING:** Practice good housekeeping procedures to prevent dust accumulations. Keep material dry. Avoid storage near incompatible materials (See Section V). Keep product away from children and their environment and domestic animals.

**OTHER PRECAUTIONS:** Special attention is drawn to the requirements of the U.S. Respirator Standard 1910.134 should airborne exposures exceed the U.S. OSHA PEL. Inadvertent contaminants to product such as moisture, ice, snow, grease or oil can cause an explosion when charged to a molten metal bath or melting furnace (Preheating metal will remove moisture from product).

## SECTION IX SPILL OR LEAK PROCEDURES

### **SPILL OR LEAK PROCEDURES:**

1. Material in dust form-minimize exposure. Clean up using dustless methods (i.e. HEPA Vacuum). Do not use compressed air.
2. Place in closed labeled containers for recycling or disposal.
3. Keep out of waterways.

**NOTE:** Cleanup personnel should wear protective clothing and respiratory protection where significant dust/fume exposure exists.

**OTHER PROCEDURES:** We recommend that the purchaser establish a spill prevention, control and counter measure plan. This plan should include procedures for proper storage as well as clean up of spills or leaks. The procedures should conform to safe practices and provide for proper recovery and/or disposal. Depending on the quantity spilled, notification to the U.S. National Response Center (800-424-8802) may be required in case of hazardous substances. (See USEPA and USDOT regulations: also various states and local regulations.)

**WASTE DISPOSAL METHODS:** May have value on a recycled basis. If disposed of, dispose of in a permitted disposal site in accordance with all federal, state and local disposal or discharge regulations.

### SECTION X UNITED STATES SARA TITLE III INFORMATION

This product/mixture contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. The percent by weight of each toxic chemical and its associated chemical abstract system (CAS) number are to be found in Section II of this Material Safety Data Sheet.

<u>CHEMICAL NAME</u>	<u>EHS RQ (LBS)</u> *1	<u>EHS TPQ (LBS)</u> *2	<u>SEC.313</u> *3	<u>313 CATEGORY</u> *4	<u>311/312 CATEGORY</u> *5
Copper	Not Applicable	Not Applicable	YES	Copper	H-1

#### -FOOTNOTES-

- \*1 = Reportable quantity of extremely hazardous substance, Section 302.
- \*2 = Threshold planning quantity, extremely hazardous substance, Section 302.
- \*3 = Toxic chemical list, Section 313
- \*4 = Chemical category as required by Section 313 (40 CFR 372.42). Subject to annual release reporting requirements.
- \*5 = Hazard category for SARA Section 311/312 reporting:

Health	H-1 = Immediate (ACUTE) Health Hazard	Physical	P-3 = Fire Hazard
	H-2 = Delayed (CHRONIC) Health Hazard		P-4 = Sudden Release of Pressure Hazard
			P-5 = Reactive Hazard

### SECTION XI UNITED STATES CERCLA SECTION 103 INFORMATION

This product/mixture contains the following chemicals subject to the release reporting of Section 302.

<u>CHEMICAL NAME</u>	<u>RQ (LBS)</u>
Copper	5000 (*1)

#### -FOOTNOTES-

\*1 = Reportable quantity (RQ) under CERCLA Section 302. Spills to the environment exceeding the reportable quantity in any 24-hour period must be reported to the U.S. National Response Center (800-424-8802). No reporting of releases of the hazardous substance(s) is required if the diameter of the pieces of the solid metal(s) released is equal to or exceeds 100 micrometers (0.004 inches).

### SECTION XII TRANSPORTATION INFORMATION

<b>PROPER SHIPPING NAME:</b>	Non-regulated as shipped
<b>TECHNICAL NAME:</b>	N/A
<b>HAZARD CLASS:</b>	N/A
<b>UN NO.:</b>	N/A
<b>EMERGENCY RESPONSE NUMBER:</b>	N/A
<b>PACKING GROUP:</b>	N/A
<b>OTHER:</b>	N/A

### SECTION XIII ADDITIONAL INFORMATION

**VOC CONTENT:** None

This Material Safety Data Sheet is offered solely for your information, consideration and investigation. LENOX® provides no warranties, either express or implied, and assumes no responsibilities for the accuracy or completeness of the data contained in this document. The data in this Material Safety Data Sheet relates only to this product and does not relate to use in combination with any other material or in any process.