



# Cumene

## Material Safety Data Sheet

CITGO Petroleum Corporation  
P.O. Box 4689  
Houston, TX 77210

MSDS No. 07503  
Revision Date 6/26/2012

**IMPORTANT:** This MSDS is prepared in accordance with 29 CFR 1910.1200. Read this MSDS before transporting, handling, storing or disposing of this product and forward this information to employees, customers and users of this product.

| Hazard Rankings |      |      |
|-----------------|------|------|
|                 | HMIS | NFPA |
| Health Hazard   | * 2  | 2    |
| Fire Hazard     | 3    | 3    |
| Reactivity      | 1    | 1    |

\* = Chronic Health Hazard

| Emergency Overview  |                         |
|---|-------------------------|
| <b>Physical State</b>   | Liquid.                 |
| <b>Color</b>  | Transparent, colorless. |
| <b>Odor</b>   | Aromatic.               |
| <b>WARNING:</b>   |                         |
| Flammable liquid; vapor may cause flash fire.   |                         |
| Harmful or fatal if swallowed - can enter lungs and cause damage.                                 |                         |
| Can cause eye, skin or respiratory tract irritation.  |                         |
| Overexposure can cause central nervous system (CNS) depression and/or other target organ effects. |                         |
| Harmful to aquatic organisms.   |                         |

| Protective Equipment                             |
|--|
| Minimum Recommended<br>See Section 8 for Details |
|  |

### SECTION 1. PRODUCT IDENTIFICATION

|                       |   |  |                |
|-----------------------|---|--|----------------|
| <b>Trade Name</b>     | Cumene  | <b>Technical Contact</b>                       | (800) 248-4684 |
| <b>Product Number</b> | 07503   | <b>Medical Emergency</b>                       | (832) 486-4700 |
| <b>CAS Number</b>     | 98-82-8   | <b>CHEMTREC Emergency (United States Only)</b> | (800) 424-9300 |
| <b>Product Family</b> | Petroleum hydrocarbon solvent   |  |                |
| <b>Synonyms</b>       | Isopropylbenzene; Benzene, (1-methylethyl)-; 2-Phenylpropane; (1-Methylethyl)benzene; CITGO® Material Code: 07503 |  |                |

### SECTION 2. COMPOSITION

| Component Name(s) | CAS Registry No. | Concentration (%) |
|-------------------|------------------|-------------------|
| Cumene            | 98-82-8          | >99               |

### SECTION 3. HAZARDS IDENTIFICATION

Also see Emergency Overview and Hazard Ratings on the top of Page 1 of this MSDS.

**Major Route(s) of Entry** Skin contact. Eye contact. Inhalation. Ingestion.

#### Signs and Symptoms of Acute Exposure

|                    |  |
|--------------------|--|
| <b>Inhalation</b>  | Breathing high concentrations may be harmful. Mist or vapor can irritate the throat and lungs. Breathing this material may cause central nervous system depression with symptoms including nausea, headache, dizziness, fatigue, drowsiness, or unconsciousness. |
| <b>Eye Contact</b> | This material can cause eye irritation with tearing, redness, or a stinging or burning feeling. Further, it can cause swelling of the eyes with blurred vision. Effects may become more serious with repeated or prolonged contact.                              |

## Cumene

**Skin Contact** May cause mild skin irritation with redness and/or an itching or burning feeling. Effects may become more serious with repeated or prolonged contact. It is likely that some components of this material are able to pass into the body through the skin and may cause similar effects as from breathing or swallowing it.

**Ingestion** Swallowing this material may be harmful. Swallowing this material may cause stomach or intestinal upset with pain, nausea, and/or diarrhea. This material can get into the lungs during swallowing or vomiting. Small amounts in the lungs can cause lung damage, possibly leading to chronic lung dysfunction or death. Swallowing this material may cause effects similar to those described in the inhalation section (see "inhalation" above).

**Chronic Health Effects Summary** Secondary effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. This material (or a component) may cause harm to the human fetus based on tests with laboratory animals. See Toxicological Information (Section 11)

**Conditions Aggravated by Exposure** Disorders of the following organs or organ systems that may be aggravated by significant exposure to this material or its components include: Skin, Respiratory System, Central Nervous System (CNS)

**Target Organs** May cause damage to the following organs: kidneys, liver, mucous membranes, spleen, upper respiratory tract, skin, adrenal, central nervous system (CNS), eye, lens or cornea

**Carcinogenic Potential** This material contains cumene at concentrations at or above 0.1%. Cumene is considered possibly carcinogenic to humans by IARC (Group 2B) based on laboratory animal studies.

**OSHA Hazard Classification is indicated by an "X" in the box adjacent to the hazard title. If no "X" is present, the product does not exhibit the hazard as defined in the OSHA Hazard Communication Standard (29 CFR 1910.1200).**

| OSHA Health Hazard Classification |                                     |              |                                     | OSHA Physical Hazard Classification |                                     |                  |                          |
|-----------------------------------|-------------------------------------|--------------|-------------------------------------|-------------------------------------|-------------------------------------|------------------|--------------------------|
| Irritant                          | <input checked="" type="checkbox"/> | Sensitizer   | <input type="checkbox"/>            | Combustible                         | <input type="checkbox"/>            | Explosive        | <input type="checkbox"/> |
| Toxic                             | <input type="checkbox"/>            | Highly Toxic | <input type="checkbox"/>            | Flammable                           | <input checked="" type="checkbox"/> | Oxidizer         | <input type="checkbox"/> |
| Corrosive                         | <input type="checkbox"/>            | Carcinogenic | <input checked="" type="checkbox"/> | Compressed Gas                      | <input type="checkbox"/>            | Organic Peroxide | <input type="checkbox"/> |
|                                   |                                     |              |                                     |                                     |                                     | Pyrophoric       | <input type="checkbox"/> |
|                                   |                                     |              |                                     |                                     |                                     | Water-reactive   | <input type="checkbox"/> |
|                                   |                                     |              |                                     |                                     |                                     | Unstable         | <input type="checkbox"/> |

## SECTION 4. FIRST AID MEASURES

**Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.**

**Inhalation** Move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If breathing is difficult, 100 percent humidified oxygen should be administered by a qualified individual. Seek medical attention immediately. Keep the affected individual warm and at rest.

**Eye Contact** Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water for at least 15 minutes while occasionally lifting and lowering eyelids. Do not use eye ointment unless directed to by a physician. Seek medical attention if excessive tearing, irritation, or pain persists.

**Skin Contact** Remove contaminated shoes and clothing. Flush affected area with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. Do not use ointments. If skin surface is not damaged, clean affected area thoroughly with mild soap and water. Seek medical attention if tissue appears damaged or if pain or irritation persists.

**Ingestion** Do not induce vomiting. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Never give anything by mouth to a person who is not fully conscious. Do not leave victim unattended. Seek medical attention immediately.

# Cumene

## Notes to Physician

**INHALATION:** Inhalation overexposure can produce toxic effects. Monitor for respiratory distress. If cough or difficulty in breathing develops, evaluate for upper respiratory tract inflammation, bronchitis, and pneumonitis. Administer supplemental oxygen with assisted ventilation, as required.

This material (or a component) sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. Administration of sympathomimetic drugs should be avoided.

**INGESTION:** If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

## SECTION 5. FIRE FIGHTING MEASURES

---

**NFPA Flammability Classification** NFPA Class-IC flammable liquid.

**Flash Point** Closed cup: 36°C (96°F). (Pensky-Martens.)

**Lower Flammable Limit** AP 0.9 % **Upper Flammable Limit** AP 6.5 %

**Autoignition Temperature** 424°C (795°F)

**Hazardous Combustion Products** Carbon dioxide, carbon monoxide, smoke, fumes, and/or unburned hydrocarbons.

**Special Properties** Flammable Liquid! This material releases vapors at or below ambient temperatures. When mixed with air in certain proportions and exposed to an ignition source, its vapor can cause a flash fire. Use only with adequate ventilation. Vapors are heavier than air and may travel long distances along the ground to an ignition source and flash back. A vapor and air mixture can create an explosion hazard in confined spaces such as sewers. If container is not properly cooled, it can rupture in the heat of a fire.

**Extinguishing Media** **SMALL FIRE:** Use dry chemicals, carbon dioxide, foam, or inert gas (nitrogen). Carbon dioxide and inert gas can displace oxygen. Use caution when applying carbon dioxide or inert gas in confined spaces.  
**LARGE FIRE:** Use foam, water fog, or water spray. Water fog and spray are effective in cooling containers and adjacent structures. However, water can cause frothing and/or may not extinguish the fire. Water can be used to cool the external walls of vessels to prevent excessive pressure, autoignition or explosion. **DO NOT** use a solid stream of water directly on the fire as the water may spread the fire to a larger area.

**Protection of Fire Fighters** Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles. Cover pooling liquid with foam. Containers can build pressure if exposed to radiant heat; cool adjacent containers with flooding quantities of water until well after the fire is out. Withdraw immediately from the area if there is a rising sound from a venting safety device or discoloration of vessels, tanks, or pipelines. Be aware that burning liquid will float on water. Notify appropriate authorities of potential fire and explosion hazard if liquid enter sewers or waterways.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

---

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. For more specific information, refer to the Emergency Overview on Page 1, Exposure Controls and Personal Protection in Section 8 and Disposal Considerations in Section 13 of this MSDS.

## Cumene

Flammable Liquid! Release causes an immediate fire or explosion hazard. Evacuate all non-essential personnel from immediate area and establish a "regulated zone" with site control and security. A vapor-suppressing foam may be used to reduce vapors. Eliminate all ignition sources. All equipment used when handling this material must be grounded. Stop the leak if it can be done without risk. Do not touch or walk through spilled material. Remove spillage immediately from hard, smooth walking areas. Prevent spilled material from entering waterways, sewers, basements, or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material.

For large spills, secure the area and control access. Prevent spilled material from entering sewers, storm drains, other drainage systems, and natural waterways. Dike far ahead of a liquid spill to ensure complete collection. Water mist or spray may be used to reduce or disperse vapors; but, it may not prevent ignition in closed spaces. This material will float on water and its run-off may create an explosion or fire hazard. Verify that responders are properly HAZWOPER-trained and wearing appropriate respiratory equipment and fire-resistant protective clothing during cleanup operations. In an urban area, cleanup spill as soon as possible; in natural environments, cleanup on advice from specialists. Pick up free liquid for recycle and/or disposal if it can be accomplished safely with explosion-proof equipment. Collect any excess material with absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal. Comply with all applicable local, state and federal laws and regulations.

## SECTION 7. HANDLING AND STORAGE

---

### Handling

A spill or leak can cause an immediate fire or explosion hazard. Keep containers closed and do not handle or store near heat, sparks, or any other potential ignition sources. Avoid contact with oxidizing agents. Do NOT breathe vapor. Use only with adequate ventilation and personal protection. Never siphon by mouth. Avoid contact with eyes, skin, and clothing. Prevent contact with food and tobacco products. Do NOT take internally.

When performing repairs and maintenance on contaminated equipment, keep unnecessary persons away from the area. Eliminate all potential ignition sources. Drain and purge equipment, as necessary, to remove material residues. Follow proper entry procedures, including compliance with 29 CFR 1910.146 prior to entering confined spaces such as tanks or pits. Use gloves constructed of impervious materials and protective clothing if direct contact is anticipated. Use appropriate respiratory protection when concentrations exceed any established occupational exposure level (See Section 8) Promptly remove contaminated clothing. Wash exposed skin thoroughly with soap and water after handling.

Non-equilibrium conditions may increase the fire hazard associated with this product. A static electrical charge can accumulate when this material is flowing through pipes, nozzles or filters and when it is agitated. A static spark discharge can ignite accumulated vapors particularly during dry weather conditions. Always bond receiving containers to the fill pipe before and during loading. Always confirm that receiving container is properly grounded. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards associated with electrostatic charges. Carefully review operations that may increase the risks associated with static electricity such as tank and container filling, tank cleaning, sampling, gauging, loading, filtering, mixing, agitation, etc. In addition to bonding and grounding, efforts to mitigate the hazards of an electrostatic discharge may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities. Dissipation of electrostatic charges may be improved with the use of conductivity additives when used with other mitigation efforts, including bonding and grounding. Always keep nozzle in contact with the container throughout the loading process.

Do NOT fill any portable container in or on a vehicle. Do NOT use compressed air for filling, discharging or other handling operations. Product container is NOT designed for elevated pressure. Do NOT pressurize, cut, weld, braze solder, drill, or grind on containers. Do NOT expose product containers to flames, sparks, heat or other potential ignition sources. Empty containers may contain material residues which can ignite with explosive force. Observe label precautions.

# Cumene

**Storage** Keep container tightly closed. Store in a cool, dry, well-ventilated area. Store only in approved containers. Do not store with oxidizing agents. Do not store at elevated temperatures or in direct sunlight. Protect containers against physical damage. Head spaces in tanks and other containers may contain a mixture of air and vapor in the flammable range. Vapor may be ignited by static discharge. Storage area must meet OSHA requirements and applicable fire codes. Additional information regarding the design and control of hazards associated with the handling and storage of flammable and combustible liquids may be found in professional and industrial documents including, but not limited to, the National Fire Protection Association (NFPA) publications NFPA 30 ("Flammable and Combustible Liquid Code"), NFPA 77 ("Recommended Practice on Static Electricity") and the American Petroleum Institute (API) Recommended Practice 2003, ("Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents").

Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers or waste residues of this product.

## SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**Engineering Controls** Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated below. All electrical equipment should comply with the National Electrical Code. An emergency eye wash station and safety shower should be located near the work-station.

**Personal Protective Equipment** Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. The following pictograms represent the minimum requirements for personal protective equipment. For certain operations, additional PPE may be required.



**Eye Protection** Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. Chemical goggles should be worn during transfer operations or when there is a likelihood of misting, splashing, or spraying of this material. A suitable emergency eye wash water and safety shower should be located near the work station.

**Hand Protection** Avoid skin contact. Use heavy duty gloves constructed of chemical resistant materials such as Viton® or heavy nitrile rubber. Wash hands with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities or leaving work. DO NOT use gasoline, kerosene, solvents or harsh abrasives as skin cleaners.

**Body Protection** Avoid skin contact. Wear long-sleeved fire-retardant garments (e.g., Nomex®) while working with flammable and combustible liquids. Additional chemical-resistant protective gear may be required if splashing or spraying conditions exist. This may include an apron, boots and additional facial protection. If product comes in contact with clothing, immediately remove soaked clothing and shower. Promptly remove and discard contaminated leather goods.

**Respiratory Protection** For known vapor concentrations above the occupational exposure guidelines (see below), use a NIOSH-approved organic vapor respirator if adequate protection is provided. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134). For airborne vapor concentrations that exceed the recommended protection factors for organic vapor respirators, use a full-face, positive-pressure, supplied air respirator. Due to fire and explosion hazards, do not enter atmospheres containing concentrations greater than 10% of the lower flammable limit of this product.

**General Comments** Warning! Use of this material in spaces without adequate ventilation may result in generation of hazardous levels of combustion products and/or inadequate oxygen levels for breathing. Odor is an inadequate warning for hazardous conditions.

# Cumene

## Occupational Exposure Guidelines

### Substance

Cumene

### Applicable Workplace Exposure Levels

**ACGIH (United States).**

TWA: 50 ppm 8 hour(s).

**OSHA (United States). Skin**

TWA: 50 ppm 8 hour(s).

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES (TYPICAL)

|                              |  |              |                         |                               |                   |
|------------------------------|--|--------------|-------------------------|-------------------------------|-------------------|
| <b>Physical State</b>        | Liquid.  | <b>Color</b> | Transparent, colorless. | <b>Odor</b>                   | Aromatic.         |
| <b>Specific Gravity</b>      | 0.86 (Water = 1)   | <b>pH</b>    | Not applicable.         | <b>Vapor Density</b>          | 4.1 (Air = 1)     |
| <b>Boiling Range</b>         | 152°C (306°F)  |              |                         | <b>Melting/Freezing Point</b> | Not available.    |
| <b>Vapor Pressure</b>        | 1.1 kPa (8 mm Hg) (at 20°C)  |              |                         | <b>Volatility</b>             | 862 g/l VOC (w/v) |
| <b>Solubility in Water</b>   | Negligible solubility in cold water.   |              |                         | <b>Viscosity (cSt @ 40°C)</b> | 0.7               |
| <b>Flash Point</b>           | Closed cup: 36°C (96°F). (Pensky-Martens.)   |              |                         |                               |                   |
| <b>Additional Properties</b> | Paraffin, Isoparaffin and Cycloparaffin Hydrocarbons Content = <1 Wt.% (ASTM D-1319);<br>Aromatic Hydrocarbon Content = >99 Wt. % (ASTM D-1319);<br>Average Density at 60°F = 7.19 lbs./gal. (Calculated via ASTM D-287);<br>Aniline Cloud Point Temperature = 52°F (11°C) (ASTM D-611);<br>Kauri-Butanol (KB) Value = 96 (ASTM D-1133);<br>Dry Point Temperature = 307°F (153°C) (ASTM D-86, D-850 or D-1078);<br>Evaporation Rate = 0.5 (n-Butyl acetate = 1.0);<br>Heat Value = 18,670 Btu. per pound |              |                         |                               |                   |

## SECTION 10. STABILITY AND REACTIVITY

|   |   |                                 |                        |
|---|---|---------------------------------|------------------------|
| <b>Chemical Stability</b>               | Stable.   | <b>Hazardous Polymerization</b> | Not expected to occur. |
| <b>Conditions to Avoid</b>              | Keep away from heat, sparks and flame. Forms explosive peroxides with prolonged storage.  |                                 |                        |
| <b>Materials Incompatibility</b>        | Strong acids, alkalies, and oxidizers.  |                                 |                        |
| <b>Hazardous Decomposition Products</b> | No additional hazardous decomposition products were identified other than the combustion products identified in Section 5 of this MSDS. |                                 |                        |

## SECTION 11. TOXICOLOGICAL INFORMATION

For other health-related information, refer to the Emergency Overview on Page 1 and the Hazards Identification in Section 3 of this MSDS.

### Toxicity Data

#### Cumene:

Effects from Acute Exposure:

Overexposure to cumene may cause upper respiratory tract irritation and severe CNS depression.

Effects from Prolonged or Repeated Exposure:

Studies in laboratory animals indicate evidence of adverse effects on the kidney and adrenal glands following high level exposure. The relevance of these findings to humans is not clear at this time. IARC has classified cumene as "possibly carcinogenic to humans" (Group 2B).

# Cumene

## SECTION 12. ECOLOGICAL INFORMATION

|                           |  |
|---------------------------|--|
| <b>Ecotoxicity</b>        | LC50 (fish): 1- 10 mg/l. This product is potentially toxic to freshwater and saltwater ecosystems.   |
| <b>Environmental Fate</b> | This product will normally float on water. Components will evaporate rapidly. Aquatic toxicity values are expected to be in the range of 1 - 10 mg/l based upon data from components and similar products. This material may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment. The log Kow value for this product is 3.66. |


## SECTION 13. DISPOSAL CONSIDERATIONS

**Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.**

If discarded, Cumene is regulated by US EPA as a listed hazardous waste (U055). Transportation, treatment, storage and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact the RCRA/Superfund Hotline at (800) 424-9346 or your regional US EPA office for guidance concerning case specific disposal issues.

## SECTION 14. TRANSPORT INFORMATION

**The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.**

|                             |   |                                     |  |
|-----------------------------|---|-------------------------------------|--|
| <b>US DOT Status</b>        | A U.S. Department of Transportation (DOT) regulated material.                         |                                     |  |
| <b>Proper Shipping Name</b> | Isopropylbenzene (Cumene)   |                                     |  |
| <b>Hazard Class</b>         | 3   | <b>Packing Group</b>                | III  |
|                             |   | <b>UN/NA Number</b>                 | UN 1918  |
| <b>Reportable Quantity</b>  | RQ 5000 lbs. [Based upon maximum Cumene concentration of 100% and an RQ of 5000 lbs.] |                                     |  |
| <b>Placard(s)</b>           |    | <b>Emergency Response Guide No.</b> | 128  |
|                             |   | <b>MARPOL III Status</b>            | Not a DOT "Marine Pollutant" per 49 CFR 171.8. |

## SECTION 15. REGULATORY INFORMATION

|   |  |
|---|--|
| <b>TSCA Inventory</b>                                   | This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.  |
| <b>SARA 302/304 Emergency Planning and Notification</b> | The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified. |

## Cumene

|   |  |
|---|--|
| <b>SARA 311/312 Hazard Identification</b>                         | The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories:<br>Fire, Acute (Immediate) Health Hazard, Chronic (Delayed) Health Hazard   |
| <b>SARA 313 Toxic Chemical Notification and Release Reporting</b> | This product contains the following components in concentrations above <i>de minimis</i> levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA:<br>Cumene [CAS No.: 98-82-8] Concentration: >99%  |
| <b>CERCLA</b>   | The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQ's) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subject to this statute are:<br>Cumene [CAS No.: 98-82-8] RQ = 5000 lbs. (2268 kg) Concentration: >99%   |
| <b>Clean Water Act (CWA)</b>                                      | Discharges or spills of this material onto or in waters of the United States, adjoining shorelines, or into conduits leading to surface waters of the US without proper Federal or State permits should be reported to the National Response Center at (800) 424-8802.   |
| <b>California Proposition 65</b>                                  | This material may contain the following components which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):<br>Cumene: ~100%<br>Benzene: <0.005%   |
| <b>New Jersey Right-to-Know Label</b>                             | For New Jersey R-T-K labeling requirements, refer to components listed in Section 2.   |
| <b>Additional Remarks</b>   | Federal Hazardous Substances Act, related statutes, and Consumer Product Safety Commission regulations, as defined by 16 CFR 1500.14(b)(3) and 1500.83(a)(13): This product contains "Petroleum Distillates" which may require special labeling if distributed in a manner intended or packaged in a form suitable for use in the household or by children. Precautionary label dialogue should display the following: <b>DANGER: Contains Petroleum Distillates! Harmful or fatal if swallowed! Call Physician Immediately. KEEP OUT OF REACH OF CHILDREN!</b><br>WHMIS Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).<br>WHMIS Class D-2A: Material causing other toxic effects (VERY TOXIC). - Carcinogenicity |

## SECTION 16. OTHER INFORMATION

Refer to the top of Page 1 for the HMIS and NFPA Hazard Ratings for this product.

### REVISION INFORMATION

|                       |           |
|-----------------------|-----------|
| <b>Version Number</b> | 10.5      |
| <b>Revision Date</b>  | 6/26/2012 |

### ABBREVIATIONS

|                    |             |                     |              |
|--------------------|-------------|---------------------|--------------|
| AP: Approximately  | EQ: Equal   | >: Greater Than     | <: Less Than |
| NA: Not Applicable | ND: No Data | NE: Not Established |              |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

IARC: International Agency for Research on Cancer

NIOSH: National Institute of Occupational Safety and Health

NPCA: National Paint and Coating Manufacturers Association

EPA: US Environmental Protection Agency

# Cumene

HMIS: Hazardous Materials Information System

OSHA: Occupational Safety and Health Administration

NTP: National Toxicology Program

NFPA: National Fire Protection Association

## DISCLAIMER OF LIABILITY

---

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS MSDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS MSDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

---

\*\*\*\*\* END OF MSDS \*\*\*\*\*