MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 077-001

Product name Slide N' Glide Silicone Spray

Effective date 23-Apr-2009

Total Cleanse Solutions Company information

Northvale, NJ 07647 United States

General Assistance 877-672-4727 Company phone

800-535-5053 **Emergency telephone US Emergency telephone outside US** 703-527-3887

05 Version #

12-Nov-2007 Supersedes date

2. Hazards Identification

Emergency overview EXTREMELY FLAMMABLE

CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when

exposed to heat or flame.

Harmful in contact with eyes. Irritating to skin. Irritating to respiratory system. Prolonged

exposure may cause chronic effects.

Potential health effects

Routes of exposure Ingestion. Inhalation. Skin contact. Eye contact.

Contact may irritate or burn eyes. Eye contact may result in corneal injury. **Eyes**

Skin Irritating to skin. Prolonged or repeated contact can result in defatting and drying of the

skin which may result in skin irritation and dermatitis (rash).

Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Inhalation

Irritating to respiratory system. Prolonged inhalation may be harmful.

Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Ingestion

Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss

of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

May cause delayed lung damage.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Acetone	67-64-1	20 - 30
Propane	74-98-6	20 - 30
n-Butane	106-97-8	20 - 30
Aliphatic Petroleum Solvent	64742-89-8	10 - 15
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	5 - 8
Non-hazardous and other components below reportable levels		2.5 - 10

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Remove and isolate contaminated clothing and shoes. Wash off with warm water and Skin contact

soap. Get medical attention if irritation develops or persists.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Call a physician if symptoms

develop or persist.

trade_name Slide N' Glide Silicone Spray

MSDS US Revision date: 23-APR-2009 Print date: 23-APR-2009 Product #: 077-001

Ingestion

If material is ingested, immediately contact a poison control center. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media Protection of firefighters Alcohol foam. Dry chemical. Carbon dioxide (CO2). Do not use water jet.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. Level 3 Aerosol.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

Not established

Not established

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Acetone

Propane

Components	CAS#	TWA	STEL	Ceiling
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
OSHA				
Components	CAS#	TWA	STEL	Ceiling

1000 ppm

1000 ppm

Personal protective equipment

Eye / face protection Wear chemical goggles.

67-64-1

74-98-6

Not established

Not established

Skin protection Respiratory protection Wear appropriate chemical resistant clothing. Protective gloves.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance Compressed liquefied gas. **Boiling point** 82.4 °F (27.8 °C) estimated

Color Colorless.

Flammability (HOC) 37.3419 kJ/g estimated

Flash back Yes

Flash point -156 °F (-104.4 °C) estimated

Form Aerosol.

Odor Solvent.
pH Not applicable

Physical state Liquid.

Pressure 50 - 70 psig @ 70F

SolubilityNegligibleSpecific gravity0.6446 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition.

Conditions to avoid Heat, flames and sparks.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological Information

Acute effects Acute LD50: 10501 mg/kg estimated, Rat, Dermal

12. Ecological Information

Ecotoxicity

Components of this product have been identified as having potential environmental concerns.

LC50 715 mg/L, Fish, 96.00 Hours, FC50 40538 mg/L, Daphnia, 48.00 Hours

EC50 40538 mg/L, Daphnia, 48.00 Hours, IC50 31333 mg/L, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes

D001: Waste Flammable material with a flash point <140 F

Disposal instructions

Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container at hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306
Packaging non bulk 156, 306
Packaging bulk None

trade_name Slide N' Glide Silicone Spray MSDS US

Product #: 077-001 Revision date: 23-APR-2009 Print date: 23-APR-2009

IMDG

Basic shipping requirements:

AEROSOLS Proper shipping name

Hazard class 2.1 **UN number** 1950

Additional information:

LTD QTY **Packaging exceptions** Item Labels required None **Transport Category** 2



Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class 2.1 **UN** number 1950

Additional information:

Packaging exceptions LTD QTY Labels required 2.1





15. Regulatory Information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely

hazardous substance

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region Inventory name On inventory (yes/no)* China Inventory of Existing Chemical Substances in China (IECSC) Yes Europe European Inventory of New and Existing Chemicals (EINECS) No European List of Notified Chemical Substances (ELINCS) No Europe Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

67-64-1 Acetone Environmental hazard

Aliphatic Petroleum Solvent 64742-89-8 Present 106-97-8 Present n-Butane 74-98-6 Propane Present Synthetic Isoparaffinic 64742-47-8 Present

Hydrocarbon

trade_name Slide N' Glide Silicone Spray

Product #: 077-001 Revision date: 23-APR-2009 Print date: 23-APR-2009

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings
Health: 1*
Flammability: 4
Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updatedThis document has undergone significant changes and should be reviewed in its entirety.

trade_name Slide N' Glide Silicone Spray MSDS US