# Vacuum Pumps and Systems

Busch LLC, 516 Viking Drive, Virginia Beach, VA 23452



## MATERIAL SAFETY DATA SHEET

## **SECTION I - PRODUCT AND COMPANY IDENTIFICATION**

Product/Material:Busch R 530Emergency TelephoneManufacturer:Busch LLCChemtrec: (800)424-9300

Address: 516 Viking Drive Non-emergency Telephone No.

Virginia Beach, VA 23452 **Busch LLC (757)463-7800** 

#### SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Highly refined mineral oils and additives.

The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

## **SECTION III - HAZARDS IDENTIFICATION**

**Emergency Overview** 

**Appearance and Odor:** Pale yellow, liquid Slight hydrocarbon.

**Health Hazards:** Not classified as dangerous for supply or conveyance.

Safety Hazards: Not classified as flammable but will burn.

**Environmental Hazards:** Not classified as dangerous for the environment.

Health Hazards: Not expected to be a health hazard when used under normal

conditions.

**Health Hazards Inhalation:** Under normal conditions if use, this is not expected to be a primary

route of exposure.

**Skin Contact:** Prolonged or repeated skin contact without proper cleaning can clog

the pores of the skin resulting in disorders such as oil

Acne/folliculitis.

**Eye Contact:** May cause slight irritation to eyes.

**Ingestion:** Low toxicity if swallowed.

**Other information:** Used oil may contain harmful impurities.

Signs and Symptoms: Oil acne/folliculitis signs and symptoms may include formation of

black pustules and spots on the skin of exposed areas. Ingestion

may result in nausea, vomiting and/or diarrhea.

Aggravated Medical Condition: Pre-existing medical conditions of the following organ(s) or organ

system(s) may be aggravated by exposure to this material: Skin.

**Environmental Hazards:** Not classified as dangerous for the environment.

Additional Information: Under normal conditions of use or in a foreseeable emergency, this

product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

## **SECTION IV - FIRST AID MEASURES**

**General Information:** Not expected to be a health hazard when used under normal

conditions.

Inhalation: No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

**Skin Contact:** Remove contaminated clothing. Flush exposed area with water and

follow by washing with soap if available. If persistent irritation occurs

obtain medical attention.

Eye Contact: Flush eye with copious quantities of water. If persistent irritation

occurs obtain medical attention.

**Ingestion:** In general, no treatment is necessary unless large quantities are

swallowed, however, get medical advice.

Advice to Physician: Treat symptomatically.

## **SECTION V - FIRE FIGHTING MEASURES**

Clear Fire area of all non-emergency personnel.

Flash Point: Typical 201 °C / 394 °F

**Upper / lower:** Typical 1 – 10%(V)(based on mineral oil)

Flammability or Explosion Limits:

**Auto Ignition Temperature:** >320 °C / 608 °F

Specific Hazards: Hazardous combustion products may include: A complex mixture of

airborne solid and liquid particulates and gases (smoke). Carbon

monoxide. Unidentified organic and inorganic compounds.

Suitable Extinguishing:

**Media:** Foam, water spray or fog. Dry chemical powder, carbon dioxide,

sand or earth may be used for small fires only.

**Unsuitable Extinguishing:** 

**Media:** Do not use water in a jet.

**Protective Equipment for** 

Firefighters: Proper protective equipment including breathing apparatus must be

worn when approaching a fire in a confined space.

## **SECTION VI - ACCIDENTAL RELEASE MEASURES**

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations.

Protective Measures: Avoid contact with skin and eyes. Use appropriate containment to

avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other

appropriate barriers.

Clean Up Methods: Slippery when spilt. Avoid accidents, clean up immediately. Prevent

from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable

material and dispose or properly.

Additional Advice: Local authorities should be advised if significant spillages cannot be

contained.

#### **SECTION VII - HANDLING AND STORAGE**

General Precautions: Use local exhaust ventilation if there is risk of inhalation of vapors,

mists or aerosols. Properly dispose of any contaminated rags or

cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances

to help determine appropriate controls of sage handling, storage

and disposal of this material.

Avoid prolonged or repeated contact with skin. Avoid inhaling vapor Handling:

and/or mists. When handling product in drums, safety footwear should

be worn and proper handling equipment should be used.

Keep container tightly closed and in a cool, well-ventilated place. Use Storage:

properly labeled and closeable containers. Storage Temperature: 0 –

50 °C / 32 – 122 °F.

PVC **Unsuitable Materials:** 

Additional Information: Polyethylene containers should not be exposed high

temperatures because of possible risk of distortion.

#### SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

## Occupational Exposure Limits

Material	Source	Type	ppm	mg	<sub>l</sub> /m3 ľ	Votation
Oil mist, mineral	ACGIH	TWA(Mist)	5 mg/m3			
Oil mist, mineral	ACGIH	STEL(Mist)	10 mg/m3			
Exposure Controls:		The level of	protection	and types	of controls	necessary

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Personal Protective Equipment: Personal protective equipment (PPE) should meet recommended

national standards. Check with PPE suppliers.

**Respiratory Protection:** 

No respiratory protection is ordinarily required under normal conditions In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapors [boiling point >65°C(149 °F)].

**Hand Protection:** 

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, and dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a nonperfumed moisturizer is recommended.

**Eye Protection: Protective Clothing:**  Wear safety glasses or full face shield if splashes are likely to occur. Skin protection not ordinarily required beyond standard issue work

clothes.

Monitoring Methods: Monitoring of the concentration of substances in the breathing zone

of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

**Environmental Exposure** 

Controls: Minimize release to the environment. An environmental

assessment must be made to ensure compliance with local

environmental legislation.

## **SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:Pale yellow liquid.Odor:Slight hydrocarbonpH:Not applicable

Initial Boiling Point and Boiling Range: >280 °C / 536 °F (estimated value(s))

Flash Point: Typical 201 °C / 394 °F

Upper / lower Flammability or Explosion limits: Typical 1 – 10%(V)(based on mineral oil)

**Auto-ignition temperature:** >320 °C / 608 °F

**Vapor pressure:** <0.5 Pa at 20 °C / 68 °F (estimated value(s))

**Specific gravity:** Data not available

**Density:** 0.9 g/cm3 **Water solubility:** Negligible

**n-octanol/water partition:** >6 (based on information on similar products) coefficient (log POW)

Kinematic Viscosity:42 mm2/s at 40 °C / 104 °FVapor density (air=1):>1 (estimated value(s))Evaporation rate (nBuAc=1):Data not available

## **SECTION X - STABILITY AND REACTIVITY**

Stability: Stable

**Conditions to Avoid:** Extremes of temperature and direct sunlight.

Materials to Avoid: Strong oxidizing agents.

Hazardous Decomposition Products: Hazardous decomposition products are not expected to form

during normal storage.

#### **SECTION XI - TOXICOLOGICAL INFORMATION**

**Basis for Assessment:** Information given is based on data on the components and the

toxicology of similar products.

Acute Oral Toxicity: Expected to be of low toxicity: LD50 > 5000 mg/kg, Rat

Acute Dermal Toxicity: Expected to be of low toxicity LD50 > 5000 mg/kg, Rabbit

Acute Inhalation Toxicity: Not considered to be an inhalation hazard under normal conditions

of use.

**Skin Irritation:** Expected to be slightly irritating. Prolonged or repeated skin contact

without proper cleaning can clog the pores of the skin resulting in

MSDS p/n 0872.914.920

www.buschusa.com

disorders such as oil acne/folliculitis.

**Eye Irritation:** Expected to be slightly irritating.

**Respiratory Irritation:** Inhalation of vapors or mists may cause irritation.

**Sensitization:** Not expected to be a skin sensitizer.

**Repeated Dose Toxicity:** Not expected to be a hazard.

**Mutagenicity:** Not considered a mutagenic hazard.

Carcinogenicity: Product contains mineral oils of types shown to be non-carcinogenic

in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be

associated with carcinogenic effects.

Reproductive and Developmental Toxicity: Not expected to be a hazard.

Additional Information: Used oils may contain harmful impurities that have accumulated

during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. All used oil should be handled with caution and skin

contact avoided as far as possible.

## **SECTION XII - ECOLOGICAL INFORMATION**

Ecotoxicological data have not been determined specifically for this product. Information given is based on knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity: Poorly soluble mixture. May cause physical fouling of aquatic

organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic

organisms at concent5rations less than 1 mg/l.

Mobility: Liquid under most environmental conditions. Floats on water. If it

enters soil, it will adsorb to soil particles and will not be mobile.

Persistence/degradability: Expected to be not readily biodegradable. Major constituents are

expected to be inherently biodegradable, but the product contains

components that may persist in the environment.

**Bioaccumulation:** Contains components with the potential to bioaccumulate.

Other Adverse Effects: Product is a mixture of non-volatile components, which are not

expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone

creation potential or global warning potential.

## **SECTION XIII - DISPOSAL CONSIDERATIONS**

Material Disposal: Recover or recycle if possible. It is the responsibility of the waste

generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not

dispose into the environment, on drains or in water courses.

**Container Disposal:** Dispose in accordance with prevailing regulations, preferably to a

recognized collector or contractor. The competence of the collector

or contractor should be established beforehand.

**Local Legislation:** Disposal should be in accordance with applicable regional, national,

and local laws and regulations.

## **SECTION XIV - TRANSPORT INFORMATION**

## **US** Department of Transportation Classification:

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

IMDG: This material is not classified as dangerous under IMDG

regulations.

IATA (Country variations may apply): This material is not classified as dangerous under IATA

regulations.

#### **SECTION XV - REGULATORY INFORMATION**

The regulatory information is not intended to be comprehensive. Other regulations may apply to this.

**Federal Regulatory Status** 

Notification Status: TSCA All components listed.

EINECS All components listed.

DSL All components listed.

AICS All components listed.

SARA Hazard Categories (311/312): No SARA 311/312 Hazards.

**State Regulatory Status** 

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

#### **SECTION XVI - OTHER INFORMATION**

NFPA Rating (Health, Fire: 0, 1, 1

Reactivity)

MSDS Version Number: 2.0

MSDS Effective Date: 07/11/2008

**MSDS Revisions:** A vertical bar (I) in the left margin indicates an amendment from the

previous version.

MSDS Regulation: The content and format of this MSDS is in accordance with the

OSHA Hazard Communication Standard, 29 CFR 1910.1200.

MSDS Distribution: The information in this document should be made available to all

who may handle the product.

**Disclaimer:** The information contained herein is based on our current knowledge

of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of

the product.