

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity

Skilcraft Power Duster, 10 oz

Alternate Names

Skilcraft Power Duster, 10 oz
LHB Part Number: 0894---010
National Stock Number: 7930-01-398-2473
CAGE Code: 0FTT5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See product label.

Application Method

See product label.

1.3. Details of the supplier of the safety data sheet

Company Name

LHB Industries
8833 Fleischer Place
Berkeley, MO 63134

Emergency

24 hour Emergency Telephone No.

(800) 633-8253 (PERS)

Customer Service: LHB Industries

(314) 423-4333

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222

Extremely flammable aerosol.

Liquified Gas;H280

Contains gas under pressure; may explode if heated.

Simple Asphyxiant

May displace oxygen and cause rapid suffocation.

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

[Response]:

No GHS response statements

[Storage]:

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1,1-difluoroethane (HFC-152A) CAS Number: 0000075-37-6	100	Flam. Gas 1;H220 Liquified Gas;H280 STOT SE 3;H336 Simple Asphyxiant	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



4. First aid measures

4.1. Description of first aid measures

General	Move victim to fresh air. Call 911 or emergency medical service if deemed necessary. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Remove and isolate contaminated clothing and shoes. Clothing frozen to the skin should be thawed before being removed. In case of contact with liquefied gas, thaw frosted parts with lukewarm water. In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. Wash skin with soap and water. Keep victim warm and quiet.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
4.2. Most important symptoms and effects, both acute and delayed	
Overview	Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. See section 2 for further details.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hydrofluoric acid and carbonyl halides.
Keep away from heat / sparks / open flames / hot surfaces - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).
Structural firefighters' protective clothing will only provide limited protection.
Always wear thermal protective clothing when handling refrigerated/cryogenic liquids.

EXTREMELY FLAMMABLE.

Will be easily ignited by heat, sparks or flames.
Will form explosive mixtures with air.
Vapors from liquefied gas are initially heavier than air and spread along ground.
Cylinders exposed to fire may vent and release flammable gas through pressure relief devices.
Containers may explode when heated.
Ruptured cylinders may rocket.
Vapors may cause dizziness or asphyxiation without warning.
Some may be irritating if inhaled at high concentrations.
Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
Fire may produce irritating and/or toxic gases.

ERG Guide No. 115

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
All equipment used when handling the product must be grounded.
Do not touch or walk through spilled material.
Stop leak if you can do it without risk.
If possible, turn leaking containers so that gas escapes rather than liquid.
Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
Do not direct water at spill or source of leak.
Prevent spreading of vapors through sewers, ventilation systems and confined areas.
Isolate area until gas has dispersed.
CAUTION: When in contact with refrigerated/cryogenic liquids, many materials become brittle and are likely to break without warning.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
Keep unauthorized personnel away.
Stay upwind.
Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).
Keep out of low areas.

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Strong alkalis or alkaline earth metals, finely powdered metals such as aluminum, magnesium or zinc and strong oxidizers.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000075-37-6	1,1-difluoroethane (HFC-152A)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000075-37-6	1,1-difluoroethane (HFC-152A)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



8.2. Exposure controls

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.
Skin	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Clear Colorless Liquid/Gas
Odor	Slight Ethereal Odor
Odor threshold	Not Measured
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	-58 F (Estimated)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 3.9% (vol.) Gas in air Upper Explosive Limit: 16.9% (vol.) Gas in air
Vapor pressure (Pa)	62.5 PSIG @ 70 F
Vapor Density	2.4 (Heavier than Air)
Specific Gravity	0.909 (7.58 lb/gal)
Solubility in Water	0.28% @ 70 F
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



Viscosity (cSt)	Not Measured
VOC %	0% by wt, 0 g/L
Maximum Incremental Reactivity	Not Measured
HAPS (lbs/gal)	0.0
HAPS (lbs/gal of Solids)	0.0
HAPS (lbs/lb of Solids)	0.0
% Volatile (by volume)	Not Measured

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Do not expose to heat or store at temperature above 120°F

10.5. Incompatible materials

Strong alkalis or alkaline earth metals, finely powdered metals such as aluminum, magnesium or zinc and strong oxidizers.

10.6. Hazardous decomposition products

Hydrofluoric acid and carbonyl halides

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
1,1-difluoroethane (HFC-152A) - (75-37-6)	No data available	No data available	No data available	No data available	No data available

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
1,1-difluoroethane (HFC-152A) - (75-37-6)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1030	UN1030	UN1030
14.2. UN proper shipping name	UN1030, 1,1-difluoroethane (HFC-152A), 2.1	1,1-difluoroethane (HFC-152A)	1,1-difluoroethane (HFC-152A)
14.3. Transport hazard class(es)	DOT Hazard Class: 2.1 DOT Label: 2.1	IMDG: 2.1	Air Class: 2.1
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification A

US EPA Tier II Hazards

Fire: No

Sudden Release of Pressure: Yes

Reactive: No

Immediate (Acute): No

Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:
(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:
(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):
(No Product Ingredients Listed)

N.J. RTK Substances (>1%):
1,1-difluoroethane (HFC-152A)

Penn RTK Substances (>1%) :
(No Product Ingredients Listed)

Safety Data Sheet

Skilcraft Power Duster, 10 oz

SDS Revision Date:

10/30/2014



16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H336 May cause drowsiness and dizziness.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document