

Version 2.4 Revision Date 2017-06-21

according to GB/T 16483 and GB/T 17519

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : ORFOM® MCO Collector

Material : 1119702, 1119671, 1119669, 1119668, 1119693, 1119692,

1119650, 1117263, 1114151, 1108013, 1104301, 1096190,

1086158, 1016847, 1016846

Use : Mineral Processing Aide

Company : Chevron Phillips Chemical Company LP

Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380

Emergency telephone:

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

SECTION 2: Hazards identification

Classification of the substance or mixture GHS Classification and Labeling: Follow GB 13690, GB 15258 and GB 30000.2 to GB 30000.29 (GHS 2011)

Emergency Overview

Danger

Physical state: Liquid Color: Black Odor: Mild

Hazards : Flammable liquid and vapor. May be harmful if swallowed.

SDS Number:100000013323 1/12

Version 2.4 Revision Date 2017-06-21

Causes skin irritation. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Classification

Flammable liquids, Category 3
 Acute toxicity, Category 5, Oral
 Skin corrosion/irritation, Category 2
 Carcinogenicity, Category 1B
 Reproductive toxicity, Category 2

Specific target organ systemic toxicity - repeated exposure,

Category 2, Blood, Liver, thymus gland

Aspiration hazard, Category 1 Acute aquatic toxicity, Category 1 Chronic aquatic toxicity, Category 1

Labeling

Symbol(s)









Signal Word : Danger

Hazard Statements : H226: Flammable liquid and vapor.

H303: May be harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation. H350: May cause cancer.

H361: Suspected of damaging fertility or the unborn child. H373: May cause damage to organs (Blood, Liver, thymus

gland) through prolonged or repeated exposure.

H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been

read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapor/spray.

P264: Wash skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

SDS Number:100000013323

2/12

Version 2.4 Revision Date 2017-06-21

> P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P312: Call a POISON CENTER/doctor if you feel unwell. P331: Do NOT induce vomiting.

P332 + P313: If skin irritation occurs: Get medical advice/

attention.

P362 + P364: Take off contaminated clothing and wash it

before reuse.

P370 + P378: In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

P391: Collect spillage.

Storage:

P403 + P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/ container to an approved waste

disposal plant.

SECTION 3: Composition/information on ingredients

Synonyms Flotation Oil

Molecular formula Mixture

Chemical name	CAS-No. / EINECS-No.	Concentration [wt%]
Decant (clarified) Oils	64741-62-4	0 - 80
Light Cycle Oil	64741-59-9	0 - 80

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data

> sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious,

place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well

with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

SDS Number: 100000013323 3/12

ORFOM® MCO Collector

Version 2.4 Revision Date 2017-06-21

SECTION 5: Firefighting measures

Flash point 43 °C (110 °F)

Method: PMCC

Autoignition temperature : No data available

Suitable extinguishing

media

: Carbon dioxide (CO2).

Unsuitable extinguishing

media

: High volume water jet.

Specific hazards during fire

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective

equipment for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case

of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed

containers.

Fire and explosion

protection

: Do not spray on an open flame or any other incandescent material. Keep away from open flames, hot surfaces and

sources of ignition.

Hazardous decomposition

products

: Carbon oxides. Sulfur oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate

ventilation.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable.

closed containers for disposal.

SECTION 7: Handling and storage

Handling

: Avoid formation of aerosol. Do not breathe vapors/dust. Avoid Advice on safe handling

exposure - obtain special instructions before use. Avoid

SDS Number:100000013323 4/12

Version 2.4 Revision Date 2017-06-21

contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion

Do not spray on an open flame or any other incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection

Engineering measures

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless

ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators

may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Wear as appropriate: Flame retardant protective clothing.

SDS Number:100000013323 5/12

Version 2.4 Revision Date 2017-06-21

Footwear protecting against chemicals.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Physical state : Liquid Color : Black Odor : Mild

Safety data

Flash point : 43 °C (110 °F)

Method: PMCC

Lower explosion limit : No data available

Upper explosion limit : No data available

Autoignition temperature : No data available

Molecular formula : Mixture

Molecular weight : Not applicable

pH : Not applicable

Pour point : No data available

Boiling point/boiling range : 165 - 538 °C (329 - 1,000 °F)

Vapor pressure : 1.00 MMHG

at 21 °C (70 °F)

estimated

Relative density : 0.985

at 15.6 °C (60.1 °F)

Water solubility : Negligible

Partition coefficient: n-

octanol/water

: No data available

Viscosity, kinematic : 35 - 45 cSt

at 25 °C (77 °F)

Relative vapor density : 3

(Air = 1.0)

Evaporation rate : 1

SECTION 10: Stability and reactivity

SDS Number:100000013323 6/12

ORFOM® MCO Collector

Version 2.4 Revision Date 2017-06-21

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

Hazardous decomposition

products

: Carbon oxides Sulfur oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

ORFOM® MCO Collector

Acute oral toxicity : 3,678 mg/kg

Method: Acute toxicity estimate

Acute toxicity estimate: 2,500 mg/kg

Method: Calculation method

ORFOM® MCO Collector

Acute inhalation toxicity : > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Acute toxicity estimate

Acute toxicity estimate: 2.72 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

ORFOM® MCO Collector

Acute dermal toxicity : > 2,000 mg/kg

Method: Acute toxicity estimate

ORFOM® MCO Collector

Skin irritation

: Irritating to skin.

ORFOM® MCO Collector

Eye irritation

: Vapors may cause irritation to the eyes, respiratory system

and the skin.

ORFOM® MCO Collector

Sensitization

: Contains no substance or substances classified as sensitizing. Information refers to the main ingredient.

Repeated dose toxicity

SDS Number:100000013323 7/12

ORFOM® MCO Collector

Version 2.4 Revision Date 2017-06-21

Decant (clarified) Oils : Species: Rat

> Application Route: Dermal Dose: 0, 8, 30, 125, 500 mg/kg

Exposure time: 13 wk

Lowest observable effect level: 8 mg/kg

Target Organs: Liver

Light Cycle Oil Species: Rat, males

Sex: males

Application Route: Dermal

Dose: 0, 8, 25, 125, 500, 1250 mg/kg

Exposure time: 90 day

Number of exposures: 5 days/wk

NOEL: 25 mg/kg

Target Organs: Blood, Liver, Thymus

Species: Rat, females

Sex: females

Application Route: Dermal

Dose: 0, 8, 25, 125, 500, 1250 mg/kg

Exposure time: 90 day

Number of exposures: 5 days/wk

NOEL: 125 mg/kg

Target Organs: Blood, Liver, Thymus

Reproductive toxicity

Decant (clarified) Oils : Suspected of damaging fertility or the unborn child.

Developmental Toxicity

Decant (clarified) Oils : Species: Rat

Application Route: Dermal

Dose: 0, 0.05, 1, 50, 250 mg/kg/bw/d

Exposure time: 6h/d Number of exposures: daily Test period: GD 0-19

NOAEL Teratogenicity: 0.05 mg/kg NOAEL Maternal: 0.05 mg/kg

Suspected of damaging fertility or the unborn child.

Light Cycle Oil Species: Rat

> Application Route: Dermal Dose: 1, 50, 250 mg/kg/d Number of exposures: once daily

Test period: GD 0-19

Method: OECD Guideline 414 NOAEL Teratogenicity: 1 mg/kg NOAEL Maternal: 1 mg/kg

ORFOM® MCO Collector

Aspiration toxicity : May be fatal if swallowed and enters airways.

CMR effects

Decant (clarified) Oils : Carcinogenicity: Possible human carcinogen

> Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on

SDS Number:100000013323 8/12

ORFOM® MCO Collector

Version 2.4 Revision Date 2017-06-21

animal experiments.

Light Cycle Oil Carcinogenicity: Possible human carcinogen

ORFOM® MCO Collector

Further information : Solvents may degrease the skin. Inhalation of high vapor

concentrations may cause symptoms like headache,

dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information

Toxicity to fish

Decant (clarified) Oils : LL50: 79 mg/l

Exposure time: 96 h

semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar

substances.

Light Cycle Oil LL50: > 0.3 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

Decant (clarified) Oils : EL50: 0.22 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

Light Cycle Oil EL50: 0.32 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea)

Immobilization Method: OECD Test Guideline 202

Toxicity to algae

Decant (clarified) Oils : EL50: 0.32 mg/l

Exposure time: 72 h

static test Method: OECD Test Guideline 201

Light Cycle Oil EL50: 0.51 mg/l

Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (green algae) Growth inhibition Method: OECD Test Guideline 201

M-Factor

Clarified oils (petroleum),

catalytic cracked

Distillates (petroleum), light

catalytic cracked

Elimination information (persistence and degradability)

Biodegradability : This material is not expected to be readily biodegradable.

SDS Number:100000013323 9/12

: 1

Version 2.4 Revision Date 2017-06-21

Ecotoxicology Assessment

Acute aquatic toxicity

Decant (clarified) Oils : Very toxic to aquatic life.

Light Cycle Oil : Very toxic to aquatic life.

Chronic aquatic toxicity

Decant (clarified) Oils : Very toxic to aquatic life with long lasting effects.

Light Cycle Oil : Very toxic to aquatic life with long lasting effects.

Results of PBT assessment

Decant (clarified) Oils : Non-classified PBT substance, Non-classified vPvB substance

Light Cycle Oil : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological

information

: Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

SDS Number:100000013323 10/12

Version 2.4 Revision Date 2017-06-21

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1268, PETROLEUM DISTILLATES, N.O.S., (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL), 3, III, (43 °C), MARINE POLLUTANT, (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS, (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS, (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS, (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

Notification status

Europe REACH : Not in compliance with the inventory

United States of America (USA) : On TSCA Inventory

TSCA

Canada DSL : All components of this product are on the Canadian

DSL

Australia AICS : On the inventory, or in compliance with the inventory

New Zealand NZIoC : Not in compliance with the inventory

Japan ENCS : On the inventory, or in compliance with the inventory Korea KECI : On the inventory, or in compliance with the inventory

Philippines PICCS : Not in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory

Other regulations : Law on Prevention and Control of Environment

Pollution by Solid Waste, Regulation on the Safety Management of Hazardous Chemicals, Provisions on the Safe Use of Chemicals at Workplace, GB13690:

General rule for classification and hazard

communication of chemicals, Fire Protection Law

SDS Number:100000013323 11/12

ORFOM® MCO Collector

Version 2.4 Revision Date 2017-06-21

SECTION 16: Other information

Further information

Legacy SDS Number : 59730

Local emergency contact number: 0532-83889090

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

	ey or legend to abbreviations and a	cronyms used	d in the safety data sheet
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

SDS Number:100000013323 12/12