

**ORFOM® MCO Collector**

Version 2.3

Revision Date 2017-04-12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : ORFOM® MCO Collector
Material : 1119702, 1119671, 1119669, 1119668, 1119693, 1119692,
1119650, 1117263, 1114151, 1108013, 1104301, 1096190,
1086158, 1016847, 1016846

Use : Mineral Processing Aide

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: +800 CHEMCALL (+800 2436 2255) China: +86-21-22157316

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 3
Skin irritation, Category 2
Carcinogenicity, Category 1B
Reproductive toxicity, Category 2
Specific target organ systemic toxicity - repeated exposure,
Category 2, Blood, Liver, thymus gland
Aspiration hazard, Category 1

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H226: Flammable liquid and vapor.
 H303: May be harmful if swallowed.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H350: May cause cancer.
 H361: Suspected of damaging fertility or the unborn child.
 H373: May cause damage to organs (Blood, Liver, thymus gland) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/fume/gas/mist/vapor/spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

disposal plant.

Carcinogenicity:**IARC**

Group 2B: Possibly carcinogenic to humans

Decant (clarified) Oils 64741-62-4

Light Cycle Oil 64741-59-9

NTP

Known to be human carcinogen

Light Cycle Oil 64741-59-9

SECTION 3: Composition/information on ingredients

Synonyms : Flotation Oil

Molecular formula : Mixture

Component	CAS-No.	Weight %
Decant (clarified) Oils	64741-62-4	0 - 80
Light Cycle Oil	64741-59-9	0 - 80

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : 43 °C (110 °F)
Method: PMCC

Autoignition temperature : No data available

Suitable extinguishing media : Carbon dioxide (CO2).

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

- | | | |
|--|---|--|
| Unsuitable extinguishing media | : | High volume water jet. |
| Specific hazards during fire fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. |
| Fire and explosion protection | : | Do not spray on an open flame or any other incandescent material. Keep away from open flames, hot surfaces and sources of ignition. |
| Hazardous decomposition products | : | Carbon oxides. Sulfur oxides. |

SECTION 6: Accidental release measures

- | | | |
|---------------------------|---|---|
| Personal precautions | : | Use personal protective equipment. Ensure adequate ventilation. |
| Environmental precautions | : | Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods for cleaning up | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal. |

SECTION 7: Handling and storage**Handling**

- | | | |
|---|---|--|
| Advice on safe handling | : | Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. |
| Advice on protection against fire and explosion | : | Do not spray on an open flame or any other incandescent material. Keep away from open flames, hot surfaces and sources of ignition. |

Storage

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Engineering measures**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Flame retardant protective clothing. Footwear protecting against chemicals.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Physical state : Liquid
Color : Black

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

Odor : Mild

Safety dataFlash point : 43 °C (110 °F)
Method: PMCC

Lower explosion limit : No data available

Upper explosion limit : No data available

Autoignition temperature : No data available

Molecular formula : Mixture

Molecular weight : Not applicable

pH : Not applicable

Pour point : No data available

Boiling point/boiling range : 165 - 538 °C (329 - 1,000 °F)

Vapor pressure : 1.00 MMHG
at 21 °C (70 °F)
estimatedRelative density : 0.985
at 15.6 °C (60.1 °F)

Water solubility : Negligible

Partition coefficient: n-
octanol/water : No data availableViscosity, kinematic : 35 - 45 cSt
at 25 °C (77 °F)Relative vapor density : 3
(Air = 1.0)

Evaporation rate : 1

SECTION 10: Stability and reactivity

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous decomposition : Carbon oxides

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

products

Sulfur oxides

Other data

: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**ORFOM® MCO Collector****Acute oral toxicity**

: : 3,678 mg/kg

Method: Acute toxicity estimate

Acute toxicity estimate: 2,500 mg/kg

Method: Calculation method

Acute toxicity estimate: 1,980 mg/kg

Method: Calculation method

ORFOM® MCO Collector**Acute inhalation toxicity**

: : > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: Acute toxicity estimate

Acute toxicity estimate: 2.72 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: Calculation method

Acute toxicity estimate: 2.72 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: Calculation method

ORFOM® MCO Collector**Acute dermal toxicity**

: : > 2,000 mg/kg

Method: Acute toxicity estimate

Acute toxicity estimate: 2,500 mg/kg

Method: Calculation method

Acute toxicity estimate: 1,563 mg/kg

Method: Calculation method

ORFOM® MCO Collector**Skin irritation**

: Irritating to skin.

ORFOM® MCO Collector**Eye irritation**

: Vapors may cause irritation to the eyes, respiratory system and the skin.

ORFOM® MCO Collector**Sensitization**

: Contains no substance or substances classified as sensitizing. Information refers to the main ingredient.

Repeated dose toxicity

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

Decant (clarified) Oils : Species: Rat
 Application Route: Dermal
 Dose: 0, 8, 30, 125, 500 mg/kg
 Exposure time: 13 wk
 Lowest observable effect level: 8 mg/kg
 Target Organs: Liver

Light Cycle Oil : Species: Rat, males
 Sex: males
 Application Route: Dermal
 Dose: 0, 8, 25, 125, 500, 1250 mg/kg
 Exposure time: 90 day
 Number of exposures: 5 days/wk
 NOEL: 25 mg/kg
 Target Organs: Blood, Liver, Thymus

Species: Rat, females
 Sex: females
 Application Route: Dermal
 Dose: 0, 8, 25, 125, 500, 1250 mg/kg
 Exposure time: 90 day
 Number of exposures: 5 days/wk
 NOEL: 125 mg/kg
 Target Organs: Blood, Liver, Thymus

Reproductive toxicity

Decant (clarified) Oils : Suspected of damaging fertility or the unborn child.

Developmental Toxicity

Decant (clarified) Oils : Species: Rat
 Application Route: Dermal
 Dose: 0, 0.05, 1, 50, 250 mg/kg/bw/d
 Exposure time: 6h/d
 Number of exposures: daily
 Test period: GD 0-19
 NOAEL Teratogenicity: 0.05 mg/kg
 NOAEL Maternal: 0.05 mg/kg
 Suspected of damaging fertility or the unborn child.

Light Cycle Oil : Species: Rat
 Application Route: Dermal
 Dose: 1, 50, 250 mg/kg/d
 Number of exposures: once daily
 Test period: GD 0-19
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 1 mg/kg
 NOAEL Maternal: 1 mg/kg

**ORFOM® MCO Collector
Aspiration toxicity**

: May be fatal if swallowed and enters airways.

CMR effects

Decant (clarified) Oils : Carcinogenicity: Possible human carcinogen
 Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

animal experiments.

Light Cycle Oil

Carcinogenicity: Possible human carcinogen

**ORFOM® MCO Collector
Further information**

: Solvents may degrease the skin. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information**Toxicity to fish**

Decant (clarified) Oils : LL50: 79 mg/l
 Exposure time: 96 h
 semi-static test Method: OECD Test Guideline 203
 Information given is based on data obtained from similar substances.

Light Cycle Oil LL50: > 0.3 mg/l
 Exposure time: 96 h
 Species: Oncorhynchus mykiss (rainbow trout)
 semi-static test Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

Decant (clarified) Oils : EL50: 0.22 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 static test Method: OECD Test Guideline 202

Light Cycle Oil EL50: 0.32 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 Immobilization Method: OECD Test Guideline 202

Toxicity to algae

Decant (clarified) Oils : EL50: 0.32 mg/l
 Exposure time: 72 h
 static test Method: OECD Test Guideline 201

Light Cycle Oil EL50: 0.51 mg/l
 Exposure time: 72 h
 Species: Pseudokirchneriella subcapitata (green algae)
 Growth inhibition Method: OECD Test Guideline 201

M-Factor

Clarified oils (petroleum),
 catalytic cracked : 1
 Distillates (petroleum), light
 catalytic cracked : 1

Elimination information (persistence and degradability)

Biodegradability : This material is not expected to be readily biodegradable.

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

Ecotoxicology Assessment

Acute aquatic toxicity
Decant (clarified) Oils : Very toxic to aquatic life.

Light Cycle Oil : Very toxic to aquatic life.

Chronic aquatic toxicity
Decant (clarified) Oils : Very toxic to aquatic life with long lasting effects.

Light Cycle Oil : Very toxic to aquatic life with long lasting effects.

Results of PBT assessment
Decant (clarified) Oils : Non-classified PBT substance, Non-classified vPvB substance

Light Cycle Oil : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological
information : Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)
UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1268, PETROLEUM DISTILLATES, N.O.S., (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL), 3, III, (43 °C), MARINE POLLUTANT, (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS, (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS, (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS, (DECANT (CLARIFIED) OILS, LIGHT CYCLE OIL)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation**

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

EPCRA - EMERGENCY PLANNING COMMUNITY RIGHT - TO - KNOW

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable : This material does not contain any components with a section

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

Quantity 304 EHS RQ.

SARA 313 Ingredients : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

Pennsylvania Right To Know : Light Cycle Oil - 64741-59-9

California Prop. 65 Ingredients : WARNING! This product contains a chemical known in the State of California to cause cancer.

Notification status

Europe REACH	:	Not in compliance with the inventory
United States of America (USA) TSCA	:	On TSCA Inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	On the inventory, or in compliance with the inventory
Philippines PICCS	:	Not in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory


ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

SECTION 16: Other information

NFPA Classification : Health Hazard: 3
Fire Hazard: 3
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 59730

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act

ORFOM® MCO Collector

Version 2.3

Revision Date 2017-04-12

	New Chemical Substances		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		