

**Tertiary Butyl Mercaptan**

Version 1.5

Revision Date 2016-05-16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Tertiary Butyl Mercaptan
Material : 1069500, 1086416, 1086415, 1070007, 1064730, 1021473,
1021470, 1017940, 1036143, 1024807, 1021472, 1021471,
1024806, 1021469, 1028495, 1021474, 1027458, 1029711,
1017329, 1021468

EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
t-Butyl Mercaptan	75-66-1 200-890-2	Chevron Phillips Chemicals International NV 01-2119491288-26-0000

Relevant Identified Uses : Manufacture
Supported Distribution
Formulation
Use as an intermediate
Injection as odorant in fuels – industrial

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
Airport Plaza (Stockholm Building)
Leonardo Da Vincilaan 19
1831 Diegem
Belgium

SDS Requests: (800) 852-5530
Technical Information: (832) 813-4862
Responsible Party: Product Safety Group
Email:sds@cpchem.com

Emergency telephone:

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Health:

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: +800 CHEMCALL (+800 2436 2255) China: +86-21-22157316

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com

Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture****REGULATION (EC) No 1272/2008**

Flammable liquids, Category 2

H225:

Highly flammable liquid and vapor.

Skin sensitization, Category 1

H317:

May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 2

H411:

Toxic to aquatic life with long lasting effects.

Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H225

Highly flammable liquid and vapor.

H317

May cause an allergic skin reaction.

H411

Toxic to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**

P210

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P243

Take precautionary measures against static discharge.

P273

Avoid release to the environment.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Storage:

P403 + P235

Store in a well-ventilated place. Keep cool.

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Hazardous ingredients which must be listed on the label:

- 75-66-1 t-Butyl Mercaptan

SECTION 3: Composition/information on ingredients

Synonyms : t-Butyl Mercaptan
tert-Butanethiol
2-Methyl Propane-2-Thiol
TBM
TC4SH
tert-Butyl Mercaptan

Molecular formula : C₄H₁₀S

Mixtures**Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
t-Butyl Mercaptan	75-66-1 200-890-2	Flam. Liq. 2; H225 Aquatic Acute 2; H401 Skin Sens. 1; H317 Aquatic Chronic 2; H411	100

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

SECTION 5: Firefighting measures

Flash point	: -26 °C (-15 °F) estimated
Autoignition temperature	: No data available
Suitable extinguishing media	: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.
Unsuitable extinguishing media	: High volume water jet.
Specific hazards during fire fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Fire and explosion protection	: Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	: Carbon oxides. Sulfur oxides.

SECTION 6: Accidental release measures

Personal precautions	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Chevron Phillips Chemical Company LP**

Ingredients	Basis	Value	Control parameters	Note
t-Butyl Mercaptan	Manufacturer	TWA	0,5 ppm,	

DNEL : End Use: Industrial use
Routes of exposure: Skin contact
Potential health effects: Chronic effects, Systemic effects
Value: 2,06 mg/kg

DNEL : End Use: Industrial use
Routes of exposure: Inhalation
Potential health effects: Chronic effects, Systemic effects
Value: 14,5 mg/m3

DNEL : End Use: Industrial use
Routes of exposure: Inhalation
Potential health effects: Chronic effects, Local effects
Value: 18,6 mg/m3

DNEL : End Use: Consumer use
Routes of exposure: Ingestion
Potential health effects: Chronic effects, Systemic effects
Value: 0,74 mg/kg

DNEL : End Use: Consumer use
Routes of exposure: Inhalation
Potential health effects: Chronic effects, Systemic effects

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

	Value: 2,57 mg/m3
DNEL	: End Use: Consumer use Routes of exposure: Inhalation Potential health effects: Chronic effects, Local effects Value: 3,30 mg/m3
PNEC	: Fresh water Value: 0,0067 mg/l
PNEC	: Marine water Value: 0,00067 mg/l
PNEC	: Fresh water sediment Value: 0,0535 mg/kg
PNEC	: Sea sediment Value: 0,00535 mg/kg
PNEC	: Soil Value: 0,00718 mg/kg

Personal protective equipment

Hand protection	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggles.
Skin and body protection	: Impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

For additional details, see the Exposure Scenario in the Annex portion

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Form	: Liquid
Physical state	: Liquid
Color	: clear
Odor	: Repulsive

Safety data

Flash point	: -26 °C (-15 °F) estimated
Lower explosion limit	: No data available

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Upper explosion limit	: No data available
Oxidizing properties	: no
Autoignition temperature	: No data available
Molecular formula	: C ₄ H ₁₀ S
Molecular weight	: 90,2 g/mol
pH	: Not applicable
Pour point	: No data available
Boiling point/boiling range	: 63 - 65 °C (145 - 149 °F)
Vapor pressure	: 5,90 PSI at 38 °C (100 °F)
Relative density	: 0,81 at 16 °C (61 °F)
Water solubility	: Negligible
Partition coefficient: n-octanol/water	: No data available
Relative vapor density	: 3 (Air = 1.0)
Evaporation rate	: 1
Percent volatile	: > 99 %

SECTION 10: Stability and reactivity**Possibility of hazardous reactions**

Conditions to avoid	: Heat, flames and sparks.
Hazardous decomposition products	: Carbon oxides Sulfur oxides

Other data	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
------------	--

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

t-Butyl Mercaptan	: LD50: 4.729 mg/kg
-------------------	---------------------

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Species: Rat

Sex: male

Acute inhalation toxicity

t-Butyl Mercaptan

: LC50: 26643 ppm
Exposure time: 4 h
Species: Rat
Sex: male and female
Test atmosphere: vapor
Method: OECD Test Guideline 403

LC50: 22200 ppm
Exposure time: 4 h
Species: Rat
Sex: male
Test atmosphere: vapor
Method: OECD Test Guideline 403

LC50: 16500 ppm
Exposure time: 4 h
Species: Mouse
Sex: male
Test atmosphere: vapor
Method: OECD Test Guideline 403

**Tertiary Butyl Mercaptan
Skin irritation**

: No skin irritation.

**Tertiary Butyl Mercaptan
Eye irritation**

: Vapors may cause irritation to the eyes, respiratory system and the skin.

**Tertiary Butyl Mercaptan
Sensitization**

: Causes sensitization.

Repeated dose toxicity

t-Butyl Mercaptan

: Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 9, 97, 196 ppm
Exposure time: 13 wks
Number of exposures: 6 hrs/d, 5 d/wk
NOEL: > 196 ppm

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Species: Rat, Male and female
Sex: Male and female
Application Route: oral gavage
Dose: 10, 50, 200 mg/kg bw/day
Exposure time: 42-53 days
Number of exposures: Daily
NOEL: 50 mg/kg bw/day
Lowest observable effect level: 200 mg/kg bw/day
Method: OECD Guideline 422

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 25.1, 99.6, 403.4 ppm
Exposure time: 13 wks
Number of exposures: 6 hrs/d, 5 d/wk
NOEL: 99.6 ppm
Lowest observable effect level: 403.4 ppm
Method: OECD Guideline 413
Target Organs: Liver, Kidney, Blood, Upper respiratory tract
Information given is based on data obtained from similar substances.

Reproductive toxicity

t-Butyl Mercaptan : Species: Rat
Sex: male and female
Application Route: oral gavage
Dose: 10, 50, 200 mg/kg bw/day
Number of exposures: Daily
Test period: 42 -53 days
Method: OECD Guideline 422
NOAEL Parent: 200 mg/kg bw/day
NOAEL F1: 50 mg/kg bw/day
No adverse effects expected

Developmental Toxicity

t-Butyl Mercaptan : Species: Mouse
Application Route: Inhalation
Dose: 11, 99, 195 ppm
Exposure time: GD 6-16
Number of exposures: 6 hrs/d
NOAEL Teratogenicity: > = 195 ppm
NOAEL Maternal: > = 195 ppm

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Species: Rat
 Application Route: Inhalation
 Dose: 11, 99, 195 ppm
 Exposure time: GD6-19
 Number of exposures: 6 hrs/d
 NOAEL Teratogenicity: > =195 ppm
 NOAEL Maternal: > = 195 ppm

Species: Rat
 Application Route: oral gavage
 Dose: 10, 50, 200 mg/kg bw/day
 Exposure time: 42-53 days
 Number of exposures: Daily
 NOAEL Teratogenicity: 50 mg/kg bw /day
 NOAEL Maternal: 200 mg/kg bw /day

**Tertiary Butyl Mercaptan
Aspiration toxicity**

: May be harmful if swallowed and enters airways.

CMR effects

t-Butyl Mercaptan

: Carcinogenicity: Not available
 Mutagenicity: Did not show mutagenic effects in animal experiments.
 Teratogenicity: Did not show teratogenic effects in animal experiments.
 Reproductive toxicity: No toxicity to reproduction

**Tertiary Butyl Mercaptan
Further information**

: Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

t-Butyl Mercaptan

: LC50: 34 mg/l
 Exposure time: 96 h
 Species: Oncorhynchus mykiss (rainbow trout)
 semi-static test Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

t-Butyl Mercaptan

: EC50: 6,7 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 static test Method: OECD Test Guideline 202

Toxicity to algae

t-Butyl Mercaptan

: EC50: 24 mg/l
 Exposure time: 72 h
 Species: Pseudokirchneriella subcapitata (green algae)
 Method: OECD Test Guideline 201

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Bioaccumulation

t-Butyl Mercaptan : Bioconcentration factor (BCF): 12
Bioaccumulation is unlikely.

Biodegradability

t-Butyl Mercaptan : aerobic
Result: Not readily biodegradable.
6 %
Testing period: 63 d
Method: OECD Test Guideline 301

Ecotoxicology Assessment

Acute aquatic toxicity
t-Butyl Mercaptan : Toxic to aquatic life.

Chronic aquatic toxicity
t-Butyl Mercaptan : Toxic to aquatic life with long lasting effects.

Results of PBT assessment
t-Butyl Mercaptan : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological
information : An environmental hazard cannot be excluded in the event of
unprofessional handling or disposal., Toxic to aquatic life with
long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water
courses or the soil. Do not contaminate ponds, waterways or
ditches with chemical or used container. Send to a licensed
waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.
Do not re-use empty containers. Do not burn, or use a cutting
torch on, the empty drum.

For additional details, see the Exposure Scenario in the Annex portion

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN2347, BUTYL MERCAPTANS, 3, II

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN2347, BUTYL MERCAPTANS, 3, II, (-26 °C), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2347, BUTYL MERCAPTAN, 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2347, BUTYL MERCAPTAN, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN2347, BUTYL MERCAPTAN, 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2347, BUTYL MERCAPTAN, 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation****Chemical Safety Assessment**

Ingredients : 2-methylpropane-2-thiol A Chemical Safety Assessment has been carried out for this substance. 200-890-2

Major Accident Hazard : 96/82/EC Update: 2003

SDS Number:100000013356

12/25

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Legislation

Highly flammable
7b
Quantity 1: 5.000 t
Quantity 2: 50.000 t

: 96/82/EC Update: 2003
Dangerous for the environment
9b
Quantity 1: 200 t
Quantity 2: 500 t

Notification status

Europe REACH	:	On the inventory, or in compliance with the inventory
United States of America TSCA	:	On the inventory, or in compliance with the inventory
Canada DSL	:	On the inventory, or in compliance with the inventory
Australia AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	On the inventory, or in compliance with the inventory
Philippines PICCS	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information**Further information**

Legacy SDS Number : 95900

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure	OSHA	Occupational Safety & Health

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

	Scenario Tool		Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H317	May cause an allergic skin reaction.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Annex**1. Short title of Exposure Scenario: Manufacture**

Main User Groups	:	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	:	SU3, SU8, SU9: Industrial Manufacturing (all), Manufacture of bulk, large scale chemicals (including petroleum products), Manufacture of fine chemicals
Process category	:	PROC1: Use in closed process, no likelihood of exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental release category	:	ERC1, ERC4: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles
Further information	:	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities

**2.1 Contributing scenario controlling environmental exposure for:ERC1, ERC4:
Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles**
Product characteristics

Viscosity, dynamic : 1,6 mPa.s at 20 °C

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 365
Emission or Release Factor: Water : 0 %
Emission or Release Factor: Soil : 0,01 %
Remarks : Emission or Release Factor: Air : < 0.001 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,9 %)
Remarks : Wastewater emission controls are not applicable as there is no direct release to wastewater.
Remarks : Prevent environmental discharge consistent with regulatory requirements.

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Conditions and measures related to municipal sewage treatment plant

Flow rate of sewage treatment : 2.000 m3/d
 plant effluent
 Remarks : Not applicable as there is no release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC3, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in closed batch process (synthesis or formulation), Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC1, ERC4	EUSES		Freshwater		0,413 ng/L	0,000062
			Marine water		0,0348 ng/L	0,000052
			Freshwater sediment		1,7 ng/kg	0,000146
			Marine sediment		0,143 ng/kg	0,000123
			Soil		0,514 ng/kg	0,000074

ERC1: Manufacture of substances

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

1. Short title of Exposure Scenario: **Distribution**

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Main User Groups	:	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	:	SU3: Industrial Manufacturing (all)
Process category	:	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities : Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC15: Use as laboratory reagent
Environmental release category	:	ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7: Manufacture of substances, Formulation of preparations, Formulation in materials, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in inclusion into or onto a matrix, Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids, Industrial use of monomers for manufacture of thermoplastics, Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers, Industrial use of substances in closed systems
Further information	:	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

2.1 Contributing scenario controlling environmental exposure for:ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7: Manufacture of substances, Formulation of preparations, Formulation in materials, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in inclusion into or onto a matrix, Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids, Industrial use of monomers for manufacture of thermoplastics, Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers, Industrial use of substances in closed systems

Product characteristics

Viscosity, dynamic : 1,6 mPa.s at 20 °C

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Other given operational conditions affecting environmental exposure

Number of emission days per year : 300
 Emission or Release Factor: Air : 0,01 %
 Emission or Release Factor: Water : 0,001 %
 Emission or Release Factor: Soil : 0,001 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,9 %)
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): (Effectiveness: 99,9 %)
 Remarks : Negligible wastewater emissions as process operates without water contact.

Conditions and measures related to municipal sewage treatment plant

Flow rate of sewage treatment : 2.000 m3/d
 plant effluent
 Remarks : Not applicable as there is no release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Use as laboratory reagent

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
-----------------------	----------------------------	---------------------	-------------	------------	-------------------	-----------------------------

SDS Number:100000013356

18/25

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7	EUSES		Freshwater		0,107 µg/L	0,016
			Marine water		0,10 µg/L	0,149
			Freshwater sediment		0,44 µg/kg	0,0379
			Marine sediment		0,411 µg/kg	0,354
			Soil		1,63 µg/kg	0,236

ERC1: Manufacture of substances
 ERC2: Formulation of preparations
 ERC3: Formulation in materials
 ERC4: Industrial use of processing aids in processes and products, not becoming part of articles
 ERC5: Industrial use resulting in inclusion into or onto a matrix
 ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)
 ERC6b: Industrial use of reactive processing aids
 ERC6c: Industrial use of monomers for manufacture of thermoplastics
 ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers
 ERC7: Industrial use of substances in closed systems

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

1. Short title of Exposure Scenario: **Formulation**

Main User Groups	: SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	: SU3, SU 10: Industrial Manufacturing (all), Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
Process category	: PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises : PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities : Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC15: Use as laboratory reagent
Environmental release category	: ERC2: Formulation of preparations

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Further information : Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

2.1 Contributing scenario controlling environmental exposure for: ERC2: Formulation of preparations**Product characteristics**

Viscosity, dynamic : 1,6 mPa.s at 20 °C

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
 Dilution Factor (River) : 10
 Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 365
 Emission or Release Factor: Air : 0,25 %
 Emission or Release Factor: Water : 0,001 %
 Emission or Release Factor: Soil : 0,01 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,8 %)
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99,9 %)
 Remarks : Negligible wastewater emissions as process operates without water contact.

Conditions and measures related to municipal sewage treatment plant

Flow rate of sewage treatment plant effluent : 2.000 m3/d
 Remarks : Not applicable as there is no release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting;, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Use as laboratory reagent

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC2	EUSES		Freshwater		0,0395 µg/L	0,00589
			Marine water		0,0367 µg/L	0,0548
			Freshwater sediment		0,162 µg/kg	0,0140
			Marine sediment		0,151 µg/kg	0,130
			Soil		1,71 µg/kg	0,248

ERC2: Formulation of preparations

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

1. Short title of Exposure Scenario: Use as an intermediate

Main User Groups	: SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	: SU3, SU8, SU9: Industrial Manufacturing (all), Manufacture of bulk, large scale chemicals (including petroleum products), Manufacture of fine chemicals
Process category	: PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC15: Use as laboratory reagent

Environmental release category : **ERC6a:** Industrial use resulting in manufacture of another substance (use of intermediates)

Further information :
 Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

2.1 Contributing scenario controlling environmental exposure for:ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)
Product characteristics

Viscosity, dynamic : 1,6 mPa.s at 20 °C

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
 Dilution Factor (River) : 10
 Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 300
 Emission or Release Factor: Air : 0,5 %
 Emission or Release Factor: Water : 1,0 %
 Emission or Release Factor: Soil : 0,1 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,5 %)
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99 %)
 Remarks : Negligible wastewater emissions as process operates without water contact.

Conditions and measures related to municipal sewage treatment plant

Flow rate of sewage treatment plant effluent : 2.000 m3/d
 Remarks : Not applicable as there is no release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15: Use in closed process, no likelihood of exposure,

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC6a	EUSES		Freshwater		0,178 µg/L	0,0266
			Marine water		0,167 µg/L	0,249
			Freshwater sediment		0,732 µg/kg	0,0631
			Marine water		0,685 µg/kg	0,590
			Soil		2,52 µg/kg	0,364

ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

1. Short title of Exposure Scenario: Injection as odorant in fuels – industrial

Main User Groups	: SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	: SU3: Industrial Manufacturing (all)
Process category	: PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

discharging) from/ to vessels/ large containers at dedicated facilities

PROC15: Use as laboratory reagent

Environmental release category : **ERC7:** Industrial use of substances in closed systems

Further information :
Covers injection as odourant in fuel and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

2.1 Contributing scenario controlling environmental exposure for: **ERC7: Industrial use of substances in closed systems**

Product characteristics

Viscosity, dynamic : 1,6 mPa.s at 20 °C

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d

Dilution Factor (River) : 10

Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 365

Emission or Release Factor: Air : 0,25 %

Emission or Release Factor: Water : 0,001 %

Emission or Release Factor: Soil : 0 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,8 %)

Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99,9 %)

Remarks : Soil emission controls are not applicable as there is no direct release to soil.

Remarks : Negligible wastewater emissions as process operates without water contact.

Remarks : Wastewater emissions generated from equipment cleaning with water.

Conditions and measures related to municipal sewage treatment plant

Flow rate of sewage treatment plant effluent : 2.000 m3/d

Remarks : Not applicable as there is no release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: **PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in**

Tertiary Butyl Mercaptan

Version 1.5

Revision Date 2016-05-16

closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC7	EUSES		Freshwater		0,0324 µg/L	0,00484
			Marine water		0,0301 µg/L	0,0449
			Marine sediment		0,124 µg/kg	0,107
			Freshwater sediment		0,133 µg/kg	0,0115
			Soil		1,61 µg/kg	0,233

ERC7: Industrial use of substances in closed systems

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.