

SAFETY DATA SHEET

**Liquid Flowzan® Biopolymer XPT**

Version 1.8

Revision Date 2016-05-18

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Liquid Flowzan® Biopolymer XPT
 Material : 1095838, 1101333, 1097137, 1091030

EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
Isoprene	78-79-5 201-143-3 601-014-00-5	Chevron Phillips Chemicals International NV 01-2119457891-29-0009
Styrene	100-42-5 202-851-5 601-026-00-0	Chevron Phillips Chemicals International NV 01-2119457861-32-0005
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclic, <2% aromatics		Chevron Phillips Chemicals International NV 01-2119456620-43-0010

Relevant Identified Uses Supported : Use in Oil and Gas field drilling and production operations - Industrial

Company : Chevron Phillips Chemical Company LP
 Drilling Specialties Company LLC
 10001 Six Pines Drive
 The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
 Airport Plaza (Stockholm Building)
 Leonardo Da Vincilaan 19
 1831 Diegem
 Belgium

SDS Requests: (800) 852-5530
 Technical Information: (832) 813-4862

Liquid Flowzan® Biopolymer XPT

Version 1.8

Revision Date 2016-05-18

Responsible Party: Product Safety Group
Email:sds@cpchem.com

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture
REGULATION (EC) No 1272/2008**

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

Additional Labeling:

EUH210 Safety data sheet available on request.

SECTION 3: Composition/information on ingredients

Synonyms : Drilling Mud Additive

Molecular formula : Mixture

Contains no hazardous ingredients according to GHS. :

Remarks : Contains no hazardous ingredients according to GHS.

SECTION 4: First aid measures

General advice : No hazards which require special first aid measures.

If inhaled : If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Liquid Flowzan® Biopolymer XPT

Version 1.8

Revision Date 2016-05-18

- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water. Keep respiratory tract clear. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.

SECTION 5: Firefighting measures

- Flash point : 77 °C (171 °F)
Method: ASTM D 93
- Autoignition temperature : 225 °C (437 °F)
- Unsuitable extinguishing media : High volume water jet.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on an open flame or any other incandescent material. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment.
- Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.
- A quantitative risk assessment is not required for the environment.
A quantitative risk assessment is not required for human health.

SECTION 7: Handling and storage**Handling**

Liquid Flowzan® Biopolymer XPT

Version 1.8

Revision Date 2016-05-18

Advice on safe handling : Avoid formation of aerosol. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Engineering measures**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Air-Purifying Respirator for Dusts and Mists. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection according to the amount and

Liquid Flowzan® Biopolymer XPT

Version 1.8

Revision Date 2016-05-18

concentration of the dangerous substance at the work place.
Wear as appropriate: Safety shoes. Protective suit.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of work day.

A quantitative risk assessment is not required for the environment.
A quantitative risk assessment is not required for human health.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Physical state : Liquid
Color : Light brown
Odor : Slight

Safety data

Flash point : 77 °C (171 °F)
Method: ASTM D 93

Lower explosion limit : 0,6 %(V)
Upper explosion limit : 5,1 %(V)

Oxidizing properties : no

Autoignition temperature : 225 °C (437 °F)

Molecular formula : Mixture

Molecular weight : Not applicable

pH : No data available

Pour point : No data available

Boiling point/boiling range : 217,8 - 237,8 °C (424,0 - 460,0 °F)

Vapor pressure : No data available

Relative density : 0,97

Water solubility : Soluble

Partition coefficient: n-octanol/water : No data available

Viscosity, kinematic : 79983 mm²/s
at 40 °C (104 °F)

Relative vapor density : No data available

Evaporation rate : No data available

Liquid Flowzan® Biopolymer XPT

Version 1.8

Revision Date 2016-05-18

SECTION 10: Stability and reactivity

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous decomposition products : Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Liquid Flowzan® Biopolymer XPT**

Aspiration toxicity : No aspiration toxicity classification.

Liquid Flowzan® Biopolymer XPT

Further information : Solvents may degrease the skin.

SECTION 12: Ecological information

Elimination information (persistence and degradability)

Biodegradability : Expected to be biodegradable

Ecotoxicology Assessment

Additional ecological information : This material is not expected to be harmful to aquatic organisms.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Liquid Flowzan® Biopolymer XPT

Version 1.8

Revision Date 2016-05-18

Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

A quantitative risk assessment is not required for the environment.
A quantitative risk assessment is not required for human health.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Testing (ASTM D4206) has shown product does not sustain combustion.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Liquid Flowzan® Biopolymer XPT

Version 1.8

Revision Date 2016-05-18

SECTION 15: Regulatory information**National legislation**

Major Accident Hazard Legislation : 96/82/EC Update: 2003
Directive 96/82/EC does not apply

Water contaminating class (Germany) : WGK 1 slightly water endangering

Other Registrations


Regulation	Registration number
Danish PR number:	1182417

Notification status

Europe REACH	:	On the inventory, or in compliance with the inventory
United States of America TSCA	:	Not On TSCA Inventory
Canada DSL	:	This product contains one or several components that are not on the Canadian DSL nor NDSL.
Australia AICS	:	Not in compliance with the inventory
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	Not in compliance with the inventory
Korea KECI	:	Not in compliance with the inventory
Philippines PICCS	:	Not in compliance with the inventory
China IECSC	:	Not in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 1
Fire Hazard: 1
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : E303

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Liquid Flowzan® Biopolymer XPT

Version 1.8

Revision Date 2016-05-18

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		