

SAFETY DATA SHEET



**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**Product information**

Product Name : HEC Liquid Polymer  
 Material : 1105037, 1101269, 1016918

**EC-No.Registration number**

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
C12-C14 Isoalkanes	68551-19-9 271-369-5	Chevron Phillips Chemicals International NV 01-2119491311-45-0000
Distillates (petroleum), hydrotreated light	64742-47-8	Chevron Phillips Chemicals International NV 01-2119456620-43-0010
Isoprene	78-79-5 201-143-3 601-014-00-5	Chevron Phillips Chemicals International NV 01-2119457891-29-0009
Styrene	100-42-5 202-851-5 601-026-00-0	Chevron Phillips Chemicals International NV 01-2119457861-32-0005
Oxirane	75-21-8 200-849-9 603-023-00-X	Chevron Phillips Chemicals International NV 01-2119432402-53-0030

**Company** : Chevron Phillips Chemical Company LP  
 Drilling Specialties Company LLC  
 10001 Six Pines Drive  
 The Woodlands, TX 77380

**Local** : Chevron Phillips Chemicals International N.V.  
 Airport Plaza (Stockholm Building)  
 Leonardo Da Vincilaan 19  
 1831 Diegem  
 Belgium

SDS Requests: (800) 852-5530

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

Technical Information: (832) 813-4862  
 Responsible Party: Product Safety Group  
 Email:sds@cpchem.com

**Emergency telephone:****Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group  
 E-mail address : SDS@CPChem.com  
 Website : www.CPChem.com

**SECTION 2: Hazards identification****Classification of the substance or mixture****Globally Harmonized System of Classification and Labeling of Chemicals (GHS)****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 4

H227: Combustible liquid.

**Classification (67/548/EEC, 1999/45/EC)**

**Not a hazardous substance or mixture according to EC-directives 67/548/EEC or 1999/45/EC. Label elements**

**Labeling (REGULATION (EC) No 1272/2008)**

Signal Word : Warning

Hazard Statements : H227 Combustible liquid.

Precautionary Statements : **Prevention:**  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 Store in a well-ventilated place.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

**SECTION 3: Composition/information on ingredients**

Synonyms : Drilling Mud Additive  
Liquid HEC Polymer

Molecular formula : Mixture

**Mixtures****Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
<b>C12-C14 Isoalkanes</b>	<b>68551-19-9</b> <b>271-369-5</b>	Asp. Tox. 1; H304	0 - 60
Distillates (petroleum), hydrotreated light	64742-47-8		0 - 60

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air. If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**SECTION 5: Firefighting measures**

Flash point : 85 °C (185 °F)

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>).

Unsuitable extinguishing media : High volume water jet.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion : Do not spray on an open flame or any other incandescent

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

protection

material. Keep away from open flames, hot surfaces and sources of ignition.

**SECTION 6: Accidental release measures**

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

**SECTION 7: Handling and storage****Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

**Storage**

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****Chevron Phillips Chemical Company LP**

Ingredients	Basis	Value	Control parameters	Note
C12-C14 Isoalkanes	Manufacturer	TWA	1.200 mg/m3	RCP,

**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

**Personal protective equipment**

- Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame-resistant clothing. Footwear protecting against chemicals.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

- Physical state : Liquid  
 Color : Opaque  
 Odor : Hydrocarbon

**Safety data**

- Flash point : 85 °C (185 °F)  
 Lower explosion limit : No data available  
 Upper explosion limit : No data available  
 Molecular formula : Mixture  
 Molecular weight : Not applicable  
 pH : Not applicable  
 Pour point : No data available

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

Boiling point/boiling range	: 217 - 237 °C (423 - 459 °F)
Vapor pressure	: No data available
Relative density	: 0,97 at 15,6 °C (60,1 °F)
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: 91937 cSt
Relative vapor density	: No data available
Evaporation rate	: No data available

**SECTION 10: Stability and reactivity**

Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
--------------------	--

**Possibility of hazardous reactions**

Conditions to avoid	: Heat, flames and sparks.
Other data	: No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****Acute oral toxicity**

C12-C14 Isoalkanes	: LD50: > 5000 milligram per kilogram Species: Rat Method: OECD Test Guideline 401 Information given is based on data obtained from similar substances.
--------------------	--

Distillates (petroleum), hydrotreated light	No data available
---	-------------------

**Acute inhalation toxicity**

C12-C14 Isoalkanes	: LC50: > 5.0milligram per liter Exposure time: 4 h Species: Rat Test atmosphere: vapor Method: OECD Test Guideline 403 An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration. Information given is based on data obtained from similar
--------------------	---

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

substances.

Distillates (petroleum),  
hydrotreated light

No data available

**Acute dermal toxicity**Distillates (petroleum),  
hydrotreated light:  
No data available**HEC Liquid Polymer  
Skin irritation**

: No skin irritation

**HEC Liquid Polymer  
Eye irritation**

: No eye irritation

**Sensitization**

C12-C14 Isoalkanes

: Classification: Did not cause sensitization on laboratory  
animals.  
Information given is based on data obtained from similar  
substances.Distillates (petroleum),  
hydrotreated lightDoes not cause skin sensitization.  
Information given is based on data obtained from similar  
substances.**Repeated dose toxicity**

C12-C14 Isoalkanes

: Species: Monkey  
Application Route: Inhalation  
Dose: 0, 654 ppm  
Exposure time: 4 wk  
Number of exposures: 6 h/d, 3 d/wk  
NOEL: > 654 ppm  
Method: OECD Test Guideline 412Species: Rat, male and female  
Sex: male and female  
Application Route: oral gavage  
Dose: 0, 25, 150, 1000 mg/kg/d  
Exposure time: 4 wk  
Number of exposures: daily  
NOEL: >= 1000 mg/kg/d  
Method: OECD Guideline 422Information given is based on data obtained from similar  
substances.**Reproductive toxicity**

C12-C14 Isoalkanes

: Species: Rat  
Sex: male  
Application Route: oral gavage  
Dose: 0, 750, 1500, 3000 mg/kg/bw/d  
Number of exposures: daily  
Test period: 90 d  
Method: OECD Test Guideline 415  
NOAEL Parent: >= 3000 mg/kg/bw/d  
Information given is based on data obtained from similar

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

substances.

Species: Rat  
Sex: female  
Application Route: oral gavage  
Dose: 0, 750, 1500 mg/kg/bw/d  
Number of exposures: daily  
Test period: 90 d  
Method: OECD Test Guideline 415  
NOAEL Parent:  $\geq$  1500 mg/kg/bw/d  
NOAEL F1: 750 mg/kg/bw/d  
Information given is based on data obtained from similar substances.

Species: Rat  
Sex: male and female  
Application Route: inhalation (vapor)  
Dose: 100, 300 ppm  
Number of exposures: 6 h/d/5d/wk  
Test period: 8 wk  
Method: OECD Guideline 421  
NOAEL Parent:  $\geq$  300 ppm  
NOAEL F1:  $\geq$  300 ppm  
Information given is based on data obtained from similar substances.

**Developmental Toxicity**

C12-C14 Isoalkanes

: Species: Rat  
Application Route: Inhalation  
Dose: 100, 300 ppm  
Exposure time: GD 6-15  
Number of exposures: 6 h/d  
NOAEL Teratogenicity:  $\geq$  300 ppm  
Information given is based on data obtained from similar substances.

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

Species: Rat  
 Application Route: Inhalation  
 Dose: 300, 900 ppm  
 Exposure time: GD 6-15  
 Number of exposures: 6 h/d  
 Method: OECD Guideline 414  
 NOAEL Teratogenicity:  $\geq$  900 ppm  
 NOAEL Maternal:  $\geq$  900 ppm  
 Information given is based on data obtained from similar substances.

Species: Rat  
 Application Route: oral gavage  
 Dose: 0, 500, 1000, 1500 mg/kg/d  
 Exposure time: GD 6-15  
 Number of exposures: Daily  
 Method: OECD Guideline 414  
 NOAEL Teratogenicity: 1.000 mg/kg  
 NOAEL Maternal: 500 mg/kg  
 Information given is based on data obtained from similar substances.

**HEC Liquid Polymer  
 Aspiration toxicity** : No aspiration toxicity classification.

**CMR effects**

C12-C14 Isoalkanes : Carcinogenicity: Limited evidence of carcinogenicity in animal studies  
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects  
 Teratogenicity: Animal testing did not show any effects on fetal development.  
 Reproductive toxicity: No adverse effects expected

**HEC Liquid Polymer  
 Further information** : Solvents may decrease the skin.

**SECTION 12: Ecological information****Toxicity to fish**

C12-C14 Isoalkanes : LL50: > 1.000 mg/l  
 Exposure time: 96 h  
 Species: Oncorhynchus mykiss (rainbow trout)  
 semi-static test Method: OECD Test Guideline 203  
 Information given is based on data obtained from similar substances.

**Toxicity to daphnia and other aquatic invertebrates**

C12-C14 Isoalkanes : EL50: > 1.000 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 static test Method: OECD Test Guideline 202

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

Information given is based on data obtained from similar substances.

Distillates (petroleum),  
hydrotreated light

EL50: > 100 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)  
static test Method: OECD Test Guideline 202  
Aquatic toxicity is unlikely due to low solubility.

**Toxicity to algae**

C12-C14 Isoalkanes

: EL50: > 1.000 mg/l  
Exposure time: 72 h  
Species: Pseudokirchneriella subcapitata (green algae)  
Growth inhibition Method: OECD Test Guideline 201  
Information given is based on data obtained from similar substances.

**Toxicity to fish (Chronic toxicity)**

C12-C14 Isoalkanes

: NOELR: 0,316 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)  
Method: QSAR modeled data

**Biodegradability**

C12-C14 Isoalkanes

: aerobic  
31 %  
Testing period: 28 d  
Method: OECD Test Guideline 301F  
Information given is based on data obtained from similar substances.  
Expected to be inherently biodegradable.

Distillates (petroleum),  
hydrotreated light

: No data available

**Results of PBT assessment**

C12-C14 Isoalkanes

: Non-classified PBT substance, Non-classified vPvB substance

**Additional ecological information**

C12-C14 Isoalkanes

: This material is not expected to be harmful to aquatic organisms.

Distillates (petroleum),  
hydrotreated light

: No data available

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Testing (ASTM D4206) has shown product does not sustain combustion.

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

**SECTION 15: Regulatory information****National legislation**

**Major Accident Hazard Legislation** : 96/82/EC Update: 2003  
Directive 96/82/EC does not apply

**Water contaminating class (Germany)** : WGK 2 water endangering

**Notification status**

Europe REACH : A substance or substances in this product is not registered or notified to be registered. Importation or manufacture of this product is still permitted provided that it does not exceed the REACH minimum threshold quantity of the non-regulated substances.

Switzerland CH INV : Not in compliance with the inventory

United States of America TSCA : On TSCA Inventory

Canada DSL : All components of this product are on the Canadian DSL

Australia AICS : On the inventory, or in compliance with the inventory

New Zealand NZIoC : Not in compliance with the inventory

Japan ENCS : Not in compliance with the inventory


Korea KECI : On the inventory, or in compliance with the inventory

Philippines PICCS : Not in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 1  
Fire Hazard: 1  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 297870

**HEC Liquid Polymer**

Version 1.8

Revision Date 2016-06-01

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

**Full text of H-Statements referred to under sections 2 and 3.**