

Version 2.0 Revision Date 2012-05-31

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product information**

Trade name : DSGA® Polymer Emulsion

Material : 1064101, 1010396, 1020396, 1016929

Use : Friction Reducer, Acid Gelling Agent

**Company** : Drilling Specialties Company

10001 Six Pines Drive The Woodlands, TX 77380

#### **Emergency telephone:**

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887 Asia: +800 CHEMCALL (+800 2436 2255) China: 0532.8388.9090 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Chemcare Asia: Tel: +65 6848 9048 - Mob: +65 8382 9188 - Fax: +65 6848

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group

E-mail address : MSDS@CPChem.com Website : www.CPChem.com

#### **SECTION 2: Hazards identification**

## **Emergency Overview**

#### Danger

**Physical state**: Liquid **Color**: White to light green, opaque **Odor**: Hydrocarbon

OSHA Hazards : Moderate skin irritant, Moderate eye irritant

**GHS Classification** 

Skin irritation, Category 2Eye irritation, Category 2AAspiration hazard, Category 1

#### **GHS-Labeling**

MSDS Number:100000013884 1/11

Version 2.0 Revision Date 2012-05-31

Symbol(s)





Signal Word : Danger

Hazard Statements : H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation. H319: Causes serious eye irritation.

Precautionary Statements : Prevention:

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON

CENTER or doctor/ physician.

P302 + P352: IF ON SKIN: Wash with plenty of soap and

water.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321: Specific treatment (see supplemental first aid

instructions on this label).

P331: Do NOT induce vomiting.

P332 + P313: If skin irritation occurs: Get medical advice/

attention.

P337 + P313: If eye irritation persists: Get medical advice/

attention.

P362: Take off contaminated clothing and wash before reuse.

Storage:

P405: Store locked up.

Disposal:

P501: Dispose of contents/ container to an approved waste

disposal plant.

Carcinogenicity:

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcinogen

by ACGIH.

#### **SECTION 3: Composition/information on ingredients**

Synonyms : None Established

Molecular formula : Mixture

Component	CAS-No.	Weight %	
Distillates (petroleum), Hydrotreated	64742-47-8	10 - 30	
light			

MSDS Number:100000013884 2/11

# DSGA® Polymer Emulsion Version 2.0 Carbonic Acid Disodium Salt 497-19-8 1 - 5 Ethoxylated Sorbitol, Hexaoleate 57171-56-9 1 - 5

68439-49-6

#### SECTION 4: First aid measures

C16-C18, Ethoxylated Alcohols

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

1 - 5

If inhaled : If unconscious place in recovery position and seek medical

advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well

with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

#### **SECTION 5: Firefighting measures**

Flash point : > 93.4 °C (> 200.1 °F)

Method: Tag closed cup

Autoignition temperature : No data available

Unsuitable extinguishing

media

: High volume water jet.

Special protective

equipment for fire-fighters

: Wear self contained breathing apparatus for fire fighting if

necessary.

Further information : Standard procedure for chemical fires. Use extinguishing

measures that are appropriate to local circumstances and the

surrounding environment.

Fire and explosion

protection

: Normal measures for preventive fire protection.

Hazardous decomposition

products

: No data available.

#### **SECTION 6: Accidental release measures**

Personal precautions : Use personal protective equipment. Ensure adequate

ventilation.

MSDS Number:100000013884 3/11

#### MATERIAL SAFETY DATA SHEET

# **DSGA®** Polymer Emulsion

Version 2.0 Revision Date 2012-05-31

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Keep in suitable, closed

containers for disposal.

#### SECTION 7: Handling and storage

#### Handling

Advice on safe handling : Do not breathe vapors/dust. Avoid contact with skin and eyes.

For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose

of rinse water in accordance with local and national

regulations.

Advice on protection against fire and explosion

: Normal measures for preventive fire protection.

#### **Storage**

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

## SECTION 8: Exposure controls/personal protection

#### Ingredients with workplace control parameters

US

Ingredients	Basis	Value	Control parameters	Note
Distillates (petroleum), Hydrotreated light	OSHA Z-1	TWA	500 ppm, 2,000 mg/m3	(b),
	OSHA Z-1-A	TWA	400 ppm, 1,600 mg/m3	
Potassium Bromate	US WEEL	TWA	0.1 mg/m3	

<sup>(</sup>b) The value in mg/m3 is approximate.

#### **Engineering measures**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

#### Personal protective equipment

Respiratory protection : Wear a NIOSH approved respirator that provides protection

when working with this material if exposure to harmful levels of airborne material may occur, such as:. Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or

MSDS Number:100000013884 4/11

Version 2.0 Revision Date 2012-05-31

other circumstances where air-purifying respirators may not

provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Wear as appropriate:. Protective suit. Safety shoes.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid

Color : White to light green, opaque

Odor : Hydrocarbon

Safety data

Flash point :  $> 93.4 \, ^{\circ}\text{C} \, (> 200.1 \, ^{\circ}\text{F})$ 

Method: Tag closed cup

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : no

Autoignition temperature : No data available

Molecular formula : Mixture

Molecular Weight : Not applicable

pH : 4-5

Boiling point/boiling range : 217 - 238 °C (423 - 460 °F)

Vapor pressure : No data available

Relative density : 1.024, 16.6 °C(61.9 °F)

Water solubility : Soluble

MSDS Number:100000013884 5/11

#### MATERIAL SAFETY DATA SHEET

# **DSGA®** Polymer Emulsion

Version 2.0 Revision Date 2012-05-31

Relative vapor density : 3

(Air = 1.0)

Evaporation rate : 1

Percent volatile : 55 - 70 %

### **SECTION 10: Stability and reactivity**

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

### Possibility of hazardous reactions

Conditions to avoid : No data available.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

Other data : No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

**DSGA®** Polymer Emulsion

Acute oral toxicity : LD50: > 5,000 mg/kg

Species: rat

Acute inhalation toxicity

Distillates (petroleum), : LC50: > 5.28 mg/l Hydrotreated light Exposure time: 4 h

Species: rat

Test atmosphere: vapor

Method: OECD Test Guideline 403

: 2.3 mg/l Carbonic Acid Disodium Salt

Exposure time: 2 h Species: rat

Test atmosphere: dust/mist

Acute dermal toxicity

Distillates (petroleum), : LD50: > 2,000 mg/kg

Hydrotreated light Species: rabbit

Method: OECD Test Guideline 402

Carbonic Acid Disodium Salt LD50 Dermal: > 2,000 mg/kg

Species: rat

Test substance: yes

**DSGA®** Polymer Emulsion

Skin irritation Irritating to skin.

MSDS Number: 100000013884 6/11

Version 2.0 Revision Date 2012-05-31

May cause skin irritation in susceptible persons.

**DSGA® Polymer Emulsion** 

**Eye irritation** : Eye irritation

May cause irreversible eye damage.

**Sensitization** 

Distillates (petroleum), Hydrotreated light

: Did not cause sensitization on laboratory animals.

**DSGA® Polymer Emulsion** 

**Aspiration toxicity** : May be fatal if swallowed and enters airways.

Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity

hazard.

**DSGA®** Polymer Emulsion

**Further information** : Solvents may degrease the skin.

## **SECTION 12: Ecological information**

## Toxicity to fish

Distillates (petroleum), : NOEC: 2 mg/l Hydrotreated light : Exposure time: 96 h

Species: Salmo gairdneri (Rainbow trout) Method: OECD Test Guideline 203

#### Toxicity to daphnia and other aquatic invertebrates

Distillates (petroleum), : EL50: 1.4 mg/l Hydrotreated light : Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

Toxicity to algae

Distillates (petroleum), : EL50: 1 - 3 mg/l Hydrotreated light Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (green algae)

Method: OECD Test Guideline 201

## Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Distillates (petroleum), : NOEC: 0.48 mg/l Hydrotreated light Exposure time: 21 Days

Species: Daphnia magna (Water flea)

Elimination information (persistence and degradability)

Biodegradability : No data available

MSDS Number:100000013884 7/11

Version 2.0 Revision Date 2012-05-31

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

No data available

## **SECTION 13: Disposal considerations**

The information in this MSDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate

ponds, waterways or ditches with chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers.

#### **SECTION 14: Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and the bill of lading.

#### **US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

#### IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

#### IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

#### ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

MSDS Number:100000013884 8/11

Version 2.0 Revision Date 2012-05-31

## RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF **DANGEROUS GOODS (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

#### ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

## **SECTION 15: Regulatory information**

#### **National legislation**

SARA 311/312 Hazards : Acute Health Hazard

SARA 302 Reportable

Quantity

: This material does not contain any components with a SARA

302 RQ.

SARA 302 Threshold

Planning Quantity

: SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable

Quantity

: This material does not contain any components with a section

304 EHS RQ.

: SARA 313: This material does not contain any chemical SARA 313 Ingredients

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III. Section 313.

#### Clean Air Act

Ozone-Depletion

Potential

: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

MSDS Number:100000013884 9/11

Version 2.0 Revision Date 2012-05-31

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

#### **US State Regulations**

Pennsylvania Right To Know

: Distillates (petroleum), 64742-47-8

Hydrotreated light

: Copper Sulfate 7758-98-7

New Jersey Right To Know

: Distillates (petroleum), 64742-47-8

Hydrotreated light

: Copper Sulfate 7758-98-7

California Prop. 65 : WARNING! This product contains a chemical known in the

Ingredients State of California to cause cancer.

**Notification status** 

Europe REACH : Not in compliance with the inventory

United States of America US.TSCA : On TSCA Inventory

Canada DSL : All components of this product are on the Canadian

DSL list.

Australia AICS : On the inventory, or in compliance with the inventory New Zealand NZIoC : On the inventory, or in compliance with the inventory


Japan ENCS : Not in compliance with the inventory Korea KECI : Not in compliance with the inventory

Philippines PICCS : On the inventory, or in compliance with the inventory China IECSC : On the inventory, or in compliance with the inventory

#### **SECTION 16: Other information**

NFPA Classification : Health Hazard: 2

Fire Hazard: 1 Reactivity Hazard: 0



#### **Further information**

Legacy MSDS Number : 168840

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

MSDS Number:100000013884 10/11

Version 2.0 Revision Date 2012-05-31

The information in this MSDS pertains only to the product as shipped.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet					
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%		
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level		
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency		
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health		
CNS	Central Nervous System	NTP	National Toxicology Program		
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals		
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level		
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration		
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration		
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit		
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philipines Inventory of Commercial Chemical Substances		
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic		
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act		
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit		
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.		
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value		
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Compositon, Complex Reaction Products, and Biological Materials		
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System		
LC50	Lethal Concentration 50%				

MSDS Number:100000013884 11/11