

# **Isopentane 95%**

Version 1.1 Revision Date 2014-01-02

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product information** 

Trade name : Isopentane 95%

Material : 1108283, 1025135, 1024849, 1016656, 1016655, 1020537,

1016654, 1024848

Use : Solvent

Company : Chevron Phillips Chemical Company LP

Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380

**Emergency telephone:** 

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887

Asia: +800 CHEMCALL (+800 2436 2255)

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group

E-mail address : MSDS@CPChem.com Website : www.CPChem.com

### **SECTION 2: Hazards identification**

## **Emergency Overview**

Form: Liquid Physical state: Liquid Color: Colorless Odor: gasoline-like

OSHA Hazards : Flammable Liquid, Aspiration hazard

**GHS Classification** 

: Flammable liquids, Category 1

Specific target organ systemic toxicity - single exposure,

Category 3, Central nervous system Aspiration hazard, Category 1 Acute aquatic toxicity, Category 2 Chronic aquatic toxicity, Category 2

**GHS-Labeling** 

MSDS Number:100000014175 1/14

# **Isopentane 95%**

Version 1.1 Revision Date 2014-01-02

Symbol(s)









Signal Word : Danger

Hazard Statements : H224: Extremely flammable liquid and vapor.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces.

- No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON

CENTER or doctor/ physician.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340: IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P312: Call a POISON CENTER or doctor/ physician if you

feel unwell.

P331: Do NOT induce vomiting.

P370 + P378: In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

P391: Collect spillage.

Storage:

P403 + P233: Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/ container to an approved waste

disposal plant.

Carcinogenicity:

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcinogen

by ACGIH.

MSDS Number:100000014175

2/14

# **Isopentane 95%**

Version 1.1 Revision Date 2014-01-02

# **SECTION 3: Composition/information on ingredients**

Synonyms : Dimethylethylmethane

2-Methylbutane

Isopentane (Borger Polymerization Grade)
Isopentane (Borger commercial Grade)

Molecular formula : C5H12

Component	CAS-No.	Weight %
Isopentane	78-78-4	95

#### **SECTION 4: First aid measures**

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious

place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

## **SECTION 5: Firefighting measures**

Flash point :  $< -40 \,^{\circ}\text{C} \, (< -40 \,^{\circ}\text{F})$ 

estimated

Autoignition temperature : 420 °C (788 °F)

estimated

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

Specific hazards during fire

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective

equipment for fire-fighters

: Wear self contained breathing apparatus for fire fighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

MSDS Number:100000014175 3/14

# **Isopentane 95%**

Version 1.1 Revision Date 2014-01-02

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection

Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

Hazardous decomposition

products

: Carbon oxides.

## **SECTION 6: Accidental release measures**

Personal precautions : Use personal protective equipment. Ensure adequate

ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low

areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

## SECTION 7: Handling and storage

## Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

exposure - obtain special instructions before use. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in

accordance with local and national regulations.

Advice on protection against fire and explosion

Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

### **Storage**

Requirements for storage areas and containers

: No smoking. Keep container tightly closed in a dry and wellventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

MSDS Number:100000014175 4/14

# **Isopentane 95%**

Version 1.1 Revision Date 2014-01-02

Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

#### SECTION 8: Exposure controls/personal protection

#### Ingredients with workplace control parameters

US

Ingredients	Basis	Value	Control parameters	Note
Isopentane	ACGIH	TWA	600 ppm,	

## **Engineering measures**

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

## Personal protective equipment

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless

ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators

may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place. Wear as appropriate:. Flame retardant antistatic protective

clothing. Footwear protecting against chemicals.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9: Physical and chemical properties**

Information on basic physical and chemical properties

**Appearance** 

Eye protection

MSDS Number:100000014175 5/14

# Isopentane 95%

Version 1.1 Revision Date 2014-01-02

Form : Liquid
Physical state : Liquid
Color : Colorless
Odor : gasoline-like

Safety data

Flash point :  $< -40 \, ^{\circ}\text{C} \, (< -40 \, ^{\circ}\text{F})$ 

estimated

Lower explosion limit : 1.4 %(V)

Upper explosion limit : 8.3 %(V)

Oxidizing properties : no

Autoignition temperature : 420 °C (788 °F)

estimated

Molecular formula : C5H12

Molecular Weight : 72.17 g/mol

pH : Not applicable

Pour point : No data available

Freezing point No data available

Boiling point/boiling range : 28 °C (82 °F)

estimated

Vapor pressure : 20.10 PSI

at 37.8 °C (100.0 °F)

Relative density : 0.62, 15.6 °C(60.1 °F)

Density : 623.1 g/l

Water solubility : Negligible

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : 0.224 cP

Relative vapor density : 2.6

(Air = 1.0)

Evaporation rate : > 1

Percent volatile : > 99 %

## **SECTION 10: Stability and reactivity**

MSDS Number:100000014175 6/14

Isopentane 95%

Version 1.1 Revision Date 2014-01-02

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

Other data : No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information** 

**Acute oral toxicity** 

Isopentane : LD50: > 2,000 mg/kg

Species: rat

Sex: male and female

Method: OECD Test Guideline 401

Information given is based on data obtained from similar

substances.

Acute inhalation toxicity

Isopentane : LC50: > 25.3 mg/l

Exposure time: 4 h Species: rat

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Information given is based on data obtained from similar

substances.

Acute dermal toxicity

Isopentane

No data available

Skin irritation

Isopentane : No skin irritation

Information given is based on data obtained from similar

substances.

Eye irritation

Isopentane : No eye irritation

Information given is based on data obtained from similar

substances.

Sensitization

Isopentane : Did not cause sensitization on laboratory animals.

Repeated dose toxicity

MSDS Number:100000014175 7/14

# **Isopentane 95%**

Version 1.1 Revision Date 2014-01-02

Isopentane : Species: rat, male and female

Sex: male and female Application Route: Inhalation Dose: 668, 2220, 6646 ppm Exposure time: 13 wk

Number of exposures: 6 h/d, 5 d/wk

NOEL: > 2220 ppm

Lowest observable effect level: > = 6646 ppm

Method: OECD Guideline 413

Target Organs: Kidney

## Reproductive toxicity

Isopentane : Species: rat

Sex: male and female

Application Route: inhalation (vapor) Dose: 0, 500, 2000, 7000 ppm Number of exposures: 6 h/d 5 d/wk Method: OECD Test Guideline 416

NOAEL Parent: 7000 ppm NOAEL F1: 2000 ppm NOAEL F2: 2000 ppm

Information given is based on data obtained from similar

substances.

Species: rat Sex: female

Application Route: oral gavage Dose: 0, 100, 300, 1000 mg/kg/d Method: OECD Test Guideline 415 NOAEL Parent: >= 1,000 mg/kg NOAEL F1: >= 1,000 mg/kg

Species: rat Sex: male

Application Route: oral gavage Dose: 0, 100, 300, 1000 mg/kg/d Method: OECD Test Guideline 415 NOAEL Parent: >= 300 mg/kg

## **Developmental Toxicity**

Isopentane : Species: rat

Application Route: oral gavage Dose: 0, 100, 500, 1000 mg/kg/d Exposure time: GD 6-15

Number of exposures: daily Method: OECD Guideline 414 NOAEL Teratogenicity: 1,000 mg/kg NOAEL Maternal: 1,000 mg/kg

Information given is based on data obtained from similar

substances.

# Isopentane 95%

Version 1.1 Revision Date 2014-01-02

Species: rat

Application Route: Inhalation Dose: 0, 500, 2000, 7000 ppm Exposure time: GD 6-15 Number of exposures: 5 d/wk Method: OECD Guideline 414 NOAEL Teratogenicity: 7000 ppm NOAEL Maternal: 500 ppm

Information given is based on data obtained from similar

substances.

Species: rabbit

Application Route: Inhalation
Dose: 0, 500, 2000, 7000 ppm
Exposure time: GD 6-18
Method: OECD Guideline 414
NOAEL Teratogenicity: 7000 ppm
NOAEL Maternal: 7000 ppm

Information given is based on data obtained from similar

substances.

Isopentane 95% Aspiration toxicity

: May be fatal if swallowed and enters airways.

Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity

hazard.

**CMR** effects

Isopentane : Carcinogenicity: Not available

Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show

mutagenic effects

Teratogenicity: Animal testing did not show any effects on

fetal development.

Reproductive toxicity: Animal testing did not show any effects

on fertility.

Isopentane 95%

**Further information** : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents

may degrease the skin.

## **SECTION 12: Ecological information**

#### Toxicity to fish

Isopentane : LC50: 4.26 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar

substances.

#### Toxicity to daphnia and other aquatic invertebrates

MSDS Number:100000014175 9/14

# **Isopentane 95%**

Version 1.1 Revision Date 2014-01-02

Isopentane : EC50: 2.3 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

Toxicity to algae

Isopentane : EC50: 7.51 mg/l

Exposure time: 72 h

Species: Scenedesmus capricornutum (fresh water algae) Growth inhibition Method: OECD Test Guideline 201 Information given is based on data obtained from similar

substances.

## **Toxicity to fish (Chronic toxicity)**

Isopentane

Bioaccumulation

Isopentane : Accumulation in aquatic organisms is unlikely.

Biodegradability

Isopentane : aerobic

Result: Readily biodegradable.

71.43 %

Testing period: 28 d

Method: OECD Test Guideline 301F

#### **Results of PBT assessment**

Isopentane : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological

information

: Toxic to aquatic life with long lasting effects.

#### **SECTION 13: Disposal considerations**

The information in this MSDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

MSDS Number:100000014175 10/14

# Isopentane 95%

Version 1.1 Revision Date 2014-01-02

Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14: Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and the bill of lading.

## **US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN1265, PENTANES, 3, I

#### IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1265, PENTANES, 3, I, (< -40 °C), MARINE POLLUTANT, (ISOPENTANE)

#### IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1265, PENTANES, 3, I

#### ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1265, PENTANES, 3, I, (D/E), ENVIRONMENTALLY HAZARDOUS, (ISOPENTANE)

# RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1265, PENTANES, 3, I, ENVIRONMENTALLY HAZARDOUS, (ISOPENTANE)

# ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1265, PENTANES, 3, I, ENVIRONMENTALLY HAZARDOUS, (ISOPENTANE)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

## **SECTION 15: Regulatory information**

**National legislation** 

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

CERCLA Reportable

Quantity

: 105 lbs

MSDS Number:100000014175

11/14

# **Isopentane 95%**

Version 1.1 Revision Date 2014-01-02

Isopentane

SARA 302 Reportable

Quantity

: This material does not contain any components with a SARA

302 RQ.

SARA 302 Threshold

Planning Quantity

: SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable

Quantity

: This material does not contain any components with a section

304 EHS RQ.

SARA 313 Ingredients : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

#### Clean Air Act

Ozone-Depletion

Potential

: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F):

: Isopentane - 78-78-4

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

: Isopentane - 78-78-4

#### **US State Regulations**

Pennsylvania Right To Know

: Isopentane - 78-78-4 Related Materials -

New Jersey Right To Know

: Isopentane - 78-78-4 Related Materials -

MSDS Number:100000014175 12/14

# **Isopentane 95%**

Version 1.1 Revision Date 2014-01-02

California Prop. 65

Ingredients

: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive

defects.

#### **Notification status**

Europe REACH : On the inventory, or in compliance with the inventory

United States of America TSCA : On TSCA Inventory

Canada DSL : All components of this product are on the Canadian

DSL.

Australia AICS

: On the inventory, or in compliance with the inventory New Zealand NZIoC

: On the inventory, or in compliance with the inventory Japan ENCS

: On the inventory, or in compliance with the inventory Korea KECI

Philippines PICCS


: On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory China IECSC

: On the inventory, or in compliance with the inventory

#### **SECTION 16: Other information**

NFPA Classification : Health Hazard: 1

Fire Hazard: 4 Reactivity Hazard: 0



## **Further information**

Legacy MSDS Number : 26680

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this MSDS pertains only to the product as shipped.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet				
American Conference of	LD50	Lethal Dose 50%		
Government Industrial Hygienists				
Australia, Inventory of Chemical	LOAEL	Lowest Observed Adverse Effect		
Substances		Level		
Canada, Domestic Substances	NFPA	National Fire Protection Agency		
List				
Canada, Non-Domestic	NIOSH	National Institute for Occupational		
Substances List		Safety & Health		
Central Nervous System	NTP	National Toxicology Program		
	American Conference of Government Industrial Hygienists Australia, Inventory of Chemical Substances Canada, Domestic Substances List Canada, Non-Domestic Substances List	American Conference of Government Industrial Hygienists  Australia, Inventory of Chemical Substances  Canada, Domestic Substances List  Canada, Non-Domestic Substances List  NIOSH		

MSDS Number:100000014175 13/14

# Isopentane 95%

Version 1.1 Revision Date 2014-01-02

CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

14/14