

Version 3.0 Revision Date 2013-05-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Trade name : Scentinel® P-T Gas Odorant

Material: 1024679

Use : Odorant

Company : Specialty Chemicals

10001 Six Pines Drive The Woodlands, TX 77380

Emergency telephone:

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887

Asia: +800 CHEMCALL (+800 2436 2255)

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group

E-mail address : MSDS@CPChem.com Website : www.CPChem.com

SECTION 2: Hazards identification

Emergency Overview

Form: Liquid Physical state: Liquid Color: Clear Odor: Repulsive

OSHA Hazards : Flammable Liquid, Moderate eye irritant, Specific Target Organ

Toxicity

GHS Classification

: Flammable liquids, Category 2 Acute toxicity, Category 5, Oral Eye irritation, Category 2A

Specific target organ systemic toxicity - single exposure,

Category 3

Aspiration hazard, Category 2
Acute aquatic toxicity, Category 1
Chronic aquatic toxicity, Category 1
Skin sensitization, Sub-category 1B

GHS-Labeling

MSDS Number:100000014178 1/12

Version 3.0 Revision Date 2013-05-29

Symbol(s)









Signal Word : Danger

Hazard Statements : H225: Highly flammable liquid and vapor.

H303: May be harmful if swallowed.

H305: May be harmful if swallowed and enters airways.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.

H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces.

- No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P264: Wash skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON

CENTER or doctor/ physician.

P303 + P361 + P353: IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340: IF INHALED: Remove victim to fresh air and

keep at rest in a position comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor/ physician if you feel unwell.

P331: Do NOT induce vomiting.

P337 + P313: If eye irritation persists: Get medical advice/attention.

P370 + P378: In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam for extinction.

P391: Collect spillage.

Storage:

P403 + P233: Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/ container to an approved waste

disposal plant.

Carcinogenicity:

MSDS Number:100000014178

MATERIAL SAFETY DATA SHEET

Scentinel® P-T Gas Odorant

Version 3.0 Revision Date 2013-05-29

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcinogen

by ACGIH.

SECTION 3: Composition/information on ingredients

Synonyms : Propanethiol

Molecular formula : C3H8S

Component	CAS-No.	Weight %
Isopropyl Mercaptan	75-33-2	65 - 68
n-Propyl Mercaptan	107-03-9	32 - 35

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious

place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : -34 °C (-29 °F)

estimated

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

Specific hazards during fire

fighting

: Do not allow run-off from fire fighting to enter drains or water

3/12

courses.

MSDS Number:100000014178

Version 3.0 Revision Date 2013-05-29

Special protective equipment for fire-fighters

: Wear self contained breathing apparatus for fire fighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed

containments. Use a water spray to cool fully closed

containers.

Fire and explosion protection

Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate

ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low

areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7: Handling and storage

Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with

local and national regulations.

Advice on protection against fire and explosion

Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

Storage

Requirements for storage : No smoking. Keep container tightly closed in a dry and well-

MSDS Number:100000014178 4/12

MATERIAL SAFETY DATA SHEET

Scentinel® P-T Gas Odorant

Version 3.0 Revision Date 2013-05-29

areas and containers

ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

US

Ingredients	Basis	Value	Control parameters	Note
n-Propyl Mercaptan	NIOSH REL	С	0.5 ppm, 1.6 mg/m3	

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Eye protection

Skin and body protection

Respiratory protection : In the case of vapor formation use a respirator with an

approved filter. Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying

respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant

Choose body protection in relation to its type, to the

: Eye wash bottle with pure water. Tightly fitting safety goggles.

antistatic protective clothing. Workers should wear antistatic

footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

MSDS Number:100000014178 5/12

Version 3.0 Revision Date 2013-05-29

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Form : Liquid
Physical state : Liquid
Color : Clear
Odor : Repulsive

Safety data

Flash point : -34 °C (-29 °F)

estimated

Lower explosion limit : No data available

Upper explosion limit : No data available

Molecular formula : C3H8S

pH : Not applicable

Freezing point : No data available

Boiling point/boiling range : 52 °C (126 °F)

Vapor pressure : 8.80 PSI

at 37.8 °C (100.0 °F)

Relative density : 0.82, 15.6 °C(60.1 °F)

Water solubility : Slightly soluble

Viscosity, dynamic : 0.369 cP

at 20 °C (68 °F)

Relative vapor density : 2.62

(Air = 1.0)

Evaporation rate : 1

estimated

SECTION 10: Stability and reactivity

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.

Other data : No decomposition if stored and applied as directed.

MSDS Number:100000014178 6/12

Version 3.0 Revision Date 2013-05-29

SECTION 11: Toxicological information

Scentinel® P-T Gas Odorant

Acute oral toxicity : LD50 Oral: 2,167 mg/kg

Species: rat

Method: Acute toxicity estimate

Acute inhalation toxicity

Isopropyl Mercaptan : LC50: > 32.24 mg/l

Exposure time: 4 h

Species: rat

Sex: male and female Test atmosphere: vapor

Method: OECD Test Guideline 403

Test substance: yes

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable

concentration.

n-Propyl Mercaptan LC50: > 25.5 mg/l

Exposure time: 4 h

Species: rat

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable

concentration.

Acute dermal toxicity

Isopropyl Mercaptan : LD50: > 2,000 mg/kg

Species: rat

Method: No information available.

see user defined free text

n-Propyl Mercaptan LD50: > 1,682 mg/kg

Species: rabbit Sex: male and female

Method: OECD Test Guideline 402

Scentinel® P-T Gas Odorant

Skin irritation : May irritate skin.

Scentinel® P-T Gas Odorant

Eye irritation : May irritate eyes.

Sensitization

Isopropyl Mercaptan : Causes sensitization.

Scentinel® P-T Gas Odorant

Further information : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents

MSDS Number:100000014178 7/12

Version 3.0 Revision Date 2013-05-29

may degrease the skin.

SECTION 12: Ecological information

Toxicity to fish

Isopropyl Mercaptan : LC50: 34 mg/l

Exposure time: 96 h

semi-static test Analytical monitoring: yes Method: OECD Test Guideline 203

Information given is based on data obtained from similar

substances.

n-Propyl Mercaptan LC50: 1.3 mg/l

Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)

Analytical monitoring: yes Test substance: yes

Method: OECD Test Guideline 203

Toxic to aquatic organisms.

Toxicity to daphnia and other aquatic invertebrates

Isopropyl Mercaptan : EC50: 0.25 - 0.5 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Test substance: yes Method: OECD Test Guideline 202

n-Propyl Mercaptan 0.07 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea)

Analytical monitoring: yes Test substance: yes

Method: OECD Test Guideline 202 Very toxic to aquatic organisms.

M-Factor

propane-2-thiol : 1 propane-1-thiol : 10

Biodegradability

Isopropyl Mercaptan : 0 %

Testing period: 28 Days Test substance: yes

This material is not expected to be readily biodegradable.

n-Propyl Mercaptan : aerobic

Result: Not readily biodegradable.

17 %

Testing period: 28 Days

Method: OECD Test Guideline 301

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

MSDS Number:100000014178 8/12

Version 3.0 Revision Date 2013-05-29

SECTION 13: Disposal considerations

The information in this MSDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN2402, PROPANETHIOLS, 3, II

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN2402, PROPANETHIOLS, 3, II, (-34 °C), MARINE POLLUTANT, (N-PROPYL MERCAPTAN, ISOPROPYL MERCAPTAN)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2402, PROPANETHIOLS, 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2402, PROPANETHIOLS, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (N-PROPYL MERCAPTAN, ISOPROPYL MERCAPTAN)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN2402, PROPANETHIOLS, 3, II, ENVIRONMENTALLY HAZARDOUS, (N-PROPYL MERCAPTAN, ISOPROPYL MERCAPTAN)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE

MSDS Number:100000014178 9/12

Version 3.0 Revision Date 2013-05-29

OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2402, PROPANETHIOLS, 3, II, ENVIRONMENTALLY HAZARDOUS, (N-PROPYL MERCAPTAN, ISOPROPYL MERCAPTAN)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

National legislation

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

CERCLA Reportable

Quantity

: This material does not contain any components with a CERCLA

RQ.

SARA 302 Reportable

Quantity

: This material does not contain any components with a SARA

302 RQ.

SARA 302 Threshold

Planning Quantity

: SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable

Quantity

: This material does not contain any components with a section

304 EHS RQ.

SARA 313 Ingredients : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

Clean Air Act

Ozone-Depletion

Potential

: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

MSDS Number:100000014178 10/12

Version 3.0 Revision Date 2013-05-29

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

Pennsylvania Right To Know

: Isopropyl Mercaptan - 75-33-2 n-Propyl Mercaptan - 107-03-9

New Jersey Right To Know

: Isopropyl Mercaptan - 75-33-2 n-Propyl Mercaptan - 107-03-9

California Prop. 65

Ingredients

: This product does not contain any chemicals known to the State

of California to cause cancer, birth, or any other reproductive

defects.

Notification status

Europe REACH : On the inventory, or in compliance with the inventory

United States of America US.TSCA: On TSCA Inventory

Canada DSL : All components of this product are on the Canadian


DSL.

Australia AICS : On the inventory, or in compliance with the inventory New Zealand NZIoC : On the inventory, or in compliance with the inventory Japan ENCS : On the inventory, or in compliance with the inventory Korea KECI : On the inventory, or in compliance with the inventory Philippines PICCS : On the inventory, or in compliance with the inventory China IECSC : On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2

Fire Hazard: 3 Reactivity Hazard: 0



Further information

Legacy MSDS Number : 398540

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

11/12

MSDS Number:100000014178

Version 3.0 Revision Date 2013-05-29

The information in this MSDS pertains only to the product as shipped.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

	Key or legend to abbreviations and acronyms used in the safety data sheet				
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%		
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level		
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency		
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health		
CNS	Central Nervous System	NTP	National Toxicology Program		
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals		
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level		
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration		
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration		
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit		
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances		
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic		
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act		
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit		
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.		
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value		
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials		
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System		
LC50	Lethal Concentration 50%				

MSDS Number:100000014178 12/12