

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

SECTION 1: Identification of the substance/mixture and of the company/undertaking
Product information

Product Name : PRF Octane No. Blends (60, 80-99)

Material : 1024452, 1024451, 1024450, 1024448, 1024447, 1024446, 1024444, 1024443, 1024442, 1024440, 1024439, 1024438, 1024436, 1024435, 1024434, 1024432, 1024431, 1024430, 1024428, 1024427, 1024426, 1024424, 1024423, 1024422, 1024420, 1024419, 1024418, 1024416, 1024415, 1024414, 1024412, 1024411, 1024410, 1024408, 1024407, 1024406, 1024404, 1024403, 1024402, 1024400, 1024399, 1024398, 1024396, 1024395, 1024394, 1024392, 1024391, 1024390, 1024388, 1024384, 1024383, 1024382, 1024381, 1024380, 1024379, 1024378, 1024376, 1024372, 1024341, 1024340, 1024339, 1024386, 1024387, 1024453, 1024449, 1024445, 1024441, 1024437, 1024433, 1024429, 1024425, 1024421, 1024342, 1024417, 1024413, 1024409, 1024405, 1024401, 1024397, 1024393, 1024389, 1024385, 1024377, 1024375, 1024374

EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
2,2,4-Trimethylpentane (Isooctane)	540-84-1 208-759-1 601-009-00-8	Chevron Phillips Chemicals International NV 01-2119457965-22-0002
n-Heptane	142-82-5 205-563-8 601-008-00-2	Chevron Phillips Chemicals International NV 01-2119457603-38-0002

Relevant Identified Uses : Formulation
Supported
Use as a fuel - industrial
Use as a fuel – professional
Manufacture
Use as a laboratory agent – industrial
Use as a laboratory agent – professional
Distribution
Use in coatings – industrial
Use in coatings – professional
Use as a cleaning agent – industrial
Use as a cleaning agent – professional
Use as a cleaning agent – consumer
Use in Coatings - Consumer

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Use as a fuel – consumer

Company : Chevron Phillips Chemical Company LP
 Specialty Chemicals
 10001 Six Pines Drive
 The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
 Airport Plaza (Stockholm Building)
 Leonardo Da Vincilaan 19
 1831 Diegem
 Belgium

SDS Requests: (800) 852-5530
 Technical Information: (832) 813-4862
 Responsible Party: Product Safety Group
 Email:sds@cpchem.com

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification
Classification of the substance or mixture
REGULATION (EC) No 1272/2008

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ systemic toxicity - single exposure, Category 3	H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Acute aquatic toxicity, Category 1	H400: Very toxic to aquatic life.
Chronic aquatic toxicity, Category 1	H410: Very toxic to aquatic life with long lasting effects.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

:

H225

Highly flammable liquid and vapor.

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

H335

May cause respiratory irritation.

H336

May cause drowsiness or dizziness.

H410

Very toxic to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**

P210

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P243

Take precautionary measures against static discharge.

P273

Avoid release to the environment.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331

Do NOT induce vomiting.

Storage:

P403 + P235

Store in a well-ventilated place. Keep cool.

Hazardous ingredients which must be listed on the label:

- 540-84-1 2,2,4-Trimethylpentane (Isooctane)

SECTION 3: Composition/information on ingredients

Synonyms

: Primary Reference Fuel
60,80-99 Octane Reference Fuel

Molecular formula

: Mixture

Mixtures**Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
2,2,4-Trimethylpentane	540-84-1	Flam. Liq. 2; H225	60 - 100

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

(Isooctane)	208-759-1 601-009-00-8	Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 STOT SE 3; H336	
n-Heptane	142-82-5 205-563-8 601-008-00-2	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	30 - 60

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

- Flash point : -8 °C (18 °F)
Method: Tag closed cup
- Autoignition temperature : No data available
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- For additional details, see the Exposure Scenario in the Annex portion

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****SK**

Zložka	Podstata	Hodnota	Kontrolné parametre	Poznámka
n-heptane	SK OEL	NPEL priemerný	500 ppm, 2.085 mg/m3	

SI

Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
n-heptane	SI OEL	MV	500 ppm, 2.085 mg/m3	EU*

EU* Mejna vrednost, določena z Direktivo Komisije 2000/39/ES z dne 8. junija 2000 o določitvi prvega seznama indikativnih mejnih vrednosti za poklicno izpostavljenost pri izvajanju Direktive Sveta 98/24/ES o varovanju zdravja in zagotavljanju varnosti delavcev pred tveganjem zaradi izpostavljenosti kemičnim dejavnikom pri delu (UL L, št. 142, z dne 16. junija 2000, str. 47).

SE

Beståndsdelar	Grundval	Värde	Kontrollparametrar	Anmärkning
n-heptane	SE AFS	NGV	200 ppm, 800 mg/m3	V.
	SE AFS	KTV	300 ppm, 1.200 mg/m3	V.

V Vägledande kortidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas

RO

Componente	Bază	Valoare	Parametri de control	Notă
n-heptane	RO OEL	TWA	500 ppm, 2.085 mg/m3	

PT

Componentes	Bases	Valor	Parâmetros de controlo	Nota
n-heptane	PT DL 305/2007	oito horas	500 ppm, 2.085 mg/m3	
	PT OEL	VLE-MP	400 ppm,	(1), irritação do TRS, afeção do SNC,
	PT OEL	VLE_CD	500 ppm,	(1), irritação do TRS, afeção do SNC,

(1) Abrangido por legislação nacional específica ou por legislação comunitária não transposta
afeção do SNC afeção do sistema nervoso central
irritação do TRS irritação do trato respiratório superior

PL

Składniki	Podstawa	Wartość	Parametry dotyczące kontroli	Uwaga
n-heptane	PL NDS	NDS	1.200 mg/m3	
	PL NDS	NDSch	2.000 mg/m3	

NO

Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
n-heptane	FOR-2011-12-06-1358	TWA	200 ppm, 800 mg/m3	E,

E EU har en veiledende grenseverdi for stoffet

NL

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
n-heptane	NL WG	TGG-8 uur	1.200 mg/m3	
	NL WG	TGG-15 min	1.600 mg/m3	

MT

Ingredients	Basis	Value	Control parameters	Note
n-Heptane	MT OEL	TWA	500 ppm, 2.085 mg/m3	

LV

Sastāvdaļas	Bāze	Vērtība	Pārvaldības parametri	Piezīme
n-heptane	LV OEL	AER 8 st	85 ppm, 350 mg/m3	
	LV OEL	AER īslaicīgā	500 ppm, 2.085 mg/m3	

LU

Composants	Base	Valeur	Paramètres de contrôle	Note

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

n-heptane	LU OEL	TWA	500 ppm, 2.085 mg/m3	
-----------	--------	-----	----------------------	--

LT

Komponentai	Pagrindas, bazė	Vertė	Kontrolės parametrai	Pastaba
n-heptane	LT OEL	IPRD	500 ppm, 2.085 mg/m3	
	LT OEL	TPRD	750 ppm, 3.128 mg/m3	

IT

Componenti	Base	Valore	Parametri di controllo	Nota
n-heptane	IT OEL	TWA	500 ppm, 2.085 mg/m3	

IE

Ingredients	Basis	Value	Control parameters	Note
n-Heptane	IE OEL	OELV - 8 hrs (TWA)	500 ppm, 2.085 mg/m3	IOELV,

IOELV Indicative Occupational Exposure Limit Value

HU

Komponensek	Bázis	Érték	Ellenőrzési paraméterek	Megjegyzés
n-heptane	HU OEL	AK-érték	2.000 mg/m3	*, EU3,
	HU OEL	CK-érték	8.000 mg/m3	*, EU3,

* Európai 'indikatív' határértékek (96/94/EK, 2000/39/EK, 2006/15/EK, 2009/161/EU), amelyeknél nincs csúcskoncentráció megadva. Ezekben az esetekben jelen melléklet 1.3. pontja szerint kell eljárni

EU3 2000/39/EK irányelvben közölt érték

GR

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
n-heptane	GR OEL	TWA	500 ppm, 2.000 mg/m3	
	GR OEL	STEL	500 ppm, 2.000 mg/m3	

GB

Ingredients	Basis	Value	Control parameters	Note
n-Heptane	GB EH40	TWA	500 ppm,	2,

2 Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

FR

Composants	Base	Valeur	Paramètres de contrôle	Note
n-heptane	FR VLE	VME	400 ppm, 1.668 mg/m3	noir,
	FR VLE	VLCT (VLE)	500 ppm, 2.085 mg/m3	noir,

noir Valeurs limites réglementaires contraignantes

FI

Aineosat	Peruste	Arvo	Valvontaa koskevat muuttujat	Huomautus
2,2,4-Trimethylpentane (Isooctane)	FI OEL	HTP-arvot 8h	300 ppm, 1.400 mg/m3	
	FI OEL	HTP-arvot 15 min	380 ppm, 1.800 mg/m3	
n-heptane	FI OEL	HTP-arvot 8h	300 ppm, 1.200 mg/m3	
	FI OEL	HTP-arvot 15 min	500 ppm, 2.100 mg/m3	
	FI OEL	HTP-arvot 8h	300 ppm, 1.200 mg/m3	
	FI OEL	HTP-arvot 15 min	500 ppm, 2.100 mg/m3	

ES

Componentes	Base	Valor	Parámetros de control	Nota
n-heptane	ES VLA	VLA-ED	500 ppm, 2.085 mg/m3	VLI,

VLI Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.

EE

Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
n-heptane	EE OEL	Piimorm	500 ppm, 2.085 mg/m3	

DK

Komponenter	Basis	Værdi	Kontrolparametre	Note
n-heptane	DK OEL	GV	200 ppm, 820 mg/m3	E,

E At stoffet har en EF-grænseværdi

DE

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
n-heptane	DE TRGS 900	AGW	500 ppm, 2.100 mg/m3	DFG,

DFG Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission)

CZ

Složky	Základ	Hodnota	Kontrolní parametry	Poznámka
--------	--------	---------	---------------------	----------

SDS Number:100000014260

7/134

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

n-heptane	CZ OEL	PEL	1.000 mg/m3	I,
	CZ OEL	NPK-P	2.000 mg/m3	I,

I dráždí sliznice (oči, dýchací cesty) resp. kůže

CY

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
n-heptane	CY OEL	TWA	500 ppm, 2.085 mg/m3	

CH

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
n-heptane	CH SUVA	KZGW	400 ppm, 1.600 mg/m3	NIOSH,
	CH SUVA	MAK-Wert	400 ppm, 1.600 mg/m3	NIOSH,

NIOSH National Institute for Occupational Safety and Health

BG

Съставки	Основа	Стойност	Параметри на контрол	Бележка
n-heptane	BG OEL	TWA	1.600 mg/m3	-,

- Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност. Граничните стойности на тези химични агенти във въздуха на работната среда, определени с наредбата, са съобразени със съответните стойности, приети за Европейската общност, като могат да бъдат равни или по-ниски от тях.

BE

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
n-heptane	BE OEL	TGG 8 hr	400 ppm, 1.664 mg/m3	
	BE OEL	TGG 15 min	500 ppm, 2.085 mg/m3	

AT

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
n-heptane	AT OEL	TMW	500 ppm, 2.000 mg/m3	
	AT OEL	KZW	2.000 ppm, 8.000 mg/m3	

DNEL
n-Heptane :

Personal protective equipment

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

For additional details, see the Exposure Scenario in the Annex portion

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Physical state : Liquid
- Color : Colorless
- Odor : gasoline-like

Safety data

- Flash point : -8 °C (18 °F)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Method: Tag closed cup

Lower explosion limit	: 1 %(V)
Upper explosion limit	: 7 %(V)
Oxidizing properties	: no
Autoignition temperature	: No data available
Molecular formula	: Mixture
Molecular weight	: Not applicable
pH	: Not applicable
Freezing point	: No data available
Pour point	No data available
Boiling point/boiling range	: 96 - 103 °C (205 - 217 °F)
Vapor pressure	: 1,70 PSI at 37,8 °C (100,0 °F)
Relative density	: 0,693 at 15,6 °C (60,1 °F)
Water solubility	: Negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Relative vapor density	: 3 (Air = 1.0)
Evaporation rate	: 1
Percent volatile	: > 99 %

SECTION 10: Stability and reactivity

Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
--------------------	--

Possibility of hazardous reactions

Conditions to avoid	: Heat, sparks, fire, and oxidizing agents. Heat, flames and sparks.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Hazardous decomposition products : chlorates, nitrates, peroxides, etc.
: Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

2,2,4-Trimethylpentane (Isooctane) : LD50: > 5.000 mg/kg
Species: Rat
Sex: male and female
Method: OECD Test Guideline 401
Symptoms: Salivation

n-Heptane : LD50: > 5.000 mg/kg
Species: Rat
Method: OECD Test Guideline 401
Information given is based on data obtained from similar substances.

PRF Octane No. Blends (60, 80-99)

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Test atmosphere: dust/mist
Method: Calculation method

PRF Octane No. Blends (60, 80-99)

Acute dermal toxicity : LD50: > 2.000 mg/kg
Species: Rabbit

PRF Octane No. Blends (60, 80-99)

Skin irritation : May cause skin irritation in susceptible persons.

PRF Octane No. Blends (60, 80-99)

Eye irritation : Vapors may cause irritation to the eyes, respiratory system and the skin.

PRF Octane No. Blends (60, 80-99)

Sensitization : No adverse effects expected.

Repeated dose toxicity

2,2,4-Trimethylpentane (Isooctane) : Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 0, 668, 2220, 6646 ppm
Exposure time: 13 weeks
Number of exposures: 6 hr/day 5 d/wk
NOEL: 8,117 mg/l 2220 ppm
Method: OECD Guideline 413
Information given is based on data obtained from similar substances.

n-Heptane : Species: Rat, male
Sex: male

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Application Route: Inhalation
 Dose: 12.47 mg/l
 Exposure time: 16 wk
 Number of exposures: 12 h/d, 7 d/wk
 NOEL: 12,47 mg/l
 No adverse effect has been observed in chronic toxicity tests.

Reproductive toxicity

2,2,4-Trimethylpentane
 (Isooctane)

: Species: Rat
 Sex: male and female
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6 h/d 5 d/wk
 Method: OECD Test Guideline 416
 NOAEL Parent: 3000 ppm
 NOAEL F1: 3000 ppm
 NOAEL F2: 3000 ppm
 Information given is based on data obtained from similar substances.

n-Heptane

Species: Rat
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6 hr/d, 5 d/wk
 Test period: 13 wk
 Method: OECD Test Guideline 416
 NOAEL Parent: 9000 ppm
 NOAEL F1: 3000 ppm
 NOAEL F2: 3000 ppm

Developmental Toxicity

2,2,4-Trimethylpentane
 (Isooctane)

: Species: Rat
 Application Route: Inhalation
 Dose: 0, 400, 1200 ppm
 Number of exposures: 6h/d
 Test period: GD6-15
 NOAEL Teratogenicity: 1200 ppm
 NOAEL Maternal: 1200 ppm
 Information given is based on data obtained from similar substances.

Species: Rat
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6h/d
 Test period: GD6-15
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 9000 ppm
 NOAEL Maternal: 3000 ppm
 Information given is based on data obtained from similar substances.

n-Heptane

Species: Rat
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Exposure time: GD6-15
 Number of exposures: 6 hrs/d

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

NOAEL Teratogenicity: 9000 ppm

NOAEL Maternal: 3000 ppm

PRF Octane No. Blends (60, 80-99)

Aspiration toxicity : May be fatal if swallowed and enters airways.
Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity hazard.

CMR effects

2,2,4-Trimethylpentane (Isooctane) : Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Teratogenicity: Animal testing did not show any effects on fetal development.
Reproductive toxicity: Animal testing did not show any effects on fertility.

n-Heptane : Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Teratogenicity: Animal testing did not show any effects on fetal development.
Reproductive toxicity: No toxicity to reproduction

PRF Octane No. Blends (60, 80-99)

Further information : Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

2,2,4-Trimethylpentane (Isooctane) : LC50: 0,11 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
semi-static test Method: OECD Test Guideline 203
Information given is based on data obtained from similar substances.

n-Heptane : LL50: 1,284 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
Method: QSAR

LC50: 375 mg/l
Exposure time: 96 h
Species: Tilapia mosambica (Fish)

Toxicity to daphnia and other aquatic invertebrates

2,2,4-Trimethylpentane (Isooctane) : EC50: 0,4 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
static test Information given is based on data obtained from similar substances.

n-Heptane : EC50: 1,5 mg/l

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Exposure time: 48 h
 Species: *Daphnia magna* (Water flea)
 static test Toxic to aquatic organisms.

LC50: 0,1 mg/l
 Exposure time: 96 h
 Species: *Mysidopsis bahia* (mysid shrimp)
 semi-static test Very toxic to aquatic organisms.

Toxicity to algae

2,2,4-Trimethylpentane (Isooctane) : EL50: 2,943 mg/l
 Exposure time: 72 h
 Method: QSAR modeled data

n-Heptane : EL50: 4,338 mg/l
 Exposure time: 72 h
 Species: *Pseudokirchneriella subcapitata* (microalgae)
 Method: QSAR

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

2,2,4-Trimethylpentane (Isooctane) : NOEC: 0,17 mg/l
 Exposure time: 21 d
 Species: *Daphnia magna* (Water flea)

Elimination information (persistence and degradability)

Biodegradability : Not applicable

Ecotoxicology Assessment

Acute aquatic toxicity
 2,2,4-Trimethylpentane (Isooctane) : Very toxic to aquatic life.
 n-Heptane : Very toxic to aquatic life.

Chronic aquatic toxicity
 2,2,4-Trimethylpentane (Isooctane) : Very toxic to aquatic life with long lasting effects.
 n-Heptane : Very toxic to aquatic life with long lasting effects.

Results of PBT assessment
 2,2,4-Trimethylpentane (Isooctane) : Non-classified PBT substance, Non-classified vPvB substance
 n-Heptane : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

For additional details, see the Exposure Scenario in the Annex portion

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE), RQ (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (-8 °C), MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation****Chemical Safety Assessment**

Ingredients	:	2,2,4-trimethylpentane	A Chemical Safety Assessment has been carried out for this substance.	208-759-1
--------------------	---	------------------------	---	-----------

Chemical Safety Assessment

	:	heptane	A Chemical Safety Assessment has been carried out for this substance.	205-563-8
--	---	---------	---	-----------

Major Accident Hazard Legislation	:	96/82/EC	Update: 2003
		Highly flammable	
		7b	
		Quantity 1: 5.000 t	
		Quantity 2: 50.000 t	

:	96/82/EC	Update: 2003
	Dangerous for the environment	
	9a	
	Quantity 1: 100 t	
	Quantity 2: 200 t	

Water contaminating class (Germany)	:	WGK 2 water endangering
--	---	-------------------------

Notification status

Europe REACH	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On the inventory, or in compliance with the inventory
Canada DSL	:	On the inventory, or in compliance with the inventory
Australia AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	On the inventory, or in compliance with the inventory
Philippines PICCS	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory


PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

SECTION 16: Other information

NFPA Classification : Health Hazard: 1
Fire Hazard: 3
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 28440

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

	New Chemical Substances		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Annex**1. Short title of Exposure Scenario: Formulation**

Main User Groups	: SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	: SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
Process category	: PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting; PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC14: Production of mixtures or articles by tableting, compression, extrusion, pelletization; Industrial setting; PROC15: Use as laboratory reagent
Environmental release category	: ERC2: Formulation of preparations
Further information	: Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

2.1 Contributing scenario controlling environmental exposure for:ERC2: Formulation of preparations

Maximum allowable site tonnage : 900 tonnes/day
(MSafe) based on release
following total wastewater
treatment removal (tonnes/day):
(Msafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Continuous use/release
 Number of emission days per year : 300
 Emission or Release Factor: Air : 2,5 %
 Emission or Release Factor: Water : 0,002 %
 Emission or Release Factor: Soil : 0,01 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: 0 %)
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): (Effectiveness: 61,8 %)
 Remarks : Risk from environmental exposure is driven by freshwater sediment.
 Water : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): (Effectiveness: 0 %)
 Remarks : If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
 Remarks : Prevent discharge of undissolved substance to or recover from wastewater.
 Remarks : Do not apply industrial sludge to natural soils.
 Remarks : Sludge should be incinerated, contained or reclaimed.
 Remarks : Common practices vary across sites thus conservative process release estimates used.

Conditions and measures related to municipal sewage treatment plant

Flow rate of sewage treatment plant effluent : 2.000 m3/d
 Effectiveness (of a measure) : 96,3 %
 Percentage removed from waste water : 96,3 %
 Sludge Treatment : No data available
 Procedures to limit air emissions from Sewage Treatment Plant : No data available

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure**Product characteristics**

Physical Form (at time of use) : Liquid substance

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Handle substance within a closed system., Store substance within a closed system., Transfer via enclosed lines.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC3: Use in closed batch process (synthesis or formulation)**Product characteristics**

Physical Form (at time of use) : Liquid substance

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Avoid dip sampling., Formulate in enclosed or ventilated mixing vessels., Provide enhanced general ventilation by mechanical means.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC4, PROC15: Use in batch and other process (synthesis) where opportunity for exposure arises, Use as laboratory reagent**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

2.2 Contributing scenario controlling worker exposure for: PROC5: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting;**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Provide extraction ventilation at points where emissions occur., Use drum pumps or carefully pour from container.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Provide extraction ventilation at points where emissions occur., Use drum pumps or carefully pour from container.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC9, PROC14: Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Production of mixtures or articles by tableting, compression, extrusion, pelletization; Industrial setting;
Product characteristics

SDS Number:100000014260

22/134

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC2	Hydrocarbon Block Method with Petrorisk		Air		0,5 mg/m3	
			Fresh water		0,0032 mg/L	0,086
			Freshwater sediment		0,14 mg/kg	0,097
			Marine water		0,32 µg/L	0,0085
			Marine sediment		0,014 mg/kg	0,0097
			Agricultural soil		0,0046 mg/kg	0,01

ERC2: Formulation of preparations

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC1, CS15, CS67	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	0,05 mg/m3	0,000
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,000
PROC2, CS67, CS15	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	1,37 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,025
PROC3, CS2, CS15	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	116,79 mg/m3	0,057
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			Worker – long-term – systemic Combined routes		0,058
PROC3, CS136	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	140,15 mg/m3	0,069
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,069
PROC4, CS16	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	93,43 mg/m3	0,046
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,055
PROC15, CS36	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,023
PROC5, CS30	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118
PROC8a, CS34, CS22	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	23,36 mg/m3	0,011
			Worker – dermal, long-term – systemic	0,1371 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,012
PROC8a, CS39	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118
PROC8b, CS14	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,117
PROC8b, CS8	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	7,01 mg/m3	0,003
			Worker – dermal, long-term – systemic	0,686 mg/kg/d	0,001
			Worker – long-term – systemic Combined routes		0,004
PROC9, CS6	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,124
PROC14, CS100	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	3,43 mg/kg/d	0,004
			Worker – long-term – systemic Combined		0,119

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

	routes
PROC1: Use in closed process, no likelihood of exposure CS15: General exposures (closed systems) CS67: Storage	
PROC2: Use in closed, continuous process with occasional controlled exposure CS67: Storage CS15: General exposures (closed systems)	
PROC3: Use in closed batch process (synthesis or formulation) CS2: Process sampling CS15: General exposures (closed systems)	
PROC3: Use in closed batch process (synthesis or formulation) CS136: Batch processes at elevated temperatures	
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises CS16: General exposures (open systems)	
PROC15: Use as laboratory reagent CS36: Laboratory activities	
PROC5: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting; CS30: Mixing operations (open systems)	
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities CS34: Manual CS22: Transfer from/pouring from containers	
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities CS39: Equipment cleaning and maintenance	
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities CS14: Bulk transfers	
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities CS8: Drum/batch transfers	
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) CS6: Drum and small package filling	
PROC14: Production of mixtures or articles by tableting, compression, extrusion, pelletization; Industrial setting; CS100: Production or preparation or articles by tableting, compression, extrusion or pelletization	

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
 Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
 Risk Management Measures are based on qualitative risk characterisation.
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Use as a fuel - industrial

Main User Groups	: SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	: SU3: Industrial Manufacturing (all)
Process category	: PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities PROC16: Using material as fuel sources, limited exposure to unburned product to be expected
Environmental release category	: ERC7, ERC8b: Industrial use of substances in closed systems, Wide dispersive indoor use of reactive substances in open systems
Further information	: Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

**2.1 Contributing scenario controlling environmental exposure for:ERC7, ERC8b:
 Industrial use of substances in closed systems, Wide dispersive indoor use of reactive substances in open systems**

(Msafe) : 1.800 tonnes/day

Environment factors not influenced by risk management

Flow rate	: 18.000 m ³ /d
Dilution Factor (River)	: 10
Dilution Factor (Coastal Areas)	: 100

Other given operational conditions affecting environmental exposure

SDS Number:100000014260

26/134

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Number of emission days per year : 300
 Emission or Release Factor: Air : 5 %
 Emission or Release Factor: Water : 0,001 %
 Emission or Release Factor: Soil : 0 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide a typical removal efficiency of (%): (Effectiveness: 95 %)
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): (Effectiveness: 23,4 %)
 Remarks : Risk from environmental exposure is driven by freshwater sediment.
 Water : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): (Effectiveness: 0 %)
 Remarks : Do not apply industrial sludge to natural soils.
 Remarks : Sludge should be incinerated, contained or reclaimed.
 Remarks : Common practices vary across sites thus conservative process release estimates used.
 Remarks : If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Conditions and measures related to municipal sewage treatment plant

Flow rate of sewage treatment plant effluent : 2.000 m3/d
 Effectiveness (of a measure) : 96,3 %
 Percentage removed from waste water : 96,3 %
 Sludge Treatment : No data available
 Procedures to limit air emissions from Sewage Treatment Plant : No data available

Conditions and measures related to external treatment of waste for disposal

Remarks : Combustion emissions limited by required exhaust emission controls.
 Combustion emissions considered in regional exposure assessment.

Conditions and measures related to external recovery of waste

Recovery Methods : This substance is consumed during use and no waste of the substance is generated.

2.2 Contributing scenario controlling worker exposure for: PROC1: Use in closed process, no likelihood of exposure**Product characteristics**

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system., Store substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC2: Use in closed, continuous process with occasional controlled exposure**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system., Transfer via enclosed lines., Store substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC3: Use in closed batch process (synthesis or formulation)**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

2.2 Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Drain down and flush system prior to equipment opening or maintenance.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., Apply vessel entry procedures including use of forced supplied air.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable coveralls to prevent exposure to the skin., Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC16: Using material as fuel sources, limited exposure to unburned product to be expected**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization
-----------------------	---------------------	---------------------	-------------	------------	-------------------	-----------------------

SDS Number:100000014260

30/134

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

	Method				ratio
ERC7, ERC8b	Hydrocarbon Block Method with Petrorisk		Air		0,05 mg/m3
			Freshwater		0,0016 mg/L
			Freshwater sediment		0,07 mg/kg
			Marine water		0,16 µg/L
			Marine sediment		0,007 mg/kg
			Agricultural soil		0,46 µg/kg

ERC7: Industrial use of substances in closed systems

ERC8b: Wide dispersive indoor use of reactive substances in open systems

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC1, CS15, CS37, CS67	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	0,05 mg/m3	0,000
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,000
PROC2, CS15, CS37, CS67	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	1,37 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,025
PROC3, CS15, CS37, CS107	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	116,79 mg/m3	0,057
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,058
PROC8a, CS39	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118
PROC8a, CS103	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	23,36 mg/m3	0,011
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,015
PROC8b, CS8, CS14	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,117
PROC16, CS15, CS107	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	23,36 mg/m3	0,011
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,012

PROC1: Use in closed process, no likelihood of exposure

CS15: General exposures (closed systems)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

CS37: Use in contained batch processes

CS67: Storage

PROC2: Use in closed, continuous process with occasional controlled exposure

CS15: General exposures (closed systems)

CS37: Use in contained batch processes

CS67: Storage

PROC3: Use in closed batch process (synthesis or formulation)

CS15: General exposures (closed systems)

CS37: Use in contained batch processes

CS107: (closed systems)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

CS39: Equipment cleaning and maintenance

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

CS103: Vessel and container cleaning

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

CS8: Drum/batch transfers

CS14: Bulk transfers

PROC16: Using material as fuel sources, limited exposure to unburned product to be expected

CS15: General exposures (closed systems)

CS107: (closed systems)

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Use as a fuel – professional

Main User Groups	: SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Sector of use	: SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process category	: PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)**PROC8a:** Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**PROC8b:** Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities**PROC16:** Using material as fuel sources, limited exposure to unburned product to be expected

Environmental release category : **ERC8b, ERC8e, ERC9a, ERC9b:** Wide dispersive indoor use of reactive substances in open systems, Wide dispersive outdoor use of reactive substances in open systems, Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

Further information : Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

2.1 Contributing scenario controlling environmental exposure for:ERC8b, ERC8e, ERC9a, ERC9b: Wide dispersive indoor use of reactive substances in open systems, Wide dispersive outdoor use of reactive substances in open systems, Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

(Msafe) : 240 tonnes/day

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 365
Emission or Release Factor: Air : 0,1 %
Emission or Release Factor: Water : 0,001 %
Emission or Release Factor: Soil : 0,001 %

Technical conditions and measures / Organizational measures

Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%):
(Effectiveness: 0 %)

Remarks : Risk from environmental exposure is driven by freshwater.

Water : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%):
(Effectiveness: 0 %)

Remarks : Common practices vary across sites thus conservative process release estimates used.

Remarks : No wastewater treatment required.

Conditions and measures related to municipal sewage treatment plant

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Flow rate of sewage treatment plant effluent : 2.000 m3/d
 Effectiveness (of a measure) : 96,3 %
 Percentage removed from waste water : 96,3 %
 Sludge Treatment : No data available
 Procedures to limit air emissions from Sewage Treatment Plant : No data available

Conditions and measures related to external treatment of waste for disposal

Remarks : Combustion emissions limited by required exhaust emission controls.
 Combustion emissions considered in regional exposure assessment.

Conditions and measures related to external recovery of waste

Recovery Methods : This substance is consumed during use and no waste of the substance is generated.

2.2 Contributing scenario controlling worker exposure for: PROC1: Use in closed process, no likelihood of exposure**Product characteristics**

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system., Store substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC2: Use in closed, continuous process with occasional controlled exposure**Product characteristics**

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC3, PROC16: Use in closed batch process (synthesis or formulation), Using material as fuel sources, limited exposure to unburned product to be expected
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Drain down system prior to equipment opening or maintenance.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., Apply vessel entry procedures including use of forced supplied air.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., Wear suitable coveralls to prevent exposure to the skin.

2.2 Contributing scenario controlling worker exposure for: PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system., Use drum pumps or carefully pour from container., Ensure operation is undertaken outdoors., Clear transfer lines prior to de-coupling.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC8b, ERC8e, ERC9a, ERC9b	Hydrocarbon Block Method with Petrorisk		Air		0,074 µg/m3	
			Freshwater		0,0058 µg/L	0,00015
			Freshwater sediment		0,0001 mg/kg	0,000073
			Marine water		0,066 ng/L	< 0,000017
			Marine sediment		0,0028 µg/kg	0,000002
			Agricultural soil		0,012 µg/kg	0,000021

ERC8b: Wide dispersive indoor use of reactive substances in open systems

ERC8e: Wide dispersive outdoor use of reactive substances in open systems

ERC9a: Wide dispersive indoor use of substances in closed systems

ERC9b: Wide dispersive outdoor use of substances in closed systems

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC1, CS15, CS67	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	0,05 mg/m3	0,000
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,000
PROC2, CS15	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	93,43 mg/m3	0,046
			Worker – dermal, long-term – systemic	1,37 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,048
PROC3, CS15, CS107	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	116,79 mg/m3	0,057
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,058
PROC16, CS15, CS107	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,023
PROC8a, CS39, CS103	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	93,43 mg/m3	0,046
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,049
PROC8b, CS1, CS8	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,025

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

PROC8b, CS14	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	163,51 mg/m3	0,080
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,082

PROC1: Use in closed process, no likelihood of exposure

CS15: General exposures (closed systems)

CS67: Storage

PROC2: Use in closed, continuous process with occasional controlled exposure

CS15: General exposures (closed systems)

PROC3: Use in closed batch process (synthesis or formulation)

CS15: General exposures (closed systems)

CS107: (closed systems)

PROC16: Using material as fuel sources, limited exposure to unburned product to be expected

CS15: General exposures (closed systems)

CS107: (closed systems)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

CS39: Equipment cleaning and maintenance

CS103: Vessel and container cleaning

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

CS1: General exposures

CS8: Drum/batch transfers

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

CS14: Bulk transfers

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: **Manufacture**

Main User Groups : **SU 3: Industrial uses: Uses of substances as such or in**

SDS Number:100000014260

38/134

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Sector of use	: preparations at industrial sites SU3, SU8, SU9: Industrial Manufacturing (all), Manufacture of bulk, large scale chemicals (including petroleum products), Manufacture of fine chemicals
Process category	: PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental release category	: ERC1, ERC4: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles
Further information	: Manufacture of the substance or use as an intermediate or process chemical or extraction agent. Includes recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

2.1 Contributing scenario controlling environmental exposure for:ERC1, ERC4: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles

(Msafe) : 3.000 tonnes/day

Environment factors not influenced by risk management

Flow rate	: 18.000 m3/d
Dilution Factor (River)	: 10
Dilution Factor (Coastal Areas)	: 100

Other given operational conditions affecting environmental exposure

Continuous use/release	
Number of emission days per year	: 300
Emission or Release Factor: Air	: 5 %
Emission or Release Factor: Water	: 0,003 %
Emission or Release Factor: Soil	: 0,01 %

Technical conditions and measures / Organizational measures

Air	: Treat air emission to provide the required removal efficiency of (%): (Effectiveness: 90 %)
Water	: Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 0 %)
Remarks	: Risk from environmental exposure is driven by freshwater

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

- Water : sediment.
 : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%):
 (Effectiveness: 0 %)
- Remarks : No wastewater treatment required.
- Remarks : Prevent discharge of undissolved substance to or recover from onsite wastewater.
- Remarks : Common practices vary across sites thus conservative process release estimates used.

Conditions and measures related to municipal sewage treatment plant

- Flow rate of sewage treatment plant effluent : 10.000 m³/d
- Effectiveness (of a measure) : 96,3 %
- Percentage removed from waste water : 96,3 %
- Sludge Treatment : No data available
- Procedures to limit air emissions from Sewage Treatment Plant : No data available

Conditions and measures related to external treatment of waste for disposal

- Waste treatment : During manufacturing no waste of the substance is generated.

Conditions and measures related to external recovery of waste

- Recovery Methods : During manufacturing no waste of the substance is generated.

2.2 Contributing scenario controlling worker exposure for: PROC1: Use in closed process, no likelihood of exposure**Product characteristics**

- Physical Form (at time of use) : Liquid substance

Amount used

- Remarks : No limit

Frequency and duration of use

- Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

- Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

- Store substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

- Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

2.2 Contributing scenario controlling worker exposure for: PROC2: Use in closed, continuous process with occasional controlled exposure**Product characteristics**

- Physical Form (at time of use) : Liquid substance

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Handle substance within a closed system., Store substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC3: Use in closed batch process (synthesis or formulation)**Product characteristics**

Physical Form (at time of use) : Liquid substance

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Handle substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC4, PROC15: Use in batch and other process (synthesis) where opportunity for exposure arises, Use as laboratory reagent**Product characteristics**

Physical Form (at time of use) : Liquid substance

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Handle substance within a closed system., Store substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
Product characteristics

Physical Form (at time of use) : Liquid substance

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
Product characteristics

Physical Form (at time of use) : Liquid substance

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Handle substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC1, ERC4	Hydrocarbon Block Method with Petrorisk		Air		0,1 mg/m3	
			Fresh water		0,001 mg/L	0,026
			Freshwater sediment		0,043 mg/kg	0,03
			Marine water		0,0001 mg/L	0,0026
			Marine sediment		0,0043 mg/kg	0,003
			Agricultural soil		0,95 µg/kg	0,0021

ERC1: Manufacture of substances

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC1, CS15, CS67	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	0,05 mg/m3	0,000
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,000
PROC2, CS15, CS67	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	1,37 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,025
PROC3, CS15	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	116,79 mg/m3	0,057
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			term – systemic		
			Worker – long-term – systemic Combined routes		0,058
PROC4, CS16	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	93,43 mg/m3	0,046
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,055
PROC15, CS36	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,023
PROC8a, CS39	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118
PROC8b, CS2, CS14, CS107, CS108	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,124

PROC1: Use in closed process, no likelihood of exposure

CS15: General exposures (closed systems)

CS67: Storage

PROC2: Use in closed, continuous process with occasional controlled exposure

CS15: General exposures (closed systems)

CS67: Storage

PROC3: Use in closed batch process (synthesis or formulation)

CS15: General exposures (closed systems)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

CS16: General exposures (open systems)

PROC15: Use as laboratory reagent

CS36: Laboratory activities

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

CS39: Equipment cleaning and maintenance

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

CS2: Process sampling

CS14: Bulk transfers

CS107: (closed systems)

CS108: (open systems)

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Scaled local assessments for EU refineries have been performed using site-specific data and are attached in PETRORISK file – “Site-Specific Production” worksheet.

1. Short title of Exposure Scenario: Use as a laboratory agent – industrial

Main User Groups	: SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	: SU3: Industrial Manufacturing (all)
Process category	: PROC1: Use in closed process, no likelihood of exposure PROC10: Roller application or brushing PROC15: Use as laboratory reagent
Environmental release category	: ERC2, ERC4: Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles
Further information	: Use of the substance within laboratory settings, including material transfers and equipment cleaning.

2.1 Contributing scenario controlling environmental exposure for:ERC2, ERC4: Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles

Maximum allowable site tonnage : 900
(MSafe) based on release
following total wastewater
treatment removal (kg/d):(MSafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m³/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
Number of emission days per year : 20
Emission or Release Factor: Air : 2,5 %
Emission or Release Factor: Water : 2,0 %

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Emission or Release Factor: Soil : 0,01 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: 0 %)

Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): (Effectiveness: 66,5 %)

Remarks : Risk from environmental exposure is driven by freshwater sediment.

Water : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): (Effectiveness: 0 %)

Remarks : If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Remarks : Do not apply industrial sludge to natural soils.

Remarks : Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Flow rate of sewage treatment plant effluent : 2.000 m3/d

Effectiveness (of a measure) : 96,3 %

Percentage removed from waste water : 96,3 %

Sludge Treatment : No data available

Procedures to limit air emissions from Sewage Treatment Plant : No data available

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC10: Roller application or brushing**Product characteristics**

Physical Form (at time of use) : Liquid substance

Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent /

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC15: Use as laboratory reagent**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC2, ERC4	Hydrocarbon Block Method with Petrorisk		Air		0,13 µg/m3	
			Freshwater		0,0037 mg/L	0,098
			Freshwater sediment		0,16 mg/kg	0,11
			Marine water		0,37 µg/L	0,0098
			Marine sediment		0,016 mg/kg	0,011
			Agricultural soil		0,0019 µg/kg	< 0,000002

ERC2: Formulation of preparations

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC10, CS47	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	5,486 mg/kg/d	0,007

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			Worker – long-term – systemic Combined routes		0,122
PROC15, CS36	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,023

PROC10: Roller application or brushing
CS47: Cleaning

PROC15: Use as laboratory reagent
CS36: Laboratory activities

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Risk Management Measures are based on qualitative risk characterisation.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: **Use as a laboratory agent – professional**

Main User Groups : **SU 22:** Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Sector of use : **SU 22:** Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process category : **PROC10:** Roller application or brushing
PROC15: Use as laboratory reagent
Environmental release category : **ERC8a:** Wide dispersive indoor use of processing aids in open systems
Further information :
Use of the substance within laboratory settings, including material transfers and equipment cleaning.

2.1 Contributing scenario controlling environmental exposure for: **ERC8a: Wide dispersive indoor use of processing aids in open systems**

Maximum allowable site tonnage : 14
(MSafe) based on release

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

following total wastewater
treatment removal (kg/d):(Msafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
Number of emission days per year : 365
Emission or Release Factor: Air : 50 %
Emission or Release Factor: Water : 50 %
Emission or Release Factor: Soil : 0 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: 0 %)
Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): (Effectiveness: 0 %)
Remarks : Risk from environmental exposure is driven by freshwater.
Water : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): (Effectiveness: 0 %)
Remarks : No wastewater treatment required.

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
Flow rate of sewage treatment plant effluent : 2.000 m3/d
Effectiveness (of a measure) : 96,3 %
Percentage removed from waste water : 96,3 %

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC10: Roller application or brushing**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Handle in a fume cupboard or under extract ventilation.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC15: Use as laboratory reagent**Product characteristics**

Physical Form (at time of use) : Liquid substance

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Handle in a fume cupboard or under extract ventilation.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC8a	Hydrocarbon Block Method with Petrorisk		Air		0,074 µg/m ³	
			Freshwater		0,0077 µg/L	0,0002
			Freshwater sediment		0,00011 mg/kg	0,000076
			Marine water		0,00025 µg/L	< 0,000007
			Marine sediment		0,000011 mg/kg	< 0,000008
			Agricultural soil		0,047 µg/kg	0,00008

ERC8a: Wide dispersive indoor use of processing aids in open systems

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC10, CS47	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	93,43 mg/m ³	0,046
			Worker – dermal, long-term – systemic	1,3715 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,048
PROC15, CS36	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m ³	0,023
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,023

PROC10: Roller application or brushing
CS47: Cleaning

PROC15: Use as laboratory reagent
CS36: Laboratory activities

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Risk Management Measures are based on qualitative risk characterisation.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Distribution

Main User Groups : **SU 3:** Industrial uses: Uses of substances as such or in preparations at industrial sites

Sector of use : **SU3:** Industrial Manufacturing (all)

Process category : **PROC1:** Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

	non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC15: Use as laboratory reagent
Environmental release category	: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7: Manufacture of substances, Formulation of preparations, Formulation in materials, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in inclusion into or onto a matrix, Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids, Industrial use of monomers for manufacture of thermoplastics, Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers, Industrial use of substances in closed systems
Further information	: Bulk loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading, maintenance and associated laboratory activities. Excludes emissions during transport.

2.1 Contributing scenario controlling environmental exposure for:ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7: Manufacture of substances, Formulation of preparations, Formulation in materials, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in inclusion into or onto a matrix, Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids, Industrial use of monomers for manufacture of thermoplastics, Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers, Industrial use of substances in closed systems

Maximum allowable site tonnage : 97.000
(MSafe) based on release
following total wastewater
treatment removal (kg/d):(Msafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
Number of emission days per year : 20
Emission or Release Factor: Air : 0,1 %
Emission or Release Factor: Soil : 0,001 %
Remarks : Emission or Release Factor: Water : < 0.001 %

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Technical conditions and measures / Organizational measures

- Water : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): (Effectiveness: 0 %)
- Remarks : Risk from environmental exposure is driven by freshwater.
- Remarks : Common practices vary across sites thus conservative process release estimates used.
- Remarks : No wastewater treatment required.
- Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: 90 %)
- Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): (Effectiveness: 0 %)

Conditions and measures related to municipal sewage treatment plant

- Type of Sewage Treatment Plant : Municipal sewage treatment plant
- Flow rate of sewage treatment plant effluent : 2.000 m3/d
- Effectiveness (of a measure) : 96,3 %
- Percentage removed from waste water : 96,3 %
- Sludge Treatment : No data available
- Procedures to limit air emissions from Sewage Treatment Plant : No data available

Conditions and measures related to external treatment of waste for disposal

- Remarks : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

- Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1: Use in closed process, no likelihood of exposure**Product characteristics**

- Physical Form (at time of use) : Liquid substance
- Vapor pressure : 2,8 kPa

Amount used

- Remarks : No limit

Frequency and duration of use

- Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

- Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

- Handle substance within a closed system.
- Transfer via enclosed lines.

Organizational measures to prevent /limit releases, dispersion and exposure

- Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent /

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC2: Use in closed, continuous process with occasional controlled exposure**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Store substance within a closed system., Transfer via enclosed lines.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC3, PROC9, PROC15: Use in closed batch process (synthesis or formulation), Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Use as laboratory reagent**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent /

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

minimise exposures and to report any skin problems that may develop., No specific measures identified.

2.2 Contributing scenario controlling worker exposure for: PROC4, PROC8b: Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent /

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

minimise exposures and to report any skin problems that may develop., Apply vessel entry procedures including use of forced supplied air.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., Wear suitable coveralls to prevent exposure to the skin., Wear rubber boots.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7	Hydrocarbon Block Method with Petrorisk		Air		74 ng/m3	
			Fresh water		5,1 ng/L	0,00013
			Fresh water sediment		0,000075 mg/kg	0,000054
			Marine water		0,019 ng/L	< 0,000044
			Marine sediment		0,26 ng/kg	< 0,000002
			Agricultural soil		1,2 ng/kg	< 0,000034

ERC1: Manufacture of substances

ERC2: Formulation of preparations

ERC3: Formulation in materials

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

ERC5: Industrial use resulting in inclusion into or onto a matrix

ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

ERC6b: Industrial use of reactive processing aids

ERC6c: Industrial use of monomers for manufacture of thermoplastics

ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

ERC7: Industrial use of substances in closed systems

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC1, CS15, CS67	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	0,05 mg/m3	0,000
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,000
PROC2, CS15, CS67	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	1,37 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,025
PROC3, CS15, CS2	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	116,79 mg/m3	0,057
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,058

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

PROC9, CS6	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/kg/d	0,115
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,124
PROC15, CS36	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/kg/d	0,023
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,023
PROC4, CS16	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	93,43 mg/m3	0,046
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,048
PROC8b, CS14, CS107, CS108	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,117
PROC8a, CS39	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118

PROC1: Use in closed process, no likelihood of exposure

CS15: General exposures (closed systems)

CS67: Storage

PROC2: Use in closed, continuous process with occasional controlled exposure

CS15: General exposures (closed systems)

CS67: Storage

PROC3: Use in closed batch process (synthesis or formulation)

CS15: General exposures (closed systems)

CS2: Process sampling

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

CS6: Drum and small package filling

PROC15: Use as laboratory reagent

CS36: Laboratory activities

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

CS16: General exposures (open systems)

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

CS14: Bulk transfers

CS107: (closed systems)

CS108: (open systems)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

CS39: Equipment cleaning and maintenance

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
 Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
 Risk Management Measures are based on qualitative risk characterisation.
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Use in coatings – industrial

Main User Groups	: SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	: SU3: Industrial Manufacturing (all)
Process category	: PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting; PROC7: Industrial spraying PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC14: Production of mixtures or articles by tableting, compression, extrusion, pelletization; Industrial setting; PROC15: Use as laboratory reagent
Environmental release category	: ERC4: Industrial use of processing aids in processes and products, not becoming part of articles
Further information	: Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk,

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

2.1 Contributing scenario controlling environmental exposure for:ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Maximum allowable site tonnage : 260.000
(MSafe) based on release
following total wastewater
treatment removal (kg/d):(Msafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
Number of emission days per year : 20
Emission or Release Factor: Air : 98 %
Emission or Release Factor: Water : 0,007 %
Emission or Release Factor: Soil : 0 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: 90 %)
Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): (Effectiveness: 4,3 %)
Water : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): (Effectiveness: 0 %)
Remarks : Common practices vary across sites thus conservative process release estimates used.
Remarks : Prevent discharge of undissolved substance to or recover from onsite wastewater.
Remarks : Risk from environmental exposure is driven by freshwater sediment.
Remarks : If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Remarks : Do not apply industrial sludge to natural soils.
Remarks : Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
Flow rate of sewage treatment plant effluent : 2.000 m3/d
Effectiveness (of a measure) : 96,3 %
Percentage removed from waste water : 96,3 %
Sludge Treatment : No data available
Procedures to limit air emissions from Sewage Treatment Plant : No data available

Conditions and measures related to external treatment of waste for disposal

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Remarks : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation)
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Handle substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC4, PROC9, PROC15: Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Use as laboratory reagent
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

2.2 Contributing scenario controlling worker exposure for: PROC5, PROC10, PROC14: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting;,, Roller application or brushing, Production of mixtures or articles by tableting, compression, extrusion, pelletization; Industrial setting;

Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC7: Industrial spraying

Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Carry out in a vented booth provided with laminar airflow., Provide enhanced general ventilation by

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

mechanical means.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

2.2 Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Clear transfer lines prior to de-coupling.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Clear transfer lines prior to de-coupling.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC13: Treatment of articles by dipping and pouring**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., Avoid manual contact with wet work pieces.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC4	Hydrocarbon Block Method with Petrorisk		Air		0,015 mg/m3	
			Fresh water		0,0013 mg/L	0,034
			Fresh water		0,056 mg/kg	0,039

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			sediment			
			Marine water		0,13 µg/L	0,0034
			Marine sediment		0,0056 mg/kg	0,0039
			Agricultural soil		0,14 µg/kg	0,0003

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC1, CS15	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	0,05 mg/m3	0,000
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		
PROC2, CS15, CS56, CS38	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	1,37 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,025
PROC2, CS94	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	1,37 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,117
PROC3, CS29, CS15	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	116,79 mg/m3	0,057
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,058
PROC4, CS95	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	93,43 mg/m3	0,046
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,055
PROC9, CS3, CS8, CS22	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,124
PROC15, CS36	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,023
PROC5, CS96, CS30	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118
PROC10, CS98	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	5,486 mg/kg/d	0,007

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			term – systemic		
			Worker – long-term – systemic Combined routes		0,122
PROC14, CS100	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	0,686 mg/kg/d	0,001
			Worker – long-term – systemic Combined routes		0,116
PROC7, CS97	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	58,39 mg/m3	0,029
			Worker – dermal, long-term – systemic	2,143 mg/kg/d	0,003
			Worker – long-term – systemic Combined routes		0,031
PROC7, CS34, CS10	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	350,37 mg/m3	0,172
			Worker – dermal, long-term – systemic	4,286 mg/kg/d	0,006
			Worker – long-term – systemic Combined routes		0,178
PROC8a, CS3	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118
PROC8b, CS3	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,124
PROC13, CS4	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118

PROC1: Use in closed process, no likelihood of exposure

CS15: General exposures (closed systems)

PROC2: Use in closed, continuous process with occasional controlled exposure

CS15: General exposures (closed systems)

CS56: with sample collection

CS38: Use in contained systems

PROC2: Use in closed, continuous process with occasional controlled exposure

CS94: Film formation - force drying (50 - 100°C). Stoving (>100°C). UV/EB radiation curing

PROC3: Use in closed batch process (synthesis or formulation)

CS29: Mixing operations (closed systems)

CS15: General exposures (closed systems)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

CS95: Film formation - air drying

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

CS3: Material transfers

CS8: Drum/batch transfers

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

CS22: Transfer from/pouring from containers

PROC15: Use as laboratory reagent

CS36: Laboratory activities

PROC5: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting;

CS96: Preparation of material for application

CS30: Mixing operations (open systems)

PROC10: Roller application or brushing

CS98: Roller, spreader, flow application

PROC14: Production of mixtures or articles by tableting, compression, extrusion, pelletization; Industrial setting;

CS100: Production or preparation or articles by tableting, compression, extrusion or pelletization

PROC7: Industrial spraying

CS97: Spraying (automatic/robotic)

PROC7: Industrial spraying

CS34: Manual

CS10: Spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

CS3: Material transfers

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

CS3: Material transfers

PROC13: Treatment of articles by dipping and pouring

CS4: Dipping, immersion and pouring

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Use in coatings – professionalMain User Groups : **SU 22:** Professional uses: Public domain (administration,

SDS Number:100000014260

66/134

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Sector of use	:	education, entertainment, services, craftsmen) SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process category	:	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting; PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities PROC10: Roller application or brushing PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring PROC15: Use as laboratory reagent PROC19: Hand-mixing with intimate contact and only PPE available
Environmental release category	:	ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems
Further information	:	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

2.1 Contributing scenario controlling environmental exposure for:ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

(Msafe) : 1.000

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
Number of emission days per year : 365
Emission or Release Factor: Air : 98 %
Emission or Release Factor: Water : 1 %
Emission or Release Factor: Soil : 1 %

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Technical conditions and measures / Organizational measures

Water	:	Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%): (Effectiveness: 0 %)
Water	:	If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%): (Effectiveness: 0 %)
Remarks	:	No wastewater treatment required.
Remarks	:	Common practices vary across sites thus conservative process release estimates used.
Remarks	:	Risk from environmental exposure is driven by freshwater.
Air	:	Treat air emission to provide a typical removal efficiency of (%):
Remarks	:	Not applicable

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant	:	Municipal sewage treatment plant
Flow rate of sewage treatment plant effluent	:	2.000 m3/d
Effectiveness (of a measure)	:	96,3 %
Percentage removed from waste water	:	96,3 %
Sludge Treatment	:	No data available
Procedures to limit air emissions from Sewage Treatment Plant	:	No data available

Conditions and measures related to external treatment of waste for disposal

Remarks	:	External treatment and disposal of waste should comply with applicable local and/or national regulations.
---------	---	---

Conditions and measures related to external recovery of waste

Recovery Methods	:	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------	---	---

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure**Product characteristics**

Physical Form (at time of use)	:	Liquid substance
Vapor pressure	:	2,8 kPa

Amount used

Remarks	:	No limit
---------	---	----------

Frequency and duration of use

Remarks	:	Covers daily exposures up to 8 hours (unless stated differently)
---------	---	--

Other operational conditions affecting workers exposure

Remarks	:	Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.
---------	---	--

Technical conditions and measures

Handle substance within a closed system.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC3, PROC8b, PROC15: Use in closed batch process (synthesis or formulation), Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent

Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

2.2 Contributing scenario controlling worker exposure for: PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Ensure operation is undertaken outdoors.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent /

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

minimise exposures and to report any skin problems that may develop., No specific measures identified.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC5: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting;**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Provide enhanced general ventilation by mechanical means., Ensure operation is undertaken outdoors.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Technical conditions and measures

Provide enhanced general ventilation by mechanical means.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC10: Roller application or brushing**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Provide enhanced general ventilation by mechanical means., Ensure operation is undertaken outdoors.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

2.2 Contributing scenario controlling worker exposure for: PROC11: Non industrial spraying**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Carry out in a vented booth or extracted enclosure., Ensure operation is undertaken outdoors.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., Avoid carrying out operation for more than 1 hour., Limit the substance content in the product to 25%

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training., Wear chemically resistant gloves (tested to EN374) in combination with specific activity training., Wear a respirator conforming to EN140 with Type A filter or better.

2.2 Contributing scenario controlling worker exposure for: PROC13: Treatment of articles by dipping and pouring**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Provide extraction ventilation at points where emissions occur., Ensure operation is undertaken outdoors.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., Avoid manual contact with wet work pieces.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC19: Hand-mixing with intimate contact and only PPE available

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Product characteristics

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Ensure operation is undertaken outdoors., Ensure doors and windows are opened

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., Avoid carrying out operation for more than 4 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls., Wear a respirator conforming to EN140 with Type A filter or better.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC8a, ERC8d	Hydrocarbon Block Method with Petrorisk		Air		0,000074 mg/m3	
			Fresh water		10 ng/L	0,00027
			Freshwater sediment		220 ng/kg	0,00015
			Marine water		0,51 ng/L	0,000013
			Marine sediment		22 ng/kg	0,000015
			Agricultural soil		93 ng/kg	0,00016

ERC8a: Wide dispersive indoor use of processing aids in open systems

ERC8d: Wide dispersive outdoor use of processing aids in open systems

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC1, CS15	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	0,05 mg/m3	0,000
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term –		0,000

SDS Number:100000014260

73/134

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			systemic Combined routes		
PROC2, CS15, CS38, CS45	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	93,43 mg/m3	0,046
			Worker – long-term – systemic Combined routes	1,37 mg/kg/d	0,002
			Worker – inhalation, long-term – systemic		0,048
PROC3, CS96	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	116,79 mg/m3	0,057
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,058
PROC8b, CS3, CS8	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,124
PROC15, CS36	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,023
PROC4, CS95	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	163,51 mg/m3	0,080
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,082
PROC4, CS95	ECETOC TRA Modified	Indoor	Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,124
PROC5, CS96	ECETOC TRA Modified	Indoor	Worker – inhalation, long-term – systemic	140,15 mg/m3	0,069
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,072
PROC5, CS96	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	327,01 mg/m3	0,161
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,164
PROC8a, CS3, CS8	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	140,15 mg/m3	0,069
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,072
PROC10, CS98	ECETOC TRA Modified	Indoor	Worker – inhalation, long-term – systemic	140,15 mg/m3	0,069
			Worker – dermal, long-term – systemic	2,743 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,072

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

PROC10, CS98	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	327,01 mg/m3	0,161
			Worker – dermal, long-term – systemic	2,743 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,164
PROC11, CS10, CS34	ECETOC TRA Modified	Indoor	Worker – inhalation, long-term – systemic	280,29 mg/m3	0,138
			Worker – dermal, long-term – systemic	1,2859 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,139
PROC11, CS10, CS34	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	196,21 mg/m3	0,096
			Worker – dermal, long-term – systemic	6,4284 mg/kg/d	0,008
			Worker – long-term – systemic Combined routes		0,105
PROC11, CS10, CS34	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	163,51 mg/m3	0,080
			Worker – dermal, long-term – systemic	5,357 mg/kg/d	0,007
			Worker – inhalation, long-term – systemic		0,087
PROC13, CS4	ECETOC TRA Modified	Indoor	Worker – inhalation, long-term – systemic	93,43 mg/m3	0,046
			Worker – dermal, long-term – systemic	0,6855 mg/kg/d	0,001
			Worker – long-term – systemic Combined routes		0,047
PROC13, CS4	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	327,01 mg/m3	0,161
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,164
PROC19, CS72	ECETOC TRA Modified	Indoor	Worker – inhalation, long-term – systemic	140,15 mg/m3	0,069
			Worker – dermal, long-term – systemic	2,8286 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,073
PROC19, CS72	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	196,21 mg/m3	0,096
			Worker – dermal, long-term – systemic	2,8286 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,100
PROC19, CS72	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	32,70 mg/m3	0,016
			Worker – dermal, long-term – systemic	2,8286 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,020

PROC1: Use in closed process, no likelihood of exposure

CS15: General exposures (closed systems)

PROC2: Use in closed, continuous process with occasional controlled exposure

CS15: General exposures (closed systems)

CS38: Use in contained systems

CS45: Filling/ preparation of equipment from drums or containers.

PROC3: Use in closed batch process (synthesis or formulation)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

CS96: Preparation of material for application

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

CS3: Material transfers

CS8: Drum/batch transfers

PROC15: Use as laboratory reagent

CS36: Laboratory activities

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

CS95: Film formation - air drying

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

CS95: Film formation - air drying

PROC5: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting;

CS96: Preparation of material for application

PROC5: Mixing or blending in batch processes for formulation of mixtures and articles (multistage and/or significant contact) Industrial setting;

CS96: Preparation of material for application

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

CS3: Material transfers

CS8: Drum/batch transfers

PROC10: Roller application or brushing

CS98: Roller, spreader, flow application

PROC10: Roller application or brushing

CS98: Roller, spreader, flow application

PROC11: Non industrial spraying

CS10: Spraying

CS34: Manual

PROC11: Non industrial spraying

CS10: Spraying

CS34: Manual

PROC11: Non industrial spraying

CS10: Spraying

CS34: Manual

PROC13: Treatment of articles by dipping and pouring

CS4: Dipping, immersion and pouring

PROC13: Treatment of articles by dipping and pouring

CS4: Dipping, immersion and pouring

PROC19: Hand-mixing with intimate contact and only PPE available

CS72: Hand application - finger-paints, pastels, adhesives

PROC19: Hand-mixing with intimate contact and only PPE available

CS72: Hand application - finger-paints, pastels, adhesives

PROC19: Hand-mixing with intimate contact and only PPE available

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

CS72: Hand application - finger-paints, pastels, adhesives

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Use as a cleaning agent – industrial

Main User Groups	:	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	:	SU3: Industrial Manufacturing (all)
Process category	:	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC7: Industrial spraying PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring
Environmental release category	:	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles
Further information	:	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

2.1 Contributing scenario controlling environmental exposure for: ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Maximum allowable site tonnage : 6.800 tonnes/day
(MSafe) based on release
following total wastewater
treatment removal (tonnes/day):
(Msafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
Number of emission days per year : 20
Emission or Release Factor: Air : 100 %
Emission or Release Factor: Soil : 0 %
Remarks : Emission or Release Factor: Water : < 0.001 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide a typical removal efficiency of (%) (Effectiveness: 70 %)
Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%) (Effectiveness: 0 %)
Water : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%) (Effectiveness: 0 %)
Remarks : Common practices vary across sites thus conservative process release estimates used.
Remarks : Prevent discharge of undissolved substance to or recover from onsite wastewater.
Remarks : Risk from environmental exposure is driven by freshwater.
Remarks : No wastewater treatment required.

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
Flow rate of sewage treatment plant effluent : 2.000 m3/d
Effectiveness (of a measure) : 96,3 %
Percentage removed from waste water : 96,3 %

Conditions and measures related to external treatment of waste for disposal

Remarks : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC2, PROC3: Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation)**Product characteristics**

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

2.2 Contributing scenario controlling worker exposure for: PROC4, PROC13: Use in batch and other process (synthesis) where opportunity for exposure arises, Treatment of articles by dipping and pouring
Product characteristics

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Provide extraction ventilation at points where emissions occur.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

2.2 Contributing scenario controlling worker exposure for: PROC7: Industrial spraying
Product characteristics

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures

Provide enhanced general ventilation by mechanical means.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., Avoid carrying out operation for more than 4 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training., Wear a respirator conforming to EN140 with Type A filter or better.

2.2 Contributing scenario controlling worker exposure for: PROC8a, PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
Product characteristics

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC10: Roller application or

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

brushing**Product characteristics**

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes a good basic standard of occupational hygiene is implemented., Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC4	Hydrocarbon Block Method with Petrorisk		Air		4,6 µg/m3	
			Fresh water		5,7 ng/L	0,00015
			Freshwater sediment		99 ng/kg	0,00007
			Marine water		0,000056 µg/L	< 0,000015
			Marine sediment		2,4 ng/kg	< 0,000017
			Agricultural soil		42 ng/kg	< 0,000091

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC2, CS93, CS38	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	46,72 mg/m3	0,023
			Worker – dermal, long-term – systemic	1,37 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,025
PROC3, CS8, CS93, CS101	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	116,79 mg/m3	0,057
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			term – systemic		
			Worker – long-term – systemic Combined routes		0,058
PROC4, CS37	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	9,34 mg/m3	0,005
			Worker – dermal, long-term – systemic	0,686 mg/kg/d	0,001
			Worker – long-term – systemic Combined routes		0,005
PROC13, CS41	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	23,86 mg/m3	0,011
			Worker – dermal, long-term – systemic	0,6855 mg/kg/d	0,001
			Worker – long-term – systemic Combined routes		0,0012
PROC7, CS44	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	210,22 mg/m3	0,103
			Worker – dermal, long-term – systemic	4,286 mg/kg/d	0,006
			Worker – long-term – systemic Combined routes		0,109
PROC7, CS44	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	35,04 mg/m3	0,017
			Worker – dermal, long-term – systemic	4,286 mg/kg/d	0,006
			Worker – long-term – systemic Combined routes		0,023
PROC8b, CS14	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118
PROC8b, CS45	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,117
PROC10, CS34, CS42, CS48, CS47	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	2,743 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,118

PROC2: Use in closed, continuous process with occasional controlled exposure

CS93: Automated process with (semi) closed systems.

CS38: Use in contained systems

PROC3: Use in closed batch process (synthesis or formulation)

CS8: Drum/batch transfers

CS93: Automated process with (semi) closed systems.

CS101: Application of cleaning products in closed systems

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

CS37: Use in contained batch processes

PROC13: Treatment of articles by dipping and pouring

CS41: Degreasing small objects in cleaning station

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

PROC7: Industrial spraying
CS44: Cleaning with high pressure washers

PROC7: Industrial spraying
CS44: Cleaning with high pressure washers

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
CS14: Bulk transfers

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
CS45: Filling/ preparation of equipment from drums or containers.

PROC10: Roller application or brushing
CS34: Manual
CS42: Cleaning with low-pressure washers
CS48: Surfaces
CS47: Cleaning

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Risk Management Measures are based on qualitative risk characterisation.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Use as a cleaning agent – professional

Main User Groups	:	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Sector of use	:	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process category	:	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

facilities
PROC10: Roller application or brushing
PROC11: Non industrial spraying
PROC13: Treatment of articles by dipping and pouring

Environmental release category : **ERC8a, ERC8d:** Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

Further information :
 Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).

2.1 Contributing scenario controlling environmental exposure for:ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems

Maximum allowable site tonnage : 210
 (MSafe) based on release
 following total wastewater
 treatment removal (kg/d):(MSafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
 Dilution Factor (River) : 10
 Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
 Number of emission days per year : 365
 Emission or Release Factor: Air : 2 %
 Emission or Release Factor: Soil : 0 %
 Remarks : Emission or Release Factor: Water : < 0.001 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide a typical removal efficiency of (%):
 Remarks : Not applicable
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of \geq (%):
 (Effectiveness: 0 %)
 Water : If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of \geq (%):
 (Effectiveness: 0 %)
 Remarks : Common practices vary across sites thus conservative process release estimates used.

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
 Flow rate of sewage treatment plant effluent : 2.000 m3/d
 Effectiveness (of a measure) : 96,3 %
 Percentage removed from waste : 96,3 %

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

water
 Sludge Treatment : No data available
 Procedures to limit air emissions : No data available
 from Sewage Treatment Plant

Conditions and measures related to external treatment of waste for disposal

Remarks : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC2, PROC3: Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation)
Product characteristics

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., No specific measures identified.

2.2 Contributing scenario controlling worker exposure for: PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
Product characteristics

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Technical conditions and measures

Provide enhanced general ventilation by mechanical means., Ensure operation is undertaken outdoors.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Ensure operation is undertaken outdoors.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC10: Roller application or brushing**Product characteristics**

Physical Form (at time of use) : Liquid substance
Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Ensure doors and windows are opened, Provide enhanced general ventilation by mechanical means., Provide extraction ventilation at points where emissions occur.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., Limit the substance content in the product to 25%

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

2.2 Contributing scenario controlling worker exposure for: PROC11: Non industrial spraying**Product characteristics**

Physical Form (at time of use) : Liquid substance

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Provide enhanced general ventilation by mechanical means., Ensure operation is undertaken outdoors.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop., Limit the substance content in the product to 1%, Limit the substance content in the product to 5%

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

2.2 Contributing scenario controlling worker exposure for: PROC13: Treatment of articles by dipping and pouring**Product characteristics**

Physical Form (at time of use) : Liquid substance
 Vapor pressure : 2,8 kPa

Amount used

Remarks : No limit

Frequency and duration of use

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting workers exposure

Remarks : Assumes use at not more than 20°C above ambient temperature, unless stated differently., Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures

Provide enhanced general ventilation by mechanical means.

Organizational measures to prevent /limit releases, dispersion and exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC8a, ERC8d	Hydrocarbon Block Method with Petrorisk		Air		74 ng/m3	
			Fresh water		5,1 ng/L	0,00013
			Fresh water sediment		75 ng/kg	0,000053
			Marine water		0,017 ng/L	< 0,000033
			Marine sediment		0,16 ng/kg	< 0,000012
			Agricultural soil		1,2 ng/kg	< 0,000034

ERC8a: Wide dispersive indoor use of processing aids in open systems

ERC8d: Wide dispersive outdoor use of processing aids in open systems

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PROC2, CS93, CS38	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	93,43 mg/m3	0,046
			Worker – dermal, long-term – systemic	1,37 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,048
PROC3, CS8, CS38, CS93	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	116,79 mg/m3	0,057
			Worker – dermal, long-term – systemic	0,34 mg/kg/d	0,000
			Worker – long-term – systemic Combined routes		0,058
PROC4, CS76	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	70,07 mg/m3	0,034
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,036
PROC4, CS101	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	163,51 mg/m3	0,080
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,082
PROC4, CS74	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	6,86 mg/kg/d	0,009
			Worker – long-term – systemic Combined routes		0,124
PROC8a, CS45	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	327,01 mg/m3	0,161
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,164

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

PROC8b, CS45	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	233,58 mg/m3	0,115
			Worker – dermal, long-term – systemic	1,372 mg/kg/d	0,002
			Worker – long-term – systemic Combined routes		0,117
PROC10, CS42, CS51, CS60	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	140,15 mg/m3	0,069
			Worker – dermal, long-term – systemic	5,486 mg/kg/d	0,007
			Worker – long-term – systemic Combined routes		0,076
PROC10, CS10, CS34, CS47, CS48	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	140,15 mg/m3	0,069
			Worker – dermal, long-term – systemic	2,743 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,072
PROC10, CS27, CS51	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	56,06 mg/m3	0,028
			Worker – dermal, long-term – systemic	0,8229 mg/kg/d	0,001
			Worker – long-term – systemic Combined routes		0,142
PROC10, CS27, CS51	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	280,29 mg/m3	0,138
			Worker – dermal, long-term – systemic	3,2916 mg/kg/d	0,004
			Worker – inhalation, long-term – systemic		0,142
PROC11, CS44, CS10	ECETOC TRA Modified	Indoor	Worker – inhalation, long-term – systemic	140,15 mg/m3	0,069
			Worker – dermal, long-term – systemic	4,2856 mg/kg/d	0,006
			Worker – long-term – systemic Combined routes		0,074
PROC11, CS44, CS10	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	163,51 mg/m3	0,080
			Worker – dermal, long-term – systemic	2,1428 mg/kg/d	0,003
			Worker – long-term – systemic Combined routes		0,083
PROC11, CS10, CS44	ECETOC TRA Modified	Outdoor	Worker – inhalation, long-term – systemic	327,01 mg/m3	0,161
			Worker – dermal, long-term – systemic	4,2856 mg/kg/d	0,006
			Worker – long-term – systemic Combined routes		0,166
PROC13, CS4, CS34, CS47, CS48	ECETOC TRA Modified		Worker – inhalation, long-term – systemic	140,15 mg/m3	0,069
			Worker – dermal, long-term – systemic	2,742 mg/kg/d	0,004
			Worker – long-term – systemic Combined routes		0,072

PROC2: Use in closed, continuous process with occasional controlled exposure

CS93: Automated process with (semi) closed systems.

CS38: Use in contained systems

PROC3: Use in closed batch process (synthesis or formulation)

CS8: Drum/batch transfers

CS38: Use in contained systems

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

CS93: Automated process with (semi) closed systems.

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

CS76: Semi Automated process. (e.g.: Semi automatic application of floor care and maintenance products)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

CS101: Application of cleaning products in closed systems

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

CS74: Cleaning of medical devices

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

CS45: Filling/ preparation of equipment from drums or containers.

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

CS45: Filling/ preparation of equipment from drums or containers.

PROC10: Roller application or brushing

CS42: Cleaning with low-pressure washers

CS51: Rolling, Brushing

CS60: no spraying

PROC10: Roller application or brushing

CS10: Spraying

CS34: Manual

CS47: Cleaning

CS48: Surfaces

PROC10: Roller application or brushing

CS27: Ad hoc manual application via trigger sprays, dipping, etc.

CS51: Rolling, Brushing

PROC10: Roller application or brushing

CS27: Ad hoc manual application via trigger sprays, dipping, etc.

CS51: Rolling, Brushing

PROC11: Non industrial spraying

CS44: Cleaning with high pressure washers

CS10: Spraying

PROC11: Non industrial spraying

CS44: Cleaning with high pressure washers

CS10: Spraying

PROC11: Non industrial spraying

CS10: Spraying

CS44: Cleaning with high pressure washers

PROC13: Treatment of articles by dipping and pouring

CS4: Dipping, immersion and pouring

CS34: Manual

CS47: Cleaning

CS48: Surfaces

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
 Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
 Risk Management Measures are based on qualitative risk characterisation.
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Use as a cleaning agent – consumer

Main User Groups	: SU 21: Consumer uses: Private households (= general public = consumers)
Sector of use	: SU 21: Consumer uses: Private households (= general public = consumers)
Product category	: PC3: Air care products PC4: Anti-Freeze and de-icing products PC8: Biocidal products (e.g. Disinfectants, pest control) PC9a: Coatings and paints, thinners, paint removers PC9b: Fillers, putties, plasters, modelling clay PC9c: Finger paints PC24: Lubricants, greases, release products PC35: Washing and cleaning products (including solvent based products) PC38: Welding and soldering products (with flux coatings or flux cores.), flux products
Environmental release category	: ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems
Further information	: Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

2.1 Contributing scenario controlling environmental exposure for:ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems**Product characteristics**

Maximum allowable site tonnage : 160
 (MSafe) based on release

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

following total wastewater
treatment removal (kg/d): (Msafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
Number of emission days per year : 365
Emission or Release Factor: Air : 95 %
Emission or Release Factor: Water : 2,5 %
Emission or Release Factor: Soil : 2,5 %

Technical conditions and measures / Organizational measures

Remarks : Not applicable

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
Flow rate of sewage treatment : 2.000 m3/d
plant effluent
Percentage removed from waste : 96,3 %
water
Sludge Treatment : No data available
Procedures to limit air emissions : No data available
from Sewage Treatment Plant

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling consumer exposure for: PC3, PC4, PC8, PC9, PC24, PC35, PC38: Air care products, Anti-Freeze and de-icing products, Biocidal products (e.g. Disinfectants, pest control), Coatings and Paints, Fillers, Putties, Thinners, Lubricants, greases, release products, Washing and cleaning products (including solvent based products), Welding and soldering products (with flux coatings or flux cores.), flux products

Product characteristics

Physical Form (at time of use) : Liquid substance

Amount used

: 13800 g

Frequency and duration of use

Exposure duration : 8 h
Frequency of use : 4 times/day

Human factors not influenced by risk management

Exposed skin area : Skin
: 857,5 cm2

Other given operational conditions affecting consumers exposure

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Room size : 20 M3
 Remarks : Unless otherwise stated assumes use at ambient temperatures, Assumes use with typical ventilation.

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

2.2 Contributing scenario controlling consumer exposure for: PC3: Air care products**Product characteristics**

Concentration of the Substance in Mixture/Article :
 Remarks : Air care, instant action (aerosol sprays)

Concentration of the Substance in Mixture/Article :
 Remarks : Air care, continuous action (solid and liquid)

Amount used

Remarks : 0,1 g
 : Air care, instant action (aerosol sprays)

Remarks : 0,48 g
 : Air care, continuous action (solid and liquid)

Frequency and duration of use

Exposure duration : 0,25 h
 Frequency of use : 4 times/day
 Remarks : Air care, instant action (aerosol sprays)

Exposure duration : 8 h
 Frequency of use : 1 times/day
 Remarks : Air care, continuous action (solid and liquid)

Human factors not influenced by risk management

Exposed skin area : Skin
 : 35,70 cm2
 Remarks : Air care, continuous action (solid and liquid)

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Air care, instant action (aerosol sprays)

Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Air care, instant action (aerosol sprays)

Use frequency : 365 days/year
 Remarks : Air care, instant action (aerosol sprays)

Use frequency : 365 days/year
 Remarks : Air care, continuous action (solid and liquid)

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

2.2 Contributing scenario controlling consumer exposure for: PC4: Anti-Freeze and de-icing products**Product characteristics**

Concentration of the Substance in Mixture/Article :
 Remarks Washing car window

Concentration of the Substance in Mixture/Article :
 Remarks Pouring into radiator

Concentration of the Substance in Mixture/Article :
 Remarks Lock de- icer

Amount used

Remarks : 0,5 g
 : Washing car window

Remarks : 2000 g
 : Pouring into radiator

Remarks : 4 g
 : Lock de- icer

Frequency and duration of use

Exposure duration : 0,02 h
 Frequency of use : 1 times/day
 Remarks : Washing car window

Exposure duration : 0,17 h
 Frequency of use : 1 times/day
 Remarks : Pouring into radiator

Exposure duration : 0,25 h
 Frequency of use : 1 times/day
 Remarks : Lock de- icer

Human factors not influenced by risk management

Exposed skin area : Skin
 : 428,00 cm2

Remarks : Pouring into radiator

Exposed skin area : Skin
 : 214,40 cm2

Remarks : Lock de- icer

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Garage
 Room size : 34 M3
 Ventilation rate per hour : 1,5
 Remarks : Washing car window

Outdoor / Indoor : Garage
 Room size : 34 M3
 Ventilation rate per hour : 1,5
 Remarks : Pouring into radiator

Outdoor / Indoor : Garage
 Room size : 34 M3

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Ventilation rate per hour : 1,5
 Remarks : Lock de- icer

Use frequency : 365 days/year
 Remarks : Washing car window

Use frequency : 365 days/year
 Remarks : Pouring into radiator

Use frequency : 365 days/year
 Remarks : Lock de- icer

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

2.2 Contributing scenario controlling consumer exposure for: PC8: Biocidal products (e.g. Disinfectants, pest control)**Product characteristics**

Concentration of the Substance in Mixture/Article :
 Remarks : Laundry and dish washing products

Concentration of the Substance in Mixture/Article :
 Remarks : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Concentration of the Substance in Mixture/Article :
 Remarks : Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Amount used

Remarks : 15 g
 : Laundry and dish washing products

Remarks : 27 g
 : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Remarks : 35 g
 : Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Frequency and duration of use

Exposure duration : 0,50 h
 Frequency of use : 1 times/day
 Remarks : Laundry and dish washing products

Exposure duration : 0,33 h
 Frequency of use : 1 times/day
 Remarks : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Exposure duration : 0,17 h
 Frequency of use : 1 times/day
 Remarks : Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Human factors not influenced by risk management

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Exposed skin area	:	Skin
	:	857,50 cm2
Remarks	:	Laundry and dish washing products
Exposed skin area	:	Skin
	:	857,50 cm2
Remarks	:	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)
Exposed skin area	:	Skin
	:	428,00 cm2
Remarks	:	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Other given operational conditions affecting consumers exposure

Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Laundry and dish washing products
Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)
Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)
Use frequency	:	365 days/year
Remarks	:	Laundry and dish washing products
Use frequency	:	128 days/year
Remarks	:	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)
Use frequency	:	128 days/year
Remarks	:	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks	:	No specific Risk Management Measures identified beyond those Operational Conditions stated.
---------	---	---

2.2 Contributing scenario controlling consumer exposure for: PC9a: Coatings and paints, thinners, paint removers**Product characteristics**

Concentration of the Substance in Mixture/Article	:	
Remarks	:	Waterborne latex wall paint
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Solvent rich, high solid, water borne paint
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Aerosol spray can

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Concentration of the Substance in :
 Mixture/Article
 Remarks Removers (paint-, glue-, wall paper-, sealant-remover)

Amount used

Remarks : 2760 g
 : Waterborne latex wall paint
 : 744 g
 Remarks : Solvent rich, high solid, water borne paint
 : 215 g
 Remarks : Aerosol spray can
 : 491 g
 Remarks : Removers (paint-, glue-, wall paper-, sealant-remover)

Frequency and duration of use

Exposure duration : 2,20 h
 Frequency of use : 1 times/day
 Remarks : Waterborne latex wall paint
 Exposure duration : 2,20 h
 Frequency of use : 1 times/day
 Remarks : Solvent rich, high solid, water borne paint
 Exposure duration : 0,33 h
 Frequency of use : 1 times/day
 Remarks : Aerosol spray can
 Exposure duration : 2,00 h
 Frequency of use : 1 times/day
 Remarks : Removers (paint-, glue-, wall paper-, sealant-remover)

Human factors not influenced by risk management

Exposed skin area : Skin
 : 428,75 cm2
 Remarks : Waterborne latex wall paint
 Exposed skin area : Skin
 : 428,75 cm2
 Remarks : Solvent rich, high solid, water borne paint
 Exposed skin area : Skin
 : 857,50 cm2
 Remarks : Removers (paint-, glue-, wall paper-, sealant-remover)

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Waterborne latex wall paint
 Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Solvent rich, high solid, water borne paint
 Outdoor / Indoor : Garage
 Room size : 34 M3
 Ventilation rate per hour : 1,5
 Remarks : Aerosol spray can
 Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Removers (paint-, glue-, wall paper-, sealant-remover)
 Use frequency : 4 days/year
 Remarks : Waterborne latex wall paint

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Use frequency	:	6 days/year
Remarks	:	Solvent rich, high solid, water borne paint
Use frequency	:	2 days/year
Remarks	:	Aerosol spray can
Use frequency	:	3 days/year
Remarks	:	Removers (paint-, glue-, wall paper-, sealant-remover)

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks	:	No specific Risk Management Measures identified beyond those Operational Conditions stated.
---------	---	---

2.2 Contributing scenario controlling consumer exposure for: PC9b, PC9c: Fillers, putties, plasters, modelling clay, Finger paints**Product characteristics**

Concentration of the Substance in Mixture/Article	:	
Remarks	:	Fillers and putty
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Plasters and floor equalizers
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Modeling Clay
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Finger paints

Amount used

Remarks	:	85 g
Remarks	:	Fillers and putty
Remarks	:	13800 g
Remarks	:	Plasters and floor equalizers
Remarks	:	1 g
Remarks	:	Modeling Clay
Remarks	:	1,35 g
Remarks	:	Finger paints

Frequency and duration of use

Exposure duration	:	4,00 h
Frequency of use	:	1 times/day
Remarks	:	Fillers and putty
Exposure duration	:	2,00 h
Frequency of use	:	1 times/day
Remarks	:	Plasters and floor equalizers

Human factors not influenced by risk management

Exposed skin area	:	Skin
Remarks	:	35,73 cm2
Exposed skin area	:	Fillers and putty
Remarks	:	Skin
Exposed skin area	:	857,50 cm2
Remarks	:	Plasters and floor equalizers

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Exposed skin area : Skin
 : 254,40 cm²
 Remarks : Modeling Clay
 Exposed skin area : Skin
 : 254,40 cm²
 Remarks : Finger paints

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Indoor activities
 Room size : 20 M³
 Ventilation rate per hour : 0,6
 Remarks : Fillers and putty
 Outdoor / Indoor : Indoor activities
 Room size : 20 M³
 Ventilation rate per hour : 0,6
 Remarks : Plasters and floor equalizers

Use frequency : 12 days/year
 Remarks : Fillers and putty
 Use frequency : 12 days/year
 Remarks : Plasters and floor equalizers
 Use frequency : 365 days/year
 Remarks : Modeling Clay
 Use frequency : 365 days/year
 Remarks : Finger paints

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

2.2 Contributing scenario controlling consumer exposure for: PC24: Lubricants, greases, release products**Product characteristics**

Concentration of the Substance in :
 Mixture/Article
 Remarks : Liquid
 Concentration of the Substance in :
 Mixture/Article
 Remarks : Paste
 Concentration of the Substance in :
 Mixture/Article
 Remarks : Sprays

Amount used

: 2200 g
 Remarks : Liquid
 : 34 g
 Remarks : Paste
 : 73 g
 Remarks : Sprays

Frequency and duration of use

Exposure duration : 0,17 h

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Frequency of use	: 1 times/day
Remarks	: Liquid
Frequency of use	: 1 times/day
Remarks	: Paste
Exposure duration	: 0,17 h
Frequency of use	: 1 times/day
Remarks	: Sprays

Human factors not influenced by risk management

Exposed skin area	: Skin
	: 468 cm ²
Remarks	: Liquid
Exposed skin area	: Skin
	: 468 cm ²
Remarks	: Paste
Exposed skin area	: Skin
	: 428,75 cm ²
Remarks	: Sprays

Other given operational conditions affecting consumers exposure

Outdoor / Indoor	: Indoor activities
Room size	: 34 M ³
Ventilation rate per hour	: 0,6
Remarks	: Liquid
Outdoor / Indoor	: Indoor activities
Room size	: 20 M ³
Ventilation rate per hour	: 0,6
Remarks	: Sprays

Use frequency	: 4 days/year
Remarks	: Liquid
Use frequency	: 10 days/year
Remarks	: Paste
Use frequency	: 6 days/year
Remarks	: Sprays

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks	: No specific Risk Management Measures identified beyond those Operational Conditions stated.
---------	---

2.2 Contributing scenario controlling consumer exposure for: PC35, PC38: Washing and cleaning products (including solvent based products), Welding and soldering products (with flux coatings or flux cores.), flux products**Product characteristics**

Concentration of the Substance in Mixture/Article	:
Remarks	Laundry and dish washing products
Concentration of the Substance in Mixture/Article	:
Remarks	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)
Concentration of the Substance in Mixture/Article	:
Remarks	Cleaners, trigger sprays (all purpose cleaners, sanitary

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

products, glass cleaners)

Concentration of the Substance in :
Mixture/Article

Remarks

Welding and soldering products (with flux coatings or flux cores.), flux products

Amount used

Remarks : 15 g

: Laundry and dish washing products

Remarks : 27 g

: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Remarks : 35 g

: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Remarks : 12 g

: Welding and soldering products (with flux coatings or flux cores.), flux products

Frequency and duration of use

Exposure duration : 0,50 h

Frequency of use : 1 times/day

Remarks : Laundry and dish washing products

Exposure duration : 0,33 h

Frequency of use : 1 times/day

Remarks : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Exposure duration : 0,17 h

Frequency of use : 1 times/day

Remarks : Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Exposure duration : 1 h

Frequency of use : 1 times/day

Remarks : Welding and soldering products (with flux coatings or flux cores.), flux products

Human factors not influenced by risk management

Exposed skin area : Skin

: 857,50 cm2

Remarks : Laundry and dish washing products

Exposed skin area : Skin

: 857,50 cm2

Remarks : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Exposed skin area : Skin

: 428,00 cm2

Remarks : Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Indoor activities

Room size : 20 M3

Ventilation rate per hour : 0,6

Remarks : Laundry and dish washing products

Outdoor / Indoor : Indoor activities

Room size : 20 M3

Ventilation rate per hour : 0,6

Remarks : Cleaners, liquids (all purpose cleaners, sanitary products, floor

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Outdoor / Indoor	:	cleaners, glass cleaners, carpet cleaners, metal cleaners)
Room size	:	Indoor activities
Ventilation rate per hour	:	20 M3
Remarks	:	0,6
Outdoor / Indoor	:	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)
Room size	:	Indoor activities
Ventilation rate per hour	:	20 M3
Remarks	:	0,6
Use frequency	:	Welding and soldering products (with flux coatings or flux cores.), flux products
Remarks	:	365 days/year
Use frequency	:	Laundry and dish washing products
Remarks	:	128 days/year
Use frequency	:	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)
Remarks	:	128 days/year
Use frequency	:	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)
Remarks	:	365 days/year
Use frequency	:	Washing and cleaning products (including solvent based products)
Remarks	:	

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks	:	No specific Risk Management Measures identified beyond those Operational Conditions stated.
---------	---	---

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC8a, ERC8d	Hydrocarbon Block Method with Petrorisk		Air		0,000074 mg/m3	
			Freshwater		0,0000064 mg/L	0,00017
			Freshwater sediment		0,00013 mg/kg	0,000091
			Marine water		0,0000001 mg/L	0,000003
			Marine sediment		0,0000055 mg/kg	0,000004
			Agricultural soil		0,000023 mg/kg	0,00004

ERC8a: Wide dispersive indoor use of processing aids in open systems

ERC8d: Wide dispersive outdoor use of processing aids in open systems

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PC3, PC3_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – oral, long-	0,00 mg/kg/d	0,00

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			term – systemic		
			Consumer – inhalation, long-term – systemic	0,10 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC3, PC3_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,02 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC4, PC4_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,00 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC4, PC4_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	7,13 mg/kg/d	0,01
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,18 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,01
PC4, PC4_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	17,87 mg/kg/d	0,03
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,51 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,03
PC8, PC8_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,07 mg/kg/d	0,00
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,07 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC8, PC8_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	7,15 mg/kg/d	0,01
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,08 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,01
PC8, PC8_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	10,70 mg/kg/d	0,02
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term –	1,77 mg/m3	0,00

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			systemic		
			Consumer – long-term – systemic Combined routes		0,02
PC9a, PC9a_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	1,07 mg/kg/d	0,00
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	10,53 mg/m3	0,02
			Consumer – long-term – systemic Combined routes		0,02
PC9a, PC9a_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	19,65 mg/kg/d	0,03
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	52,06 mg/m3	0,09
			Consumer – long-term – systemic Combined routes		0,11
PC9a, PC9a_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	34,29 mg/m3	0,06
			Consumer – long-term – systemic Combined routes		0,06
PC9a, PC9a_4	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	71,46 mg/kg/d	0,10
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	59,57 mg/m3	0,10
			Consumer – long-term – systemic Combined routes		0,20
PC9b, PC9b_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,12 mg/kg/d	0,00
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,54 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC9b, PC9b_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	2,86 mg/kg/d	0,00
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	66,97 mg/m3	0,11
			Consumer – long-term – systemic Combined routes		0,11
PC9b, PC9b_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	2,54 mg/kg/d	0,00
			Consumer – oral, long- term – systemic	1,00 mg/kg/d	0,00
			Consumer – long-term – systemic Combined routes		0,01
PC9c	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	127,20 mg/kg/d	0,18

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			Consumer – oral, long-term – systemic	67,50 mg/kg/d	0,10
			Consumer – long-term – systemic Combined routes		0,28
PC24, PC24_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	78,00 mg/kg/d	0,11
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,40 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,11
PC24, PC24_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	15,60 mg/kg/d	0,02
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – long-term – systemic Combined routes		0,02
PC24, PC24_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	35,73 mg/kg/d	0,05
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	12,29 mg/m3	0,02
			Consumer – long-term – systemic Combined routes		0,07
PC35, PC35_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,07 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,07 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC35, PC35_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	7,15 mg/kg/d	0,01
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,08 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,01
PC35, PC35_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	10,70 mg/kg/d	0,02
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	1,77 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,02
PC38	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,38 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

PC3: Air care products

PC3_1: Air care, instant action (aerosol sprays)

PC3: Air care products

PC3_2: Air care, continuous action (solid and liquid)

PC4: Anti-Freeze and de-icing products

PC4_1: Washing car window

PC4: Anti-Freeze and de-icing products

PC4_2: Pouring into radiator

PC4: Anti-Freeze and de-icing products

PC4_3: Lock de- icer

PC8: Biocidal products (e.g. Disinfectants, pest control)

PC8_1: Laundry and dish washing products

PC8: Biocidal products (e.g. Disinfectants, pest control)

PC8_2: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

PC8: Biocidal products (e.g. Disinfectants, pest control)

PC8_3: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

PC9a: Coatings and paints, thinners, paint removers

PC9a_1: Waterborne latex wall paint

PC9a: Coatings and paints, thinners, paint removers

PC9a_2: Solvent rich, high solid, water borne paint

PC9a: Coatings and paints, thinners, paint removers

PC9a_3: Aerosol spray can

PC9a: Coatings and paints, thinners, paint removers

PC9a_4: Removers (paint-, glue-, wall paper-, sealant-remover)

PC9b: Fillers, putties, plasters, modelling clay

PC9b_1: Fillers and putty

PC9b: Fillers, putties, plasters, modelling clay

PC9b_2: Plasters and floor equalizers

PC9b: Fillers, putties, plasters, modelling clay

PC9b_3: Modeling Clay

PC9c: Finger paints

PC24: Lubricants, greases, release products

PC24_1: Liquid

PC24: Lubricants, greases, release products

PC24_2: Paste

PC24: Lubricants, greases, release products

PC24_3: Sprays

PC35: Washing and cleaning products (including solvent based products)

PC35_1: Laundry and dish washing products

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

PC35: Washing and cleaning products (including solvent based products)
 PC35_2: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

PC35: Washing and cleaning products (including solvent based products)
 PC35_3: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

PC38: Welding and soldering products (with flux coatings or flux cores.), flux products

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
 Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
 Risk Management Measures are based on qualitative risk characterisation.
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Use in Coatings - Consumer

Main User Groups	: SU 21: Consumer uses: Private households (= general public = consumers)
Sector of use	: SU 21: Consumer uses: Private households (= general public = consumers)
Product category	: PC1: Adhesives, sealants PC4: Anti-Freeze and de-icing products PC8: Biocidal products (e.g. Disinfectants, pest control) PC9a: Coatings and paints, thinners, paint removers PC9b: Fillers, putties, plasters, modelling clay PC9c: Finger paints PC15: Non-metal-surface treatment products PC18: Ink and toners PC23: Leather tanning, dye, finishing, impregnation and care products PC24: Lubricants, greases, release products PC31: Polishes and wax blends PC34: Textile dyes, finishing and impregnating products; including bleaches and other processing aids
Environmental release category	: ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems
Further information	: Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d: Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems**Product characteristics**

Maximum allowable site tonnage : 1.000
(MSafe) based on release
following total wastewater
treatment removal (kg/d): (Msafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
Number of emission days per year : 365
Emission or Release Factor: Air : 99 %
Emission or Release Factor: Water : 1 %
Emission or Release Factor: Soil : 6 %

Technical conditions and measures / Organizational measures

Remarks : Not applicable

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
Flow rate of sewage treatment : 2.000 m3/d
plant effluent
Percentage removed from waste : 96,3 %
water
Sludge Treatment : No data available
Procedures to limit air emissions : No data available
from Sewage Treatment Plant

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling consumer exposure for: PC1, PC4, PC8, PC9a, PC9b, PC15, PC9c, PC18, PC23, PC24, PC31, PC34: Adhesives, sealants, Anti-Freeze and de-icing products, Biocidal products (e.g. Disinfectants, pest control), Coatings and paints, thinners, paint removers, Fillers, putties, plasters, modelling clay, Non-metal-surface treatment products, Finger paints, Ink and toners, Leather tanning, dye, finishing, impregnation and care products, Lubricants, greases, release products, Polishes and wax blends, Textile dyes, finishing and impregnating products; including bleaches and other processing aids**Product characteristics**

Physical Form (at time of use) : Liquid substance

Amount used

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

: 13800 g

Frequency and duration of use

Exposure duration : 6 h
 Frequency of use : 1 times/day

Human factors not influenced by risk management

Exposed skin area : Skin
 : 857,5 cm²

Other given operational conditions affecting consumers exposure

Room size : 20 M³
 Remarks : Unless otherwise stated assumes use at ambient temperatures, Assumes use with typical ventilation.

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

2.2 Contributing scenario controlling consumer exposure for: PC1: Adhesives, sealants**Product characteristics**

Concentration of the Substance in Mixture/Article :
 Remarks : Glues, hobby use

Concentration of the Substance in Mixture/Article :
 Remarks : Glues DIY -use (carpet glue, tile glue, wood parquet glue)

Concentration of the Substance in Mixture/Article :
 Remarks : Glue from spray

Concentration of the Substance in Mixture/Article :
 Remarks : Sealants

Amount used

Remarks : 9 g
 : Glues, hobby use
 : 6390 g

Remarks : Glues DIY -use (carpet glue, tile glue, wood parquet glue)
 : 85,05 g

Remarks : Glue from spray
 : 75 g

Remarks : Sealants

Frequency and duration of use

Exposure duration : 4,00 h
 Frequency of use : 1 times/day
 Remarks : Glues, hobby use

Exposure duration : 6,00 h
 Frequency of use : 1 times/day
 Remarks : Glues DIY -use (carpet glue, tile glue, wood parquet glue)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Exposure duration : 4,00 h
 Frequency of use : 1 times/day
 Remarks : Glue from spray
 Exposure duration : 1,00 h
 Frequency of use : 1 times/day
 Remarks : Sealants

Human factors not influenced by risk management

Exposed skin area : Skin
 : 35,73 cm2
 Remarks : Glues, hobby use
 Exposed skin area : Skin
 : 110,00 cm2
 Remarks : Glues DIY -use (carpet glue, tile glue, wood parquet glue)
 Exposed skin area : Skin
 : 35,73 cm2
 Remarks : Glue from spray
 Exposed skin area : Skin
 : 35,73 cm2
 Remarks : Sealants

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Glues, hobby use
 Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Glues DIY -use (carpet glue, tile glue, wood parquet glue)
 Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Glue from spray
 Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Sealants
 Use frequency : 365 days/year
 Remarks : Glues, hobby use
 Use frequency : 1 days/year
 Remarks : Glues DIY -use (carpet glue, tile glue, wood parquet glue)
 Use frequency : 6 days/year
 Remarks : Glue from spray
 Use frequency : 365 days/year
 Remarks : Sealants

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

2.2 Contributing scenario controlling consumer exposure for: PC4: Anti-Freeze and de-icing products**Product characteristics**

Concentration of the Substance in :

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Mixture/Article
Remarks Washing car window

Concentration of the Substance in :
Mixture/Article
Remarks Pouring into radiator

Concentration of the Substance in :
Mixture/Article
Remarks Lock de- icer

Amount used

Remarks : 0,5 g
: Washing car window
Remarks : 2000 g
: Pouring into radiator
Remarks : 4 g
: Lock de- icer

Frequency and duration of use

Exposure duration : 0,02 h
Frequency of use : 1 times/day
Remarks : Washing car window
Exposure duration : 0,17 h
Frequency of use : 1 times/day
Remarks : Pouring into radiator
Exposure duration : 0,25 h
Frequency of use : 1 times/day
Remarks : Lock de- icer

Human factors not influenced by risk management

Exposed skin area : Skin
: 428,00 cm2
Remarks : Pouring into radiator
Exposed skin area : Skin
: 214,40 cm2
Remarks : Lock de- icer

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Garage
Room size : 34 M3
Ventilation rate per hour : 1,5
Remarks : Washing car window
Outdoor / Indoor : Garage
Room size : 34 M3
Ventilation rate per hour : 1,5
Remarks : Pouring into radiator
Outdoor / Indoor : Garage
Room size : 34 M3
Ventilation rate per hour : 1,5
Remarks : Lock de- icer

Use frequency : 365 days/year
Remarks : Washing car window
Use frequency : 365 days/year
Remarks : Pouring into radiator
Use frequency : 365 days/year
Remarks : Lock de- icer

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

2.2 Contributing scenario controlling consumer exposure for: PC8: Biocidal products (e.g. Disinfectants, pest control)**Product characteristics**

Concentration of the Substance in Mixture/Article :

Remarks Laundry and dish washing products

Concentration of the Substance in Mixture/Article :

Remarks Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Concentration of the Substance in Mixture/Article :

Remarks Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Amount used

Remarks : 15 g

Remarks : Laundry and dish washing products

Remarks : 27 g

Remarks : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Remarks : 35 g

Remarks : Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Frequency and duration of use

Exposure duration : 0,50 h

Frequency of use : 1 times/day

Remarks : Laundry and dish washing products

Exposure duration : 0,33 h

Frequency of use : 1 times/day

Remarks : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Exposure duration : 0,17 h

Frequency of use : 1 times/day

Remarks : Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Human factors not influenced by risk management

Exposed skin area : Skin

: 857,50 cm²

Remarks : Laundry and dish washing products

Exposed skin area : Skin

: 857,50 cm²

Remarks : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Exposed skin area : Skin

: 428,00 cm²

Remarks : Cleaners, trigger sprays (all purpose cleaners, sanitary

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

products, glass cleaners)

Other given operational conditions affecting consumers exposure

Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Laundry and dish washing products
Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)
Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)
Use frequency	:	365 days/year
Remarks	:	Laundry and dish washing products
Use frequency	:	128 days/year
Remarks	:	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)
Use frequency	:	128 days/year
Remarks	:	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks	:	No specific Risk Management Measures identified beyond those Operational Conditions stated.
---------	---	---

2.2 Contributing scenario controlling consumer exposure for: PC9a: Coatings and paints, thinners, paint removers**Product characteristics**

Concentration of the Substance in Mixture/Article	:	
Remarks	:	Waterborne latex wall paint
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Solvent rich, high solid, water borne paint
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Aerosol spray can
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Removers (paint-, glue-, wall paper-, sealant-remover)

Amount used

Remarks	:	2760 g
Remarks	:	Waterborne latex wall paint
Remarks	:	744 g
Remarks	:	Solvent rich, high solid, water borne paint

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Remarks : 215 g
 : Aerosol spray can
 : 491 g
 Remarks : Removers (paint-, glue-, wall paper-, sealant-remover)

Frequency and duration of use

Exposure duration : 2,20 h
 Frequency of use : 1 times/day
 Remarks : Waterborne latex wall paint
 Exposure duration : 2,20 h
 Frequency of use : 1 times/day
 Remarks : Solvent rich, high solid, water borne paint
 Exposure duration : 0,33 h
 Frequency of use : 1 times/day
 Remarks : Aerosol spray can
 Exposure duration : 2,00 h
 Frequency of use : 1 times/day
 Remarks : Removers (paint-, glue-, wall paper-, sealant-remover)

Human factors not influenced by risk management

Exposed skin area : Skin
 : 428,75 cm2
 Remarks : Waterborne latex wall paint
 Exposed skin area : Skin
 : 428,75 cm2
 Remarks : Solvent rich, high solid, water borne paint
 Exposed skin area : Skin
 : 857,50 cm2
 Remarks : Aerosol spray can

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Waterborne latex wall paint
 Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Solvent rich, high solid, water borne paint
 Outdoor / Indoor : Garage
 Room size : 34 M3
 Ventilation rate per hour : 1,5
 Remarks : Aerosol spray can
 Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Removers (paint-, glue-, wall paper-, sealant-remover)
 Use frequency : 4 days/year
 Remarks : Waterborne latex wall paint
 Use frequency : 6 days/year
 Remarks : Solvent rich, high solid, water borne paint
 Use frequency : 2 days/year
 Remarks : Aerosol spray can
 Use frequency : 3 days/year
 Remarks : Removers (paint-, glue-, wall paper-, sealant-remover)

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

those Operational Conditions stated.

2.2 Contributing scenario controlling consumer exposure for: PC9b, PC9c: Fillers, putties, plasters, modelling clay, Finger paints**Product characteristics**

Concentration of the Substance in Mixture/Article	:	
Remarks	:	Fillers and putty
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Plasters and floor equalizers
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Modeling Clay
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Finger paints

Amount used

Remarks	:	85 g
Remarks	:	Fillers and putty
Remarks	:	13800 g
Remarks	:	Plasters and floor equalizers
Remarks	:	1 g
Remarks	:	Modeling Clay
Remarks	:	1,35 g
Remarks	:	Finger paints

Frequency and duration of use

Exposure duration	:	4,00 h
Frequency of use	:	1 times/day
Remarks	:	Fillers and putty
Exposure duration	:	2,00 h
Frequency of use	:	1 times/day
Remarks	:	Plasters and floor equalizers
Frequency of use	:	1 times/day
Remarks	:	Modeling Clay
Frequency of use	:	1 times/day
Remarks	:	Finger paints

Human factors not influenced by risk management

Exposed skin area	:	Skin
Remarks	:	35,73 cm2
Exposed skin area	:	Fillers and putty
Exposed skin area	:	Skin
Remarks	:	857,50 cm2
Exposed skin area	:	Plasters and floor equalizers
Exposed skin area	:	Skin
Remarks	:	254,40 cm2
Exposed skin area	:	Modeling Clay
Exposed skin area	:	Skin
Remarks	:	254,40 cm2
Remarks	:	Finger paints

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Other given operational conditions affecting consumers exposure

Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Fillers and putty
Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Plasters and floor equalizers
Use frequency	:	12 days/year
Remarks	:	Fillers and putty
Use frequency	:	12 days/year
Remarks	:	Plasters and floor equalizers
Use frequency	:	365 days/year
Remarks	:	Modeling Clay
Use frequency	:	365 days/year
Remarks	:	Finger paints

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks	:	No specific Risk Management Measures identified beyond those Operational Conditions stated.
---------	---	---

2.2 Contributing scenario controlling consumer exposure for: PC15: Non-metal-surface treatment products**Product characteristics**

Concentration of the Substance in Mixture/Article	:	
Remarks	:	Waterborne latex wall paint
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Solvent rich, high solid, water borne paint
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Aerosol spray can
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Removers (paint-, glue-, wall paper-, sealant-remover)

Amount used

Remarks	:	2760 g
Remarks	:	Waterborne latex wall paint
Remarks	:	744 g
Remarks	:	Solvent rich, high solid, water borne paint
Remarks	:	215 g
Remarks	:	Aerosol spray can
Remarks	:	491 g
Remarks	:	Removers (paint-, glue-, wall paper-, sealant-remover)

Frequency and duration of use

Exposure duration	:	2,20 h
-------------------	---	--------

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Frequency of use	:	1 times/day
Remarks	:	Waterborne latex wall paint
Exposure duration	:	2,20 h
Frequency of use	:	1 times/day
Remarks	:	Solvent rich, high solid, water borne paint
Exposure duration	:	0,33 h
Frequency of use	:	1 times/day
Remarks	:	Aerosol spray can
Exposure duration	:	2,00 h
Frequency of use	:	1 times/day
Remarks	:	Removers (paint-, glue-, wall paper-, sealant-remover)

Human factors not influenced by risk management

Exposed skin area	:	Skin
	:	428,75 cm2
Remarks	:	Waterborne latex wall paint
Exposed skin area	:	Skin
	:	428,75 cm2
Remarks	:	Solvent rich, high solid, water borne paint
Exposed skin area	:	Skin
	:	857,50 cm2
Remarks	:	Removers (paint-, glue-, wall paper-, sealant-remover)

Other given operational conditions affecting consumers exposure

Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Waterborne latex wall paint
Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Solvent rich, high solid, water borne paint
Outdoor / Indoor	:	Garage
Room size	:	34 M3
Ventilation rate per hour	:	1,5
Remarks	:	Aerosol spray can
Outdoor / Indoor	:	Indoor activities
Room size	:	20 M3
Ventilation rate per hour	:	0,6
Remarks	:	Removers (paint-, glue-, wall paper-, sealant-remover)
Use frequency	:	4 days/year
Remarks	:	Waterborne latex wall paint
Use frequency	:	6 days/year
Remarks	:	Solvent rich, high solid, water borne paint
Use frequency	:	2 days/year
Remarks	:	Aerosol spray can
Use frequency	:	3 days/year
Remarks	:	Removers (paint-, glue-, wall paper-, sealant-remover)

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks	:	No specific Risk Management Measures identified beyond those Operational Conditions stated.
---------	---	---

2.2 Contributing scenario controlling consumer exposure for: PC18, PC23: Ink and toners, Leather tanning, dye, finishing, impregnation and care products

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Product characteristics

Concentration of the Substance in Mixture/Article :
 Remarks Ink and toners

Concentration of the Substance in Mixture/Article :
 Remarks Polishes, wax / cream (floor, furniture, shoes)

Concentration of the Substance in Mixture/Article :
 Remarks Polishes, spray (furniture, shoes)

Amount used

Remarks : 40 g
 : Ink and toners

Remarks : 56 g
 : Polishes, wax / cream (floor, furniture, shoes)

Remarks : 56 g
 : Polishes, spray (furniture, shoes)

Frequency and duration of use

Exposure duration : 2,20 h
 Frequency of use : 1 times/day
 Remarks : Ink and toners

Exposure duration : 1,23 h
 Frequency of use : 1 times/day
 Remarks : Polishes, wax / cream (floor, furniture, shoes)

Exposure duration : 0,33 h
 Frequency of use : 1 times/day
 Remarks : Polishes, spray (furniture, shoes)

Human factors not influenced by risk management

Exposed skin area : Skin
 : 71,40 cm2
 Remarks : Ink and toners

Exposed skin area : Skin
 : 430,00 cm2
 Remarks : Polishes, wax / cream (floor, furniture, shoes)

Exposed skin area : Skin
 : 430,00 cm2
 Remarks : Polishes, spray (furniture, shoes)

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Ink and toners

Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Polishes, wax / cream (floor, furniture, shoes)

Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Polishes, spray (furniture, shoes)

Use frequency : 365 days/year
 Remarks : Ink and toners

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Use frequency	:	29 days/year
Remarks	:	Polishes, wax / cream (floor, furniture, shoes)
Use frequency	:	8 days/year
Remarks	:	Polishes, spray (furniture, shoes)

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks	:	No specific Risk Management Measures identified beyond those Operational Conditions stated.
---------	---	---

2.2 Contributing scenario controlling consumer exposure for: PC24: Lubricants, greases, release products**Product characteristics**

Concentration of the Substance in Mixture/Article	:	
Remarks	:	Liquid
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Paste
Concentration of the Substance in Mixture/Article	:	
Remarks	:	Sprays

Amount used

Remarks	:	2200 g
Remarks	:	Liquid
Remarks	:	34 g
Remarks	:	Paste
Remarks	:	73 g
Remarks	:	Sprays

Frequency and duration of use

Exposure duration	:	0,17 h
Frequency of use	:	1 times/day
Remarks	:	Liquid
Frequency of use	:	1 times/day
Remarks	:	Paste
Exposure duration	:	0,17 h
Frequency of use	:	1 times/day
Remarks	:	Sprays

Human factors not influenced by risk management

Exposed skin area	:	Skin
Remarks	:	468,00 cm2
Exposed skin area	:	Liquid
Remarks	:	Skin
Exposed skin area	:	468,00 cm2
Remarks	:	Paste
Exposed skin area	:	Skin
Remarks	:	428,75 cm2
Remarks	:	Sprays

Other given operational conditions affecting consumers exposure

Outdoor / Indoor	:	Garage
------------------	---	--------

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Room size : 34 M3
 Ventilation rate per hour : 1,5
 Remarks : Liquid
 Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Sprays

Use frequency : 4 days/year
 Remarks : Liquid
 Use frequency : 10 days/year
 Remarks : Paste
 Use frequency : 6 days/year
 Remarks : Sprays

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

2.2 Contributing scenario controlling consumer exposure for: PC31, PC34: Polishes and wax blends, Textile dyes, finishing and impregnating products; including bleaches and other processing aids**Product characteristics**

Concentration of the Substance in Mixture/Article :
 Remarks : Polishes, wax / cream (floor, furniture, shoes)

Concentration of the Substance in Mixture/Article :
 Remarks : Polishes, spray (furniture, shoes)

Concentration of the Substance in Mixture/Article :
 Remarks : Textile dyes, finishing and impregnating products; including bleaches and other processing aids

Amount used

Remarks : 142 g
 : Polishes, wax / cream (floor, furniture, shoes)

Remarks : 35 g
 : Polishes, spray (furniture, shoes)

Remarks : 115 g
 : Textile dyes, finishing and impregnating products; including bleaches and other processing aids

Frequency and duration of use

Exposure duration : 1,23 h
 Frequency of use : 1 times/day
 Remarks : Polishes, wax / cream (floor, furniture, shoes)

Exposure duration : 0,33 h
 Frequency of use : 1 times/day
 Remarks : Polishes, spray (furniture, shoes)

Exposure duration : 1,00 h
 Frequency of use : 1 times/day
 Remarks : Textile dyes, finishing and impregnating products; including

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

bleaches and other processing aids

Human factors not influenced by risk management

Exposed skin area : Skin
: 430,00 cm²

Remarks : Polishes, wax / cream (floor, furniture, shoes)

Exposed skin area : Skin
: 430,00 cm²

Remarks : Polishes, spray (furniture, shoes)

Exposed skin area : Skin
: 857,50 cm²

Remarks : Textile dyes, finishing and impregnating products; including bleaches and other processing aids

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Indoor activities
Room size : 20 M³
Ventilation rate per hour : 0,6
Remarks : Polishes, wax / cream (floor, furniture, shoes)

Outdoor / Indoor : Indoor activities
Room size : 20 M³
Ventilation rate per hour : 0,6
Remarks : Polishes, spray (furniture, shoes)

Outdoor / Indoor : Indoor activities
Room size : 20 M³
Ventilation rate per hour : 0,6
Remarks : Textile dyes, finishing and impregnating products; including bleaches and other processing aids

Use frequency : 29 days/year
Remarks : Polishes, wax / cream (floor, furniture, shoes)

Use frequency : 8 days/year
Remarks : Polishes, spray (furniture, shoes)

Use frequency : 365 days/year
Remarks : Textile dyes, finishing and impregnating products; including bleaches and other processing aids

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC8a, ERC8d	Hydrocarbon Block Method with Petrorisk		Air		0,000074 mg/m ³	
			Freshwater		0,00001 mg/L	0,00027
			Freshwater sediment		0,00022 mg/kg	0,00015
			Marine water		0,0000005 mg/L	0,000013
			Marine sediment		0,000022 mg/kg	0,000015
			Agricultural soil		0,000093	0,00016

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

					mg/kg	
--	--	--	--	--	-------	--

ERC8a: Wide dispersive indoor use of processing aids in open systems
 ERC8d: Wide dispersive outdoor use of processing aids in open systems

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PC1, PC1_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	1,79 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,85 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC1, PC1_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,01 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	1,75 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC1, PC1_3	ECETOC TRA Modified		Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – dermal, long-term – systemic	1,79 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	80,56 mg/m3	0,13
			Consumer – long-term – systemic Combined routes		0,14
PC1, PC1_4	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	1,79 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	3,52 mg/m3	0,01
			Consumer – long-term – systemic Combined routes		0,01
PC4, PC4_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,00 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC4, PC4_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	7,13 mg/kg/d	0,01
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,18 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,01
PC4, PC4_3	ECETOC TRA		Consumer – dermal,	17,87 mg/kg/d	0,03

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

	Modified		long-term – systemic		
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,51 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,03
PC8, PC8_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,07 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,07 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC8, PC8_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	7,15 mg/kg/d	0,01
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,08 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,01
PC8, PC8_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	10,70 mg/kg/d	0,02
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	1,77 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,02
PC9a, PC9a_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	1,07 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	10,53 mg/m3	0,02
			Consumer – long-term – systemic Combined routes		0,02
PC9a, PC9a_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	19,65 mg/kg/d	0,03
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	52,06 mg/m3	0,09
			Consumer – long-term – systemic Combined routes		0,11
PC9a, PC9a_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	34,29 mg/m3	0,06
			Consumer – long-term – systemic Combined routes		0,06
PC9a, PC9a_4	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	71,46 mg/kg/d	0,10
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			Consumer – inhalation, long-term – systemic	59,57 mg/m3	0,10
			Consumer – long-term – systemic Combined routes		0,20
PC9b, PC9b_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,12 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,54 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC9b, PC9b_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	2,86 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	66,97 mg/m3	0,11
			Consumer – long-term – systemic Combined routes		0,11
PC9b, PC9b_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	2,54 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	1,00 mg/kg/d	0,00
			Consumer – long-term – systemic Combined routes		0,01
PC9c	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	127,20 mg/kg/d	0,18
			Consumer – oral, long-term – systemic	67,50 mg/kg/d	0,10
			Consumer – long-term – systemic Combined routes		0,28
PC15, PC15_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	1,07 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	10,53 mg/m3	0,02
			Consumer – long-term – systemic Combined routes		0,02
PC15, PC15_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	19,65 mg/kg/d	0,03
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	52,06 mg/m3	0,09
			Consumer – long-term – systemic Combined routes		0,11
PC15, PC15_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	34,29 mg/m3	0,06
			Consumer – long-term – systemic Combined routes		0,06
PC15, PC15_4	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	71,46 mg/kg/d	0,10
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			term – systemic		
			Consumer – inhalation, long-term – systemic	59,57 mg/m3	0,10
			Consumer – long-term – systemic Combined routes		0,20
PC18	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	1,19 mg/kg/d	0,00
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	1,02 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC23, PC23_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	35,83 mg/kg/d	0,05
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	5,07 mg/m3	0,01
			Consumer – long-term – systemic Combined routes		0,06
PC23, PC23_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	35,83 mg/kg/d	0,05
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	17,46 mg/m3	0,03
			Consumer – long-term – systemic Combined routes		0,08
PC24, PC24_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	78,00 mg/kg/d	0,11
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,40 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,11
PC24, PC24_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	15,60 mg/kg/d	0,02
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – long-term – systemic Combined routes		0,02
PC24, PC24_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	35,73 mg/kg/d	0,05
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	12,29 mg/m3	0,02
			Consumer – long-term – systemic Combined routes		0,07
PC31, PC31_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	35,83 mg/kg/d	0,05
			Consumer – oral, long- term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	12,87 mg/m3	0,02
			Consumer – long-term – systemic Combined		0,07

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			routes		
PC31, PC31_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	35,83 mg/kg/d	0,05
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	10,92 mg/m3	0,02
			Consumer – long-term – systemic Combined routes		0,07
PC34	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,14 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	1,80 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00

PC1: Adhesives, sealants

PC1_1: Glues, hobby use

PC1: Adhesives, sealants

PC1_2: Glues DIY -use (carpet glue, tile glue, wood parquet glue)

PC1: Adhesives, sealants

PC1_3: Glue from spray

PC1: Adhesives, sealants

PC1_4: Sealants

PC4: Anti-Freeze and de-icing products

PC4_1: Washing car window

PC4: Anti-Freeze and de-icing products

PC4_2: Pouring into radiator

PC4: Anti-Freeze and de-icing products

PC4_3: Lock de- icer

PC8: Biocidal products (e.g. Disinfectants, pest control)

PC8_1: Laundry and dish washing products

PC8: Biocidal products (e.g. Disinfectants, pest control)

PC8_2: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

PC8: Biocidal products (e.g. Disinfectants, pest control)

PC8_3: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

PC9a: Coatings and paints, thinners, paint removers

PC9a_1: Waterborne latex wall paint

PC9a: Coatings and paints, thinners, paint removers

PC9a_2: Solvent rich, high solid, water borne paint

PC9a: Coatings and paints, thinners, paint removers

PC9a_3: Aerosol spray can

PC9a: Coatings and paints, thinners, paint removers

PC9a_4: Removers (paint-, glue-, wall paper-, sealant-remover)

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

PC9b: Fillers, putties, plasters, modelling clay
PC9b_1: Fillers and putty

PC9b: Fillers, putties, plasters, modelling clay
PC9b_2: Plasters and floor equalizers

PC9b: Fillers, putties, plasters, modelling clay
PC9b_3: Modeling Clay

PC9c: Finger paints

PC15: Non-metal-surface treatment products
PC15_1: Waterborne latex wall paint

PC15: Non-metal-surface treatment products
PC15_2: Solvent rich, high solid, water borne paint

PC15: Non-metal-surface treatment products
PC15_3: Aerosol spray can

PC15: Non-metal-surface treatment products
PC15_4: Removers (paint-, glue-, wall paper-, sealant-remover)

PC18: Ink and toners

PC23: Leather tanning, dye, finishing, impregnation and care products
PC23_1: Polishes, wax / cream (floor, furniture, shoes)

PC23: Leather tanning, dye, finishing, impregnation and care products
PC23_2: Polishes, spray (furniture, shoes)

PC24: Lubricants, greases, release products
PC24_1: Liquid

PC24: Lubricants, greases, release products
PC24_2: Paste

PC24: Lubricants, greases, release products
PC24_3: Sprays

PC31: Polishes and wax blends
PC31_1: Polishes, wax / cream (floor, furniture, shoes)

PC31: Polishes and wax blends
PC31_2: Polishes, spray (furniture, shoes)

PC34: Textile dyes, finishing and impregnating products; including bleaches and other processing aids

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
 Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
 Risk Management Measures are based on qualitative risk characterisation.
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

1. Short title of Exposure Scenario: Use as a fuel – consumer

Main User Groups	: SU 21: Consumer uses: Private households (= general public = consumers)
Sector of use	: SU 21: Consumer uses: Private households (= general public = consumers)
Product category	: PC13: Fuels
Environmental release category	: ERC8b, ERC8e, ERC9a, ERC9b: Wide dispersive indoor use of reactive substances in open systems, Wide dispersive outdoor use of reactive substances in open systems, Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems
Further information	: Covers consumer uses in liquid fuels.

2.1 Contributing scenario controlling environmental exposure for: ERC8b, ERC8e, ERC9a, ERC9b: Wide dispersive indoor use of reactive substances in open systems, Wide dispersive outdoor use of reactive substances in open systems, Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

Product characteristics

Maximum allowable site tonnage : 240.000
 (MSafe) based on release
 following total wastewater
 treatment removal (kg/d): (Msafe)

Environment factors not influenced by risk management

Flow rate : 18.000 m3/d
 Dilution Factor (River) : 10
 Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Continuous use/release
 Number of emission days per year : 365
 Emission or Release Factor: Air : 0,1 %
 Emission or Release Factor: Water : 0,001 %
 Emission or Release Factor: Soil : 0,001 %

Technical conditions and measures / Organizational measures

Remarks : Not applicable

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
 Flow rate of sewage treatment plant effluent : 2.000 m3/d
 Percentage removed from waste water : 96,3 %
 Sludge Treatment : No data available
 Procedures to limit air emissions from Sewage Treatment Plant : No data available

Conditions and measures related to external treatment of waste for disposal

Remarks : Combustion emissions limited by required exhaust emission controls.
 Combustion emissions considered in regional exposure assessment.

Conditions and measures related to external recovery of waste

Recovery Methods : This substance is consumed during use and no waste of the substance is generated.

2.2 Contributing scenario controlling consumer exposure for: PC13: Fuels- Liquid**Product characteristics**

Physical Form (at time of use) : Liquid substance

Amount used

: 37500 g

Frequency and duration of use

Exposure duration : 2 h
 Frequency of use : > 1 times/day

Human factors not influenced by risk management

Exposed skin area : Skin
 : 420 cm2

Other given operational conditions affecting consumers exposure

Room size : 20 M3
 Remarks : Unless otherwise stated assumes use at ambient temperatures, Assumes use with typical ventilation.

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

2.1 Contributing scenario controlling environmental exposure for: ERC8b, ERC8e, ERC9a, ERC9b: Wide dispersive indoor use of reactive substances in open systems, Wide dispersive outdoor use of reactive substances in open systems, Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems**Product characteristics**

Concentration of the Substance in Mixture/Article :
 Remarks Automotive Refuelling

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Concentration of the Substance in Mixture/Article	:	
Remarks		Scooter Refuelling
Concentration of the Substance in Mixture/Article	:	
Remarks		Garden Equipment- Use
Concentration of the Substance in Mixture/Article	:	
Remarks		Garden Equipment- Refueling
Concentration of the Substance in Mixture/Article	:	
Remarks		Lamp Oil

2.2 Contributing scenario controlling consumer exposure for: PC13: Fuels- Liquid**Product characteristics**

Concentration of the Substance in Mixture/Article	:	
Remarks		Automotive Refuelling
Concentration of the Substance in Mixture/Article	:	
Remarks		Scooter Refuelling
Concentration of the Substance in Mixture/Article	:	
Remarks		Garden Equipment- Use
Concentration of the Substance in Mixture/Article	:	
Remarks		Garden Equipment- Refueling
Concentration of the Substance in Mixture/Article	:	
Remarks		Lamp Oil

Amount used

Remarks	:	37500 g
Remarks	:	Automotive Refuelling
Remarks	:	3750 g
Remarks	:	Scooter Refuelling
Remarks	:	750 g
Remarks	:	Garden Equipment- Use
Remarks	:	750 g
Remarks	:	Garden Equipment- Refueling
Remarks	:	100 g

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Remarks : Lamp Oil

Frequency and duration of use

Exposure duration : 0,05 h
 Frequency of use : 1 times/day
 Remarks : Automotive Refuelling
 Exposure duration : 0,03 h
 Frequency of use : 1 times/day
 Remarks : Scooter Refuelling
 Exposure duration : 2,00 h
 Frequency of use : 1 times/day
 Remarks : Garden Equipment- Use
 Exposure duration : 0,03 h
 Frequency of use : 1 times/day
 Remarks : Garden Equipment- Refueling
 Exposure duration : 0,01 h
 Frequency of use : 1 times/day
 Remarks : Lamp Oil

Human factors not influenced by risk management

Exposed skin area : Skin
 : 210,00 cm2
 Remarks : Automotive Refuelling
 Exposed skin area : Skin
 : 210,00 cm2
 Remarks : Scooter Refuelling
 Exposed skin area : Skin
 : 420,00 cm2
 Remarks : Garden Equipment- Refueling
 Exposed skin area : Skin
 : 210,00 cm2
 Remarks : Lamp Oil

Other given operational conditions affecting consumers exposure

Outdoor / Indoor : Outdoor Activities
 Room size : 100 M3
 Ventilation rate per hour : 0,6
 Remarks : Automotive Refuelling
 Outdoor / Indoor : Outdoor Activities
 Room size : 100 M3
 Ventilation rate per hour : 0,6
 Remarks : Scooter Refuelling
 Outdoor / Indoor : Outdoor Activities
 Room size : 100 M3
 Ventilation rate per hour : 0,6
 Remarks : Garden Equipment- Use
 Outdoor / Indoor : Garage
 Room size : 34 M3
 Ventilation rate per hour : 1,5
 Remarks : Garden Equipment- Refueling
 Outdoor / Indoor : Indoor activities
 Room size : 20 M3
 Ventilation rate per hour : 0,6
 Remarks : Lamp Oil

Use frequency : 52 days/year
 Remarks : Automotive Refuelling
 Use frequency : 52 days/year
 Remarks : Scooter Refuelling
 Use frequency : 26 days/year

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

Remarks : Garden Equipment- Use
 Use frequency : 26 days/year
 Remarks : Garden Equipment- Refueling
 Use frequency : 52 days/year
 Remarks : Lamp Oil

Conditions and measures related to protection of consumer (e.g. behavioral advice, personal protection and hygiene)

Remarks : No specific Risk Management Measures identified beyond those Operational Conditions stated.

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio
ERC8b, ERC8e, ERC9a, ERC9b	Hydrocarbon Block Method with Petrorisk		Air		0,000074 mg/m3	
			Freshwater		0,0000058 mg/L	0,00015
			Freshwater sediment		0,0001 mg/kg	0,000073
			Marine water		0,000066 µg/L	0,000002
			Marine sediment		0,0000028 mg/kg	0,000002
			Agricultural soil		0,000012 mg/kg	0,000021

ERC8b: Wide dispersive indoor use of reactive substances in open systems
 ERC8e: Wide dispersive outdoor use of reactive substances in open systems
 ERC9a: Wide dispersive indoor use of substances in closed systems
 ERC9b: Wide dispersive outdoor use of substances in closed systems

Workers/Consumers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value type	Level of Exposure	Risk characterization ratio
PC13, PC13_1	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	35,00 mg/kg/d	0,05
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,15 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,05
PC13, PC13_2	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	35,00 mg/kg/d	0,05
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,10 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,05
PC13, PC13_3	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00

PRF Octane No. Blends (60, 80-99)

Version 1.11

Revision Date 2017-02-13

			Consumer – inhalation, long-term – systemic	0,73 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,00
PC13, PC13_4	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	70,00 mg/kg/d	0,10
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,08 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,10
PC13, PC13_5	ECETOC TRA Modified		Consumer – dermal, long-term – systemic	35,00 mg/kg/d	0,05
			Consumer – oral, long-term – systemic	0,00 mg/kg/d	0,00
			Consumer – inhalation, long-term – systemic	0,01 mg/m3	0,00
			Consumer – long-term – systemic Combined routes		0,05

PC13: Fuels- Liquid
PC13_1: Automotive Refuelling

PC13: Fuels- Liquid
PC13_2: Scooter Refuelling

PC13: Fuels- Liquid
PC13_3: Garden Equipment- Use

PC13: Fuels
PC13_4: Garden Equipment- Refueling

PC13: Fuels
PC13_5: Lamp Oil

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.

Risk Management Measures are based on qualitative risk characterisation.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).