

**Diacel® WBS-200, Powder**

Version 1.8

Revision Date 2016-06-02

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Diacel® WBS-200, Powder
Material : 1078407

EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
2-Acrylamido-2-Methylpropane Sulfonic Acid, Sodium Salt	5165-97-9 225-948-4	Chevron Phillips Chemicals International NV 01-2119495270-39-0016

Company : Chevron Phillips Chemical Company LP
Drilling Specialties Company LLC
10001 Six Pines Drive
The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
Airport Plaza (Stockholm Building)
Leonardo Da Vincilaan 19
1831 Diegem
Belgium

SDS Requests: (800) 852-5530
Technical Information: (832) 813-4862
Responsible Party: Product Safety Group
Email:sds@cpchem.com

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification
Classification of the substance or mixture
REGULATION (EC) No 1272/2008

Carcinogenicity, Category 1A

H350:

May cause cancer.

Specific target organ systemic toxicity -
repeated exposure, Category 1

H372:

Causes damage to organs through prolonged or
repeated exposure if inhaled.**Label elements****Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H350
H372

May cause cancer.

Causes damage to organs through
prolonged or repeated exposure if inhaled.Precautionary Statements : **Prevention:**

P201

Obtain special instructions before use.

P202

Do not handle until all safety precautions
have been read and understood.

P260

Do not breathe
dust/fume/gas/mist/vapor/spray.

P264

Wash skin thoroughly after handling.

P281

Use personal protective equipment as
required.**Response:**

P308 + P313

IF exposed or concerned: Get medical
advice/ attention.

Hazardous ingredients which must be listed on the label:

- 14808-60-7 Crystalline Silica

Additional Labeling:

Restricted to professional users.

SECTION 3: Composition/information on ingredients

Synonyms : Cement Spacer Viscosifier

Molecular formula : Mixture

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

Mixtures**Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
Sulfomethylated Quebracho	68201-64-9 269-229-3	Aquatic Chronic 3; H412	5 - 15
Crystalline Silica	14808-60-7 238-878-4	Carc. 1A; H350 STOT RE 1; H372	1 - 11

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

General advice	: Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Wash off with soap and water.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

SECTION 5: Firefighting measures

Flash point	: Not applicable
Autoignition temperature	: No data available
Unsuitable extinguishing media	: High volume water jet.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary.
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire and explosion protection	: Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
Hazardous decomposition products	: Carbon oxides. Sulfur oxides.

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Avoid dust formation. Avoid breathing dust.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of respirable particles. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Storage

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters**

SK

Zložka	Podstata	Hodnota	Kontrolné parametre	Poznámka
Bentonite	SK OEL	NPEL priemerný	6 mg/m3	Tabuľka č. 3, Pre celkovú koncentráciu
	SK OEL	NPEL priemerný	6 mg/m3	Tabuľka č. 3, Pevný aerosol, pre celkovú koncentráciu
Crystalline Silica	SK OEL	TSH	0,1 mg/m3	1A, Merané ako respirabilná frakcia
	SK OEL	NPEL priemerný	0,1 mg/m3	TSH, 4, 3, Tabuľka č. 2, 11, 1, 5, respirabilná frakcia
	SK OEL	NPEL priemerný	0,1 mg/m3	TSH, 4, 3, Tabuľka č. 2, 11, 1, 5, Pevný aerosol, respirabilná frakcia

1 Za fibrogénny sa považuje nerozpustný pevný aerosól, vrátane kvapiek aerosólu, ktorý obsahuje viac ako 1 % fibrogénnej zložky a v pokuse na zvierati vykazuje zreteľnú fibrogénnu reakciu pľúcneho tkaniva. Ak je v aerosóle obsiahnutá fibrogénna zložka, musí sa stanoviť vždy jeho respirabilná frakcia a koncentrácia fibrogénnej zložky. V prípade, že aerosól obsahuje menej než 1 % SiO₂ a neobsahuje azbest, považuje sa za aerosól s prevažne nešpecifickým účinkom

11 Pre pevné aerosóly, ktoré sú zároveň klasifikované ako karcinogény alebo mutagény kategórie 1A a kategórie 1B, sa stanovujú technické smerné hodnoty (TSH). Definíciu TSH upravuje nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénym a mutagénym faktorom pri práci v znení nariadenia vlády Slovenskej republiky č. 301/2007 Z. z. Požiadavky na meranie a hodnotenie azbestu upravuje nariadenie vlády Slovenskej republiky č. 253/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou azbestu pri práci.

1A Kategória 1A - Dokázaný karcinogén pre ľudí

3 Respirabilná frakcia je váhový podiel častíc pevného aerosólu $\leq 5 \mu\text{m}$ odobraného vo vzorke ovzdušia v dýchacej zóne zamestnanca. Spôsob a techniku odberu, stanovenie koncentrácie polietavého prachu v respirabilnej a inhalovateľnej frakcii v pracovnom ovzduší podľa prijatej Johanesburgskej konvencie upravuje STN EN 481. Stratégiu merania, výber vhodného postupu a spracovanie výsledkov upravuje STN EN 482 a STN EN 689.

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

- 4 Fr je obsah fibrogénnej zložky v percentách v respirabilnej frakcii. Fibrogénna zložka - kremeň, kristobalit, tridymit, gama - oxid hlinitý.
- 5 Kremeň, kristobalit, tridymit, gama-oxid hlinitý je 100 % fibrogénnej zložky.
- Tabul'ka č. 2 pevné aerosóly s prevažne fibrogénnym účinkom
- Tabul'ka č. 3 pevné aerosóly s možným fibrogénnym účinkom
- TSH Technické Smerné Hodnoty

SI

Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
Crystalline Silica	SI OEL	MV	0,15 mg/m ³	A, Y, Alveolarna frakcija

A Alveolarna frakcija - del vdihnjene suspendirane snovi, ki doseže alveole

Y Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in BAT vrednosti.

SE

Beståndsdelar	Grundval	Värde	Kontrollparametrar	Anmärkning
Crystalline Silica	SE AFS	NGV	0,1 mg/m ³	2, C, M, Respirabelt
	SE AFS	NGV	0,1 mg/m ³	2, C, M, (respirabelt damm)

- 2 Med respirabelt damm menas den dammfraction som definieras i svensk standard SS-EN 481, Arbetsplatsluft. - Partikelstorleksfraktioner för mätning av luftburna partiklar, Utgåva 1, 1993, punkt 2.11 och som har en provtagningskaraktäristik enligt punkt 5.3. Med inhalerbart damm menas den dammfraction som definieras i svensk standard SS-EN 481, Arbetsplatsluft - Partikelstorleksfraktioner för mätning av luftburna partiklar, Utgåva 1, 1993, punkt 2.3 och som har en provtagningskaraktäristik enligt punkt 5.1. Med respirabelt damm menas den dammfraction som definieras i svensk standard SS-EN 481, Arbetsplatsluft - Partikelstorleksfraktioner för mätning av luftburna partiklar, Utgåva 1, 1993, punkt 2.11 och som har en provtagningskaraktäristik enligt punkt 5.3. Med totaldamm menas de partiklar (aerosoler) som fastnar på ett filter i den provtagare som beskrivs i Metodserien, Provtagning av totaldamm och respirabelt damm, Metod nr 1010, Arbetsbaserad styrelsen, numera Arbetsmiljöverket. Filterdiameteren är normalt 37 mm, men kan även vara 25 mm. Trots sitt namn provtas inte den totala mängden luftburna partiklar med denna metod.

C Ämnet är cancerframkallande.

M Medicinsk kontroll kan krävas för hantering av ämnet. Se vidare föreskrifterna om medicinska kontroller i arbetslivet. För vissa ämnen gäller kraven på medicinsk kontroll endast när ämnet används som hårdplastkomponent. Se föreskrifterna om hårdplaster.

RO

Componente	Bază	Valoare	Parametri de control	Notă
Crystalline Silica	RO OEL	TWA	0,1 mg/m ³	fracțiunea de praf respirabilă

PT

Componentes	Bases	Valor	Parâmetros de controlo	Nota
Crystalline Silica	PT OEL	VLE-MP	0,025 mg/m ³	A2, Fração respirável

A2 Agente carcinogénico suspeito no Homem.

PL

Składniki	Podstawa	Wartość	Parametry dotyczące kontroli	Uwaga
Crystalline Silica	PL NDS	NDS	1 mg/m ³	Frakcja respirabilna, frakcja respirabilna
	PL NDS	NDS	0,3 mg/m ³	Frakcja respirabilna, frakcja respirabilna
	PL NDS	NDS	4 mg/m ³	frakcja wdychalna, (frakcja wdychana)
	PL NDS	NDS	2 mg/m ³	frakcja wdychalna, (frakcja wdychana)

Frakcja respirabilna - frakcja aerozolu wnikaćca do dróg oddechowych, która stwarza zagrożenie dla zdrowia po zdeponowaniu w oszarze wymiany gazowej.

Frakcja wdychalna - frakcja aerozolu wnikaćca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia.

NO

Komponenter	Grunnlag	Verdi	Kontrollparametere	Nota
Crystalline Silica	FOR-2011-12-06-1358	TWA	0,1 mg/m ³	7, K, respirabelt støv
	FOR-2011-12-06-1358	TWA	0,3 mg/m ³	7, K, totalstøv

7 Støv som inneholder α-kvarts, kristobalitt og/eller tridymitt vurderes ut fra summasjonsformel. Samtidig må verdiene for sjenerende støv overholdes.

K Stoffer som skal betraktes som kreftfremkallende

NL

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Crystalline Silica	NL WG	TGG-8 uur	0,075vezels per cm ³	B1, Respirabel
	NL WG	TGG-8 uur	0,075vezels per cm ³	B1, (respirabel stof)

B1 Kankerverwekkende stoffen, vastgesteld op basis van het drempelwaarde-effect

LT

Komponentai	Pagrindas, bazė	Vertė	Kontrolės parametrai	Pastaba
Crystalline Silica	LT OEL	IPRD	0,1 mg/m ³	Alveolinė

HU

Komponensek	Bázis	Érték	Ellenőrzési	Megjegyzés
-------------	-------	-------	-------------	------------

SDS Number:100000014464

5/14

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

			paraméterek	
Crystalline Silica	HU OEL	AK-érték	0,15 mg/m3	respirábilis por
	HU OEL	AK-érték	0,15 mg/m3	respirábilis por

GB

Ingredients	Basis	Value	Control parameters	Note
Crystalline Silica	GB EH40	TWA	0,1 mg/m3	15, 44, 45, 46, 47, 2, Respirable
	GB EH40	TWA	0,1 mg/m3	15, 44, 45, 46, 47, 2, (respirable dust)

- 15 For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust
- 2 Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used
- 44 The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit.
- 45 Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'.
- 46 Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3.
- 47 Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with.

FR

Composants	Base	Valeur	Paramètres de contrôle	Note
Crystalline Silica	FR VLE	VME	0,1 mg/m3	noir, Fraction de poussière alvéolaire

noir Valeurs limites réglementaires contraignantes

FI

Aineosat	Peruste	Arvo	Valvontaa koskevat muuttujat	Huomautus
Crystalline Silica	FI OEL	HTP-arvot 8h	0,2 mg/m3	-, alveolijae
	FI OEL	HTP-arvot 8h	0,05 mg/m3	alveolijae

- Valtioneuvoston päätös räjäytys- ja louhintatyön järjestysohjeista [410/1986]

ES

Componentes	Base	Valor	Parámetros de control	Nota
Crystalline Silica	ES VLA	VLA-ED	0,05 mg/m3	d, n, y, fracción respirable

- d Véase UNE EN 481: Atmósferas en los puestos de trabajo. Definición de las fracciones por el tamaño de las partículas para la medición de aerosoles.
- n En las industrias extractivas véase la Orden ITC 2585/2007, de 30 de agosto (BOE nº 315 de 7 de septiembre de 2007), por la que se aprueba la Instrucción Técnica Complementaria 2.0.02 del Reglamento General de Normas Básicas de Seguridad Minera.
- y Reclasificado, por la International Agency for Research on Cancer (IARC) de grupo 2A (probablemente carcinogénico en humanos) a grupo 1 (carcinogénico en humanos).

EE

Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
Crystalline Silica	EE OEL	Piirnorm	0,1 mg/m3	1, Peentolm
	EE OEL	Piirnorm	0,1 mg/m3	1, Peentolm

- 1 Peentolm koosneb alla 2,5-mikromeetrise läbimõõduga osakestest, mis võivad jõuda koos sissehingatava õhuga kopsu alveoolidesse

DK

Komponenter	Basis	Værdi	Kontrolparametre	Note
Crystalline Silica	DK OEL	GV	0,1 mg/m3	K, (respirabelt støv)
	DK OEL	GV	0,3 mg/m3	Totalt støv

K Betyder, at stoffet er optaget på listen over stoffer, der anses for at være kræftfremkaldende.

CZ

Složky	Základ	Hodnota	Kontrolní parametry	Poznámka
Bentonite	CZ OEL	PEL	6 mg/m3	Celkové prach
Crystalline Silica	CZ OEL	PEL	0,1 mg/m3	Fr, vlákno, respirabilní frakce

Fr Fr = obsah fibrogenní složky v respirabilní frakci v procentech

CH

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Crystalline Silica	CH SUVA	MAK-Wert	0,15 mg/m3	P, Carc.Cat.1, NIOSH, OSHA, HSE, SSc, alveolengängiger Staub

Carc.Cat.1 Krebserzeugende Stoffe Kategorie 1
HSE Health and Safety Executive (Occupational Medicine and Hygiene Laboratory)
NIOSH National Institute for Occupational Safety and Health
OSHA Occupational Safety and Health Administration

SDS Number:100000014464

6/14

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

P Provisorische Festlegung - Die MAK-Werte für diese Substanzen sind aus verschiedenen Gründen noch nicht definitiv festgelegt.
 SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.

BE

Bestandteilen	Basis	Waarde	Controleparameters	Opmerking
Crystalline Silica	BE OEL	TGG 8 hr	0,1 mg/m3	inadembaar
	BE OEL	TGG 8 hr	0,1 mg/m3	(respirabel stof)

AT

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Crystalline Silica	AT OEL	TMW	0,15 mg/m3	Alveolengängige Staubfraktion

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Dusts and Mists / P100. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Protective suit. Safety shoes.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Physical state : Solid

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

Color : Reddish brown

Odor : Mild, earthy

Safety data

Flash point : Not applicable

Lower explosion limit : Not applicable

Upper explosion limit : Not applicable

Oxidizing properties : no

Autoignition temperature : No data available

Molecular formula : Mixture

Molecular weight : Not applicable

pH : No data available

Freezing point : No data available

Pour point : No data available

Boiling point/boiling range : Not applicable

Vapor pressure : No data available

Relative density : 2,2
at 15,6 °C (60,1 °F)

Water solubility : dispersible

Partition coefficient: n-
octanol/water : No data available

Viscosity, kinematic : Not applicable

Relative vapor density : No data available

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Conditions to avoid : No data available.

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

Materials to avoid : Avoid contact with strong oxidizing agents.
 Hazardous decomposition products : Carbon oxides
 Sulfur oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Diacel® WBS-200, Powder**

Acute oral toxicity : Acute toxicity estimate: > 5.000 mg/kg
 Method: Calculation method

Acute toxicity estimate: 23.629,63 mg/kg
 Method: Calculation method

Diacel® WBS-200, Powder

Acute dermal toxicity : Presumed Not Toxic

Skin irritation

Sulfomethylated Quebracho : No data available

Eye irritation

Sulfomethylated Quebracho : May cause eye irritation.

Repeated dose toxicity

Sulfomethylated Quebracho : Species: Rat, male
 Sex: male
 Application Route: oral gavage
 Dose: 100, 300, 1000 mg/kg
 Exposure time: 32 d
 Number of exposures: Daily
 NOEL: 1.000 mg/kg
 Method: OECD Guideline 422
 No adverse effects expected

Species: Rat, female
 Sex: female
 Application Route: oral gavage
 Dose: 100, 300, 1000 mg/kg
 Exposure time: 39 - 47 d
 Number of exposures: Daily
 NOEL: 1.000 mg/kg
 Method: OECD Guideline 422
 No adverse effects expected

Reproductive toxicity

Sulfomethylated Quebracho : Species: Rat
 Sex: male
 Application Route: oral gavage
 Dose: 100, 300, 1000 mg/kg

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

Exposure time: 32 d
Number of exposures: Daily
Method: OECD Guideline 422
NOAEL Parent: 1.000 mg/kg
NOAEL F1: 1.000 mg/kg
Fertility and developmental toxicity tests did not reveal any effect on reproduction.

Species: Rat
Sex: female
Application Route: oral gavage
Dose: 100, 300, 1000 mg/kg
Exposure time: 39 - 47 d
Number of exposures: Daily
Method: OECD Guideline 422
NOAEL Parent: 1.000 mg/kg
NOAEL F1: 1.000 mg/kg
Fertility and developmental toxicity tests did not reveal any effect on reproduction.

CMR effects

Crystalline Silica : Carcinogenicity: Human carcinogen.

Diacel® WBS-200, Powder

Further information : No data available.

SECTION 12: Ecological information**Toxicity to fish**

Sulfomethylated Quebracho : LL50: > 1.800 mg/l
Exposure time: 96 h
Species: Scophthalmus maximus (Flatfish, Flounder)
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

Sulfomethylated Quebracho : EL50: 73,2 mg/l
Exposure time: 48 h
Species: Acartia tonsa (Marine Copepod)
Method: ISO TC147/SC5/WG2

Toxicity to algae

Sulfomethylated Quebracho : ErC50: > 100 mg/l
Exposure time: 72 h
Species: Desmodesmus subspicatus (green algae)
Method: OECD Test Guideline 201

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

EbC50: 79 mg/l
Exposure time: 72 h
Species: *Desmodesmus subspicatus* (green algae)
Method: OECD Test Guideline 201

Elimination information (persistence and degradability)

Biodegradability : No data available

Ecotoxicology Assessment

Acute aquatic toxicity
Sulfomethylated Quebracho : Harmful to aquatic life.

Chronic aquatic toxicity
Sulfomethylated Quebracho : Harmful to aquatic life with long lasting effects.

Additional ecological information : No data available

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation**

Major Accident Hazard Legislation : 96/82/EC Update: 2003
Directive 96/82/EC does not apply

Water contaminating class (Germany) : WGK 3 highly water endangering

Notification status

Europe REACH	:	On the inventory, or in compliance with the inventory
United States of America TSCA	:	On TSCA Inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	Not in compliance with the inventory
Korea KECI	:	Not in compliance with the inventory
Philippines PICCS	:	Not in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory


Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 1
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : CPC00049

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average

Diacel® WBS-200, Powder

Version 1.8

Revision Date 2016-06-02

	Substances in China		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

Full text of H-Statements referred to under sections 2 and 3.

H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.
H412	Harmful to aquatic life with long lasting effects.