



## SOLTROL® 10 Isoparaffin Solvent

Version 1.9

Revision Date 2016-06-29

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### Product information

Product Name : SOLTROL® 10 Isoparaffin Solvent  
 Material : 1089830, 1017316, 1017315, 1017318, 1017317, 1017319,  
 1017320, 1017321, 1017314

**Company** : Chevron Phillips Chemical Company LP  
 Specialty Chemicals  
 10001 Six Pines Drive  
 The Woodlands, TX 77380

#### Emergency telephone:

##### Health:

866.442.9628 (North America)

1.832.813.4984 (International)

##### Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group  
 E-mail address : SDS@CPChem.com  
 Website : www.CPChem.com

### SECTION 2: Hazards identification

#### Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

#### Emergency Overview

##### Danger

**Form:** Liquid    **Physical state:** Liquid    **Color:** Colorless at room temperature    **Odor:** Mild

OSHA Hazards : Flammable Liquid, Moderate skin irritant, Aspiration hazard,  
 Target Organ Effects

#### Classification

: Flammable liquids, Category 2

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

Skin irritation, Category 2  
 Specific target organ systemic toxicity - single exposure,  
 Category 3, Central nervous system  
 Aspiration hazard, Category 1

**Labeling**

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H225: Highly flammable liquid and vapor.  
 H304: May be fatal if swallowed and enters airways.  
 H315: Causes skin irritation.  
 H336: May cause drowsiness or dizziness.

Precautionary Statements

: **Prevention:**  
 P210 Keep away from heat/sparks/open flames/hot surfaces.  
 No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting/  
 equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
 P301 + P310 IF SWALLOWED: Immediately call a POISON  
 CENTER/doctor.  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off  
 immediately all contaminated clothing. Rinse skin with  
 water/shower.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh  
 air and keep comfortable for breathing. Call a POISON  
 CENTER/doctor if you feel unwell.  
 P331 Do NOT induce vomiting.  
 P332 + P313 If skin irritation occurs: Get medical advice/  
 attention.  
 P362 Take off contaminated clothing and wash before reuse.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or  
 alcohol-resistant foam to extinguish.  
**Storage:**  
 P403 + P233 Store in a well-ventilated place. Keep container  
 tightly closed.  
 P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste  
 disposal plant.

**Carcinogenicity:**

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

<b>IARC</b>	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
<b>NTP</b>	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
<b>ACGIH</b>	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**SECTION 3: Composition/information on ingredients**

Synonyms : Not Established

Molecular formula : UVCB

Component	CAS-No.	Weight %
Isoalkanes C7-8	70024-92-9	100

**SECTION 4: First aid measures**

General advice	: Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious place in recovery position and seek medical advice.
In case of skin contact	: If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**SECTION 5: Firefighting measures**

Flash point	: -11 °C (12 °F) Method: Tag closed cup
Autoignition temperature	: 420 °C (788 °F)
Suitable extinguishing media	: Alcohol-resistant foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical.
Unsuitable extinguishing media	: High volume water jet.

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon Dioxide. Carbon oxides.

**SECTION 6: Accidental release measures**

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7: Handling and storage****Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

**Storage**

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Ingredients	Basis	Value	Control parameters	Note
Isoalkanes C7-8	Manufacturer	TWA	300 ppm,	

**US**

Ingredients	Basis	Value	Control parameters	Note
-------------	-------	-------	--------------------	------

**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

Wear as appropriate: Protective suit. Safety shoes.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

Form : Liquid  
Physical state : Liquid  
Color : Colorless at room temperature  
Odor : Mild

**Safety data**

Flash point : -11 °C (12 °F)  
Method: Tag closed cup

Lower explosion limit : 1 %(V)

Oxidizing properties : no

Autoignition temperature : 420 °C (788 °F)

Molecular formula : UVCB

Molecular weight : Not applicable

pH : Not applicable

Pour point : No data available

Boiling point/boiling range : 93.3 - 104.4 °C (199.9 - 219.9 °F)

Vapor pressure : 114.64 MMHG  
at 37.8 °C (100.0 °F)

Relative density : 0.697  
at 15.6 °C (60.1 °F)

Water solubility : Negligible

Partition coefficient: n-octanol/water : No data available

Viscosity, kinematic : 0.56 cSt  
at 40 °C (104 °F)

Relative vapor density : 2  
(Air = 1.0)

Evaporation rate : 1

Percent volatile : > 99 %

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

**SECTION 10: Stability and reactivity**

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Possibility of hazardous reactions**

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous decomposition products : Carbon Dioxide  
Carbon oxides

Other data : No decomposition if stored normally.

**SECTION 11: Toxicological information****Acute oral toxicity**

Isoalkanes C7-8 : LD50: > 5,000 mg/kg  
Species: Rat  
Method: OECD Test Guideline 401  
Information given is based on data obtained from similar substances.

**Acute inhalation toxicity**

Isoalkanes C7-8 : LC50: > 33,520 mg/l  
Exposure time: 4 h  
Species: Rat  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.  
Information given is based on data obtained from similar substances.

**SOLTROL® 10 Isoparaffin Solvent**

**Skin irritation** : irritating

**SOLTROL® 10 Isoparaffin Solvent**

**Eye irritation** : Vapors may cause irritation to the eyes, respiratory system and the skin.

**Sensitization**

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

Isoalkanes C7-8 : Did not cause sensitization on laboratory animals.  
Information given is based on data obtained from similar substances.

**Repeated dose toxicity**

Isoalkanes C7-8 : Species: Rat  
Application Route: Inhalation  
Dose: 0, 385, 1180 ppm  
Exposure time: 12 wk  
Number of exposures: 6 hr/d, 5 d/wk  
NOEL: > 1180 ppm  
Target Organs: Kidney

**SOLTROL® 10 Isoparaffin Solvent**

**Aspiration toxicity** : May be fatal if swallowed and enters airways.

**SOLTROL® 10 Isoparaffin Solvent**

**Further information** : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

**SECTION 12: Ecological information****Toxicity to fish**

Isoalkanes C7-8 : LC50: 5.4 mg/l  
Exposure time: 96 h  
Species: Oncorhynchus mykiss (rainbow trout)  
Information given is based on data obtained from similar substances.

**Toxicity to daphnia and other aquatic invertebrates**

Isoalkanes C7-8 : EL50: 143 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)  
static test Method: OECD Test Guideline 202

**Toxicity to algae**

Isoalkanes C7-8 : EL50: 29.0 mg/l  
Exposure time: 72 h  
Species: Raphidocellus subcapitata (algae)  
Growth inhibition Method: OECD Test Guideline 201

**Biodegradability**

Isoalkanes C7-8 : Result: Not readily biodegradable.  
22 %  
This material is not expected to be readily biodegradable.

**Ecotoxicology Assessment**

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

Acute aquatic toxicity  
Isoalkanes C7-8 : Toxic to aquatic life.

Chronic aquatic toxicity  
Isoalkanes C7-8 : Toxic to aquatic life with long lasting effects.

Additional ecological  
information : Toxic to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, (-11 °C), MARINE POLLUTANT, (ISOALKANES C7-8)

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (ISOALKANES C7-8)

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (ISOALKANES C7-8)

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (ISOALKANES C7-8)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

**SECTION 15: Regulatory information****National legislation**

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Ingredients : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

**US State Regulations**

Pennsylvania Right To Know

: No components are subject to the Pennsylvania Right to Know Act.

New Jersey Right To Know

: No components are subject to the New Jersey Right to Know Act.

California Prop. 65  
Ingredients

: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

**Notification status**

Europe REACH

: This mixture contains only ingredients which have been subject to a pre-registration according to Regulation (EU) No. 1907/2006 (REACH).

United States of America TSCA  
Canada DSL

: On TSCA Inventory

: This product has been notified and approved for listing on the Canadian DSL. At this time, only Chevron Phillips Chemical Company LP can legally import the product into Canada.

Australia AICS

: On the inventory, or in compliance with the inventory

New Zealand NZIoC

: Not in compliance with the inventory

Japan ENCS

: On the inventory, or in compliance with the inventory

Korea KECI

: On the inventory, or in compliance with the inventory

Philippines PICCS

: Not in compliance with the inventory

China IECSC

: Not in compliance with the inventory


**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 2  
Fire Hazard: 3  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 34750

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average

**SOLTROL® 10 Isoparaffin Solvent**

Version 1.9

Revision Date 2016-06-29

	Substances in China		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		