

**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****Product information**

Product Name : SOLTROL® 220 Isoparaffin Solvent  
Material : 1017375, 1017376, 1017377, 1017373, 1036759, 1017372,  
1017371, 1017378, 1017374

**Company** : Chevron Phillips Chemical Company LP  
Specialty Chemicals  
10001 Six Pines Drive  
The Woodlands, TX 77380

**Local** : Chevron Phillips Chemicals International N.V.  
Airport Plaza (Stockholm Building)  
Leonardo Da Vincilaan 19  
1831 Diegem  
Belgium

SDS Requests: (800) 852-5530  
Technical Information: (832) 813-4862  
Responsible Party: Product Safety Group  
Email:sds@cpchem.com

**Emergency telephone:****Health:**

866.442.9628 (North America)  
1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)  
Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316  
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group  
E-mail address : SDS@CPChem.com  
Website : www.CPChem.com

**SECTION 2: Hazards identification****Classification of the substance or mixture  
REGULATION (EC) No 1272/2008**

SDS Number:100000067798

1/10

**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

Aspiration hazard, Category 1

H304:

May be fatal if swallowed and enters airways.

**Label elements****Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H304

May be fatal if swallowed and enters airways.

Precautionary Statements

: **Response:**  
P301 + P310IF SWALLOWED: Immediately call a  
POISON CENTER/doctor.  
Do NOT induce vomiting.

P331

**Storage:**

P405

Store locked up.

**Disposal:**

P501

Dispose of contents/ container to an  
approved waste disposal plant.

Hazardous ingredients which must be listed on the label:

- 68551-20-2 C13-C16 Isoalkanes

**Additional Labeling:**

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 1 %  
The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 1 %

**SECTION 3: Composition/information on ingredients**

Molecular formula

: UVCB

**Mixtures****Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
C13-C16 Isoalkanes	68551-20-2 271-370-0	Asp. Tox. 1; H304	99 - 100

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

**SECTION 4: First aid measures**

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
- If inhaled : Move to fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.

**SECTION 5: Firefighting measures**

- Flash point : 100,6 °C (213,1 °F)  
Method: ASTM D 93
- Autoignition temperature : No data available
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Fire and explosion protection : Normal measures for preventive fire protection.
- Hazardous decomposition products : Carbon oxides.

**SECTION 6: Accidental release measures**

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

**SECTION 7: Handling and storage****Handling**

Advice on safe handling : Do not breathe vapors/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

**Storage**

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Dusts and Mists / P100. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the

**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

	contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggles.
Skin and body protection	: Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Lightweight protective clothing.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

Form	: Liquid
Physical state	: Liquid
Color	: Colorless
Odor	: Mild

**Safety data**

Flash point	: 100,6 °C (213,1 °F) Method: ASTM D 93
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Oxidizing properties	: no
Autoignition temperature	: No data available
Molecular formula	: UVCB
Molecular weight	: Not applicable
pH	: 7
Pour point	: No data available
Boiling point/boiling range	: 214,4 - 316 °C (417,9 - 601 °F)
Vapor pressure	: 0,36 MMHG at 37,8 °C (100,0 °F)
Relative density	: 0,79 at 15,6 °C (60,1 °F)
Density	: 794,5 g/l
Water solubility	: Negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: 3,3 cSt

**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

at 38 °C (100 °F)

Relative vapor density : 1  
(Air = 1.0)

Evaporation rate : < 1

**SECTION 10: Stability and reactivity**

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Possibility of hazardous reactions**

Conditions to avoid : No data available.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous decomposition products : Carbon oxides

Other data : No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****Acute oral toxicity**

C13-C16 Isoalkanes : LD50: > 10.000 mg/kg  
Species: Rat  
Information given is based on data obtained from similar substances.

**Skin irritation**

C13-C16 Isoalkanes : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin. Information given is based on data obtained from similar substances.

**Eye irritation**

C13-C16 Isoalkanes : No eye irritation

**Sensitization**

C13-C16 Isoalkanes : Classification: Did not cause sensitization on laboratory animals.  
Information given is based on data obtained from similar substances.

**SOLTROL® 220 Isoparaffin Solvent**

**Aspiration toxicity** : May be fatal if swallowed and enters airways.  
Substances known to cause human aspiration toxicity hazards

**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

or to be regarded as if they cause human aspiration toxicity hazard.

**SOLTROL® 220 Isoparaffin Solvent**

**Further information** : Solvents may degrease the skin.

**SECTION 12: Ecological information****Toxicity to fish**

C13-C16 Isoalkanes : LL50: > 1.000 mg/l  
Exposure time: 96 h  
Species: Oncorhynchus mykiss (rainbow trout)  
static test Information given is based on data obtained from similar substances.

**Toxicity to daphnia and other aquatic invertebrates**

C13-C16 Isoalkanes : EL50: > 1.000 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)  
Immobilization Method: OECD Test Guideline 202  
Information given is based on data obtained from similar substances.

**Toxicity to algae**

C13-C16 Isoalkanes : EL50: > 1.000 mg/l  
Exposure time: 72 h  
Species: Pseudokirchneriella subcapitata (green algae)  
Growth inhibition Method: OECD Test Guideline 201  
Information given is based on data obtained from similar substances.

Elimination information (persistence and degradability)

Biodegradability : Expected to be biodegradable  
This material is expected to be readily biodegradable.

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

Contaminated packaging : Empty remaining contents. Dispose of as unused product.  
Do not re-use empty containers.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

**SECTION 15: Regulatory information**

**National legislation**



**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

**Major Accident Hazard Legislation** : 96/82/EC Update: 2003  
Directive 96/82/EC does not apply

**Water contaminating class (Germany)** : WGK 1 slightly water endangering

**Notification status**

Europe REACH : This mixture contains only ingredients which have been subject to a pre-registration according to Regulation (EU) No. 1907/2006 (REACH).

United States of America TSCA : On TSCA Inventory

Canada DSL : All components of this product are on the Canadian DSL

Australia AICS : On the inventory, or in compliance with the inventory

New Zealand NZIoC : On the inventory, or in compliance with the inventory

Japan ENCS : On the inventory, or in compliance with the inventory


Korea KECI : On the inventory, or in compliance with the inventory

Philippines PICCS : On the inventory, or in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 1  
Fire Hazard: 1  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 59320

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency

**SOLTROL® 220 Isoparaffin Solvent**

Version 1.7

Revision Date 2016-05-19

NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

**Full text of H-Statements referred to under sections 2 and 3.**

H304 May be fatal if swallowed and enters airways.