

Version 2.1 Revision Date 2013-08-16

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product information** 

: Scentinel® O Gas Odorant Trade name

Material : 1101716

: Chevron Phillips Chemical Company LP Company

Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380

**Emergency telephone:** 

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887

Asia: +800 CHEMCALL (+800 2436 2255)

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department Product Safety and Toxicology Group

E-mail address MSDS@CPChem.com www.CPChem.com Website

### **SECTION 2: Hazards identification**

#### **Emergency Overview**

Physical state: Liquid Color: Clear Odor: Repulsive

OSHA Hazards : Flammable Liquid, Harmful by ingestion., Harmful by skin

absorption., Moderate skin irritant, Moderate eye irritant

**GHS Classification** 

: Flammable liquids, Category 2 Skin sensitization, Sub-category 1B Acute toxicity, Category 5, Oral Aspiration hazard, Category 2 Acute aquatic toxicity, Category 1

Chronic aquatic toxicity, Category 1

**GHS-Labeling** 

MSDS Number: 100000068543 1/12

Version 2.1 Revision Date 2013-08-16

Symbol(s)









Signal Word : Danger

Hazard Statements : H225: Highly flammable liquid and vapor.

H303: May be harmful if swallowed.

H305: May be harmful if swallowed and enters airways.

H317: May cause an allergic skin reaction.

H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces.

- No smoking.

P243: Take precautionary measures against static discharge.

P273: Avoid release to the environment.

P280: Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON

CENTER or doctor/ physician. P331: Do NOT induce vomiting.

P370 + P378: In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam for extinction.

P391: Collect spillage.

Storage:

P403 + P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/ container to an approved waste

disposal plant.

Carcinogenicity:

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcinogen

by ACGIH.

#### **SECTION 3: Composition/information on ingredients**

Synonyms : 2-propanethiol

IPM IC3SH

Molecular formula : C4H10S

Component	CAS-No.	Weight %	
Isopropyl Mercaptan	75-33-2	95 - 100	
n-Propyl Mercaptan	107-03-9	1 - 5	

MSDS Number:100000068543 2/12

Version 2.1 Revision Date 2013-08-16

#### **SECTION 4: First aid measures**

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Symptoms of poisoning may

appear several hours later. Do not leave the victim

unattended.

If inhaled : Move to fresh air. If unconscious place in recovery position

and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well

with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. Take victim immediately to hospital.

#### **SECTION 5: Firefighting measures**

Flash point : -34 °C (-29 °F)

estimated

Autoignition temperature : No data available

Suitable extinguishing

media

Dry chemical. Carbon dioxide (CO2). Alcohol-resistant foam.

Unsuitable extinguishing

media

: High volume water jet.

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective

equipment for fire-fighters

: Wear self contained breathing apparatus for fire fighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case

of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed

containers.

Fire and explosion

protection

: Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take

necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open

flames, hot surfaces and sources of ignition.

Hazardous decomposition : Sulfur.

MSDS Number:100000068543 3/12

Version 2.1 Revision Date 2013-08-16

products

#### **SECTION 6: Accidental release measures**

Personal precautions : Use personal protective equipment. Ensure adequate

ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low

areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

# **SECTION 7: Handling and storage**

#### Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with

local and national regulations.

Advice on protection against fire and explosion

Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open

flames, hot surfaces and sources of ignition.

#### Storage

Requirements for storage areas and containers

: No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

#### **SECTION 8: Exposure controls/personal protection**

#### **Engineering measures**

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits.

MSDS Number:100000068543 4/12

Version 2.1 Revision Date 2013-08-16

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

#### Personal protective equipment

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless

ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators

may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place. Wear as appropriate: Flame retardant antistatic protective clothing. Remove and wash contaminated clothing before re-

use. Skin should be washed after contact. Footwear

protecting against chemicals.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

# **SECTION 9: Physical and chemical properties**

# Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid Color : Clear Odor : Repulsive

Safety data

Flash point : -34 °C (-29 °F)

estimated

Lower explosion limit : No data available

MSDS Number:100000068543 5/12

Version 2.1 Revision Date 2013-08-16

Upper explosion limit : No data available

Oxidizing properties : yes

Autoignition temperature : No data available

Molecular formula : C4H10S

Molecular Weight : 90.2 g/mol

pH : Not applicable

Pour point : No data available

Boiling point/boiling range : 51 °C (124 °F)

Vapor pressure : 8.80 PSI

at 37.8 °C (100.0 °F)

Relative density : 0.82, 15.6 °C(60.1 °F)

Water solubility : slightly soluble

Partition coefficient: n-

octanol/water Viscosity, dynamic : No data available

•

Relative vapor density : 2.62

(Air = 1.0)

: 0.369 cP

Evaporation rate : 1

estimated

Percent volatile : > 99 %

### **SECTION 10: Stability and reactivity**

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

# Possibility of hazardous reactions

Conditions to avoid : No data available.

Other data : No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

**Acute oral toxicity** 

| Isopropyl Mercaptan | : LD50: > 2,000 - < 5,000 mg/kg

MSDS Number:100000068543 6/12

Version 2.1 Revision Date 2013-08-16

Species: rat Sex: Not Specified

Symptoms: Loss of reflexes

n-Propyl Mercaptan LD50: 1,848 mg/kg

Species: rat

Sex: male and female

Method: OECD Test Guideline 401

Harmful if swallowed.

Acute inhalation toxicity

Isopropyl Mercaptan : LC50: > 32.24 mg/l

Exposure time: 4 h Species: rat

Sex: male and female Test atmosphere: vapor

Method: OECD Test Guideline 403

Test substance: yes

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable

concentration.

n-Propyl Mercaptan LC50: > 25.5 mg/l

Exposure time: 4 h Species: rat

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable

concentration.

**Acute dermal toxicity** 

Isopropyl Mercaptan : LD50: > 2,000 mg/kg

Species: rat

Method: No information available.

see user defined free text

n-Propyl Mercaptan LD50: > 1,682 mg/kg

Species: rabbit Sex: male and female

Method: OECD Test Guideline 402

Scentinel® O Gas Odorant

**Skin irritation**: May cause skin irritation in susceptible persons.

Scentinel® O Gas Odorant

**Eye irritation** : May cause irreversible eye damage.

Sensitization

Isopropyl Mercaptan : Causes sensitization.

Scentinel® O Gas Odorant

**Aspiration toxicity** : May be harmful if swallowed and enters airways.

Substances known to cause human aspiration toxicity hazards

MSDS Number:100000068543 7/12

Version 2.1 Revision Date 2013-08-16

or to be regarded as if they cause human aspiration toxicity

hazard.

Scentinel® O Gas Odorant

Further information : Concentrations substantially above the TLV value may cause

narcotic effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Solvents may degrease the skin.

#### **SECTION 12: Ecological information**

# Toxicity to fish

Isopropyl Mercaptan : LC50: 34 mg/l

Exposure time: 96 h

semi-static test Analytical monitoring: yes Method: OECD Test Guideline 203

Information given is based on data obtained from similar

substances.

n-Propyl Mercaptan LC50: 1.3 mg/l

Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)

Analytical monitoring: yes Test substance: yes

Method: OECD Test Guideline 203

Toxic to aquatic organisms.

#### Toxicity to daphnia and other aquatic invertebrates

Isopropyl Mercaptan : EC50: 0.25 - 0.5 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Test substance: yes Method: OECD Test Guideline 202

n-Propyl Mercaptan 0.07 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea)

Analytical monitoring: yes Test substance: yes

Method: OECD Test Guideline 202 Very toxic to aquatic organisms.

M-Factor

propane-2-thiol : 1 propane-1-thiol : 10

Elimination information (persistence and degradability)

Biodegradability : This material is not expected to be readily biodegradable.

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life.

MSDS Number:100000068543 8/12

Version 2.1 Revision Date 2013-08-16

#### **SECTION 13: Disposal considerations**

The information in this MSDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

#### **SECTION 14: Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and the bill of lading.

#### **US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN2402, PROPANETHIOLS, 3, II

#### IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN2402, PROPANETHIOLS, 3, II, (-34 °C), MARINE POLLUTANT, (ISOPROPYL MERCAPTAN, N-PROPYL MERCAPTAN)

### IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2402, PROPANETHIOLS, 3, II

# ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2402, PROPANETHIOLS, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (ISOPROPYL MERCAPTAN, N-PROPYL MERCAPTAN)

# RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN2402, PROPANETHIOLS, 3, II, ENVIRONMENTALLY HAZARDOUS, (ISOPROPYL MERCAPTAN, N-PROPYL MERCAPTAN)

# ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2402, PROPANETHIOLS, 3, II, ENVIRONMENTALLY HAZARDOUS, (ISOPROPYL

MSDS Number:100000068543 9/12

MATERIAL SAFETY DATA SHEET

# Scentinel® O Gas Odorant

Version 2.1 Revision Date 2013-08-16

MERCAPTAN, N-PROPYL MERCAPTAN)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

#### **SECTION 15: Regulatory information**

#### **National legislation**

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 302 Threshold Planning Quantity

: SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Ingredients : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

#### Clean Air Act

Ozone-Depletion

Potential

: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

#### **US State Regulations**

New Jersey Right To Know

: Isopropyl Mercaptan - 75-33-2 n-Propyl Mercaptan - 107-03-9

California Prop. 65

Ingredients

: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive

defects.

MSDS Number:100000068543 10/12

Version 2.1 Revision Date 2013-08-16


**Notification status** 

Europe REACH On the inventory, or in compliance with the inventory United States of America TSCA On the inventory, or in compliance with the inventory Canada DSL On the inventory, or in compliance with the inventory Australia AICS On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory New Zealand NZIoC On the inventory, or in compliance with the inventory Japan ENCS Korea KECI On the inventory, or in compliance with the inventory Philippines PICCS On the inventory, or in compliance with the inventory China IECSC On the inventory, or in compliance with the inventory

#### **SECTION 16: Other information**

NFPA Classification : Health Hazard: 2

Fire Hazard: 3 Reactivity Hazard: 0



#### **Further information**

Legacy MSDS Number : CPC00510

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this MSDS pertains only to the product as shipped.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet				
ACGIH	American Conference of	LD50	Lethal Dose 50%	
	Government Industrial Hygienists			
AICS	Australia, Inventory of Chemical	LOAEL	Lowest Observed Adverse Effect	
	Substances		Level	
DSL	Canada, Domestic Substances	NFPA	National Fire Protection Agency	
	List			
NDSL	Canada, Non-Domestic	NIOSH	National Institute for Occupational	
	Substances List		Safety & Health	
CNS	Central Nervous System	NTP	National Toxicology Program	
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of	
			Chemicals	
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect	
			Level	
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration	
EGEST	EOSCA Generic Exposure	OSHA	Occupational Safety & Health	
	Scenario Tool		Administration	

MSDS Number:100000068543 11/12

# MATERIAL SAFETY DATA SHEET

# Scentinel® O Gas Odorant

Version 2.1 Revision Date 2013-08-16

EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and
			Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		