

SAFETY DATA SHEET



Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : Liquid Flowzan® Biopolymer
Material : 1106106, 1089411, 1088326, 1083196, 1087354, 1016833, 1028771, 1016798, 1105963

Company : Chevron Phillips Chemical Company LP
Drilling Specialties Company LLC
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:

Health:

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: +800 CHEMCALL (+800 2436 2255) China: +86-21-22157316

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Emergency Overview

Warning

Physical state: Liquid **Color:** Light brown **Odor:** Negligible
OSHA Hazards : Combustible Liquid

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

Classification

: Flammable liquids, Category 4

Labeling

Signal Word

: Warning

Hazard Statements

: H227: Combustible liquid.

Precautionary Statements

: **Prevention:**P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

ACGIH

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

SECTION 3: Composition/information on ingredients

Synonyms

: Drilling Mud Additive

Molecular formula

: Mixture

Component	CAS-No.	Weight %
C12-C14 Isoalkanes	68551-19-9	0 - 60
Distillates (petroleum), hydrotreated light	64742-47-8	0 - 60

SECTION 4: First aid measures

General advice

: No hazards which require special first aid measures.

If inhaled

: Move to fresh air. If symptoms persist, call a physician.

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

- In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.

SECTION 5: Firefighting measures

- Flash point : 76.7 °C (170.1 °F)
Method: Tag closed cup
- Autoignition temperature : > 200 °C (> 392 °F)
- Suitable extinguishing media : Carbon dioxide (CO₂).
- Unsuitable extinguishing media : High volume water jet.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on an open flame or any other incandescent material. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures

- Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. For personal protection see section 8. Smoking, eating and drinking should be prohibited

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Ingredients	Basis	Value	Control parameters	Note
C12-C14 Isoalkanes	Manufacturer	TWA	1,200 mg/m3	RCP,

RCP Reciprocal Calculation Procedure

US

Ingredients	Basis	Value	Control parameters	Note
-------------	-------	-------	--------------------	------

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Protective suit. Safety shoes.

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Physical state : Liquid

Color : Light brown

Odor : Negligible

Safety data

Flash point : 76.7 °C (170.1 °F)
Method: Tag closed cup

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : No

Autoignition temperature : > 200 °C (> 392 °F)

Molecular formula : Mixture

Molecular weight : Not applicable

pH : No data available

Pour point : No data available

Boiling point/boiling range : 217.8 - 237.8 °C (424.0 - 460.0 °F)

Vapor pressure : No data available

Relative density : 0.97

Water solubility : Soluble

Partition coefficient: n-octanol/water : No data available

Viscosity, dynamic : 72,000 cP

Relative vapor density : No data available

Evaporation rate : No data available

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

SECTION 10: Stability and reactivity

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous decomposition products : Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

C12-C14 Isoalkanes : LD50: > 5000 milligram per kilogram
Species: Rat
Method: OECD Test Guideline 401
Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : No data available

Acute inhalation toxicity

C12-C14 Isoalkanes : LC50: > 5.0milligram per literExposure time: 4 h
Species: Rat
Test atmosphere: vapor
Method: OECD Test Guideline 403
An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.
Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : No data available

Acute dermal toxicity

Distillates (petroleum), hydrotreated light : No data available

Liquid Flowzan® Biopolymer

Skin irritation : No skin irritation

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

Liquid Flowzan® Biopolymer**Eye irritation** : No eye irritation**Sensitization**

C12-C14 Isoalkanes : Classification: Did not cause sensitization on laboratory animals.
Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : Does not cause skin sensitization.
Information given is based on data obtained from similar substances.

Repeated dose toxicity

C12-C14 Isoalkanes : Species: Monkey
Application Route: Inhalation
Dose: 0, 654 ppm
Exposure time: 4 wk
Number of exposures: 6 h/d, 3 d/wk
NOEL: > 654 ppm
Method: OECD Test Guideline 412

Species: Rat, male and female
Sex: male and female
Application Route: oral gavage
Dose: 0, 25, 150, 1000 mg/kg/d
Exposure time: 4 wk
Number of exposures: daily
NOEL: >= 1000 mg/kg/d
Method: OECD Guideline 422
Information given is based on data obtained from similar substances.

Reproductive toxicity

C12-C14 Isoalkanes : Species: Rat
Sex: male
Application Route: oral gavage
Dose: 0, 750, 1500, 3000 mg/kg/bw/d
Number of exposures: daily
Test period: 90 d
Method: OECD Test Guideline 415
NOAEL Parent: >= 3000 mg/kg/bw/d
Information given is based on data obtained from similar substances.

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

Species: Rat
Sex: female
Application Route: oral gavage
Dose: 0, 750, 1500 mg/kg/bw/d
Number of exposures: daily
Test period: 90 d
Method: OECD Test Guideline 415
NOAEL Parent: ≥ 1500 mg/kg/bw/d
NOAEL F1: 750 mg/kg/bw/d
Information given is based on data obtained from similar substances.

Species: Rat
Sex: male and female
Application Route: inhalation (vapor)
Dose: 100, 300 ppm
Number of exposures: 6 h/d/5d/wk
Test period: 8 wk
Method: OECD Guideline 421
NOAEL Parent: ≥ 300 ppm
NOAEL F1: ≥ 300 ppm
Information given is based on data obtained from similar substances.

Developmental Toxicity

C12-C14 Isoalkanes

: Species: Rat
Application Route: Inhalation
Dose: 100, 300 ppm
Exposure time: GD 6-15
Number of exposures: 6 h/d
NOAEL Teratogenicity: ≥ 300 ppm
Information given is based on data obtained from similar substances.

Species: Rat
Application Route: Inhalation
Dose: 300, 900 ppm
Exposure time: GD 6-15
Number of exposures: 6 h/d
Method: OECD Guideline 414
NOAEL Teratogenicity: ≥ 900 ppm
NOAEL Maternal: ≥ 900 ppm
Information given is based on data obtained from similar substances.

Species: Rat
Application Route: oral gavage
Dose: 0, 500, 1000, 1500 mg/kg/d
Exposure time: GD 6-15
Number of exposures: Daily
Method: OECD Guideline 414
NOAEL Teratogenicity: 1,000 mg/kg
NOAEL Maternal: 500 mg/kg
Information given is based on data obtained from similar substances.

Liquid Flowzan® Biopolymer

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

Aspiration toxicity : No aspiration toxicity classification.

CMR effects

C12-C14 Isoalkanes : Carcinogenicity: Limited evidence of carcinogenicity in animal studies
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects
 Teratogenicity: Animal testing did not show any effects on fetal development.
 Reproductive toxicity: No adverse effects expected

Liquid Flowzan® Biopolymer

Further information : Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

C12-C14 Isoalkanes : LL50: > 1,000 mg/l
 Exposure time: 96 h
 Species: Oncorhynchus mykiss (rainbow trout)
 semi-static test Method: OECD Test Guideline 203
 Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates

C12-C14 Isoalkanes : EL50: > 1,000 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 static test Method: OECD Test Guideline 202
 Information given is based on data obtained from similar substances.

Distillates (petroleum),
 hydrotreated light

EL50: > 100 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 static test Method: OECD Test Guideline 202
 Aquatic toxicity is unlikely due to low solubility.

Toxicity to algae

C12-C14 Isoalkanes : EL50: > 1,000 mg/l
 Exposure time: 72 h
 Species: Pseudokirchneriella subcapitata (green algae)
 Growth inhibition Method: OECD Test Guideline 201
 Information given is based on data obtained from similar substances.

Toxicity to fish (Chronic toxicity)

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

C12-C14 Isoalkanes	: NOELR: 0.316 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) Method: QSAR modeled data
Biodegradability	
C12-C14 Isoalkanes	: aerobic 31 % Testing period: 28 d Method: OECD Test Guideline 301F Information given is based on data obtained from similar substances. Expected to be inherently biodegradable.
Distillates (petroleum), hydrotreated light Ecotoxicology Assessment	: No data available
Results of PBT assessment C12-C14 Isoalkanes	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information	: May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Testing (ASTM D4206) has shown product does not sustain combustion.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation**

SARA 311/312 Hazards : Fire Hazard

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Ingredients : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

Pennsylvania Right To Know : No components are subject to the Pennsylvania Right to Know Act.

New Jersey Right To Know : No components are subject to the New Jersey Right to Know Act.

California Prop. 65 Ingredients : This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Notification status

Europe REACH : On the inventory, or in compliance with the inventory
Switzerland CH INV : On the inventory, or in compliance with the inventory
United States of America TSCA : On TSCA Inventory
Canada DSL : All components of this product are on the Canadian DSL

Liquid Flowzan® Biopolymer


Version 1.10

Revision Date 2016-08-29

Australia AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	On the inventory, or in compliance with the inventory
Philippines PICCS	:	Not in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 1
Fire Hazard: 1
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 630920

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic

Liquid Flowzan® Biopolymer

Version 1.10

Revision Date 2016-08-29

GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		