

UNUSUAL FIRE AND EXPLOSION HAZARDS

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from material handling points. Keep containers tightly closed. Isolate from heat, sparks, electrical equipment, and open flames. Closed containers may explode on exposure to high temperatures.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable.

CONDITIONS TO AVOID

Do not expose to high temperatures or open ignition sources.

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

May form toxic materials on thermal decomposition including Carbon Dioxide, Carbon Monoxide, and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYES: May cause severe irritation, redness, tearing, and blurred vision. SKIN: Redness or dryness.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Moderate irritation, redness, and defatting dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: Irritation of skin, eyes, and respiratory tract. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. CHRONIC: Prolonged or repeated exposure above TLV may result in permanent brain and nervous system damage. CHRONIC: Prolonged or repeated exposure to this product may cause birth defects or other reproductive harm. CHRONIC: Prolonged or repeated exposure to this product may cause cancer.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: Yes
WARNING! This product contains chemical(s) known to the State of California to cause cancer. (California Health and Safety Code Section 25249.5) (Prop. 65).
WARNING! This product contains chemical(s) known to the State of California to cause birth defects or other reproductive harm. (California Health and Safety Code Section 25249.5) (Prop. 65).

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

May be aggravating to some skin and respiratory conditions, and to pre-existing liver and/or kidney disorders.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush with large amounts of water for at least 15 minutes. Take to a physician. SKIN: Wash affected areas with soap and water. Remove contaminated clothing. If irritation persists, consult physician. INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult physician.

INGESTION: Drink 1 or 2 glasses of water to dilute. DO NOT INDUCE VOMITING.
CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Eliminate all ignition sources. Dike, contain, or absorb with inert materials.
Transfer to containers for recovery or disposal. Prevent runoff into sewers,
streams, or other bodies of water.

WASTE DISPOSAL METHOD
Dispose of in accordance with all local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Do not store or use near sources of high temperatures, near fire or open flame,
or other ignition sources.

OTHER PRECAUTIONS
DO NOT TAKE INTERNALLY. Avoid prolonged or repeated exposure to levels above
TLV. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - CONTROL MEASURES =====
RESPIRATORY PROTECTION
If TLV is exceeded, use NIOSH/MSHA approved organic vapor, mist and dust,
supplied air, or self-contained breathing apparatus. Avoid breathing sanding
dust.

VENTILATION
Use adequate mechanical (general and/or local) ventilation to maintain exposure
below TLV.

PROTECTIVE GLOVES
Wear resistant gloves such as Nitrile Rubber.

EYE PROTECTION
Use chemical splash goggles or OSHA permitted safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
Wear impervious clothing. Eye wash station.

WORK/HYGIENIC PRACTICES
Wash hands before eating or using restrooms. Remove and wash all contaminated
clothing before reuse.

===== SECTION IX - DISCLAIMER =====
The information contained herein is furnished without warranty of any kind.
Employers should use this information only as a supplement to other information
gathered by them and must make independent determination of suitability and
completeness of information from all sources to assure proper use of these
materials and the safety and health of employees.