



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 1 of 12

1. Product and company identification

Product identifier

Trade name: RK-7100 Adhesive

Relevant identified uses of the substance or mixture and uses advised against

General use: Resin for 2 component adhesive.
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – USA (24h): Tel: ++1 202 464 2554

Transport:

TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: ++1 202 464 2554

2. Hazards identification

Emergency overview

Appearance: Physical state at 68 °F and 101.3 kPa: liquid

Form: pasty

Color: whitish

Odor: stinging

Classification: Flammable Liquid - Category 2; Skin Corrosion - Category 1A; Sensitization - skin - Category 1; Specific Target Organ Toxicity (Single Exposure) - Category 3; Aquatic toxicity - chronic - Category 3;

Hazard symbols:



Signal word:

Danger

Hazard statements: Highly flammable liquid and vapor.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause respiratory irritation.
Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page:

2 of 12

Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take action to prevent static discharges.
Avoid breathing vapors/spray.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection.
IF ON SKIN: Wash with plenty of water/soap.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see 'First aid' on this label).
Wash contaminated clothing before reuse.
In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.
Dispose of contents/container to hazardous or special waste collection point.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may have a narcotic effect.
see section 11: Toxicological information

3. Composition / Information on ingredients

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 80-62-6	Methyl methacrylate	55 - 60 %	Flammable Liquid - Category 2. Skin Irritation - Category 2. Sensitization - skin - Category 1. Specific Target Organ Toxicity (Single Exposure) - Category 3.
CAS 79-41-4	Methacrylic acid	6 - 8 %	Acute Toxicity - oral - Category 4. Acute Toxicity - dermal - Category 3. Acute Toxicity - inhalative - Category 4. Skin Corrosion - Category 1A. Eye Damage - Category 1. Specific Target Organ Toxicity (Single Exposure) - Category 3.
CAS 110-16-7	Maleic acid	< 2 %	Acute Toxicity - oral - Category 4. Skin Irritation - Category 2. Eye Irritation - Category 2A. Sensitization - skin - Category 1. Specific Target Organ Toxicity (Single Exposure) - Category 3.
CAS 128-37-0	3,5-Di-tert-butyl-4-hydroxytoluene	< 1 %	Aquatic toxicity - acute - Category 1. Aquatic toxicity - chronic - Category 1.
CAS 80-15-9	Cumene hydroperoxide	< 1 %	Organic Peroxide - Category E. Acute Toxicity - oral - Category 4. Acute Toxicity - dermal - Category 4. Acute Toxicity - inhalative - Category 3. Skin Corrosion - Category 1B. Specific Target Organ Toxicity (Repeated Exposure) - Category 2. Aquatic toxicity - chronic - Category 2.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 3 of 12

4. First aid measures

- General information: Take off immediately all contaminated clothing and wash it before reuse. First aider: Pay attention to self-protection!
- In case of inhalation: Move victim to fresh air; if necessary, provide artificial respiration or oxygen. Put victim at rest and keep warm. Immediately get medical attention.
- Following skin contact: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Immediately get medical attention.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Seek the attention of an ophthalmologist immediately.
- After swallowing: Do not induce vomiting. Rinse mouth with water. Drink large quantities of water. Never give anything by mouth to an unconscious person. Immediately get medical attention.

Most important symptoms/effects, acute and delayed

Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. Drowsiness, vomiting.

Information to physician

Treat symptomatically. Symptoms of poisoning may develop several hours following exposure. Victim should be under medical observation for at least 48 hours after exposure.

5. Fire fighting measures

- Flash point/flash point range: 51.8 °F (c.c.)
- Auto-ignition temperature: not determined
- Suitable extinguishing media: Water fog, foam, dry chemical powder, sand, carbon dioxide
- Extinguishing media which must not be used for safety reasons: High power water jet

Specific hazards arising from the chemical

Highly flammable liquid and vapor. Vapors form explosive mixtures with air. Risk of bursting/explosion. Hazardous vapors may form during fires. In case of fire may be liberated: carbon monoxide and carbon dioxide.

- Protective equipment and precautions for firefighters: Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing. In case of fire and/or explosion do not breathe fumes.
- Additional information: Cool exposed containers with water spray. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

6. Accidental release measures

- Personal precautions: Provide adequate ventilation. In case of leakage, eliminate all ignition sources. Avoid contact with skin and eyes. Wear appropriate protective equipment. Keep unprotected people away. Use a breathing protection against vapors/aerosol. Do not breathe vapor or spray.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 4 of 12

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains. Do not allow to enter into soil/subsoil.

In case of release, notify competent authorities.

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Use only explosion-proof equipment. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

7. Handling and storage

Handling

Advices on safe handling: Provide good ventilation and/or an exhaust system in the work area. Handle and open container with care. Do not breathe vapor or spray.
The vapors are heavier than air and can accumulate in high concentrations on the ground. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

Wear appropriate protective equipment. Take off immediately all contaminated clothing and wash it before reuse.

Avoid contact with skin and eyes. When using do not eat, drink or smoke. Wash hands before breaks and after work.

Precautions against fire and explosion:

Vapors may form explosive mixtures with air. Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

Use only explosion-protected equipment/instruments. Do not weld.

In partially filled containers explosive mixtures may form.

Storage

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.

Keep container dry. Keep only in the original container.

Protect from heat and direct sunlight.

Store containers in upright position. Explosion protection required.

Handle empty containers with care. Incineration may cause explosion.

Hints on joint storage:

Do not store together with combustible or self-igniting materials or any highly flammable solids.

Do not store together with alkali metals, peroxides, strong reducing agents or strong oxidizing agents. Do not store together with acids or alkalis.

Keep away from food, drink and animal feedingstuffs.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page:

5 of 12

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
80-62-6	Methyl methacrylate	USA: ACGIH: STEL	410 mg/m ³ ; 100 ppm
		USA: ACGIH: TWA	205 mg/m ³ ; 50 ppm
		USA: NIOSH: TWA	410 mg/m ³ ; 100 ppm
		USA: OSHA: TWA	410 mg/m ³ ; 100 ppm
79-41-4	Methacrylic acid	USA: ACGIH: TWA	70 mg/m ³ ; 20 ppm
		USA: NIOSH: TWA	70 mg/m ³ ; 20 ppm (May be absorbed through the skin.)
128-37-0	3,5-Di-tert-butyl-4-hydroxytoluene	USA: NIOSH: TWA	10 mg/m ³

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.
See also information in chapter 7, section storage.

Personal protection equipment (PPE)

- Eye/face protection:** Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
- Skin protection:** Flame retardant, antistatic and chemical resistant protective clothing.
Protective gloves according to OSHA Standard - 29 CFR: 1910.138.
Glove material: Neoprene, Nitrile rubber
Layer thickness: 0.6 mm
Breakthrough time: >480 min
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Respiratory protection:** Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.
- General hygiene considerations:**
Use non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
Do not breathe vapor or spray. Avoid contact with skin and eyes.
Work place should be equipped with a shower and an eye rinsing apparatus.
Take off immediately all contaminated clothing and wash it before reuse.
When using do not eat, drink or smoke. Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

- Appearance:** Physical state at 68 °F and 101.3 kPa: liquid
Form: pasty
Color: whitish
- Odor:** stinging
- Odor threshold:** not determined
- pH value:** not determined



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 6 of 12

Melting point/freezing point:	not determined
Initial boiling point and boiling range:	not determined
Flash point/flash point range:	51.8 °F (c.c.)
Evaporation rate:	No data available
Flammability:	Highly flammable liquid and vapor.
Explosion limits:	LEL (Lower Explosion Limit): not determined UEL (Upper Explosive Limit): not determined
Vapor pressure:	not determined
Vapor density:	not determined
Density:	at 68 °F: not determined
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not determined
Thermal decomposition:	No decomposition when used properly.
Viscosity, dynamic:	not determined
Viscosity, kinematic:	not determined
Explosive properties:	Vapors may form explosive mixtures with air.

10. Stability and reactivity

Reactivity:	Highly flammable liquid and vapor. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Polymerization along with heat production. Do not expose to high temperature. Danger of bursting and explosion.
Conditions to avoid:	Keep away from heat sources, sparks and open flames. Protect against direct sunlight.
Incompatible materials:	Alkali metals, peroxides, strong reducing agents, strong oxidizing agents, acids and alkalis, concentrated.
Hazardous decomposition products:	Hazardous vapors may form during fires. In case of fire may be liberated: carbon monoxide and carbon dioxide.
Thermal decomposition:	No decomposition when used properly.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 7 of 12

11. Toxicological information

Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
Acute toxicity (oral): Based on available data, the classification criteria are not met.
Acute toxicity (dermal): Based on available data, the classification criteria are not met.
Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
Skin corrosion/irritation, eye damage/irritation: Skin Corrosion - Category 1A = Causes severe skin burns and eye damage.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Sensitization - skin - Category 1 = May cause an allergic skin reaction.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) - Category 3 = May cause respiratory irritation.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Other information: Information about Methyl methacrylate:
LD50 Rat, oral: 7900-9400 mg/kg
LD50 Rabbit, dermal: >5000 mg/kg
LD50 Rat, inhalative, vapor: 29.8 mg/L/4h
Information about Methacrylic acid:
LD50 Rat, oral: 1320-2260 mg/kg
LD50 Rabbit, dermal: 500-1000 mg/kg
LD50 Rat, inhalative, vapor: 7.1 mg/L/4h
For carcinogenic effects:
Information about Methyl methacrylate:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
Information about 3,5-Di-tert-butyl-4-hydroxytoluene:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed

Symptoms

Drowsiness, vomiting.

12. Ecological information

Ecotoxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

Mobility in soil

No data available



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 8 of 12

Persistence and degradability

Further details: No data available

Additional ecological information

Volatile organic compounds (VOC):

0 % by weight = 0 g/L

General information: Do not allow to enter into ground-water, surface water or drains. Do not allow uncontrolled discharge of product into the environment.

13. Disposal considerations

Product

Recommendation: Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Handle empty containers with care. Incineration may cause explosion.

14. Transport information

USA: Department of Transportation (DOT)

Identification number: UN2924
Proper shipping name: UN 2924, flammable liquids, corrosive, n.o.s.
(Methyl methacrylate, Methacrylic acid)
Hazard class or Division: 3
Packing Group: II
Labels: 3, 8
Symbols: G
Special provisions: IB2, T11, TP2, TP27
Packaging – Exceptions: 150
Packaging – Non-bulk: 202
Packaging – Bulk: 243
Quantity limitations – Passenger aircraft / rail: 1 L
Quantity limitations – Cargo only: 5 L
Vessel stowage – Location: B
Vessel stowage – Other: 40





SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 9 of 12

Sea transport (IMDG)

UN number: UN 2924
Proper shipping name: UN 2924, FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(Methyl methacrylate, Methacrylic acid)
Class or division, Subsidiary risk: Class 3, Subrisk 8
Packing Group: II
EmS: F-E, S-C
Special provisions: 274
Limited quantities: 1 L
Excepted quantities: E2
Contaminated packaging - Instructions: P001
Contaminated packaging - Provisions: -
IBC - Instructions: IBC02
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T11
Tank instructions - Provisions: TP2, TP27
Stowage and handling: Category B. SW2
Properties and observations: Causes burns to skin, eyes and mucous membranes.
Marine pollutant: no
Segregation group: none

Air transport (IATA)

UN/ID number: UN 2924
Proper shipping name: UN 2924, FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(Methyl methacrylate, Methacrylic acid)
Class or division, Subsidiary risk: Class 3, Subrisk 8
Packing Group: II
Hazard label: Flamm. liquid & Corrosive
Excepted Quantity Code: E2
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y340 - Max. Net Qty/Pkg. 0.5 L
Passenger and Cargo Aircraft: Pack.Instr. 352 - Max. Net Qty/Pkg. 1 L
Cargo Aircraft only: Pack.Instr. 363 - Max. Net Qty/Pkg. 5 L
Special provisions: A3
Emergency Response Guide-Code (ERG): 3CH



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 10 of 12

15. Regulatory information

National regulations - U.S. Federal Regulations

Methyl methacrylate:	TSCA Inventory: listed; EPA flags T TSCA HPVC: not listed TSCA: listed - Flags: T Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed Clean Air Act: Hazardous Air Pollutants: Code XOY SOCMI Chemical: yes Clean Water Act: Hazardous Substances: RQ 1000 lbs. Other Environmental Laws: CERCLA: RQ 1000 lbs. RCRA Hazardous Wastes: Code U162 RCRA Groundwater Monitoring: Methods 8015, 8240 / PQL 2, 5 SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard NIOSH Recommendations: Occupational Health Guideline: 0426
Methacrylic acid:	TSCA Inventory: listed TSCA HPVC: not listed TSCA: listed Clean Air Act: SOCMI Chemical: yes NIOSH Recommendations: Occupational Health Guideline: 0386*
Maleic acid:	TSCA Inventory: listed TSCA HPVC: not listed Clean Water Act: Hazardous Substances: RQ 5000 lbs. Other Environmental Laws: CERCLA: RQ 5000 lbs.
3,5-Di-tert-butyl-4-hydroxytoluene:	TSCA Inventory: listed TSCA HPVC: not listed Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0246
Cumene hydroperoxide:	TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: SOCMI Chemical: yes Other Environmental Laws: CERCLA: RQ 10 lbs. RCRA Hazardous Wastes: Code U096 SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard OSHA Process Safety Management: Threshold 5000 lbs.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 11 of 12

National regulations - U.S. State Regulations

Methyl methacrylate:

Delaware Air Quality Management List:
DRQ: 1000 - RQ State: Federal Regulations Apply
Idaho Air Pollutant List:
Title 585; AAC: 20,5 - EL: 27,3 - OEL: 410 - Title 586: -
Massachusetts Haz. Substance Codes: 2,4,5,6 F8 F9
Main: HAP - 2000
Minnesota Haz. Substance:
Codes: AO - Ratings: 3.79 - Status: Air Pollutant. Title III. TRI.
New Jersey RTK Hazardous Substance:
DOT: 1247 - Sub No.: 1277
New York List of Hazardous Substances:
RQ-Air: 1000 - RQ-Land: 1
No Note Associated with this chemical
Pennsylvania Haz. Substance Code: E
Washington Air Contaminant: TWA: 100 ppm = 410 mg

Methacrylic acid:

Idaho Air Pollutant List:
Title 585 -- AAC: 3.5 -- EL: 4.67 -- WEL: 70 - Title 586 -
Massachusetts Haz. Substance codes: 4,5,6
Minnesota Haz. Substance: Codes: A -- Ratings: -
Pennsylvania Haz. Substance code: -
Washington Air Contaminant:
TWA: 20 ppm - 70 mg
Skin: Protective measures should be taken to prevent or reduce skin absorption.

Maleic acid:

Delaware Air Quality Management List:
DRQ: 5000 - RQ State: Federal Regulations Apply
Massachusetts Haz. Substance codes: F8
New York List of Hazardous Substances:
RQ-Air: 5000 - RQ-Land: 100 - Note: No Note Associated with this chemical.
Pennsylvania Haz. Substance code: E

Cumene hydroperoxide:

California Proposition 65 code: -
Delaware Air Quality Management List:
DRQ: 10 - RQ State: Federal Regulations Apply
Massachusetts Haz. Substance codes: 5,6 F8 F9
New Jersey Extraordinarily Hazardous Substances:
NJ Threshold: 2500 - NJ Group: I - NJ Table: I Part D - NJ Basis: NFPA 325
New Jersey RTK Hazardous Substance:
DOT: 2116 - Sub No.: 0543 - TPQ: -
New York List of Hazardous Substances:
RQ-Air: 10 - RQ-Land: 10 - Note: No Note Associated with this chemical.
Pennsylvania Haz. Substance code: E

National regulations - Great Britain

Hazchem-Code: •3WE

16. Other information

Text for labeling:

Contains 55 - 60 % Methyl methacrylate, 6 - 8 % Methacrylic acid, < 2 % Maleic acid, < 1 % 3,5-Di-tert-butyl-4-hydroxytoluene, < 1 % Cumene hydroperoxide. Safety data sheet available on request.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

RK-7100 Adhesive

Material number 105661

Page: 12 of 12

Hazard rating systems:



NFPA Hazard Rating:

Health: 3 (Serious)

Fire: 3 (Serious)

Reactivity: 1 (Slight)

HMIS Version III Rating:

Health: 3 (Serious)

Flammability: 3 (Serious)

Physical Hazard: 1 (Slight)

Personal Protection: X = Consult your supervisor

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	1
	X

Reason of change:

Changes in section 1: General revision

Date of first version:

Jan/2/2016

Department issuing data sheet

Contact person:

see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.