



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016  
Version: 2  
Language: en-US  
Date of print: Aug/11/2016

## Electro-Contact-Cleaner Spray

Material number 112100

Page: 1 of 10

### 1. Product and company identification

#### Product identifier

Trade name: Electro-Contact-Cleaner Spray

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol

#### Details of the supplier of the safety data sheet

Company name: WEICON Inc.  
Street/POB-No.: 20 Steckle Place, Unit 20  
Postal Code, city: Kitchener, Ontario N2E 2C3, CA  
WWW: www.weicon.ca  
E-mail: info@weicon.ca  
Telephone: +1-519-896-5252  
Telefax: +1-519-896-5254  
Dept. responsible for information:  
Product-Safety-Department  
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

#### Emergency phone number

**EMERGENCY CONTACT – USA (24h): Tel: ++1 202 464 2554**

**Transport:**

**TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: ++1 202 464 2554**

### 2. Hazards identification

#### Emergency overview

Appearance: Physical state at 68 °F and 101.3 kPa: liquid  
Form: Aerosol  
Color: colorless  
Odor: characteristic  
Classification: Aerosol - Category 1; Skin Irritation - Category 2;  
Specific Target Organ Toxicity (Single Exposure) - Category 3;  
Aquatic toxicity - chronic - Category 2;

Hazard symbols:



Signal word:

**Danger**

Hazard statements:

Extremely flammable aerosol.  
Pressurised container: May burst if heated.  
Causes skin irritation.  
May cause drowsiness or dizziness.  
Toxic to aquatic life with long lasting effects.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

## Electro-Contact-Cleaner Spray

Material number 112100

Page: 2 of 10

Precautionary statements: Keep out of reach of children.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash hands and face thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF ON SKIN: Wash with plenty of water/soap.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER/doctor if you feel unwell.  
Specific treatment (see 'First aid' on this label).  
If skin irritation occurs: Get medical advice/attention.  
Take off contaminated clothing.  
Collect spillage.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container to hazardous or special waste collection point.

### Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided.  
Inhaling can lead to irritations of the respiratory tract and mucous membrane.  
Higher doses may have a narcotic effect.  
see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterization: Preparation of active ingredients with propellant

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	50 - 75 %	Flammable Liquid - Category 2. Skin Irritation - Category 2. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 109-66-0	n-Pentane	10 - 25 %	Flammable Liquid - Category 2. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 64-17-5	Ethanol	3 - 10 %	Flammable Liquid - Category 2.
CAS 74-98-6	Propane	3 - 10 %	Flammable Gas - Category 1. Liquefied Gas.
CAS 106-97-8	n-Butane, pure	3 - 10 %	Flammable Gas - Category 1. Compressed Gas.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

## Electro-Contact-Cleaner Spray

Material number 112100

Page: 3 of 10

### 4. First aid measures

- General information: First aider: Pay attention to self-protection!  
Immediately remove any wetted clothing, shoes or stockings.
- In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing.  
Seek medical attention.
- Following skin contact: Immediately clean with water and soap followed by thorough rinsing.  
Seek medical attention.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.
- After swallowing: Immediately get medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

#### Most important symptoms/effects, acute and delayed

May cause drowsiness or dizziness. Irritates skin and mucous membranes. Irritating to respiratory system. Inhalation causes narcotic effects/intoxication. Further hazardous properties cannot be excluded.

#### Information to physician

Treat symptomatically.

### 5. Fire fighting measures

- Flash point/flash point range: not applicable
- Auto-ignition temperature: not self-igniting
- Suitable extinguishing media: Alcohol resistant foam, dry chemical powder, carbon dioxide, water mist.
- Extinguishing media which must not be used for safety reasons: full water jet

#### Specific hazards arising from the chemical

Do not expose to high temperature. Danger of bursting and explosion. Cool exposed containers with water spray.  
May form dangerous gases and vapours in case of fire.  
Carbon monoxide and carbon dioxide.  
Potentially explosive vapor/air mixtures may form.

#### Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

- Additional information: You have to dispose of contaminated extinguishing water according to the regulations of the authorities.

### 6. Accidental release measures

- Personal precautions: Do not breathe gas/vapor/spray. Avoid contact with the substance.  
In case of leakage, eliminate all ignition sources. Provide adequate ventilation.  
Wear appropriate protective equipment. Keep unprotected people away.  
Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects.
- Environmental precautions: Do not allow to enter into ground-water, surface water or drains.  
In case of release, notify competent authorities. Danger of explosion!



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

## Electro-Contact-Cleaner Spray

Material number 112100

Page: 4 of 10

Methods for clean-up: Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).  
Beware of reignition. Thoroughly clean surrounding area.

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.

## 7. Handling and storage

### Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe gas/vapor/spray.  
Avoid contact with skin and eyes. Wear appropriate protective equipment.  
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. Take off contaminated clothing and wash it before reuse.

Precautions against fire and explosion:  
Container under pressure. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Keep away from sources of ignition - No smoking.  
Take precautionary measures against static discharges.  
Use only explosion-protected equipment/instruments. Do not weld.  
In partially filled containers explosive mixtures may form. Vapors may form explosive mixtures with air.

### Storage

Requirements for storerooms and containers:  
Keep container tightly closed and in a well-ventilated place.  
Keep container dry. Keep only in the original container.  
Protect from heat and direct sunlight.  
Store containers in upright position. Explosion protection required. Store locked up.  
Keep at temperature not exceeding 122 °F.

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids. Keep away from food, drink and animal feedingstuffs.

## 8. Exposure controls / personal protection

### Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
109-66-0	n-Pentane	NIOSH: Ceiling USA: NIOSH: TWA	1800 mg/m <sup>3</sup> ; 610 ppm 350 mg/m <sup>3</sup> ; 120 ppm
64-17-5	Ethanol	USA: ACGIH: TWA USA: NIOSH: TWA USA: OSHA: TWA	1000 mg/m <sup>3</sup> (A3) 1900 mg/m <sup>3</sup> ; 1000 ppm 1900 mg/m <sup>3</sup> ; 1000 ppm
74-98-6	Propane	USA: NIOSH: TWA USA: OSHA: TWA	1800 mg/m <sup>3</sup> ; 1000 ppm 1800 mg/m <sup>3</sup> ; 1000 ppm
106-97-8	n-Butane, pure	USA: ACGIH: TWA USA: NIOSH: TWA	2370 mg/m <sup>3</sup> ; 1000 ppm 1900 mg/m <sup>3</sup> ; 800 ppm

### Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Use only explosion-proof equipment.  
See also information in chapter 7, section storage.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

## Electro-Contact-Cleaner Spray

Material number 112100

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

Page: 5 of 10

### Personal protection equipment (PPE)

- Eye/face protection** Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
- Skin protection** Flame retardant, antistatic and chemical resistant protective clothing.  
Protective gloves according to OSHA Standard - 29 CFR: 1910.138 (Solvent resistant protective gloves).  
Glove material: Nitrile rubber - Layer thickness: 0.7 mm  
Breakthrough time: >480 min.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Respiratory protection:** Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.  
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!
- General hygiene considerations:**  
Use non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.  
Do not breathe gas/vapor/spray. Avoid contact with skin and eyes.  
Take off contaminated clothing and wash it before reuse.  
When using do not eat, drink or smoke.  
Wash hands before breaks and after work.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

- Appearance:** Physical state at 68 °F and 101.3 kPa: liquid  
Form: Aerosol  
Color: colorless
- Odor:** characteristic
- Odor threshold:** No data available
- pH value:** No data available
- Melting point/freezing point:** No data available
- Initial boiling point and boiling range:** not applicable
- Flash point/flash point range:** not applicable
- Evaporation rate:** No data available
- Flammability:** Extremely flammable aerosol.
- Explosion limits:** LEL (Lower Explosion Limit): 0.80 Vol-%  
UEL (Upper Explosive Limit): 15.00 Vol-%
- Vapor pressure:** at 68 °F: 573 hPa
- Vapor density:** No data available
- Density:** at 68 °F: 0.669 g/mL
- Water solubility:** at 68 °F: 5 g/L
- Partition coefficient: n-octanol/water:** No data available
- Auto-ignition temperature:** not self-igniting
- Thermal decomposition:** No data available
- Explosive properties:** Product is not explosive. Potentially explosive vapor/air mixtures may form.
- Ignition temperature:** 392 °F



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

## Electro-Contact-Cleaner Spray

Material number 112100

Page: 6 of 10

### 10. Stability and reactivity

- Reactivity: Extremely flammable aerosol. Vapors may form explosive mixtures with air.
- Chemical stability: Stable under recommended storage conditions.
- Possibility of hazardous reactions  
Container under pressure. Do not expose to high temperature. Danger of bursting and explosion.
- Conditions to avoid: Keep away from heat sources, sparks and open flames. Protect from direct exposure to sunlight and temperatures exceeding 122 °F.
- Incompatible materials: Do not store together with combustible or self-igniting materials or any highly flammable solids.
- Hazardous decomposition products:  
May form dangerous gases and vapours in case of fire.  
carbon monoxide and carbon dioxide
- Thermal decomposition: No data available

### 11. Toxicological information

#### Toxicological tests

- Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
- Acute toxicity (oral): Based on available data, the classification criteria are not met.
- Acute toxicity (dermal): Lack of data.
- Acute toxicity (inhalative): Lack of data.
- Skin corrosion/irritation: Skin Irritation - Category 2 = Causes skin irritation.
- Eye damage/irritation: Based on available data, the classification criteria are not met.
- Sensitisation to the respiratory tract: Lack of data.
- Skin sensitisation: Based on available data, the classification criteria are not met.
- Germ cell mutagenicity/Genotoxicity: Lack of data.
- Carcinogenicity: Lack of data.
- Reproductive toxicity: Lack of data.
- Effects on or via lactation: Lack of data.
- Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) - Category 3 = May cause drowsiness or dizziness.
- Specific target organ toxicity (repeated exposure): Lack of data.
- Aspiration hazard: Based on available data, the classification criteria are not met.
- Other information: Information about Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:  
LD50 Rat, oral: > 5800 mg/kg.  
LD50 Rabbit, dermal: > 2920 mg/kg.  
LD50 Rat, inhalative: > 25 mg/l/4h.

#### Symptoms

May cause drowsiness or dizziness. Irritates skin and mucous membranes. Irritating to respiratory system. Inhalation causes narcotic effects/intoxication. Further hazardous properties cannot be excluded.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

## Electro-Contact-Cleaner Spray

Material number 112100

Page: 7 of 10

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.  
Information about Pentane:  
Fish toxicity: LC50 Oncorhynchus mykiss 4,26 mg/L/96h  
Information about Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:  
Daphnia toxicity: EC50 Daphnia magna: 3 mg/L/48h

### Mobility in soil

No data available

### Persistence and degradability

Further details: No data available

### Additional ecological information

Volatile organic compounds (VOC):

100 % by weight = 669 g/L

General information: Avoid spills and leaks. Very small amounts contaminates drinking water.  
Do not allow to enter into ground-water, surface water or drains.

## 13. Disposal considerations

### Product

Recommendation: Dispose of waste according to applicable legislation.

### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care. Incineration may cause explosion. Spray can must be completely empty for proper waste disposal.

## 14. Transport information

### USA: Department of Transportation (DOT)

Identification number: UN1950  
Proper shipping name: UN 1950, AEROSOLS  
Hazard class or Division: 2.1  
Labels: 2.1  
Special provisions: N82  
Packaging – Exceptions: 306  
Packaging – Non-bulk: None  
Packaging – Bulk: None  
Quantity limitations – Passenger aircraft / rail: 75 kg  
Quantity limitations – Cargo only: 150 kg  
Vessel stowage – Location: A  
Vessel stowage – Other: 25, 87, 126





# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

## Electro-Contact-Cleaner Spray

Material number 112100

Page: 8 of 10

### Sea transport (IMDG)

UN number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS  
Class or division, Subsidiary risk: Class 2.1, Subrisk-  
Packing Group: -  
EmS: F-D, S-U  
Special provisions: 63, 190, 277, 327, 344, 959  
Limited quantities: 1000 mL  
Excepted quantities: E0  
Contaminated packaging - Instructions: P207, LP02  
Contaminated packaging - Provisions: PP87, L2  
IBC - Instructions: -  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: -  
Tank instructions - Provisions: -  
Stowage and handling: SW1 SW22  
Segregation: SG69  
Properties and observations: -  
Marine pollutant: yes  
Segregation group: none

### Air transport (IATA)

UN/ID number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS, flammable  
Class or division, Subsidiary risk: Class 2.1  
Hazard label: Flamm. gas  
Excepted Quantity Code: E0  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg  
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg  
Special provisions: A145 A167 A802  
Emergency Response Guide-Code (ERG): 10L





# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016  
Version: 2  
Language: en-US  
Date of print: Aug/11/2016

## Electro-Contact-Cleaner Spray

Material number 112100

Page: 9 of 10

### 15. Regulatory information

#### National regulations - U.S. Federal Regulations

Hydrocarbons, C6-C7, n-alkanes,  
isoalkanes, cyclics, <5% n-hexane:  
n-Pentane:

TSCA Inventory: listed  
TSCA HPVC: not listed  
TSCA Inventory: listed; EPA flags T  
TSCA HPVC: not listed  
Clean Air Act:  
Accidental Release Prevention: Threshold 10000 lbs. / Basis  
for listing = g  
NIOSH Recommendations:  
Occupational Health Guideline: 0486

Ethanol:

TSCA Inventory: listed  
TSCA HPVC: not listed  
TSCA: listed  
NIOSH Recommendations:  
Occupational Health Guideline: 0262

Propane:

TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
Accidental Release Prevention: Threshold 10000 lbs. / Basis  
for listing = f  
NIOSH Recommendations:  
Occupational Health Guideline: 0524

n-Butane, pure:

TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
Accidental Release Prevention: Threshold 10000 lbs. / Basis  
for listing = f  
NIOSH Recommendations:  
Occupational Health Guideline: 0068\*

#### National regulations - U.S. State Regulations

California Proposition 65: Not listed.

#### National regulations - Great Britain


Hazchem-Code: -

### 16. Other information

Text for labeling:

Contains 50 - 75 % Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, 10 - 25 % n-Pentane, 3 - 10 % Ethanol, 3 - 10 % Propane, 3 - 10 % n-Butane, pure. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:  
Health: 2 (Moderate)  
Fire: 4 (Severe)  
Reactivity: 2 (Moderate)  
HMIS Version III Rating:  
Health: 2 (Moderate)  
Flammability: 4 (Severe)  
Physical Hazard: 2 (Moderate)  
Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	2
	X

Reason of change:

Changes in section 1: General revision

Date of first version:

Dec/8/2015



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

## Electro-Contact-Cleaner Spray

Material number 112100

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

Page: 10 of 10

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.