

1. Product and company identification

Product identifier

Trade name: Spray-on Grease

Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information: Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de
Additional information: WEICON GmbH & Co. KG
Königsberger Straße 255
Münster 48157
www.weicon.de
info@weicon.de
+49(0)251 / 9322 - 0
+49(0)251 / 9322 - 244

Emergency phone number

GIZ, Bonn Germany (English)
Telephone: +49(0)228 / 19 240

2. Hazards identification

Emergency overview

Appearance: Form: Aerosol
Color: black
Odor: like mineral oil
Classification: Aerosol - Category 1;

Hazard symbols:



Signal word: **Danger**
Hazard statements: Extremely flammable aerosol.
Pressurised container: May burst if heated.
Precautionary statements: Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Spray-on Grease

Article number 115300

Revision date: Feb/10/2016

Version: 2

Language: en-US

Date of print: Feb/10/2016

Page:

2 of 10

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Product has an anesthetic effect.

Exposure to temperatures exceeding 122 °F will increase pressure: resulting in danger of bursting or explosion.

Potentially explosive mixtures may form if adequate ventilation is not provided.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: Preparation of metallic soap in mineral oil with additives

Preparation of active ingredients with propellant: Propane/Butane.

Hazardous ingredients:

CAS No.	Designation	Content	Classification
CAS 67-63-0	Isopropyl alcohol	< 10 %	Flammable Liquid - Category 2. Eye Irritation - Category 2A. Specific Target Organ Toxicity (Single Exposure) - Category 3.
CAS 74-98-6	Propane	20 - 25 %	Flammable Gas - Category 1. Compressed Gas.
CAS 106-97-8	Butane	20 - 25 %	Flammable Gas - Category 1. Compressed Gas.

4. First aid measures

General information: Take off immediately all contaminated clothing and wash it before reuse.

In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical treatment in case of troubles.

Following skin contact: After contact with skin, wash immediately with soap and plenty of water. Consult a doctor if skin irritation persists.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After swallowing: Immediately get medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed

When vapors form: Dizziness, Headache and fatigue.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

not applicable

Auto-ignition temperature: not determined

Suitable extinguishing media:

Foam, dry chemical powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Spray-on Grease

Article number 115300

Revision date: Feb/10/2016

Version: 2

Language: en-US

Date of print: Feb/10/2016

Page:

3 of 10

Specific hazards arising from the chemical

Extremely flammable aerosol.

Do not expose to high temperature. Danger of bursting and explosion.

May form dangerous gases and vapours in case of fire.

Sulphur dioxide (SO₂), carbon monoxide and carbon dioxide.

Potentially explosive vapor/air mixtures may form.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information: Cool endangered containers with water jetspray. You have to dispose of contaminated extinguishing water according to the regulations of the authorities.

6. Accidental release measures

Personal precautions: Provide adequate ventilation. Do not breathe gas/vapor/spray. Avoid contact with the substance.

Eliminate all ignition sources if safe to do so. Wear protective equipment. Keep unprotected people away.

Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains.

In case of release, notify competent authorities. Danger of explosion!

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area.

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

Exposure to temperatures exceeding 122 °F will increase pressure: resulting in danger of bursting or explosion.

Potentially explosive mixtures may form if adequate ventilation is not provided.

7. Handling and storage

Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Provide room air exhaust at ground level.

Do not breathe gas/vapor/spray. Avoid contact with skin and eyes. Wear protective equipment.

Take off immediately all contaminated clothing and wash it before reuse.

Precautions against fire and explosion:

Container under pressure. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects.

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Use only explosion-protected equipment/instruments. Do not weld.

In partially filled containers explosive mixtures may form. Vapors may form explosive mixtures with air.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Spray-on Grease

Article number 115300

Revision date: Feb/10/2016

Version: 2

Language: en-US

Date of print: Feb/10/2016

Page:

4 of 10

Storage

Requirements for storerooms and containers:

- Keep container tightly closed and in a well-ventilated place.
- Keep container dry. Keep only in the original container.
- Protect from heat and direct sunlight. Keep at temperature not exceeding 122 °F.
- Store containers in upright position. Explosion protection required. Store locked up.

Hints on joint storage:

- Do not store together with combustible or self-igniting materials or any highly flammable solids.
- Keep away from food, drink and animal feedingstuffs.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
67-63-0	Isopropyl alcohol	USA: ACGIH: STEL	984 mg/m ³ ; 400 ppm
		USA: ACGIH: TWA	492 mg/m ³ ; 200 ppm
		USA: NIOSH: STEL	1225 mg/m ³ ; 500 ppm
		USA: NIOSH: TWA	980 mg/m ³ ; 400 ppm
		USA: OSHA: TWA	980 mg/m ³ ; 400 ppm
74-98-6	Propane	USA: NIOSH: TWA	1800 mg/m ³ ; 1000 ppm
		USA: OSHA: TWA	1800 mg/m ³ ; 1000 ppm
106-97-8	Butane	USA: ACGIH: TWA	2370 mg/m ³ ; 1000 ppm
		USA: NIOSH: TWA	1900 mg/m ³ ; 800 ppm

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
67-63-0	Isopropyl alcohol	USA: ACGIH-BEI, urine	40 mg/L	Acetone in urine	end of shift at end of workweek

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Use only explosion-proof equipment.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Flame retardant, antistatic and chemical resistant protective clothing.
Protective gloves according to OSHA Standard - 29 CFR: 1910.138 (Solvent resistant protective gloves).
Glove material: Nitrile rubber - Layer thickness: 0.4 mm
Breakthrough time: > 480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Spray-on Grease

Article number 115300

Revision date: Feb/10/2016

Version: 2

Language: en-US

Date of print: Feb/10/2016

Page:

5 of 10

General hygiene considerations:

- Use only non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
- Do not breathe gas/vapor/spray. Avoid contact with skin and eyes.
- Take off contaminated clothing and wash it before reuse.
- When using do not eat, drink or smoke.
- Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Form: Aerosol Color: black
Odor:	like mineral oil
Odor threshold:	not determined
pH value:	not determined
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	not applicable
Flash point/flash point range:	not applicable
Evaporation rate:	not determined
Flammability:	extremely flammable aerosol
Explosion limits:	LEL (Lower Explosion Limit): 0.60 Vol-% UEL (Upper Explosive Limit): 3.20 Vol-%
Vapor pressure:	at 68 °F: 3500 hPa
Vapor density:	not determined
Density:	at 68 °F: 0.72 g/cm³
Solubility:	not determined
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not determined
Thermal decomposition:	No decomposition when used properly.
Viscosity, dynamic:	not determined
Viscosity, kinematic:	not determined
Explosive properties:	Product is not explosive. Potentially explosive vapor/air mixtures may form.
Ignition temperature:	> 482 °F
Solid content:	29.1 %

10. Stability and reactivity

Reactivity:	Extremely flammable aerosol. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Container under pressure. Do not expose to high temperature. Danger of bursting and explosion.
Conditions to avoid:	Keep away from heat sources, sparks and open flames. Protect from direct exposure to sunlight and temperatures exceeding 122 °F.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Spray-on Grease

Article number 115300

Revision date: Feb/10/2016

Version: 2

Language: en-US

Date of print: Feb/10/2016

Page:

6 of 10

Incompatible materials: Do not store together with combustible or self-igniting materials or any highly flammable solids.

Hazardous decomposition products: May form dangerous gases and vapours in case of fire.
Sulphur dioxide (SO₂), carbon monoxide and carbon dioxide

Thermal decomposition: No decomposition when used properly.

11. Toxicological information

Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
Acute toxicity (oral): Lack of data.
Acute toxicity (dermal): Lack of data.
Acute toxicity (inhalative): Lack of data.
Skin corrosion/irritation: Based on available data, the classification criteria are not met.
Minor irritation effect - does not require labeling.
Eye damage/irritation: Based on available data, the classification criteria are not met.
Minor irritation effect - does not require labeling.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Lack of data.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Lack of data.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Other information: Further hazardous properties cannot be excluded.

Symptoms

When vapors form: Dizziness, Headache and fatigue.

General remarks

Handle in accordance with good industrial hygiene and safety practice.

12. Ecological information

Ecotoxicity

Further details: no data available

Mobility in soil

no data available

Persistence and degradability

Further details: Product is biodegradable with difficulty.

Additional ecological information

Volatile organic compounds (VOC):
62.8 % by weight = 410.9 g/L

General information: Do not allow to enter into ground-water, surface water or drains.

13. Disposal considerations

Product

Recommendation: Do not open with force or incinerate, even when empty.
Dispose of as hazardous waste. Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care. Incineration may cause explosion. Spray can must be completely empty for proper waste disposal.

14. Transport information

USA: Department of Transportation (DOT)

Identification numbers: UN1950
Proper shipping name: UN 1950, AEROSOLS
DOT hazard class or division: 2.1
Label codes: 2.1
Special provisions: N82
Packaging - Exceptions: 306
Packaging - Non-bulk: None
Packaging - Bulk: None
Quantity limitations - Passenger aircraft / rail: 75 kg
Quantity limitations - Cargo only: 150 kg
Vessel stowage - Location: A
Vessel stowage - Other: 25, 87, 126



Sea transport (IMDG)

UN number: UN 1950
Proper shipping name: UN 1950, AEROSOLS
IMDG: Class 2.1, Subrisk -
Packing Group: -
EmS: F-D, S-U
Special provisions: 63, 190, 277, 327, 344, 959
Limited quantities: 1000 mL
EQ: E0
Contaminated packaging - Instructions: P207, LP02
Contaminated packaging - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Marine pollutant: no
Segregation group: none



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Spray-on Grease

Article number 115300

Revision date: Feb/10/2016

Version: 2

Language: en-US

Date of print: Feb/10/2016

Page:

8 of 10

Air transport (IATA)

UN/ID number:	UN 1950
Proper shipping name:	UN 1950, AEROSOLS, flammable
ICAO/IATA:	Class 2.1
Hazard:	Flamm. gas
EQ:	E0
Passenger Ltd.Qty.:	Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger:	Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo:	Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisioning:	A145 A167 A802
ERG:	10L

15. Regulatory information

National regulations - U.S. Federal Regulations

Isopropyl alcohol:	TSCA Inventory: listed TSCA HPVC: not listed Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0359
Propane:	TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0524
Butane:	TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0068*

National regulations - U.S. State Regulations

Isopropyl alcohol:

Idaho Air Pollutant List:

Title 585: AAC: 49 -- EL: 65.3 -- WEL: 980 -Title 586: -

Massachusetts Haz. Substance codes: 2,4,5,6 F9

Minnesota Haz. Substance:

Codes: ANO -- Ratings: 7.84 -- Status: Title III. TRI.

New Jersey RTK Hazardous Substance:

DOT: 1219 - Sub No.: 1076 - TPQ: -

Pennsylvania Haz. Substance code: E

Washington Air Contaminant:

TWA: 400 ppm - 980 mg -- STEL: 500 ppm - 1225 mg

Propane:

California Proposition 65 code: -

Delaware Air Quality Management List:

DRQ: F 1000** - RQ State: State requirements differs from Federal

Massachusetts Haz. Substance codes: 2,4,5,6

Minnesota Haz. Substance:

Codes: AP - Ratings: - - Status: Title III

New Jersey RTK Hazardous Substance:

DOT: 1978 - Sub No.: 1594 - TPQ: -

Pennsylvania Haz. Substance code: -

Washington Air Contaminant:

TWA: 1000 ppm - 1800 mg

Butane:

Delaware Air Quality Management List:

DRQ: F 1000** - RQ State: State requirements differs from Federal

Massachusetts Haz. Substance codes: 4,5,6

Minnesota Haz. Substance:

Codes: A - Ratings: - - Status: Title III

New Jersey RTK Hazardous Substance:

DOT: 1011 - Sub No.: 0273 - TPQ: -

Pennsylvania Haz. Substance code: -

Washington Air Contaminant:

TWA: 800 ppm - 1900 mg


National regulations - Great Britain

Hazchem-Code: -

16. Other information

Text for labeling: Contains < 10 % Isopropyl alcohol, 20 - 25 % Propane, 20 - 25 % Butane. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 1 (Slight)

Fire: 4 (Severe)

Reactivity: 3 (Serious)

HMIS Version III Rating:

Health: 1 (Slight)

Flammability: 4 (Severe)

Physical Hazard: 1 (Slight)

Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	4
PHYSICAL HAZARD	1

Reason of change: Changes in section 3: Composition / Information on ingredients

Date of first version: Dec/16/2015

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Spray-on Grease

Article number 115300

Revision date: Feb/10/2016

Version: 2

Language: en-US

Date of print: Feb/10/2016

Page:

10 of 10

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.