### Safety Data Sheet



#### **Section 1: Identification**

**Product identifier** 

• Oxygen (≤ 21.5%), Ethane (≤ 1.5%), Nitrogen (Balance)

Product Code • 90109

Relevant identified uses of the substance or mixture and uses advised against

Recommended use 

• Calibration standard

Details of the supplier of the safety data sheet

Manufacturer • Air Liquide

2700 Post Oak Blvd. Houston, TX 77056 United States

www.us.airliquide.com sds@airliquide.com

Telephone (Technical) • 713-896-2896 Telephone (Technical) • 800-819-1704

**Emergency telephone number** 

Manufacturer • 800-424-9300 - CHEMTREC

Manufacturer • +1 703-527-3887 - Outside United States

#### Section 2: Hazard Identification

**United States (US)** 

According to OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Compressed Gas - H280

Simple Asphyxiant

Label elements

OSHA HCS 2012

WARNING



**Hazard statements** • Contains gas under pressure; may explode if heated - H280 May displace oxygen and cause rapid suffocation.

**Precautionary statements** 

**Storage/Disposal** • Store in a well-ventilated place. - P403

Other hazards

**OSHA HCS 2012** 

 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

#### Canada

**According to WHMIS** 

#### Classification of the substance or mixture

**WHMIS** 

. Compressed Gas - A

#### Label elements

**WHMIS** 




Compressed Gas - A

# Other hazards WHMIS

 This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.
 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

#### Other information



### Section 3 - Composition/Information on Ingredients

#### **Substances**

Material does not meet the criteria of a substance.

#### **Mixtures**

Composition				
Chemical Name	Identifiers	%	Classifications According to Regulation/Directive	
Oxygen	CAS:7782-44-7	<= 21.5%	OSHA HCS 2012: Ox. Gas 1; Press Gas Comp.	
Ethane	CAS:74-84-0	<= 1.5%	OSHA HCS 2012: Flam. Gas 1; Press. Gas - Comp., Simp. Asphyx.	
Nitrogen	CAS:7727-37-9	Balance	OSHA HCS 2012: Press. Gas - Comp. Simp. Asphyx.	

#### Section 4: First-Aid Measures

#### **Description of first aid measures**

**Inhalation**• IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

Preparation Date: 13/November/2012 Revision Date: 09/September/2013 breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

• Although exposure is unlikely, in case of contact immediately flush skin with running water. If skin irritation develops get medical advice/attention.

First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If irritation develops and persists, get medical attention.

Ingestion is not considered a potential route of exposure.

### Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

#### Indication of any immediate medical attention and special treatment needed

**Notes to Physician** 

Skin

Eye

Ingestion

All treatments should be based on observed signs and symptoms of distress in the
patient. Consideration should be given to the possibility that overexposure to materials
other than this product may have occurred. A potential health hazard associated with
this gas is anoxia.

#### Other information

• Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO GASES WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus must be worn. Victim(s) who experience any adverse effect after over-exposure to this gas mixture must be taken for medical attention. Rescuers should be taken for medical attention if necessary. Take a copy of the label and the MSDS to physician or other health professional with victim(s).

### **Section 5: Fire-Fighting Measures**

### Extinguishing media

Suitable Extinguishing Media • Use extinguishing agent suitable for type of surrounding fire.

Unsuitable Extinguishing Media

No data available

### Special hazards arising from the substance or mixture

Unusual Fire and Explosion

Hazards

Hazardous Combustion Products

Containers may explode when heated. Ruptured cylinders may rocket.

No data available

### Advice for firefighters

 Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

Wear positive pressure self-contained breathing apparatus (SCBA).

Move containers from fire area if you can do it without risk.

FIRE: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

FIRE INVOLVING TANKS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.

FIRE INVOLVING TANKS: Cool containers with flooding quantities of water until well after fire is out.

FIRE INVOLVING TANKS: Do not direct water at source of leak or safety devices; icing may occur.

FIRE INVOLVING TANKS: Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.

FIRE INVOLVING TANKS: ALWAYS stay away from tanks engulfed in fire.

Preparation Date: 13/November/2012 Revision Date: 09/September/2013 Format: GHS Language: English (US) WHMIS, OSHA HCS 2012

#### **Section 6 - Accidental Release Measures**

### Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

 Avoid breathing gas. Ventilate the area before entry. In case of insufficient ventilation, wear suitable respiratory equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

#### **Emergency Procedures**

• Evacuate area. Keep unauthorized personnel away. As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.

### **Environmental precautions**

No special environmental precautions necessary.

#### Methods and material for containment and cleaning up

## Containment/Clean-up Measures

• Stop leak if you can do it without risk.

Do not direct water at spill or source of leak.

Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container.

If possible, turn leaking containers so that gas escapes rather than liquid.

Isolate area until gas has dispersed.

Ventilate the area.

Allow substance to evaporate.

#### Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

### Section 7 - Handling and Storage

### Precautions for safe handling

#### Handling

• Use only with adequate ventilation. Ventilate closed spaces before entering. Be aware of any signs of dizziness or fatigue, especially if work is done in a poorly ventilated area; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms, due to olfactory fatigue or oxygen deficiency. Cylinders should be firmly secured to prevent falling or being knocked-over. Do not attempt to repair, adjust, or in any other way modify cylinders. If there is a malfunction or another type of operational problem, contact nearest distributor immediately. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

### Conditions for safe storage, including any incompatibilities

#### Storage

Store in a cool, dry, well-ventilated place. Protect cylinders against physical damage.
 Cylinders should be firmly secured to prevent falling or being knocked-over.

### Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

### Section 8 - Exposure Controls/Personal Protection

### **Control parameters**

Exposure Limits/Guidelines						
	Result ACGIH Canada Ontario					
Ethane (74-84-0)	IIVVAS	1000 ppm TWA (listed under Aliphatic hydrocarbon gases: Alkane C1-4)	1000 ppm TWA			

### **Exposure controls**

Engineering Measures/Controls

 Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

#### **Personal Protective Equipment**

Respiratory

Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a

NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are

experienced.

Eye/Face

Wear safety glasses.

Skin/Body

Wear leather gloves when handling cylinders.

**Environmental Exposure Controls** 

 Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

#### Key to abbreviations

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

### Section 9 - Physical and Chemical Properties

### **Information on Physical and Chemical Properties**

Material Description			
Physical Form	Gas	Appearance/Description	Colorless gas with no odor.
Color	Colorless	Odor	Odorless
Odor Threshold	No data available		
General Properties			
Boiling Point	-196 C(-320.8 F) Nitrogen	Melting Point	-210 C(-346 F) Nitrogen
Decomposition Temperature	No data available	рН	No data available
Specific Gravity/Relative Density	0.967 Water=1 Nitrogen	Water Solubility	Moderately soluble
Viscosity	No data available		
Volatility			-
Vapor Pressure	No data available	Vapor Density	0.97 Air=1 Nitrogen
Evaporation Rate	No data available		
Flammability		-	-
Flash Point	No data available	UEL	No data available
LEL	No data available	Autoignition	No data available
Flammability (solid, gas)	Nonflammable Gas.		
Environmental			
Octanol/Water Partition coefficient	No data available		

### **Section 10: Stability and Reactivity**

### Reactivity

No dangerous reaction known under conditions of normal use.

### Chemical stability

• Stable under normal temperatures and pressures.

### Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### Conditions to avoid

Excess heat.

### Incompatible materials

No data available

#### **Hazardous decomposition products**

 Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **Section 11 - Toxicological Information**

### Information on toxicological effects

Component Name	CAS	Data		
Oxygen (<= 21.5%)	7782-44-7	Reproductive: ihl-rat TCLo:10 pph/9H (22D preg)		
GHS Properties			Classification	
Acute toxicity			OSHA HCS 2012 • No data available	
Aspiration Hazard			OSHA HCS 2012 • No data available	
Carcinogenicity			OSHA HCS 2012 • No data available	
Germ Cell Mutagenicity			OSHA HCS 2012   No data available	
Skin corrosion/Irritation			OSHA HCS 2012   No data available	
Skin sensitization			OSHA HCS 2012 • No data available	
STOT-RE			OSHA HCS 2012 • No data available	
STOT-SE			OSHA HCS 2012 • No data available	
Toxicity for Reproduction			OSHA HCS 2012 • No data available	
Respiratory sensitization			OSHA HCS 2012   No data available	
Serious eye damage/Irritation			OSHA HCS 2012 • No data available	

### Route(s) of entry/exposure Potential Health Effects Inhalation

Inhalation, Skin, Eye, Ingestion

Acute (Immediate)

This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. If this material is released in a small, poorly ventilated area (i.e. an enclosed or confined space), an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of over-exposure, death may occur. The following effects associated with decreased levels of oxygen: increase in breathing and pulse rate, emotional upset, abnormal fatigue, nausea, vomiting, collapse, loss of consciousness, convulsive movements, respiratory collapse and death.

**Chronic (Delayed)** 

No data available

Skin

Acute (Immediate)

Under normal conditions of use, no health effects are expected.

**Chronic (Delayed)** 

No data available

Eye

Acute (Immediate)
Chronic (Delayed)

Under normal conditions of use, no health effects are expected.

No data available

#### Ingestion

Acute (Immediate) Chronic (Delayed)

No data available

Carcinogenic Effects

 The components of this material are not found on the following lists: NTP and IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

Ingestion will not occur due to the physical form of this product.

#### Key to abbreviations

TC = Toxic Concentration

### **Section 12 - Ecological Information**

### **Toxicity**

Material data lacking.

### Persistence and degradability

Material data lacking.

### Bioaccumulative potential

Material data lacking.

### **Mobility in Soil**

Material data lacking.

#### Other adverse effects

No adverse ecological effects are expected.

### **Section 13 - Disposal Considerations**

#### Waste treatment methods

**Product waste** 

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

### **Section 14 - Transport Information**

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1956	Compressed gas, n.o.s. (Nitrogen, Oxygen)	2.2	NDA	NDA
TDG	UN1956	COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen)	2.2	NDA	NDA
IMO/IMDG	UN1956	COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen)	2.2	NDA	NDA
IATA/ICAO	UN1956	Compressed gas, n.o.s. (Nitrogen, Oxygen)	2.2	NDA	NDA

### Special precautions for user

 Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards. If transporting these cylinders in vehicles, ensure these cylinders are not exposed to extremely high temperatures (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated during transportation.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

### **Section 15 - Regulatory Information**

# Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Pressure(Sudden Release of)

State Right To Know							
Component CAS MA NJ PA							
Ethane	74-84-0	Yes	Yes	Yes			
Nitrogen	7727-37-9	Yes	Yes	Yes			
Oxygen	7782-44-7	Yes	Yes	Yes			

Inventory					
Component CAS Canada DSL Canada NDSL TSCA					
Ethane	74-84-0	Yes	No	Yes	
Nitrogen	7727-37-9	Yes	No	Yes	
Oxygen	7782-44-7	Yes	No	Yes	

#### Canada

#### Labor

Canada - WHMIS - Classifications of Substances

• Ethane 74-84-0 A, B1

Oxygen 7782-44-7 A, C

• Nitrogen 7727-37-9 A

#### Canada - WHMIS - Ingredient Disclosure List

• Ethane 74-84-0 Not Listed

• Oxygen 7782-44-7 Not Listed

• Nitrogen 7727-37-9 Not Listed

#### Environment

Canada - CEPA - Priority Substances List

• Ethane 74-84-0 Not Listed

• Oxygen 7782-44-7 Not Listed

• Nitrogen 7727-37-9 Not Listed

#### **United States**

#### Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Ethane 74-84-0 Not Listed

• Oxygen 7782-44-7 Not Listed

• Nitrogen 7727-37-9 Not Listed

#### U.S. - OSHA - Specifically Regulated Chemicals

• Ethane 74-84-0 Not Listed

- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### Environment

#### U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - CERCLA/SARA - Section 313 - Emission Reporting

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### **United States - California**

#### **Environment**

#### U.S. - California - Proposition 65 - Carcinogens List

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - California - Proposition 65 - Developmental Toxicity

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed

• Nitrogen 7727-37-9 Not Listed

#### U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - California - Proposition 65 - Reproductive Toxicity - Female

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - California - Proposition 65 - Reproductive Toxicity - Male

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### United States - Pennsylvania

#### Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

- Ethane 74-84-0 Not Listed
- Oxygen 7782-44-7 Not Listed
- Nitrogen 7727-37-9 Not Listed

#### Section 16 - Other Information

## Last Revision Date

## Preparation Date

# Disclaimer/Statement of Liability

- 09/September/2013
- 13/November/2012
- To the best of Air Liquide's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

#### Key to abbreviations

NDA = No Data Available