

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mixture

**Product Name:** Formical-2000

**Product Code:** 1314-1,1314-5,1314-32

### Intended Use of the Product

**Use of the Substance/Mixture:** No use is specified.

### Name, Address, and Telephone of the Responsible Party

#### **Company**

StatLab Medical Products

2090 Commerce Drive

McKinney, TX 75069

800-442-3573

[www.statlab.com](http://www.statlab.com)

### Emergency Telephone Number

**Emergency Number** : CHEMTREC 800-424-9300 (USA & Canada)

CHEMTREC 703-527-3887 (International)

Non-transport 800-225-8867 (USA)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Skin Corrosion 1B H314

Eye Damage 1 H318

Full text of H-phrases: see section 16

### Label Elements

#### **GHS-US Labeling**

#### **Hazard Pictograms (GHS-US)**

:



GHS05

#### **Signal Word (GHS-US)**

: Danger

#### **Hazard Statements (GHS-US)**

: H314 - Causes severe skin burns and eye damage.

H318 - Causes serious eye damage.

#### **Precautionary Statements (GHS-US)**

: P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P330+P331 - If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353+P363 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a poison center or doctor.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### Other Hazards

May be corrosive to respiratory tract.

# Formical-2000

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Unknown Acute Toxicity (GHS-US)** Not available

### SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

#### Mixture

| Name        | Product Identifier | % (w/w) | Classification (GHS-US)                                                                                                                                                           |
|-------------|--------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Formic acid | (CAS No) 64-18-6   | 23      | Flammable Liquid 4, H227<br>Acute Toxicity 4 (Oral), H302<br>Acute Toxicity 3 (Inhalation: vapor), H331<br>Skin Corrosion 1A, H314<br>Eye Damage 1, H318<br>Aquatic Acute 3, H402 |

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. If you feel unwell, seek medical advice.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with plenty of water for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

#### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes severe skin burns and eye damage.

**Inhalation:** Contact may cause immediate severe irritation progressing quickly to chemical burns.

**Skin Contact:** Corrosive. Causes burns. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Eye Contact:** Causes serious eye damage. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision. Causes permanent damage to the cornea, iris, or conjunctiva.

**Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** None expected under normal conditions of use.

#### Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

### SECTION 5: FIRE-FIGHTING MEASURES

#### Extinguishing Media

**Suitable Extinguishing Media:** Powder, alcohol-resistant foam, water spray, carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

**Reactivity:** May be mildly corrosive to some materials.

#### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides.

#### Reference to Other Sections

Refer to section 9 for flammability properties.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing.

# Formical-2000

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### Environmental Precautions

Prevent entry to sewers and public waters.

### Methods and Material for Containment and Cleaning Up

**For Containment:** Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely.

### Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. For further information refer to section 13.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Precautions for Safe Handling:** Do not handle until all safety precautions have been read and understood.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product.

### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store locked up.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Amines. Metals.

### Specific End Use(s)

No use is specified.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

| Formic acid (64-18-6) |                                      |                       |
|-----------------------|--------------------------------------|-----------------------|
| USA ACGIH             | ACGIH TWA (ppm)                      | 5 ppm                 |
| USA ACGIH             | ACGIH STEL (ppm)                     | 10 ppm                |
| USA OSHA              | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 9 mg/m <sup>3</sup>   |
| USA OSHA              | OSHA PEL (TWA) (ppm)                 | 5 ppm                 |
| USA NIOSH             | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 9 mg/m <sup>3</sup>   |
| USA NIOSH             | NIOSH REL (TWA) (ppm)                | 5 ppm                 |
| USA IDLH              | US IDLH (ppm)                        | 30 ppm                |
| Alberta               | OEL STEL (mg/m <sup>3</sup> )        | 19 mg/m <sup>3</sup>  |
| Alberta               | OEL STEL (ppm)                       | 10 ppm                |
| Alberta               | OEL TWA (mg/m <sup>3</sup> )         | 9.4 mg/m <sup>3</sup> |
| Alberta               | OEL TWA (ppm)                        | 5 ppm                 |
| British Columbia      | OEL STEL (ppm)                       | 10 ppm                |
| British Columbia      | OEL TWA (ppm)                        | 5 ppm                 |
| Manitoba              | OEL STEL (ppm)                       | 10 ppm                |
| Manitoba              | OEL TWA (ppm)                        | 5 ppm                 |
| New Brunswick         | OEL STEL (mg/m <sup>3</sup> )        | 19 mg/m <sup>3</sup>  |
| New Brunswick         | OEL STEL (ppm)                       | 10 ppm                |
| New Brunswick         | OEL TWA (mg/m <sup>3</sup> )         | 9.4 mg/m <sup>3</sup> |
| New Brunswick         | OEL TWA (ppm)                        | 5 ppm                 |

# Formical-2000

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|                         |                               |                       |
|-------------------------|-------------------------------|-----------------------|
| Newfoundland & Labrador | OEL STEL (ppm)                | 10 ppm                |
| Newfoundland & Labrador | OEL TWA (ppm)                 | 5 ppm                 |
| Nova Scotia             | OEL STEL (ppm)                | 10 ppm                |
| Nova Scotia             | OEL TWA (ppm)                 | 5 ppm                 |
| Nunavut                 | OEL STEL (mg/m <sup>3</sup> ) | 18 mg/m <sup>3</sup>  |
| Nunavut                 | OEL STEL (ppm)                | 10 ppm                |
| Nunavut                 | OEL TWA (mg/m <sup>3</sup> )  | 9 mg/m <sup>3</sup>   |
| Nunavut                 | OEL TWA (ppm)                 | 5 ppm                 |
| Northwest Territories   | OEL STEL (mg/m <sup>3</sup> ) | 18 mg/m <sup>3</sup>  |
| Northwest Territories   | OEL STEL (ppm)                | 10 ppm                |
| Northwest Territories   | OEL TWA (mg/m <sup>3</sup> )  | 9 mg/m <sup>3</sup>   |
| Northwest Territories   | OEL TWA (ppm)                 | 5 ppm                 |
| Ontario                 | OEL STEL (ppm)                | 10 ppm                |
| Ontario                 | OEL TWA (ppm)                 | 5 ppm                 |
| Prince Edward Island    | OEL STEL (ppm)                | 10 ppm                |
| Prince Edward Island    | OEL TWA (ppm)                 | 5 ppm                 |
| Québec                  | VECD (mg/m <sup>3</sup> )     | 19 mg/m <sup>3</sup>  |
| Québec                  | VECD (ppm)                    | 10 ppm                |
| Québec                  | VEMP (mg/m <sup>3</sup> )     | 9.4 mg/m <sup>3</sup> |
| Québec                  | VEMP (ppm)                    | 5 ppm                 |
| Saskatchewan            | OEL STEL (ppm)                | 10 ppm                |
| Saskatchewan            | OEL TWA (ppm)                 | 5 ppm                 |
| Yukon                   | OEL STEL (mg/m <sup>3</sup> ) | 9 mg/m <sup>3</sup>   |
| Yukon                   | OEL STEL (ppm)                | 5 ppm                 |
| Yukon                   | OEL TWA (mg/m <sup>3</sup> )  | 9 mg/m <sup>3</sup>   |
| Yukon                   | OEL TWA (ppm)                 | 5 ppm                 |

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Gloves. Safety glasses. Face shield. Protective clothing.



**Materials for Protective Clothing:** Corrosion-proof clothing.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical safety goggles and face shield.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

|                  |                    |
|------------------|--------------------|
| Physical State   | : Liquid           |
| Appearance       | : Clear, colorless |
| Odor             | : Not available    |
| Odor Threshold   | : Not available    |
| pH               | : 1.3 - 1.7        |
| Evaporation Rate | : Not available    |
| Melting Point    | : Not available    |

# Formical-2000

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|                                                   |                                                                        |
|---------------------------------------------------|------------------------------------------------------------------------|
| Freezing Point                                    | : Not available                                                        |
| Boiling Point                                     | : Not available                                                        |
| Flash Point                                       | : Not available                                                        |
| Auto-ignition Temperature                         | : Not available                                                        |
| Decomposition Temperature                         | : Not available                                                        |
| Flammability (solid, gas)                         | : Not available                                                        |
| Lower Flammable Limit                             | : Not available                                                        |
| Upper Flammable Limit                             | : Not available                                                        |
| Vapor Pressure                                    | : Not available                                                        |
| Relative Vapor Density at 20 °C                   | : Not available                                                        |
| Relative Density                                  | : Not available                                                        |
| Specific Gravity                                  | : 1.03 - 1.05                                                          |
| Solubility                                        | : Soluble in water                                                     |
| Partition Coefficient: N-Octanol/Water            | : Not available                                                        |
| Viscosity                                         | : Not available                                                        |
| Explosion Data – Sensitivity to Mechanical Impact | : Not expected to present an explosion hazard due to mechanical impact |
| Explosion Data – Sensitivity to Static Discharge  | : Not expected to present an explosion hazard due to static discharge  |

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** May be mildly corrosive to some materials.

**Chemical Stability:** The product is stable at normal handling and storage conditions.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Metal. Amines.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>).

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes severe skin burns and eye damage

**pH:** 1.3 - 1.7

**Serious Eye Damage/Irritation:** Causes serious eye damage

**pH:** 1.3 - 1.7

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Contact may cause immediate severe irritation progressing quickly to chemical burns

**Symptoms/Injuries After Skin Contact:** Corrosive. Causes burns. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis

**Symptoms/Injuries After Eye Contact:** Causes serious eye damage. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision. Causes permanent damage to the cornea, iris, or conjunctiva

**Symptoms/Injuries After Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract

**Chronic Symptoms:** None expected under normal conditions of use

# Formical-2000

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

|                                        |              |
|----------------------------------------|--------------|
| Formic acid (64-18-6)                  |              |
| LD50 Oral Rat                          | 1100 mg/kg   |
| LC50 Inhalation Rat (Vapors - mg/l/4h) | 7.85 mg/l/4h |

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

|                       |                                                                          |
|-----------------------|--------------------------------------------------------------------------|
| Formic acid (64-18-6) |                                                                          |
| EC50 Daphnia 1        | 120 mg/l (Exposure time: 48 h - Species: Daphnia magna)                  |
| EC50 Daphnia 2        | 138 - 165.6 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| ErC50 (algae)         | 25 mg/l                                                                  |

### Persistence and Degradability

|                               |                  |
|-------------------------------|------------------|
| Formical-2000                 |                  |
| Persistence and Degradability | Not established. |

### Bioaccumulative Potential

|                           |                  |
|---------------------------|------------------|
| Formical-2000             |                  |
| Bioaccumulative Potential | Not established. |
| Formic acid (64-18-6)     |                  |
| BCF Fish 1                | 0.22             |
| Log Pow                   | -0.54            |

### Mobility in Soil Not available

### Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## SECTION 14: TRANSPORT INFORMATION

### In Accordance With ICAO/IATA/DOT/TDG

#### 14.1. UN Number

UN-No.(DOT) : 3412  
DOT NA no. : UN3412

#### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Formic acid with not less than 10% but not more than 85% acid by mass  
Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136  
Hazard Labels (DOT) : 8 - Corrosive



Packing Group (DOT) : II - Medium Danger

# Formical-2000

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**DOT Special Provisions (49 CFR 172.102)** : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $95 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula:  $a = (d_{15} - d_{50}) / 35d_{50}$  Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

**DOT Packaging Exceptions (49 CFR 173.xxx)** : 154

**DOT Packaging Non Bulk (49 CFR 173.xxx)** : 202

**DOT Packaging Bulk (49 CFR 173.xxx)** : 242

### 14.3. Additional Information

**Emergency Response Guide (ERG) Number** : 153

### Transport by Sea

**DOT Vessel Stowage Location** : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

**DOT Vessel Stowage Other** : 40 - Stow "clear of living quarters"

**EmS-No. (1)** : F-A

**EmS-No. (2)** : S-B

### Air Transport

**DOT Quantity Limitations Passenger** : 1 L

**Aircraft/Rail (49 CFR 173.27)**

**DOT Quantity Limitations Cargo Aircraft** : 30 L

**Only (49 CFR 175.75)**

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

|                                                                           |                                 |
|---------------------------------------------------------------------------|---------------------------------|
| <b>Formical-2000</b>                                                      |                                 |
| <b>SARA Section 311/312 Hazard Classes</b>                                | Immediate (acute) health hazard |
| <b>Formic acid (64-18-6)</b>                                              |                                 |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                 |
| Listed on United States SARA Section 313                                  |                                 |
| <b>SARA Section 313 - Emission Reporting</b>                              | 1.0 %                           |

### US State Regulations

|                                                                       |  |
|-----------------------------------------------------------------------|--|
| <b>Formic acid (64-18-6)</b>                                          |  |
| U.S. - Massachusetts - Right To Know List                             |  |
| U.S. - New Jersey - Right to Know Hazardous Substance List            |  |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |  |
| U.S. - Pennsylvania - RTK (Right to Know) List                        |  |

### Canadian Regulations

|                             |                                                                                                               |
|-----------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>Formical-2000</b>        |                                                                                                               |
| <b>WHMIS Classification</b> | Class D Division 2 Subdivision B - Toxic material causing other toxic effects<br>Class E - Corrosive Material |

# Formical-2000

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations



### Formic acid (64-18-6)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification

Class B Division 3 - Combustible Liquid

Class E - Corrosive Material

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 08/04/2015

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

|                                  |                                                                |
|----------------------------------|----------------------------------------------------------------|
| Acute Tox. 3 (Inhalation: vapor) | Acute toxicity (inhalation: vapor) Category 3                  |
| Acute Tox. 4 (Oral)              | Acute toxicity (oral) Category 4                               |
| Aquatic Acute 3                  | Hazardous to the aquatic environment - Acute Hazard Category 3 |
| Eye Dam. 1                       | Serious eye damage/eye irritation Category 1                   |
| Flam. Liq. 4                     | Flammable liquids Category 4                                   |
| Skin Corr. 1A                    | Skin corrosion/irritation Category 1A                          |
| Skin Corr. 1B                    | Skin corrosion/irritation Category 1B                          |
| H227                             | Combustible liquid                                             |
| H302                             | Harmful if swallowed                                           |
| H314                             | Causes severe skin burns and eye damage                        |
| H318                             | Causes serious eye damage                                      |
| H331                             | Toxic if inhaled                                               |
| H402                             | Harmful to aquatic life                                        |

### NFPA Health Hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

### NFPA Fire Hazard

: 1 - Must be preheated before ignition can occur.

### NFPA Reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

#### Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

#### Flammability

: 1 Slight Hazard

#### Physical

: 0 Minimal Hazard

### Party Responsible for the Preparation of This Document

StatLab Medical Products

Phone Number: 800-442-3573

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS