Safety Data Sheet



Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • Carbon Dioxide (1 - 25%), Helium (1 - 10%), Argon (Balance)

Synonyms BLUESHIELD 211, ARCAL 121, ARCAL 211

Product Code • 10015

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Shielding gas for arc welding.

1.3 Details of the supplier of the safety data sheet

Manufacturer • Air Liquide

2700 Post Oak Blvd. Houston, TX 77056 United States www.us.airliquide.com

www.us.airliquide.com sds@airliquide.com

Telephone (Technical) • 713-896-2896 Telephone (Technical) • 800-819-1704

1.4 Emergency telephone number

Manufacturer 800-424-9300 - CHEMTREC

Manufacturer +1 703-527-3887 - Outside United States

Section 2: Hazards Identification

EU/EEC

According to EU Directive 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP Compressed Gas - H280

DSD/DPD • Not classified

2.2 Label Elements

CLP

WARNING



Hazard statements • H280 - Contains gas under pressure; may explode if heated

Precautionary statements

Storage/Disposal • P403 - Store in a well-ventilated place.

DSD/DPD

Risk phrases . No label element(s) required

2.3 Other Hazards

CLP

 This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.
 Inhalation of carbon dioxide can increase respiration and heart rate.
 According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

DSD/DPD

 This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.
 Inhalation of carbon dioxide can increase respiration and heart rate.
 According to European Directive 1999/45/EC this preparation is not considered dangerous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

 Compressed Gas - H280 Simple Asphyxiant

2.2 Label elements

OSHA HCS 2012

WARNING



Hazard statements • Contains gas under pressure; may explode if heated - H280 May displace oxygen and cause rapid suffocation.

Precautionary statements

Storage/Disposal Store in a well-ventilated place. - P403

2.3 Other hazards

OSHA HCS 2012

 Inhalation of carbon dioxide can increase respiration and heart rate. Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

Compressed Gas - A

2.2 Label elements

WHMIS



Compressed Gas - A

2.3 Other hazards

WHMIS

Inhalation of carbon dioxide can increase respiration and heart rate.
 This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.
 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

2.4 Other information



Section 3 - Composition/Information on Ingredients

3.1 Substances

 Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

Hazardous Components							
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments		
Argon	CAS:7440-37-1 EC Number:231- 147-0	65% TO 98%	NDA	EU DSD/DPD: Not Classified - Criteria not met EU CLP: Self Classified - Press. Gas - Comp., H280 OSHA HCS 2012: Press. Gas - Comp.; Simple Asphyx.	Balance		
Carbon dioxide	CAS:124-38-9 EC Number:204- 696-9	1% TO 25%	Inhalation-Rat LC50 • 470000 ppm 30 Minute(s)	EU DSD/DPD: Not Classified - Criteria not met EU CLP: Self Classified - Press. Gas - Comp., H280 OSHA HCS 2012: Press. Gas - Comp.; Simp. Asphyx.	NDA		
Helium	CAS:7440-59-7 EINECS:231-168-5	1% TO 10%	NDA	EU DSD/DPD: Not Classified - Criteria not met EU CLP: Self Classified - Press. Gas - Comp., H280 OSHA HCS 2012: Press. Gas - Comp.; Simple Asphyx.;	NDA		

See Section 16 for full text of H-statements and R-phrases.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

Ingestion

Skin

Eve

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Get medical attention immediately if symptoms occur.

If contact with eyes directly, flush with gently flowing fresh water thoroughly. Get medical attention immediately if symptoms occur.

If swallowed, rinse mouth with water (only if the person is conscious) Never give anything by mouth to an unconscious person. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

4.4 Other information

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO GASES WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus must be worn. Victim(s) who experience any adverse effect after overexposure to this gas mixture must be taken for medical attention. Rescuers should be taken for medical attention if necessary. Take a copy of the label and the MSDS to physician or other health professional with victim(s).

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media . Use extinguishing agent suitable for type of surrounding fire.

SMALL FIRES: Dry chemical or CO2. LARGE FIRES: Water spray or fog.

Unsuitable Extinguishing Media

No data available

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

Containers may explode when heated. Ruptured cylinders may rocket.

Hazardous Combustion Products

No data available

5.3 Advice for firefighters

Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

Wear positive pressure self-contained breathing apparatus (SCBA).

Move containers from fire area if you can do it without risk.

FIRE: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

FIRE INVOLVING TANKS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.

FIRE INVOLVING TANKS: Cool containers with flooding quantities of water until well after fire is out.

FIRE INVOLVING TANKS: Do not direct water at source of leak or safety devices; icing may occur.

FIRE INVOLVING TANKS: Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.

FIRE INVOLVING TANKS: ALWAYS stay away from tanks engulfed in fire.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ventilate the area before entry.

Emergency Procedures

 Stop leak if you can do it without risk. Keep unauthorized personnel away. Keep out of low areas. Stay upwind. Do not direct water at spill or source of leak. LARGE SPILL: Consider initial downwind evacuation for at least 500 meters (1/3 mile)

6.2 Environmental precautions

Prevent spreading of vapors through sewers, ventilation systems and confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

Stop leak if you can do it without risk.

Do not direct water at spill or source of leak.

Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container.

If possible, turn leaking containers so that gas escapes rather than liquid.

Isolate area until gas has dispersed.

Ventilate the area.

Allow substance to evaporate.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

• Use only with adequate ventilation. Ventilate closed spaces before entering. Be aware of any signs of dizziness or fatigue, especially if work is done in a poorly ventilated area; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms, due to olfactory fatigue or oxygen deficiency. Cylinders should be firmly secured to prevent falling or being knocked-over. Do not attempt to repair, adjust, or in any other way modify cylinders. If there is a malfunction or another type of operational problem, contact nearest distributor immediately. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Store in a cool, dry, well-ventilated place. Protect cylinders against physical damage.
 Cylinders should be firmly secured to prevent falling or being knocked-over.

7.3 Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

			Exposure Limit	s/Gui	idelines			
	Result	ACGIH	Canada Ontario	Ca	nada Quebec	China	Europe	
Carbon dioxide	TWAs	5000 ppm TWA	5000 ppm TWA) ppm TWAEV;) mg/m3 TWAEV	9000 mg/m3 TWA	5000 ppm TWA; 9000 mg/m3 TWA	
(124-38-9)	STELs	30000 ppm STEL	30000 ppm STEL		00 ppm STEV; 00 mg/m3 STEV	18000 mg/m3 STEL	Not established	
		Ex	posure Limits/G	uideli	nes (Con't.)			
	Result	France	Germany DFG	G	ermany TRGS	Ireland	Israel	
	TWAs	5000 ppm TWA [VME] (indicative limit); 9000 mg/m3 TWA [VME] (indicative limit)	Not established	(exp	o ppm TWA AGW osure factor 2); o mg/m3 TWA V (exposure or 2)	5000 ppm TWA; 9000 mg/m3 TWA	5000 ppm TWA	
Carbon dioxide	STELs	Not established	Not established	Not e	established	Not established	30000 ppm STEL	
(124-38-9)	Ceilings	Not established	10000 ppm Peak; 18200 mg/m3 Peak	Not e	established	Not established	Not established	
	MAKs	Not established	5000 ppm TWA MAK 9100 mg/m3 TWA MAK		established	Not established	Not established	
		E	posure Limits/G	uideli	nes (Con't.)			
	Result	Italy	NIOSH		OSHA	Portugal	Spain	
	STELs	Not established	30000 ppm STEL; 54000 mg/m3 STEL	Not e	established	30000 ppm STEL [VLE-CD	Not established	
Carbon dioxide (124-38-9)	TWAs	5000 ppm TWA; 9000 mg/m3 TWA	5000 ppm TWA; 9000 mg/m3 TWA		ppm TWA; 9000 n3 TWA	5000 ppm TWA [VLE- MP]	5000 ppm TWA [VLA- ED] (indicative limit value); 9150 mg/m3 TWA [VLA-ED] (indicative limit value)	
		E	posure Limits/G	uideli	nes (Con't.)			
			Result		Sweden			
Carbon dioxide		STELs			10000 ppm STV; 18000 mg/m3 STV			
(124-38-9)			TWAs	VAs 5000 ppm LLV; 9000 mg/m3 LLV				

Exposure Control Notations

Portugal

Argon (7440-37-1): Simple Asphyxiants: (Simple Asphyxiant)
 Helium (7440-59-7): Simple Asphyxiants: (Simple Asphyxiant)

Ireland

Argon (7440-37-1): Simple Asphyxiants: (Asphyxiant)
 Helium (7440-59-7): Simple Asphyxiants: (Asphyxiant)

Spain

Argon (7440-37-1): Simple Asphyxiants: (simple asphyxiant)
 Helium (7440-59-7): Simple Asphyxiants: (simple asphyxiant)

8.2 Exposure controls

Engineering Measures/Controls

 Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof - electrical, ventilating and/or lighting equipment.

Personal Protective Equipment

Respiratory

 In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face Skin/Body

- Wear safety glasses.
- Wear leather gloves when handling cylinders.

Environmental Exposure Controls

 Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene
NIOSH = National Institute of Occupational Safety and Health
OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures
TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description					
Physical Form	Gas	Appearance/Description	Nonflammable compressed colorless odorless gas.		
Color	Colorless	Odor	Odorless		
Odor Threshold	Data lacking				
General Properties		•			
Boiling Point	-185.9 C(-302.62 F)	Melting Point	-189.4 C(-308.92 F)		
Decomposition Temperature	Data lacking	рН	Data lacking		
Specific Gravity/Relative Density	Data lacking	Water Solubility	0.0537 % @ 0 C(32 F)		
Solvent Solubility	Data lacking	Viscosity	Data lacking		
Explosive Properties	Not relevant.	Oxidizing Properties:	Not an oxidizer.		
Volatility		•	·		
Vapor Pressure	Data lacking	ta lacking Vapor Density 1.38 Air=1			
Evaporation Rate	Data lacking				
Flammability					
Flash Point	Not relevant	UEL	Not relevant		
LEL	Not relevant	Autoignition	Not relevant		
Flammability (solid, gas)	Not flammable.				
Environmental					
Octanol/Water Partition coefficient	Data lacking				

9.2 Other Information

No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4 Conditions to avoid

 Avoid exposing cylinders to extremely high temperatures, which could cause cylinders to rupture.

10.5 Incompatible materials

Carbon Dioxide, a component of this gas mixture, will ignite and explode when heated
with powdered aluminum, beryllium, cerium alloys, chromium, magnesium-aluminum
alloys, manganese, thorium, titanium, and zirconium. In the presence of moisture,
Carbon Dioxide will ignite with cesium oxide. Metal acetylides will also ignite and
explode on contact with Carbon Dioxide.

10.6 Hazardous decomposition products

None known.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Component Name	CAS	Data		
Carbon dioxide (1% TO 25%)	124-38-9	Acute Toxicity: ihl-rat LC50:470000 ppm/30M; Reproductive: ihl-rat TCLo:6 pph/24H (10D preg)		
GHS Properties	l	Classification		
Acute toxicity		EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met		
Aspiration Hazard		EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met		
Carcinogenicity		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met		
Germ Cell Mutagenicity		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met		
Skin corrosion/Irritation		U/CLP Classification criteria not met SHA HCS 2012 Classification criteria not met		
Skin sensitization		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met		
STOT-RE		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met		
STOT-SE		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met		
Toxicity for Reproduction		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met		
Respiratory sensitization		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met		
Serious eye damage/Irritation		EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met		

Route(s) of entry/exposure **Potential Health Effects** Inhalation

Inhalation, Skin, Eye, Ingestion

Acute (Immediate)

This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. Inhalation of carbon dioxide can increase respiration and heart rate. If this material is released in a small, poorly ventilated area (i.e. an enclosed or confined space), an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of overexposure, death may occur. The following effects associated with decreased levels of oxygen: increase in breathing and pulse rate, emotional upset, abnormal fatigue, nausea, vomiting, collapse, loss of consciousness, convulsive movements, respiratory collapse and death.

Chronic (Delayed)

No data available

Skin

Acute (Immediate)

Chronic (Delayed)

Under normal conditions of use, no health effects are expected.

No data available

Acute (Immediate)

Chronic (Delayed)

Ingestion

Acute (Immediate)

Chronic (Delayed)

Carcinogenic Effects

Under normal conditions of use, no health effects are expected.

No data available

Under normal conditions of use, no health effects are expected.

No data available

The components of this gas mixture are not found on the following lists: FEDERAL OSHA Z LIST, NTP and IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

Key to abbreviations

TC = Toxic Concentration LC = Lethal Concentration

Section 12 - Ecological Information

12.1 Toxicity

This gas mixture is not expected to cause significant harm to terrestrial or aquatic organisms.

12.2 Persistence and degradability

Material data lacking.

12.3 Bioaccumulative potential

Material data lacking.

12.4 Mobility in Soil

Material data lacking.

12.5 Results of PBT and vPvB assessment

PBT and vPvB assessment has not been conducted for this material.

12.6 Other adverse effects

Potential Environmental

No adverse ecological effects are expected.

Effects

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1956	Compressed gases, n.o.s. (Argon, Carbon Dioxide) or (Argon, Helium)	2.2	NDA	NDA
TDG	UN1956	COMPRESSED GASES, N.O.S. (Argon, Carbon Dioxide) or (Argon, Helium)	2.2	NDA	NDA
IMO/IMDG	UN1956	COMPRESSED GASES, N.O.S. (Argon, Carbon Dioxide) or (Argon, Helium)	2.2	NDA	NDA
IATA/ICAO	UN1956	Compressed gases, n.o.s. (Argon, Carbon Dioxide) or (Argon, Helium)	2.2	NDA	NDA

14.6 Special precautions for user

Cylinders should be transported in a secure position, in a well-ventilated vehicle. The
transportation of compressed gas cylinders in automobiles or in closed-body vehicles
can present serious safety hazards. If transporting these cylinders in vehicles, ensure
these cylinders are not exposed to extremely high temperatures (as may occur in an
enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated
during transportation.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Pressure(Sudden Release of)

State Right To Know							
Component	CAS	MA	NJ	PA			
Argon	7440-37-1	Yes	Yes	Yes			
Carbon dioxide	124-38-9	Yes	Yes	Yes			
Helium	7440-59-7	Yes	Yes	Yes			

Inventory								
Component	CAS	Canada D	SL	Canada NDSL	China	EU EINEC	S	EU ELNICS
Argon	7440-37-1	Yes		No	Yes	Yes		No
Carbon dioxide	124-38-9	Yes		No	Yes	Yes		No
Helium	7440-59-7	Yes		No	Yes	Yes		No
				Inventory (Co	n't.)			
Component CAS Japan ENCS Korea KECL TSCA					SCA			
Argon	744	0-37-1		No	Yes			Yes
Carbon dioxide	124	-38-9		Yes	Yes			Yes
Helium	744	0-59-7		No	Yes			Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Carbon dioxide 124-38-9 1% TO 25% A; Uncontrolled product according to WHMIS classification criteria (solid)

Argon
 Helium
 7440-37-1
 65% TO 98% A
 Ho TO 10% A

Canada - WHMIS - Ingredient Disclosure List

Carbon dioxide 124-38-9 1% TO 25% 1%
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

Environment

Canada - CEPA - Priority Substances List

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

China

Environment

China - Ozone Depleting Substances - First Schedule

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

China - Ozone Depleting Substances - Second Schedule

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

China - Ozone Depleting Substances - Third Schedule

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

Other

China - Annex I & II - Controlled Chemicals Lists

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

China - Dangerous Goods List

• Carbon dioxide 124-38-9 1% TO 25% UN1013; UN1845 PG = III; UN2187

Argon 7440-37-1 65% TO 98% UN1006; UN1951
 Helium 7440-59-7 1% TO 10% UN1046; UN1963

China - Export Control List - Part I Chemicals

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

Europe

_other

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

```
    Carbon dioxide 124-38-9 1% TO 25% Not Listed
    Argon 7440-37-1 65% TO 98% Not Listed
    Helium 7440-59-7 1% TO 10% Not Listed
```

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

```
    Carbon dioxide 124-38-9 1% TO 25% Not Listed
    Argon 7440-37-1 65% TO 98% Not Listed
    Helium 7440-59-7 1% TO 10% Not Listed
```

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

```
    Carbon dioxide 124-38-9 1% TO 25% Not Listed
    Argon 7440-37-1 65% TO 98% Not Listed
    Helium 7440-59-7 1% TO 10% Not Listed
```

Germany

Environment[®]

Germany - TA Luft - Types and Classes

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

Germany - Water Classification (VwVwS) - Annex 1

Carbon dioxide 124-38-9 1% TO 25% ID Number 256, not considered hazardous to water
 Argon 7440-37-1 65% TO 98% ID Number 1348, not considered hazardous to water

• Helium 7440-59-7 1% TO 10% Not Listed

Germany - Water Classification (VwVwS) - Annex 2 - Water Hazard Classes

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

Germany - Water Classification (VwVwS) - Annex 3

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

Other

Germany - Specifically Regulated Chemicals in TRGS

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

_

Mexico

Other

Mexico - Hazard Classifications

Carbon dioxide 124-38-9
 1% TO 25%
 Hazard Class = 2.2 UN1013; Hazard Class = 9 PG = III UN1845; Hazard Class = 2.3 UN2187

Argon
 Helium
 7440-37-1
 65% TO 98%
 Hazard Class = 2.2 UN1006; Hazard Class = 2.2 UN1951
 Hazard Class = 2.2 UN1046; Hazard Class = 2.2 UN1963

Mexico - Regulated Substances

Carbon dioxide 124-38-9 1% TO 25% UN1013; UN1845; UN2187

Argon
 Helium
 7440-37-1
 65% TO 98%
 UN1006; UN1951
 UN1046; UN1963
 UN1046; UN1963

Portugal

Other

Portugal - Prohibited Substances

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

United Kingdom

Environment

United Kingdom - Pollution Inventory - Schedule 1 - Thresholds for Releases to Air

• Carbon 10000000 kg (qualifying renewable fuel sources are reportable when the total amount of CO2

dioxide 124-38-9 1% TO 25% released is above 10 million kg); 10000000 kg

Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

United Kingdom - Substances Contained in Dangerous Substances or Preparations

Carbon dioxide 124-38-9 1% TO 25% Not Listed

Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

Other

United Kingdom - Workplace Exposure Limits (WELs) - Substances in Review

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

United Kingdom - The Red List - Dangerous Substances in Water

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

Environment⁻

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

United States - California

-Environment

U.S. - California - Proposition 65 - Carcinogens List

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

Carbon dioxide 124-38-9 1% TO 25% Not Listed
 Argon 7440-37-1 65% TO 98% Not Listed
 Helium 7440-59-7 1% TO 10% Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

```
    Carbon dioxide 124-38-9 1% TO 25% Not Listed
    Argon 7440-37-1 65% TO 98% Not Listed
    Helium 7440-59-7 1% TO 10% Not Listed
```

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

```
    Carbon dioxide 124-38-9 1% TO 25% Not Listed
    Argon 7440-37-1 65% TO 98% Not Listed
    Helium 7440-59-7 1% TO 10% Not Listed
```

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

```
    Carbon dioxide 124-38-9 1% TO 25% Not Listed
    Argon 7440-37-1 65% TO 98% Not Listed
    Helium 7440-59-7 1% TO 10% Not Listed
```

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

```
    Carbon dioxide 124-38-9 1% TO 25% Not Listed
    Argon 7440-37-1 65% TO 98% Not Listed
    Helium 7440-59-7 1% TO 10% Not Listed
```

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

```
    Carbon dioxide 124-38-9 1% TO 25% Not Listed
    Argon 7440-37-1 65% TO 98% Not Listed
    Helium 7440-59-7 1% TO 10% Not Listed
```

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

•	Carbon dioxide	124-38-9	1% TO 25%	Not Listed
•	Argon	7440-37-1	65% TO 98%	Not Listed
•	Helium	7440-59-7	1% TO 10%	Not Listed

_

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Last Revision Date Preparation Date Disclaimer/Statement of Liability

- . 25/April/2013
- 25/April/2013
- To the best of Air Liquide's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

Key to abbreviations NDA = No Data Available