

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 01/15/2015 Supersedes: 12/31/2014 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture

Product name : Nitrogen Dioxide (2.30% - 2.99%) in Air

SG-2002-00837 Product code

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

Details of the supplier of the safety data sheet

Air Liquide America Specialty Gases 6141 Easton Rd Plumsteadville, PA 18949 - USA T 1.800.217.2688

www.airliquide.com

Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification (GHS-US)

Ox. Gas 1 H270 Compressed gas H280 Acute Tox. 3 (Inhalation:gas) H331 Skin Irrit. 2 H315 Eve Irrit. 2A H319 STOT SE 2 H371

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS04



GHS06





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H270 - May cause or intensify fire; oxidizer

H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H371 - May cause damage to organs (lung) (Inhalation)

CGA-HG11 - Symptoms may be delayed

P202 - Do not handle until all safety precautions have been read and understood Precautionary statements (GHS-US)

P220 - Keep/Store away from combustible materials, clothing

P244 - Keep reduction valves/valves and fittings free from oil and grease

P260 - Do not breathe gas

P262 - Do not get in eyes, on skin, or on clothing

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, protective clothing, eye protection, face protection

P284 - Wear respiratory protection. Consult respirator supplier's product information for the

selection of the appropriate respiratory protection.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P308+P313 - If exposed or concerned: Get medical advice/attention

P370+P376 - In case of fire: Stop leak if safe to do so

P403 - Store in a well-ventilated place

P405 - Store locked up

01/29/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container in accordance with local/regional/national/international

regulations

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

CGA-PG05 - Use a back flow preventive device in the piping CGA-PG06 - Close valve after each use and when empty CGA-PG10 - Use only with equipment rated for cylinder pressure

CGA-PG14 - Approach suspected leak area with caution

CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug CGA-PG20 - Use only with equipment of compatible materials of construction

CGA-PG21 - Open valve slowly

CGA-PG22 - Use only with equipment cleaned for oxygen service

Other hazards

Other hazards not contributing to the classification

: None.

Unknown acute toxicity (GHS-US) 2.4.

Not applicable

SECTION 3: Composition/information on ingredients

3.1. **Substance**

Not applicable

3.2. **Mixture**

Name	Product identifier	%	Classification (GHS-US)
Compressed air	(CAS No) 132259-10-0	97.01 - 97.7	Compressed gas, H280
Nitrogen dioxide	(CAS No) 10102-44-0	2.3 - 2.99	Ox. Gas 1, H270 Liquefied gas, H280 Acute Tox. 1 (Inhalation:gas), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 2, H371

Full text of H-phrases: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : If skin irritation or rash occurs: Rinse skin with water/shower, Get medical advice/attention.

Immediately flush eyes thoroughly with water for at least 15 minutes. If eye irritation develops, First-aid measures after eye contact

seek medical attention.

First-aid measures after ingestion Ingestion is not considered a potential route of exposure.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Toxic if inhaled. May cause damage to organs (lung) through single exposure (inhalation). If

you feel unwell, seek medical advice.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms/injuries after eye contact Causes serious eye irritation.

Symptoms/injuries after ingestion Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous Not known.

administration

: None known. Chronic symptoms

Indication of any immediate medical attention and special treatment needed

If breathing is difficult, give oxygen. Obtain medical attention if breathing difficulty persists.

SECTION 5: Firefighting measures

Extinguishing media 5.1.

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

52 Special hazards arising from the substance or mixture

Fire hazard : The product is not flammable.

01/29/2015 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire

and increasing risk of burns and injuries.

Reactivity : None known.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray

or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Do not enter fire area without proper protective equipment, including respiratory

protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.

Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent

premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep

upwind.

6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Equip cleanup crew with proper protection.

Emergency procedures : Evacuate and limit access. Ventilate area

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if safe to do so.

Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder

pressure.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or

in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in

use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.

Incompatible products : None known

Incompatible materials : Flammable materials. Combustible materials.

7.3. Specific end use(s)

Test gas/Calibration gas.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nitrogen Dioxide (2.30% - 2.99%) in Air	
ACGIH Not applicable	
OSHA Not applicable	
Nitrogen dioxide (10102-44-0)	

Nitrogen dioxide (10102-44-0	Nitrogen dioxide (10102-44-0)		
ACGIH	ACGIH TWA (ppm)	0.2 ppm	
OSHA	OSHA PEL (Ceiling) (mg/m³)	9 mg/m³	

01/29/2015 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitrogen dioxide (10102-44-0)			
OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm	
Compressed air (132259-10-0)			
ACGIH	Not applicable		
OSHA	Not applicable		

8.2. Exposure controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local

exhaust ventilation. Systems under pressure should be regularly checked for leakages. Alarm detectors should be used when toxic gases may be released. Consider work permit system e.g.

for maintenance activities.

Hand protection : Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection. Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.

Respiratory protection : Wear a respirator when performing non-routine tasks not limited to line breaking or sampling.

Wear a respirator during routine operations if determined to be necessary during a processspecific review. Consult respirator suppliers' product information or their representatives for the

selection of the appropriate respirator.

Thermal hazard protection : None necessary.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Reddish brown.

Molecular mass : Not applicable for gas-mixtures.

Color : Reddish brown
Odor : Pungent.
Odor threshold : No data available

all Net and Sachta for many

pH : Not applicable for gas-mixtures.

Relative evaporation rate (butyl acetate=1) : No data available

Relative evaporation rate (ether=1) : Not applicable for gas-mixtures.

Melting point : Not applicable for gas-mixtures.

Freezing point : No data available

Boiling point : Not applicable for gas-mixtures.

Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : See Section 2.1 and 2.2

Vapor pressure : Not applicable.
Relative vapor density at 20 °C : No data available
Relative density : No data available
Relative gas density : Similar to air.

Solubility : Water: Solubility in water of component(s) of the mixture :

•: •

Log Pow : Not applicable for gas-mixtures.

Log Kow : Not applicable for gas-mixtures.

Viscosity, kinematic : Not applicable.

Viscosity, dynamic : Not applicable.

Explosive properties : Not flammable.

Oxidizing properties : Not combustible but enhances combustion of other substances. May intensify fire. Oxidizer.

Explosive limits : Not applicable - not flammable

01/29/2015 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

Additional information : None.

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Flammable materials. combustible materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Toxic if inhaled.

Nitrogen Dioxide (2.30% - 2.99%) in Air		
ATE US (gases)	1923.077 ppmV/4h	
Nitrogen dioxide (10102-44-0)		
LC50 inhalation rat (ppm)	57.5 ppm/4h	
ATE US (gases)	10.000 ppmV/4h	
Compressed air (132259-10-0)		
LC50 inhalation rat (ppm)	820000 ppm/4h	
ATE US (gases)	820000.000 ppmV/4h	
Skin corrosion/irritation :	Causes skin irritation.	
	pH: Not applicable for gas-mixtures.	
Serious eye damage/irritation	Causes serious eye irritation.	
Serious eye damage/irritation :	Causes serious eye irritation.	

pH: Not applicable for gas-mixtures.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause damage to organs (lung) (Inhalation).

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Toxic if inhaled. May cause damage to organs (lung) through single exposure (inhalation). If

you feel unwell, seek medical advice.

 $\label{thm:contact} \mbox{Symptoms/injuries after skin contact} \qquad \qquad : \mbox{ Causes skin irritation}.$

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

administration

: Not known.

Chronic symptoms : None known.

01/29/2015 EN (English US) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION	12: Ecole	ogical inf	formation
	IZ. LUUN	ogical IIII	Officialion

12.1. Toxicity

Ecology - general : Classification criteria are not met.

12.2. Persistence and degradability

Nitrogen Dioxide (2.30% - 2.99%) in Air		
Persistence and degradability No data available.		
Nitrogen dioxide (10102-44-0)		
Persistence and degradability Not applicable for inorganic gases.		
Compressed air (132259-10-0)		
Persistence and degradability No ecological damage caused by this product.		

12.3. Bioaccumulative potential

•		
Nitrogen Dioxide (2.30% - 2.99%) in Air		
Log Pow	Not applicable for gas-mixtures.	
Log Kow	Not applicable for gas-mixtures.	
Bioaccumulative potential	No data available.	
Nitrogen dioxide (10102-44-0)		
Log Pow	Not applicable for inorganic gases.	
ioaccumulative potential No data available.		
Compressed air (132259-10-0)		
Log Pow	Not applicable for inorganic gases.	
Sioaccumulative potential No ecological damage caused by this product.		

12.4. Mobility in soil

Nitrogen Dioxide (2.30% - 2.99%) in Air		
Mobility in soil No data available.		
Nitrogen dioxide (10102-44-0)		
Ecology - soil Because of its high volatility, the product is unlikely to cause ground or water pollution.		
Compressed air (132259-10-0)		
Ecology - soil No ecological damage caused by this product.		

12.5. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.

Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more

guidance on suitable disposal methods.

Additional information : None.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN3303 Compressed gas, toxic, oxidizing, n.o.s. (Nitrogen Dioxide, Compressed Air) Inhalation

Hazard Zone D, 2.3

UN-No.(DOT) : UN3303

Proper Shipping Name (DOT) : Compressed gas, toxic, oxidizing, n.o.s.

Inhalation Hazard Zone D

Department of Transportation (DOT) Hazard

Classes

: 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115

01/29/2015 EN (English US) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: 2.3 - Poison gas Hazard labels (DOT)

5.1 - Oxidizer



DOT Symbols : G - Identifies PSN requiring a technical name

: 1 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone A DOT Special Provisions (49 CFR 172.102) (see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalation

hazard under the provisions of this subchapter.

4 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone D (see 173.116(a) of this subchapter), and must be described as an inhalation hazard under the

provisions of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : None DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315 DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : Forbidden

CFR 175.75)

DOT Vessel Stowage Location

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

: Avoid transport on vehicles where the load space is not separated from the driver's Special transport precautions

compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

ADR

: UN 3303, 2.3 (5.1), (C/D) Transport document description

Class (ADR) : 2 - Gases Hazard identification number (Kemler No.) : 265 Classification code (ADR) : 1TO

Hazard labels (ADR) : 2.3 - Toxic gases

5.1 - Oxidizer



Orange plates

3303

Tunnel restriction code (ADR) : C/D 0 Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 3303

Proper Shipping Name (IMDG) : COMPRESSED GAS, TOXIC, OXIDIZING, N.O.S.

Class (IMDG) 2.3 - Toxic gases

01/29/2015 EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

UN-No.(IATA) : 3303

Proper Shipping Name (IATA) : COMPRESSED GAS, TOXIC, OXIDIZING, N.O.S.

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Nitrogen dioxide (10102-44-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302	
SARA Section 302 Threshold Planning Quantity (TPQ)	100

15.2. International regulations

CANADA

Nitrogen dioxide (10102-44-0)		
Listed on the Canadian DSL (Domesti	c Sustances List)	
WHMIS Classification Class A - Compressed Gas Class C - Oxidizing Material Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material		
Compressed air (132259-10-0)		
WHMIS Classification	Class A - Compressed Gas	

EU-Regulations

Nitrogen dioxide (10102-44-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Nitrogen dioxide (10102-44-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

Compressed air (132259-10-0)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

15.3. US State regulations

Nitrogen dioxide (10102-44-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.

01/29/2015 EN (English US) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information

: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases:

Acute Tox. 1 (Inhalation:gas) Acute toxicity (inhalation:gas) Category 1 Acute Tox. 3 (Inhalation:gas) Acute toxicity (inhalation:gas) Category 3 Compressed gas Gases under pressure Compressed gas Eye Dam. 1 Eye Irrit. 2A Serious eye damage/eye irritation Category 1 Eye Irrit. 2A Serious eye damage/eye irritation Category 2A Liquefied gas Gases under pressure Liquefied gas Ox. Gas 1 Oxidizing gases Category 1 Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 2 Specific target organ toxicity (single exposure) Category 2 H270 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Fatal if inhaled H331 Toxic if inhaled H331 May cause damage to organs	at of 11 philades.	
Compressed gas Eye Dam. 1 Eye Irrit. 2A Serious eye damage/eye irritation Category 1 Eye Irrit. 2A Liquefied gas Ox. Gas 1 Skin Corr. 1B Skin corrosion/irritation Category 1 Skin corrosion/irritation Category 2 STOT SE 2 Specific target organ toxicity (single exposure) Category 2 H270 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation Fatal if inhaled H331 Toxic if inhaled	Acute Tox. 1 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 1
Eye Dam. 1 Eye Irrit. 2A Serious eye damage/eye irritation Category 1 Eye Irrit. 2A Liquefied gas Gases under pressure Liquefied gas Ox. Gas 1 Skin Corr. 1B Skin corrosion/irritation Category 1 Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 2 H270 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation Fatal if inhaled H331 Toxic if inhaled	Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Eye Irrit. 2A Liquefied gas Gases under pressure Liquefied gas Ox. Gas 1 Skin Corr. 1B Skin corrosion/irritation Category 1 Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 2 H270 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	Compressed gas	Gases under pressure Compressed gas
Liquefied gas Ox. Gas 1 Oxidizing gases Category 1 Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 2 Specific target organ toxicity (single exposure) Category 2 H270 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	Eye Dam. 1	Serious eye damage/eye irritation Category 1
Ox. Gas 1 Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 2 H270 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 2 Specific target organ toxicity (single exposure) Category 2 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated Causes severe skin burns and eye damage H314 Causes sevin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	Liquefied gas	Gases under pressure Liquefied gas
Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 2 Specific target organ toxicity (single exposure) Category 2 H270 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated Causes severe skin burns and eye damage H314 Causes sevin irritation Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	Ox. Gas 1	Oxidizing gases Category 1
STOT SE 2 Specific target organ toxicity (single exposure) Category 2 H270 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	Skin Corr. 1B	Skin corrosion/irritation Category 1B
H270 May cause or intensify fire; oxidizer H280 Contains gas under pressure; may explode if heated H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	Skin Irrit. 2	Skin corrosion/irritation Category 2
H280 Contains gas under pressure; may explode if heated H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	STOT SE 2	Specific target organ toxicity (single exposure) Category 2
H314 Causes severe skin burns and eye damage H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	H270	May cause or intensify fire; oxidizer
H315 Causes skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	H280	Contains gas under pressure; may explode if heated
H318 Causes serious eye damage H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	H314	Causes severe skin burns and eye damage
H319 Causes serious eye irritation H330 Fatal if inhaled H331 Toxic if inhaled	H315	Causes skin irritation
H330 Fatal if inhaled H331 Toxic if inhaled	H318	Causes serious eye damage
H331 Toxic if inhaled	H319	Causes serious eye irritation
	H330	Fatal if inhaled
H371 May cause damage to organs	H331	Toxic if inhaled
	H371	May cause damage to organs

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

01/29/2015 EN (English US) 9/9