Safety Data Sheet

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • **Helium (0.001-39.99%), Oxygen (Balance)**

Product Code • M-48287/E-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Test Gas/Calibration Gas

1.3 Details of the supplier of the safety data sheet

Manufacturer • Air Liquide

2700 Post Oak Blvd.
Houston, TX 77056
United States
www.us.airliquide.com
sds@airliquide.com

Telephone (Technical) • 713-896-2896

Telephone (Technical) • 800-819-1704

1.4 Emergency telephone number

Manufacturer • 800-424-9300 - CHEMTREC

Manufacturer • +1 703-527-3887 - Outside United States

Section 2: Hazards Identification

EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]
According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP • Oxidizing Gases 1 - H270
Compressed Gas - H280

DSD/DPD • Oxidizing (O)

R8

2.2 Label Elements

CLP

DANGER

Hazard statements • H270 - May cause or intensify fire; oxidizer
H280 - Contains gas under pressure; may explode if heated

Precautionary statements

Prevention
- P202 - Do not handle until all safety precautions have been read and understood.
P220 - Keep/Store away from clothing and other combustible materials.
P244 - Keep reduction valves free from grease and oil.
P261 - Avoid breathing gas.
P271 - Use only outdoors or in a well-ventilated area.

Response
- P370+P376 - In case of fire: Stop leak if safe to do so.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P313 - Get medical advice/attention.

Storage/Disposal
- Protect from sunlight when ambient temperature exceeds 125°F (52°C)
P403 - Store in a well-ventilated place.

DSD/DPD

Risk phrases
- R8 - Contact with combustible material may cause fire.

2.3 Other Hazards

CLP
- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite.
According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

DSD/DPD
- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite.
According to European Directive 1999/45/EC this material is considered dangerous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012
- Oxidizing Gases 1 - H270
Compressed Gas - H280

2.2 Label elements

OSHA HCS 2012

DANGER

Hazard statements
- May cause or intensify fire; oxidizer - H270
Contains gas under pressure; may explode if heated - H280

Precautionary statements

Prevention
- Do not handle until all safety precautions have been read and understood. - P202
Keep/Store away from clothing and other combustible materials. - P220
Keep reduction valves free from grease and oil. - P244
Avoid breathing gas. - P261
Use only outdoors or in a well-ventilated area. - P271

Response
- In case of fire: Stop leak if safe to do so. - P370+P376
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. - P304+P340
Get medical advice/attention. - P313

Storage/Disposal
- Protect from sunlight when ambient temperature exceeds 125°F (52°C)
Store in a well-ventilated place. - P403

2.3 Other hazards

OSHA HCS 2012
- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite. Under

United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

- Compressed Gas - A
  Oxidizing - C

2.2 Label elements

WHMIS

- Compressed Gas - A
  Oxidizing - C

2.3 Other hazards

WHMIS

- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite. In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

2.4 Other information

NFPA

Section 3 - Composition/Information on Ingredients

3.1 Substances

- Material does not meet the criteria of a substance.

3.2 Mixtures

Composition				
Chemical Name	**Identifiers**	**%**	**LD50/LC50**	**Classifications According to Regulation/Directive**
Oxygen	**CAS:**7782-44-7 **EC Number:**231-956-9 **EU Index:**008-001-00-8	Balance	NDA	**EU DSD/DPD:** Annex I - O; R8 **EU CLP:** Annex VI - Ox. Gas 1, H270; Press. Gas - Comp., H280 **OSHA HCS 2012:** Ox. Gas 1; Press Gas. - Comp.
Helium	**CAS:**7440-59-7 **EINECS:**231-168-5	0.001% TO 39.99%	NDA	**EU DSD/DPD:** Not Classified **EU CLP:** Self Classified - Press. Gas - Comp., H280 **OSHA HCS 2012:** Press. Gas - Comp; Simp. Asphyx.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin
- If frostbite has occurred, seek medical attention immediately; do NOT rub the affected area(s) or flush them with water. In order to prevent further tissue damage, do NOT attempt to remove frozen clothing from frostbitten areas. If frostbite has not occurred, immediately and thoroughly wash contaminated skin with soap and water.

Eye
- If eye tissue is frozen, seek medical attention immediately; if tissue is not frozen, immediately and thoroughly flush the eyes with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation, pain, swelling, lacrimation or photophobia persist, get medical attention as soon as possible.

Ingestion
- If frostbite has occurred, seek medical attention immediately; do NOT rub the affected area(s) or flush them with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician
- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

4.4 Other information

- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO GASES WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus must be worn. Victim(s) who experience any adverse effect after over-exposure to this gas mixture must be taken for medical attention. Rescuers should be taken for medical attention if necessary. Take a copy of the label and the MSDS to physician or other health professional with victim(s).

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media
- Use extinguishing agent suitable for type of surrounding fire.
  SMALL FIRES: Dry chemical or CO2.
  LARGE FIRES: Water spray or fog.

Unsuitable Extinguishing Media
- No data available

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards
- May ignite combustibles (wood, paper, oil, clothing, etc.)
  Some may react explosively with fuels.
  Containers may explode when heated.
  Ruptured cylinders may rocket.

Hazardous Combustion Products
- No data available

5.3 Advice for firefighters

- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
  Always wear thermal protective clothing when handling refrigerated/cryogenic liquids.
  Wear positive pressure self-contained breathing apparatus (SCBA).

Move containers from fire area if you can do it without risk.
FIRE: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.
FIRE INVOLVING TANKS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
FIRE INVOLVING TANKS: Cool containers with flooding quantities of water until well after fire is out.
FIRE INVOLVING TANKS: Do not direct water at source of leak or safety devices; icing may occur.
FIRE INVOLVING TANKS: Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
FIRE INVOLVING TANKS: ALWAYS stay away from tanks engulfed in fire.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Ventilate the area before entry. Do not walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

- LARGE SPILL: Consider initial downwind evacuation for at least 500 meters (1/3 mile) Ventilate closed spaces before entering. Keep unauthorized personnel away. Keep out of low areas. Stay upwind. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

6.2 Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk.
Allow substance to evaporate.
If possible, turn leaking containers so that gas escapes rather than liquid.
Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container.
Isolate area until gas has dispersed.
Keep combustibles (wood, paper, oil, etc.) away from spilled material.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Use only with adequate ventilation. Ventilate closed spaces before entering. Be aware of any signs of dizziness or fatigue, especially if work is done in a poorly ventilated area; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms, due to olfactory fatigue or oxygen deficiency. Cylinders should be firmly secured to prevent falling or being knocked-over. Do not attempt to repair, adjust, or in any other way modify cylinders. If there is a malfunction or another type of operational problem, contact nearest distributor immediately. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Store in a cool, dry, well-ventilated place. Protect cylinders against physical damage. Cylinders should be firmly secured to prevent falling or being knocked-over. Do not allow area where cylinders are stored to exceed 52C (125F).

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines

- Currently there are no applicable exposure limits established for this material.

Exposure Control Notations

Portugal

•Helium (7440-59-7): **Simple Asphyxiants:** (Simple Asphyxiant)

Ireland

•Helium (7440-59-7): **Simple Asphyxiants:** (Asphyxiant)

Spain

•Helium (7440-59-7): **Simple Asphyxiants:** (simple asphyxiant)

8.2 Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof - electrical, ventilating and/or lighting equipment.

Personal Protective Equipment

Respiratory

- Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear safety glasses.

Skin/Body

- Wear leather gloves when handling cylinders.

Environmental Exposure Controls

- Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Gas	Appearance/Description	Colorless, odorless gas at normal temperature and pressure.
Color	Colorless	Odor	Odorless
Odor Threshold	Data lacking		
General Properties			
Boiling Point	-183 C(-297.4 F) Oxygen	Melting Point	-279 C(-470.2 F) Oxygen
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	1.14 Water=1 @ -183 C(-297.4 F) Oxygen	Density	1.4289 kg/m³ @ 21.1 C(69.98 F) Oxygen
Water Solubility	39 mg/L Oxygen	Viscosity	Not relevant
Explosive Properties	Data lacking	Oxidizing Properties:	Oxidizing gas.
Volatility			
Vapor Pressure	50800 hPa @ -118.4 C(-181.12 F) Oxygen	Vapor Density	1.1 Air=1 Oxygen
Evaporation Rate	Data lacking		
Flammability			

Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Autoignition	Not relevant
Flammability (solid, gas)	Not flammable.		
Environmental			
Octanol/Water Partition coefficient	Not relevant		

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

- Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- Excess heat, sparks, open flame.

10.5 Incompatible materials

- Reacts violently with phosphine, hydrazine, ethers, alcohols, hydrogen sulfide, and hydrocarbons. Flammable and combustible materials, especially greases and oils.

10.6 Hazardous decomposition products

- None

Section 11 - Toxicological Information

11.1 Information on toxicological effects

	CAS	
Helium (0.001-39.99%), Oxygen (Balance)	NDA	**Reproductive:** Inhalation-Rat TCLo • 10 pph 9 Hour(s)(22D preg); *Reproductive Effects:Specific Developmental Abnormalities*:**Respiratory system**; *Reproductive Effects:Effects on Newborn*:**Physical**

GHS Properties	Classification
Acute toxicity	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met
Aspiration Hazard	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met
Carcinogenicity	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met
Germ Cell Mutagenicity	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met
Skin corrosion/Irritation	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met

Skin sensitization	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met
STOT-RE	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met
STOT-SE	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met
Toxicity for Reproduction	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met
Respiratory sensitization	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met
Serious eye damage/Irritation	**EU/CLP** • Classification criteria not met **OSHA HCS 2012** • Classification criteria not met

Potential Health Effects

Inhalation

Acute (Immediate)
- Contact with rapidly expanding gas may cause burns or frostbite.

Chronic (Delayed)
- No data available

Skin

Acute (Immediate)
- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite.

Chronic (Delayed)
- No data available

Eye

Acute (Immediate)
- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite.

Chronic (Delayed)
- No data available

Ingestion

Acute (Immediate)
- Ingestion can cause burns similar to frostbite.

Chronic (Delayed)
- No data available

Section 12 - Ecological Information

12.1 Toxicity

- Material data lacking.

12.2 Persistence and degradability

- Material data lacking.

12.3 Bioaccumulative potential

- Material data lacking.

12.4 Mobility in Soil

- Material data lacking.

12.5 Results of PBT and vPvB assessment

- PBT and vPvB assessment has not been conducted for this material.

12.6 Other adverse effects

- No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste
- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste
- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN3156	Compressed gas, oxidizing, n.o.s. (Oxygen, Helium)	2.2,5.1	NDA	NDA
TDG	UN3156	COMPRESSED GAS, OXIDIZING, N.O.S. (Oxygen, Helium)	2.2,5.1	NDA	NDA
IMO/IMDG	UN3156	COMPRESSED GAS, OXIDIZING, N.O.S. (Oxygen, Helium)	2.2,5.1	NDA	NDA
IATA/ICAO	UN3156	Compressed gas, oxidizing, n.o.s. (Oxygen, Helium)	2.2,5.1	NDA	NDA

14.6 Special precautions for user
- Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards. If transporting these cylinders in vehicles, ensure these cylinders are not exposed to extremely high temperatures (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated during transportation.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
- Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications
- Pressure(Sudden Release of), Fire

State Right To Know				
Component	**CAS**	**MA**	**NJ**	**PA**
Helium	7440-59-7	Yes	Yes	Yes
Oxygen	7782-44-7	Yes	Yes	Yes

Inventory						
Component	**CAS**	**Canada DSL**	**Canada NDSL**	**China**	**EU EINECS**	**EU ELNICS**
Helium	7440-59-7	Yes	No	Yes	Yes	No
Oxygen	7782-44-7	Yes	No	Yes	Yes	No

Inventory (Con't.)		
Component	**CAS**	**TSCA**
Helium	7440-59-7	Yes
Oxygen	7782-44-7	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Oxygen	7782-44-7	A, C
• Helium	7440-59-7	A

Canada - WHMIS - Ingredient Disclosure List

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

Environment

Canada - CEPA - Priority Substances List

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

China

Environment

China - Ozone Depleting Substances - First Schedule

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

China - Ozone Depleting Substances - Second Schedule

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

China - Ozone Depleting Substances - Third Schedule

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

Other

China - Annex I & II - Controlled Chemicals Lists

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

China - Dangerous Goods List

• Oxygen	7782-44-7	(compressed or refrigerated liquid)
• Helium	7440-59-7	(compressed or refrigerated liquid)

China - Export Control List - Part I Chemicals

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

Europe

Other

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

• Oxygen	7782-44-7	O; R8
• Helium	7440-59-7	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

• Oxygen	7782-44-7	Not Listed

• Helium	7440-59-7	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

• Oxygen	7782-44-7	O R:8 S:(2)-17
• Helium	7440-59-7	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

• Oxygen	7782-44-7	S:(2)-17
• Helium	7440-59-7	Not Listed

Germany

Environment

Germany - TA Luft - Types and Classes

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

Germany - Water Classification (VwVwS) - Annex 1

• Oxygen	7782-44-7	ID Number 743, not considered hazardous to water
• Helium	7440-59-7	Not Listed

Germany - Water Classification (VwVwS) - Annex 2 - Water Hazard Classes

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

Germany - Water Classification (VwVwS) - Annex 3

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

Other

Germany - Specifically Regulated Chemicals in TRGS

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

Portugal

Other

Portugal - Prohibited Substances

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

United Kingdom

Environment

United Kingdom - Pollution Inventory - Schedule 1 - Thresholds for Releases to Air

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

Other

United Kingdom - Workplace Exposure Limits (WELs) - Substances in Review

• Oxygen	7782-44-7	Not Listed

• Helium	7440-59-7	Not Listed

United Kingdom - List of Dangerous Substances in Water

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Oxygen	7782-44-7	Not Listed

• Helium	7440-59-7	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

• Oxygen	7782-44-7	Not Listed
• Helium	7440-59-7	Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Last Revision Date
- 17/October/2014

Preparation Date
- 17/October/2014

Disclaimer/Statement of Liability
- To the best of Air Liquide's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

Key to abbreviations

NDA = No Data Available