

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : Isobutane (0.0001% - 1.30%) in Air  
 Product code : SG-2002-01055

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

#### 1.3. Details of the supplier of the safety data sheet

Air Liquide America Specialty Gases  
 6141 Easton Rd  
 Plumsteadville, PA 18949 - USA  
 T 1.800.217.2688  
[www.airliquide.com](http://www.airliquide.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Compressed gas H280

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS04

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H280 - Contains gas under pressure; may explode if heated  
 CGA-HG24 - Supports combustion.

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood  
 P271 - Use only outdoors or in a well-ventilated area  
 CGA-PG05 - Use a back flow preventive device in the piping  
 CGA-PG10 - Use only with equipment rated for cylinder pressure  
 CGA-PG21 - Open valve slowly  
 CGA-PG06 - Close valve after each use and when empty  
 CGA-PG14 - Approach suspected leak area with caution  
 CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)  
 P403 - Store in a well-ventilated place

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

# Isobutane (0.0001% - 1.30%) in Air

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
Compressed air	(CAS No) 132259-10-0	98.7 - 99.9999	Compressed gas, H280
Isobutane	(CAS No) 75-28-5	0.0001 - 1.3	Flam. Gas 1, H220 Liquefied gas, H280

Full text of H-phrases: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Adverse effects not expected from this product.  
First-aid measures after skin contact : Adverse effects not expected from this product.  
First-aid measures after eye contact : Adverse effects not expected from this product.  
First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Adverse effects not expected from this product.  
Symptoms/injuries after skin contact : Adverse effects not expected from this product.  
Symptoms/injuries after eye contact : Adverse effects not expected from this product.  
Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.  
Symptoms/injuries upon intravenous administration : Not known.  
Chronic symptoms : Adverse effects not expected from this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.  
Unsuitable extinguishing media : Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : The product is not flammable.  
Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.  
Reactivity : None known.

#### 5.3. Advice for firefighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.  
Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Ensure adequate ventilation.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment consistent with the site emergency plan.  
Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

##### 6.1.2. For emergency responders

- Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.  
Emergency procedures : Evacuate and limit access. Ventilate area.

#### 6.2. Environmental precautions

Try to stop release if safe to do so.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Try to stop release if safe to do so.

# Isobutane (0.0001% - 1.30%) in Air

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

### 6.4. Reference to other sections

See also Sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : None known.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.

Incompatible products : None known.

Incompatible materials : Flammable materials.

### 7.3. Specific end use(s)

Test gas/Calibration gas.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Isobutane (0.0001% - 1.30%) in Air		
ACGIH	Not applicable	
OSHA	Not applicable	
Isobutane (75-28-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	Not applicable	
Compressed air (132259-10-0)		
ACGIH	Not applicable	
OSHA	Not applicable	

### 8.2. Exposure controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Consider work permit system e.g. for maintenance activities.

Hand protection : Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.

Respiratory protection : None necessary during normal and routine operations. See Sections 5 & 6.

Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Clear, colorless gas.

Molecular mass : Not applicable for gas-mixtures.

Color : Colorless

Odor : Odorless

Odor threshold : No data available

pH : Not applicable for gas-mixtures.

# Isobutane (0.0001% - 1.30%) in Air

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable for gas-mixtures.
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: See Sect. 2.1 & 2.2
Vapor pressure	: Not applicable.
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Relative gas density	: Similar to air
Solubility	: Water: Solubility in water of component(s) of the mixture : • : 54 mg/l • :
Log Pow	: Not applicable for gas-mixtures.
Log Kow	: Not applicable for gas-mixtures.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable - not flammable.
Oxidizing properties	: None.
Explosive limits	: Not applicable - not flammable

### 9.2. Other information

Additional information : None.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Can form explosive mixtures with flammable materials.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Flammable materials.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Isobutane (75-28-5)	
LC50 inhalation rat (mg/l)	658 mg/l/4h
LC50 inhalation rat (ppm)	276713.11 ppm/4h
Compressed air (132259-10-0)	
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h

Skin corrosion/irritation : Not classified  
pH: Not applicable for gas-mixtures.

# Isobutane (0.0001% - 1.30%) in Air

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation	: Not classified
	pH: Not applicable for gas-mixtures.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Adverse effects not expected from this product.
Symptoms/injuries after skin contact	: Adverse effects not expected from this product.
Symptoms/injuries after eye contact	: Adverse effects not expected from this product.
Symptoms/injuries after ingestion	: Ingestion is not considered a potential route of exposure.
Symptoms/injuries upon intravenous administration	: Not known.
Chronic symptoms	: Adverse effects not expected from this product.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Classification criteria are not met.

#### 12.2. Persistence and degradability

##### Isobutane (0.0001% - 1.30%) in Air

Persistence and degradability	No data available.
-------------------------------	--------------------

##### Isobutane (75-28-5)

Persistence and degradability	The substance is biodegradable. Unlikely to persist.
-------------------------------	--

##### Compressed air (132259-10-0)

Persistence and degradability	No ecological damage caused by this product.
-------------------------------	--

#### 12.3. Bioaccumulative potential

##### Isobutane (0.0001% - 1.30%) in Air

Log Pow	Not applicable for gas-mixtures.
---------	----------------------------------

Log Kow	Not applicable for gas-mixtures.
---------	----------------------------------

Bioaccumulative potential	No data available.
---------------------------	--------------------

##### Isobutane (75-28-5)

BCF fish 1	1.57 - 1.97
------------	-------------

Log Pow	2.76
---------	------

Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
---------------------------	---

##### Compressed air (132259-10-0)

Log Pow	Not applicable for inorganic gases.
---------	-------------------------------------

Bioaccumulative potential	No ecological damage caused by this product.
---------------------------	--

#### 12.4. Mobility in soil

##### Isobutane (0.0001% - 1.30%) in Air

Mobility in soil	No data available.
------------------	--------------------

##### Isobutane (75-28-5)

Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
----------------	---

##### Compressed air (132259-10-0)

Ecology - soil	No ecological damage caused by this product.
----------------	--

#### 12.5. Other adverse effects

Effect on ozone layer : None.

# Isobutane (0.0001% - 1.30%) in Air

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Effect on the global warming : No known ecological damage caused by this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.

Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at [www.cganet.com](http://www.cganet.com) for more guidance on suitable disposal methods.

### SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1956 Compressed gas, n.o.s. (Compressed Air, Isobutane)

UN-No.(DOT) : UN1956

Proper Shipping Name (DOT) : Compressed gas, n.o.s.

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Symbols : G - Identifies PSN requiring a technical name

DOT Packaging Exceptions (49 CFR 173.xxx) : 306;307

DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

#### Additional information

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:

- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

#### ADR

No additional information available

#### Transport by sea

UN-No. (IMDG) : 1956

Proper Shipping Name (IMDG) : COMPRESSED GAS, N.O.S.

Class (IMDG) : 2.2 - Non-flammable, non-toxic gases

#### Air transport

UN-No.(IATA) : 1956

Proper Shipping Name (IATA) : COMPRESSED GAS, N.O.S.

Class (IATA) : 2

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Isobutane (75-28-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# Isobutane (0.0001% - 1.30%) in Air

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

##### Isobutane (75-28-5)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class A - Compressed Gas  
Class B Division 1 - Flammable Gas

##### Compressed air (132259-10-0)

WHMIS Classification

Class A - Compressed Gas

### EU-Regulations

##### Isobutane (75-28-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

#### 15.2.2. National regulations

##### Isobutane (75-28-5)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

##### Compressed air (132259-10-0)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)

### 15.3. US State regulations

##### Isobutane (75-28-5)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Indication of changes

: Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.

Other information

: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases:

Compressed gas	Gases under pressure Compressed gas
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated

SDS US (GHS HazCom 2012)

*This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.*