

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/22/2014 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture

Product name : Silicon Tetrachloride (0.0001% - 0.9999%) in Hydrogen

Product code : SG-2002-02488

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

Details of the supplier of the safety data sheet

Air Liquide America Specialty Gases 6141 Easton Rd Plumsteadville, PA 18949 - USA

T 1.800.217.2688 www.airliquide.com

Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification (GHS-US)

Flam. Gas 1 H220 H280 Compressed gas

Full text of H-phrases: see section 16

Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS04

GHS02

: Danger

Signal word (GHS-US) Hazard statements (GHS-US) : H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

CGA-HG04 - May form explosive mixtures with air

OSHA-H01 - May displace oxygen and cause rapid suffocation

CGA-HG08 - Burns with invisible flame

: P202 - Do not handle until all safety precautions have been read and understood Precautionary statements (GHS-US)

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective clothing, protective gloves, eye protection, face protection P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P313 - Get medical advice/attention

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 - Eliminate all ignition sources if safe to do so

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/container in accordance with local/regional/national/international

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

CGA-PG05 - Use a back flow preventive device in the piping CGA-PG06 - Close valve after each use and when empty CGA-PG10 - Use only with equipment rated for cylinder pressure CGA-PG14 - Approach suspected leak area with caution

CGA-PG21 - Open valve slowly

12/29/2014 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Hydrogen	(CAS No) 1333-74-0	99.0001 - 99.9999	Flam. Gas 1, H220 Compressed gas, H280
Silicon tetrachloride	(CAS No) 10026-04-7	0.0001 - 0.9999	Acute Tox. 2 (Inhalation:gas), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Adverse effects not expected from this product. First-aid measures after eye contact : Adverse effects not expected from this product.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. Symptoms/injuries after skin contact : Adverse effects not expected from this product. Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

administration

: Not known.

Chronic symptoms : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : This product is flammable.

Explosion hazard : May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed

containers, spreading fire and increasing risk of burns and injuries.

Reactivity : Reacts violently with water.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray

or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

12/29/2014 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

Protective equipment

: Wear protective equipment consistent with the site emergency plan.

Emergency procedures

: Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep

upwind.

6.1.2. For emergency responders

Protective equipment

: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Equip cleanup crew with proper protection.

Emergency procedures

Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment

: Try to stop release if safe to do so.

Methods for cleaning up

: Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Use equipment rated for cylinder pressure. In use, may form flammable vapor-air mixture. Close valve after each use and when empty.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

: Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.

Incompatible products

: None known.

Incompatible materials

: Oxidizing materials. Air.

7.3. Specific end use(s)

Test gas/Calibration gas.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Silicon Tetrachloride (0.0001% - 0.9999%) in Hydrogen		
ACGIH	Not applicable	
OSHA	Not applicable	
Hydrogen (1333-74-0)		
ACGIH	Not applicable	

Silicon tetrachloride (10026-04-7)		
ACGIH Not applicable		
OSHA	Not applicable	

12/29/2014 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local

exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit

system e.g. for maintenance activities.

Hand protection : Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection. Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.

Respiratory protection : None necessary during normal and routine operations. See sections 5 & 6.

Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Clear, colorless gas.

Molecular mass : Not applicable for gas-mixtures.

Color : Colorless
Odor : Pungent.

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available

Relative evaporation rate (ether=1) : Not applicable for gas-mixtures.

Melting point No data available Freezing point No data available Boiling point : No data available Flash point : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) Flammable Vapor pressure Not applicable. Relative vapor density at 20 °C : No data available Relative density : No data available Relative gas density : Lighter than air.

Solubility : Water: Solubility in water of component(s) of the mixture :

•: 1.6 mg/l •: Reacts with water

Log Pow : Not applicable for gas-mixtures.
Log Kow : Not applicable for gas-mixtures.

Viscosity, kinematic : Not applicable.
Viscosity, dynamic : Not applicable.

Explosive properties : Without adequate ventilation formation of explosive mixtures may be possible.

Oxidizing properties : None

Explosive limits : No data available

9.2. Other information

Additional information : None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with water.

10.2. Chemical stability

Stable under normal conditions.

12/29/2014 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Air. Oxidizing materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Hydrogen (1333-74-0)		
LC50 inhalation rat (ppm)	820000 ppm/4h	
Silicon tetrachloride (10026-04-7)		
LC50 inhalation rat (ppm)	375 ppm/4h	
ATE US (gases)	100.000 ppmV/4h	
Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Not classified	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: Not classified	
Specific target organ toxicity (repeated exposure)	: Not classified	
Aspiration hazard	: Not classified	
Symptoms/injuries after inhalation	: May displace oxygen and cause rapid suffocation.	
Symptoms/injuries after skin contact	: Adverse effects not expected from this product.	
Symptoms/injuries after eye contact	: Adverse effects not expected from this product.	
Symptoms/injuries after ingestion	: Ingestion is not considered a potential route of exposure.	
Symptoms/injuries upon intravenous administration	: Not known.	

SECTION 12: Ecological information

12.1. Toxicity

Chronic symptoms

Ecology - general : No ecological damage caused by this product.

12.2. Persistence and degradability

Silicon Tetrachloride (0.0001% - 0.9999%) in Hydrogen		
Persistence and degradability No data available.		
Hydrogen (1333-74-0)		
Persistence and degradability No ecological damage caused by this product.		

: Adverse effects not expected from this product.

12.3. Bioaccumulative potential

Silicon Tetrachloride (0.0001% - 0.9999%) in Hydrogen	
Log Pow	Not applicable for gas-mixtures.
Log Kow	Not applicable for gas-mixtures.
Bioaccumulative potential	No data available.

12/29/2014 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen (1333-74-0)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No ecological damage caused by this product.

12.4. Mobility in soil

Silicon Tetrachloride (0.0001% - 0.9999%) in Hydrogen		
Mobility in soil No data available.		
Hydrogen (1333-74-0)		
Ecology - soil No ecological damage caused by this product.		

12.5. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its

accumulation could be dangerous. Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a

suitable burner with flash back arrestor.

Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more

guidance on suitable disposal methods.

Ecology - waste materials : None known.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1954 Compressed gas, flammable, n.o.s.

UN-No.(DOT) : UN1954

Proper Shipping Name (DOT) : Compressed gas, flammable, n.o.s.

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Symbols : G - Identifies PSN requiring a technical name

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:

- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided)

is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

12/29/2014 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ADR

Transport document description : UN 1954, 2.1, (B/D)

Class (ADR) : 2 - Gases
Hazard identification number (Kemler No.) : 23
Classification code (ADR) : 1F

Hazard labels (ADR) : 2.1 - Flammable gases



Orange plates

23 1954

Tunnel restriction code (ADR) : B/D LQ : 0 Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 1954

Proper Shipping Name (IMDG) : COMPRESSED GAS, FLAMMABLE, N.O.S.

Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No.(IATA) : 1954

Proper Shipping Name (IATA) : COMPRESSED GAS, FLAMMABLE, N.O.S.

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Hydrogen (1333-74-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Silicon tetrachloride (10026-04-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Hydrogen (1333-74-0)	
Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Class A - Compressed Gas

Class B Division 1 - Flammable Gas

Silicon tetrachloride (10026-04-7)

Listed on the Canadian DSL (Domestic Sustances List)

EU-Regulations

Hydrogen (1333-74-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Silicon tetrachloride (10026-04-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

12/29/2014 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen (1333-74-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Silicon tetrachloride (10026-04-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Hydrogen (1333-74-0)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Silicon tetrachloride (10026-04-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Indication of changes	: R	Revised safety data sheet in accordance with OSHA final rule on GHS implementation
		1 1 1 1 1 1 0 0 0 1 1 0

promulgated March 26, 2012.

Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29

CFR, 1910.1200. Other government regulations must be reviewed for applicability to this

product.

Full text of H-phrases

At Of Fi-philases.	
Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled
H335	May cause respiratory irritation

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

12/29/2014 EN (English US) 8/8