



# SAFETY DATA SHEET

Revision Date: 13-Oct-2015

Revision Number: 3

## 1. PRODUCT AND COMPANY IDENTIFICATION

|                            |   |
|----------------------------|---|
| <b>Product Name</b>        | <b>AURA GRAND ENTRANCE HIGH GLOSS WHITE</b> |
| <b>Product Code</b>        | <b>14801</b>                                |
| <b>Product Class</b>       | WATER THINNED PAINT                         |
| <b>Color</b>               | White                                       |
| <b>Recommended use</b>     | Paint                                       |
| <b>Restrictions on use</b> | No information available                    |

**Manufacturer**  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 855-724-6802  
www.benjaminmoore.com

**Emergency Telephone Number(s)**  
CHEMTREC (US): 800-424-9300  
CHEMTREC (outside US): (703)-527-3887

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

### Label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

**Appearance** liquid

**Odor** little or no odor

### Hazards not otherwise classified (HNOC)

Avoid breathing vapors or mists

### Other information

No information available

## 3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical Name                           | CAS-No     | Weight % (max) |
|---|------------|----------------|
| Titanium dioxide                        | 13463-67-7 | 25             |
| Polyalkylene glycol alkyl ether         | -          | 5              |
| Silica, amorphous                       | 7631-86-9  | 5              |
| Tetramethyl-5-decyne-4,7-diol, 2,4,7,9- | 126-86-3   | 0.5            |

#### 4. FIRST AID MEASURES

|  |   |
|--|---|
| <b>General Advice</b>                  | No hazards which require special first aid measures.  |
| <b>Eye Contact</b>                     | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.          |
| <b>Skin Contact</b>                    | Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. |
| <b>Inhalation</b>                      | Move to fresh air. If symptoms persist, call a physician.                                       |
| <b>Ingestion</b>                       | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.  |
| <b>Most Important Symptoms/Effects</b> | None known.   |
| <b>Notes To Physician</b>              | Treat symptomatically.  |

#### 5. FIRE-FIGHTING MEASURES

|  |  |
|--|--|
| <b>Suitable Extinguishing Media</b>                          | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                |
| <b>Protective Equipment And Precautions For Firefighters</b> | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| <b>Specific Hazards Arising From The Chemical</b>            | Closed containers may rupture if exposed to fire or extreme heat.  |
| <b>Sensitivity To Mechanical Impact</b>                      | No   |
| <b>Sensitivity To Static Discharge</b>                       | No   |
| <b>Flash Point Data</b>                                      |  |
| Flash Point (°F)   | Not applicable   |
| Flash Point (°C)   | Not applicable   |
| Flash Point Method   | Not applicable   |
| <b>Flammability Limits In Air</b>                            |  |
| Lower Explosion Limit  | Not applicable   |
| Upper Explosion Limit  | Not applicable   |

**NFPA**      **Health:** 1      **Flammability:** 0      **Instability:** 0      **Special:** Not Applicable**NFPA Legend**0 - Not Hazardous  
1 - Slightly  
2 - Moderate  
3 - High  
4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).

**6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions**      Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information**      Prevent further leakage or spillage if safe to do so.

**Environmental Precautions**      See Section 12 for additional Ecological Information.

**Methods For Clean-Up**      Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**7. HANDLING AND STORAGE**

**Handling**      Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

**Storage**      Keep container tightly closed. Keep out of the reach of children.

**Incompatible Materials**      No information available

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Exposure Limits**

| Chemical Name     | ACGIH                      | OSHA   |
|-------------------|----------------------------|--|
| Titanium dioxide  | 10 mg/m <sup>3</sup> - TWA | 15 mg/m <sup>3</sup> - TWA   |
| Silica, amorphous | N/E                        | - (80)/(% SiO <sub>2</sub> ) mg/m <sup>3</sup> TWA<br>20 mppcf - TWA |

**Legend**ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits  
OSHA - Occupational Safety & Health Administration Exposure Limits  
N/E - Not Established

**Engineering Measures**      Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**      Safety glasses with side-shields.

**Skin Protection**      Protective gloves and impervious clothing.

**Respiratory Protection**      In case of insufficient ventilation wear suitable respiratory equipment.

**Hygiene Measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|  |                          |
|--|--------------------------|
| <b>Appearance</b>                              | liquid                   |
| <b>Odor</b>                                    | little or no odor        |
| <b>Odor Threshold</b>                          | No information available |
| <b>Density (lbs/gal)</b>                       | 10.75 - 10.85            |
| <b>Specific Gravity</b>                        | 1.28 - 1.30              |
| <b>pH</b>                                      | No information available |
| <b>Viscosity (cps)</b>                         | No information available |
| <b>Solubility</b>                              | No information available |
| <b>Water Solubility</b>                        | No information available |
| <b>Evaporation Rate</b>                        | No information available |
| <b>Vapor Pressure</b>                          | No information available |
| <b>Vapor Density</b>                           | No information available |
| <b>Wt. % Solids</b>                            | 50 - 60                  |
| <b>Vol. % Solids</b>                           | 35 - 45                  |
| <b>Wt. % Volatiles</b>                         | 40 - 50                  |
| <b>Vol. % Volatiles</b>                        | 55 - 65                  |
| <b>VOC Regulatory Limit (g/L)</b>              | <50                      |
| <b>Boiling Point (°F)</b>                      | 212                      |
| <b>Boiling Point (°C)</b>                      | 100                      |
| <b>Freezing Point (°F)</b>                     | 32                       |
| <b>Freezing Point (°C)</b>                     | 0                        |
| <b>Flash Point (°F)</b>                        | Not applicable           |
| <b>Flash Point (°C)</b>                        | Not applicable           |
| <b>Flash Point Method</b>                      | Not applicable           |
| <b>Flammability (solid, gas)</b>               | Not applicable           |
| <b>Upper Explosion Limit</b>                   | Not applicable           |
| <b>Lower Explosion Limit</b>                   | Not applicable           |
| <b>Autoignition Temperature (°F)</b>           | No information available |
| <b>Autoignition Temperature (°C)</b>           | No information available |
| <b>Decomposition Temperature (°F)</b>          | No information available |
| <b>Decomposition Temperature (°C)</b>          | No information available |
| <b>Partition Coefficient (n-octanol/water)</b> | No information available |

**10. STABILITY AND REACTIVITY**

|   |  |
|---|--|
| <b>Reactivity</b>                         | Not Applicable                           |
| <b>Chemical Stability</b>                 | Stable under normal conditions.          |
| <b>Conditions To Avoid</b>                | Prevent from freezing.                   |
| <b>Incompatible Materials</b>             | No materials to be especially mentioned. |
| <b>Hazardous Decomposition Products</b>   | None under normal use.                   |
| <b>Possibility Of Hazardous Reactions</b> | None under normal conditions of use.     |

## 11. TOXICOLOGICAL INFORMATION

### Product Information

#### Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

#### Acute Toxicity

**Product Information** No information available

#### Information on toxicological effects

**Symptoms** No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

|                                 |   |
|---------------------------------|---|
| <b>Eye contact</b>              | May cause slight irritation.  |
| <b>Skin contact</b>             | Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.            |
| <b>Inhalation</b>               | Inhalation of vapors in high concentration may cause irritation of respiratory system. Avoid breathing vapors or mists. |
| <b>Ingestion</b>                | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.   |
| <b>Sensitization:</b>           | No information available  |
| <b>Neurological Effects</b>     | No information available.   |
| <b>Mutagenic Effects</b>        | No information available.   |
| <b>Reproductive Effects</b>     | No information available.   |
| <b>Developmental Effects</b>    | No information available.   |
| <b>Target Organ Effects</b>     | No information available.   |
| <b>STOT - single exposure</b>   | No information available.   |
| <b>STOT - repeated exposure</b> | No information available.   |
| <b>Other adverse effects</b>    | No information available.   |
| <b>Aspiration Hazard</b>        | No information available  |

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

|                        |              |
|------------------------|--------------|
| <b>ATEmix (oral)</b>   | 37688 mg/kg  |
| <b>ATEmix (dermal)</b> | 165292 mg/kg |

#### Component

##### Acute Toxicity

###### Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)  
LD50 Dermal: > 10000 mg/m<sup>3</sup> (Rabbit)  
LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

###### Polyalkylene glycol alkyl ether

LD50 Oral: 2000 mg/kg (Rat)  
LC50 Inhalation (Vapor): 2 mg/L (Rat, 4 hr.)

###### Silica, amorphous

LD50 Oral: > 5000 mg/kg (Rat)

LD50 Dermal: 2,000 mg/kg (Rabbit)  
LC50 Inhalation (Dust): > 2 mg/L  
Tetramethyl-5-decyne-4,7-diol, 2,4,7,9-  
LC50 Inhalation (Vapor): > 20 mg/L (Rat, 1 hr.)

### Carcinogenicity

*The information below indicates whether each agency has listed any ingredient as a carcinogen:.*

| Chemical Name    | IARC                           | NTP | OSHA Carcinogen |
|------------------|--------------------------------|-----|-----------------|
| Titanium dioxide | 2B - Possible Human Carcinogen |     | Listed          |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

### Legend

IARC - International Agency for Research on Cancer  
NTP - National Toxicity Program  
OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

### Product Information

#### Acute Toxicity to Fish

No information available

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

#### Persistence / Degradability

No information available.

#### Bioaccumulation / Accumulation

No information available.

#### Mobility in Environmental Media

No information available.

#### Ozone

No information available

### Component

#### Acute Toxicity to Fish

Titanium dioxide  
LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Tetramethyl-5-decyne-4,7-diol, 2,4,7,9-  
LC50: 42 mg/L (Carp (Cyprinus carpio) - 24 hr.)

**Acute Toxicity to Aquatic Invertebrates**

Tetramethyl-5-decyne-4,7-diol, 2,4,7,9-  
LC50: 91 mg/L (Daphnia magna - 48 hr.)

**Acute Toxicity to Aquatic Plants**

Tetramethyl-5-decyne-4,7-diol, 2,4,7,9-  
EC50: 82 mg/L (Algae (Selenastrum capricornutum) - 72 hrs.)

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method** Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

### 14. TRANSPORT INFORMATION

**DOT** Not regulated

**ICAO / IATA** Not regulated

**IMDG / IMO** Not regulated

### 15. REGULATORY INFORMATION

**International Inventories**

**TSCA: United States** Yes - All components are listed or exempt.  
**DSL: Canada** No - Not all of the components are listed.  
One or more component is listed on NDSL.

**Federal Regulations**

**SARA 311/312 hazardous categorization**

|                                   |    |
|-----------------------------------|----|
| Acute Health Hazard               | No |
| Chronic Health Hazard             | No |
| Fire Hazard                       | No |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard                   | No |

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

None

**State Regulations****California Proposition 65**

*This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.*

**State Right-to-Know**

| Chemical Name     | Massachusetts | New Jersey | Pennsylvania |
|-------------------|---------------|------------|--------------|
| Titanium dioxide  | X             | X          | X            |
| Silica, amorphous | X             | X          | X            |

**Legend**

X - Listed

**16. OTHER INFORMATION**

**HMIS**      **Health:** 1      **Flammability:** 0      **Reactivity:** 0      **PPE:** -

**HMIS Legend**

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

3 - Serious Hazard

4 - Severe Hazard

\* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

*Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.*

*Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.*

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).



---

**Prepared By** Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
855-724-6802

**Revision Date:** 13-Oct-2015  
**Revision Summary** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**