

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Chlorine (5.86% - 29.29%) in Argon
 Product code : SG-2002-00205

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide
 2700 Post Oak Boulevard
 Houston, TX 77056 - USA
 T 1-800-819-1704
www.us.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Compressed gas	H280
Acute Tox. 3 (Inhalation:gas)	H331
Skin Corr. 1A	H314
Eye Dam. 1	H318

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H280 - Contains gas under pressure; may explode if heated
 H314 - Causes severe skin burns and eye damage
 H318 - Causes serious eye damage
 H331 - Toxic if inhaled
 CGA-HG22 - Corrosive to the respiratory tract.

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood
 P260 - Do not breathe gas
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear eye protection, face protection, protective gloves, protective clothing
 P284 - Wear respiratory protection. Consult respiratory device supplier's product information for the selection of the appropriate device.
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P307+P311 - If exposed: Call a poison center/doctor
 P403 - Store in a well-ventilated place
 P405 - Store locked up
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations
 CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
 CGA-PG05 - Use a back flow preventive device in the piping
 CGA-PG06 - Close valve after each use and when empty

Chlorine (5.86% - 29.29%) in Argon

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CGA-PG10 - Use only with equipment rated for cylinder pressure
CGA-PG14 - Approach suspected leak area with caution
CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug
CGA-PG21 - Open valve slowly

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Argon	(CAS No) 7440-37-1	70.71 - 94.14	Compressed gas, H280
Chlorine	(CAS No) 7782-50-5	5.86 - 29.29	Ox. Gas 1, H270 Liquefied gas, H280 Acute Tox. 2 (Inhalation:gas), H330 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Apply artificial respiration with bag or mask if breathing stopped. If not breathing, give artificial respiration. Get immediate medical advice/attention.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Get immediate medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Toxic if inhaled. Corrosive to the respiratory tract.
- Symptoms/injuries after skin contact : Causes severe skin burns and eye damage.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.
- Symptoms/injuries upon intravenous administration : Not known.
- Chronic symptoms : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : The product is not flammable.
- Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : Reacts with water to form corrosive acids. Corrosive vapors.

5.3. Advice for firefighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Chlorine (5.86% - 29.29%) in Argon

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.
Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
Emergency procedures : Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if safe to do so.
Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty.
Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.
Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.
Incompatible products : None known.
Incompatible materials : Bases or caustic materials.

7.3. Specific end use(s)

See Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Chlorine (5.86% - 29.29%) in Argon		
ACGIH	Not applicable	
OSHA	Not applicable	
Chlorine (7782-50-5)		
ACGIH	ACGIH TWA (ppm)	0.5 ppm
ACGIH	ACGIH STEL (ppm)	1 ppm
OSHA	OSHA PEL (Ceiling) (mg/m ³)	3 mg/m ³
OSHA	OSHA PEL (Ceiling) (ppm)	1 ppm
Argon (7440-37-1)		
ACGIH	Not applicable	

Chlorine (5.86% - 29.29%) in Argon

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Argon (7440-37-1)

OSHA	Not applicable
------	----------------

8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Consider work permit system e.g. for maintenance activities. Alarm detectors should be used when toxic gases may be released.
Hand protection	: Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection. Wear chemically resistant protective gloves when making or breaking process connections.
Eye protection	: Wear safety glasses with side shields. Wear goggles and a face shield when transfilling or breaking transfer connections. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: Wear a respirator when performing non-routine tasks not limited to line breaking or sampling. Wear a respirator during routine operations if determined to be necessary during a process-specific review. Consult respirator suppliers' product information or their representatives for the selection of the appropriate respirator.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Molecular mass	: Not applicable for gas-mixtures.
Color	: Colorless
Odor	: Irritating/pungent odour
Odor threshold	: No Data Available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No Data Available
Freezing point	: No data available
Boiling point	: No Data Available
Flash point	: No Data Available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: See Section 2.1 and 2.2
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Relative gas density	: Heavier than air
Solubility	: Water: Solubility in water of component(s) of the mixture : • : 8620 mg/l • : 61 mg/l
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable - not flammable.
Oxidizing properties	: None.
Explosive limits	: Not applicable - not flammable

9.2. Other information

Additional information	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
------------------------	--

Chlorine (5.86% - 29.29%) in Argon

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water to form corrosive acids. Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Moisture.

10.5. Incompatible materials

Bases or caustic materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Toxic if inhaled.

Chlorine (5.86% - 29.29%) in Argon	
ATE US (gases)	2500.000 ppmV/4h
Chlorine (7782-50-5)	
LC50 inhalation rat (mg/l)	0.86 mg/l (Exposure time: 1 h)
LC50 inhalation rat (ppm)	146.5 ppm/4h
ATE US (gases)	146.500 ppm/4h
Argon (7440-37-1)	
LC50 inhalation rat (ppm)	820000 ppm/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Toxic if inhaled. Corrosive to the respiratory tract.

Symptoms/injuries after skin contact : Causes severe skin burns and eye damage.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : Adverse effects not expected from this product.

SECTION 12: Ecological information

12.1. Toxicity

Chlorine (7782-50-5)	
LC50 fish 1	0.44 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
EC50 Daphnia 1	0.017 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	0.014 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

Chlorine (5.86% - 29.29%) in Argon

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

Chlorine (7782-50-5)	
Persistence and degradability	Not applicable for inorganic gases.

Argon (7440-37-1)	
Persistence and degradability	No ecological damage caused by this product.

12.3. Bioaccumulative potential

Chlorine (7782-50-5)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No data available.

Argon (7440-37-1)	
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No ecological damage caused by this product.

12.4. Mobility in soil

Chlorine (7782-50-5)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

Argon (7440-37-1)	
Ecology - soil	No ecological damage caused by this product.

12.5. Other adverse effects

Effect on ozone layer	: No known effects from this product.
Effect on the global warming	: No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.
Waste disposal recommendations	: Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

SECTION 14: Transport information

In accordance with DOT	
Transport document description	: UN1955 Compressed gas, toxic, n.o.s. Inhalation Hazard Zone C/D
UN-No.(DOT)	: UN1955
Proper Shipping Name (DOT)	: Compressed gas, toxic, n.o.s. Inhalation Hazard Zone C/D
Hazard labels (DOT)	: 2.3 - Poison gas



DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: 3 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone C (see 173.116(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter. B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.
DOT Packaging Exceptions (49 CFR 173.xxx)	: None
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 302;305
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315

Chlorine (5.86% - 29.29%) in Argon

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: Forbidden
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

ADR

Transport document description	: UN 3304, 2.3 (8), (C/D)
Class (ADR)	: 2 - Gases
Hazard identification number (Kemler No.)	: 268
Classification code (ADR)	: 1TC
Hazard labels (ADR)	: 2.3 - Toxic gases 8 - Corrosive substances



Orange plates :



Tunnel restriction code (ADR)	: C/D
LQ	: 0
Excepted quantities (ADR)	: E0

Transport by sea

UN-No. (IMDG)	: 3304
Proper Shipping Name (IMDG)	: COMPRESSED GAS, TOXIC, N.O.S.
Class (IMDG)	: 2 - Gases

Air transport

UN-No.(IATA)	: 3304
Proper Shipping Name (IATA)	: COMPRESSED GAS, TOXIC, N.O.S.
Class (IATA)	: 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Chlorine (7782-50-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on the United States SARA Section 302
Listed on United States SARA Section 313

SARA Section 302 Threshold Planning Quantity (TPQ)	100
--	-----

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Argon (7440-37-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Chlorine (5.86% - 29.29%) in Argon

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chlorine (7782-50-5)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material

Argon (7440-37-1)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas

EU-Regulations

Chlorine (7782-50-5)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

Argon (7440-37-1)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Chlorine (7782-50-5)	
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Japanese Poisonous and Deleterious Substances Control Law Listed on the Canadian IDL (Ingredient Disclosure List)	

Argon (7440-37-1)	
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	

15.3. US State regulations

Chlorine (7782-50-5)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	

Argon (7440-37-1)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

SECTION 16: Other information

Indication of changes	: Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.
Other information	: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Chlorine (5.86% - 29.29%) in Argon

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Liquefied gas	Gases under pressure Liquefied gas
Ox. Gas 1	Oxidizing gases Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H330	Fatal if inhaled
H331	Toxic if inhaled
H335	May cause respiratory irritation

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.