

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/26/2015 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : 3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane
 Product code : SG-2003-01858

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide
 2700 Post Oak Boulevard
 Houston, TX 77056 - USA
 T 1-800-819-1704
www.us.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Gas 1	H220
Compressed gas	H280
STOT SE 3	H336

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H220 - Extremely flammable gas
 H280 - Contains gas under pressure; may explode if heated
 H336 - May cause drowsiness or dizziness
 OSHA-H01 - May displace oxygen and cause rapid suffocation
 CGA-HG04 - May form explosive mixtures with air

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood
 P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear eye protection, face protection, protective gloves, protective clothing
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely
 P381 - Eliminate all ignition sources if safe to do so
 P403 - Store in a well-ventilated place
 P405 - Store locked up
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations
 CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
 CGA-PG05 - Use a back flow preventive device in the piping
 CGA-PG06 - Close valve after each use and when empty
 CGA-PG10 - Use only with equipment rated for cylinder pressure
 CGA-PG14 - Approach suspected leak area with caution
 CGA-PG21 - Open valve slowly

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Ethylene	(CAS No) 74-85-1	20 - 99.9998	Flam. Gas 1, H220 Liquefied gas, H280 STOT SE 3, H336
Methane	(CAS No) 74-82-8	0.0001 - 79.9999	Flam. Gas 1, H220 Compressed gas, H280
3-chloropropene, allyl chloride	(CAS No) 107-05-1	0.0001 - 0.0999	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 2, H341 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Adverse effects not expected from this product.
- First-aid measures after eye contact : Adverse effects not expected from this product.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Adverse effects not expected from this product.
- Symptoms/injuries after eye contact : Adverse effects not expected from this product.
- Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.
- Symptoms/injuries upon intravenous administration : Not known.
- Chronic symptoms : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : This product is flammable.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture.
- Reactivity : None known.

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment consistent with the site emergency plan.
- Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

- Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe.

6.2. Environmental precautions

- Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

- For containment : Try to stop release if safe to do so.
- Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

- See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture.
- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools.
- Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.
- Incompatible products : None known.
- Incompatible materials : Oxidizing materials. Air.

7.3. Specific end use(s)

- See Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane	
ACGIH	Not applicable
OSHA	Not applicable

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3-chloropropene, allyl chloride (107-05-1)		
ACGIH	Not applicable	
OSHA	Not applicable	
Ethylene (74-85-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
OSHA	Not applicable	
Methane (74-82-8)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: None necessary during normal and routine operations. See Sections 5 & 6.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Molecular mass	: Not applicable for gas-mixtures.
Color	: Colorless
Odor	: Sweet
Odor threshold	: No Data Available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No Data Available
Freezing point	: No data available
Boiling point	: No Data Available
Flash point	: No Data Available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: See Section 2.1 and 2.2
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Relative gas density	: Heavier than air
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Without adequate ventilation formation of explosive mixtures may be possible.

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties : None.
Explosive limits : No data available

9.2. Other information

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Oxidizing materials. Air.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

3-chloropropene, allyl chloride (107-05-1)	
ATE US (oral)	500.000 mg/kg body weight
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

Ethylene (74-85-1)	
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h

Methane (74-82-8)	
LC50 inhalation rat (ppm)	820000 ppm/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Ethylene (74-85-1)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified
Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact : Adverse effects not expected from this product.

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact	: Adverse effects not expected from this product.
Symptoms/injuries after ingestion	: Ingestion is not considered a potential route of exposure.
Symptoms/injuries upon intravenous administration	: Not known.
Chronic symptoms	: Adverse effects not expected from this product.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

Ethylene (74-85-1)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
Methane (74-82-8)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist. No data available.

12.3. Bioaccumulative potential

Ethylene (74-85-1)	
BCF fish 1	4 - 4.6
Log Pow	1.13
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Methane (74-82-8)	
Log Pow	Not applicable for gas mixtures
Log Kow	Not applicable for gas mixtures
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

12.4. Mobility in soil

Ethylene (74-85-1)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Methane (74-82-8)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Effect on ozone layer	: No known effects from this product.
Effect on the global warming	: Contains greenhouse gas(es) not covered by 842/2006/EC.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into areas where there is a risk of forming an explosive mixture with air.
Waste disposal recommendations	: Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

SECTION 14: Transport information

In accordance with DOT	
Transport document description	: UN1954 Compressed gas, flammable, n.o.s. (Ethylene, Methane)
UN-No.(DOT)	: UN1954
Proper Shipping Name (DOT)	: Compressed gas, flammable, n.o.s.

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Symbols : G - Identifies PSN requiring a technical name

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 1954, 2.1, (B/D)

Class (ADR) : 2 - Gases

Hazard identification number (Kemler No.) : 23

Classification code (ADR) : 1F

Hazard labels (ADR) : 2.1 - Flammable gases



Orange plates : 

Tunnel restriction code (ADR) : B/D

LQ : 0

Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 1954

Proper Shipping Name (IMDG) : COMPRESSED GAS, FLAMMABLE, N.O.S.

Class (IMDG) : 2 - Gases

Air transport

UN-No.(IATA) : 1954

Proper Shipping Name (IATA) : COMPRESSED GAS, FLAMMABLE, N.O.S.

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylene (74-85-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Methane (74-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

Ethylene (74-85-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class A - Compressed Gas
Class B Division 1 - Flammable Gas
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Methane (74-82-8)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class A - Compressed Gas
Class B Division 1 - Flammable Gas

EU-Regulations

No additional information available

Ethylene (74-85-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methane (74-82-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Ethylene (74-85-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Methane (74-82-8)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

Ethylene (74-85-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

3-Chloropropene (0.0001% - 0.0999%), Ethylene (20.00% - 99.9998%) in Methane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methane (74-82-8)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.

Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Carc. 2	Carcinogenicity Category 2
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Liquefied gas	Gases under pressure Liquefied gas
Muta. 2	Germ cell mutagenicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.