

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Methyl Alcohol (0.0001% - 0.9999%) in Ethylene
 Product code : SG-2002-01190

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide
 2700 Post Oak Boulevard
 Houston, TX 77056 - USA
 T 1-800-819-1704
www.us.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Gas 1	H220
Compressed gas	H280
STOT SE 3	H336

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS04

GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H220 - Extremely flammable gas
 H280 - Contains gas under pressure; may explode if heated
 H336 - May cause drowsiness or dizziness
 OSHA-H01 - May displace oxygen and cause rapid suffocation
 CGA-HG04 - May form explosive mixtures with air

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood
 P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
 P261 - Avoid breathing gas
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear eye protection, face protection, protective gloves, protective clothing
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely
 P381 - Eliminate all ignition sources if safe to do so
 P403 - Store in a well-ventilated place
 P405 - Store locked up
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations
 CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
 CGA-PG05 - Use a back flow preventive device in the piping
 CGA-PG06 - Close valve after each use and when empty
 CGA-PG10 - Use only with equipment rated for cylinder pressure
 CGA-PG14 - Approach suspected leak area with caution
 CGA-PG21 - Open valve slowly

Methyl Alcohol (0.0001% - 0.9999%) in Ethylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Ethylene	(CAS No) 74-85-1	99.0001 - 99.9999	Flam. Gas 1, H220 Liquefied gas, H280 STOT SE 3, H336
Methyl alcohol	(CAS No) 67-56-1	0.0001 - 0.9999	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Adverse effects not expected from this product.
- First-aid measures after eye contact : Adverse effects not expected from this product.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Adverse effects not expected from this product.
- Symptoms/injuries after eye contact : Adverse effects not expected from this product.
- Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.
- Symptoms/injuries upon intravenous administration : Not known.
- Chronic symptoms : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : This product is flammable.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture.
- Reactivity : None known.

5.3. Advice for firefighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Ensure adequate ventilation.

Methyl Alcohol (0.0001% - 0.9999%) in Ethylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment consistent with the site emergency plan.
- Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

- Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

- For containment : Try to stop release if safe to do so.
- Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture.
- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools.
- Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.
- Incompatible products : None known.
- Incompatible materials : Oxidizing materials. Air.

7.3. Specific end use(s)

See Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl Alcohol (0.0001% - 0.9999%) in Ethylene		
ACGIH	Not applicable	
OSHA	Not applicable	
Methyl alcohol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Ethylene (74-85-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
OSHA	Not applicable	

Methyl Alcohol (0.0001% - 0.9999%) in Ethylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: None necessary during normal and routine operations. See Sections 5 & 6.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Color	: Colorless
Odor	: Sweet
Odor threshold	: No Data Available
pH	: No data available
Melting point	: No Data Available
Freezing point	: No data available
Boiling point	: No Data Available
Flash point	: No Data Available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: See Section 2.1 and 2.2
Explosion limits	: No data available
Explosive properties	: Without adequate ventilation formation of explosive mixtures may be possible.
Oxidizing properties	: None.
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: Not applicable for gas-mixtures.
Relative gas density	: Similar to air
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

Methyl Alcohol (0.0001% - 0.9999%) in Ethylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Oxidizing materials. Air.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Methyl alcohol (67-56-1)	
LD50 oral rat	5628 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 inhalation rat (mg/l)	83.2 mg/l/4h
LC50 inhalation rat (ppm)	64000 ppm/4h
ATE US (oral)	100.000 mg/kg body weight
ATE US (dermal)	300.000 mg/kg body weight
ATE US (gases)	700.000 ppmV/4h
ATE US (vapors)	3.000 mg/l/4h
ATE US (dust, mist)	0.500 mg/l/4h

Ethylene (74-85-1)	
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Ethylene (74-85-1)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Adverse effects not expected from this product.

Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : Adverse effects not expected from this product.

SECTION 12: Ecological information

12.1. Toxicity

Methyl alcohol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

Methyl Alcohol (0.0001% - 0.9999%) in Ethylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylene (74-85-1)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.

12.3. Bioaccumulative potential

Methyl alcohol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

Ethylene (74-85-1)	
BCF fish 1	4 - 4.6
Log Pow	1.13
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

12.4. Mobility in soil

Ethylene (74-85-1)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

- Effect on ozone layer : No known effects from this product.
- Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into areas where there is a risk of forming an explosive mixture with air.
- Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

SECTION 14: Transport information

Department of Transportation (DOT)

- In accordance with DOT
- Transport document description : UN1954 Compressed gas, flammable, n.o.s. (Ethylene, Methyl Alcohol)
- UN-No.(DOT) : UN1954
- Proper Shipping Name (DOT) : Compressed gas, flammable, n.o.s.
- Hazard labels (DOT) : 2.1 - Flammable gas



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305
- DOT Packaging Bulk (49 CFR 173.xxx) : 314;315
- DOT Symbols : G - Identifies PSN requiring a technical name
- DOT Packaging Exceptions (49 CFR 173.xxx) : 306
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
- DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Methyl Alcohol (0.0001% - 0.9999%) in Ethylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 1954, 2.1, (B/D)
Class (ADR) : 2 - Gases
Hazard identification number (Kemler No.) : 23
Classification code (ADR) : 1F
Hazard labels (ADR) : 2.1 - Flammable gases



Orange plates :



Tunnel restriction code (ADR) : B/D
Limited quantities (ADR) : 0
Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 1954
Proper Shipping Name (IMDG) : COMPRESSED GAS, FLAMMABLE, N.O.S.
Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 1954
Proper Shipping Name (IATA) : COMPRESSED GAS, FLAMMABLE, N.O.S.
Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Methyl alcohol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Ethylene (74-85-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

15.2. International regulations

CANADA

Methyl alcohol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Ethylene (74-85-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

EU-Regulations

Methyl Alcohol (0.0001% - 0.9999%) in Ethylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methyl alcohol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Ethylene (74-85-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

National regulations

Methyl alcohol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Listed on the Canadian IDL (Ingredient Disclosure List)

Ethylene (74-85-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

Methyl alcohol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	

Methyl alcohol (67-56-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Ethylene (74-85-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes	: Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.
Other information	: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Methyl Alcohol (0.0001% - 0.9999%) in Ethylene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Compressed gas	Gases under pressure Compressed gas
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Liquefied gas	Gases under pressure Liquefied gas
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H370	Causes damage to organs

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.